

PEP 8 – Style Guide for Python Code

Author: Guido van Rossum <[guido at python.org](mailto:guido@python.org)>, Barry Warsaw <[barry at python.org](mailto:barry@python.org)>, Alyssa Coghlan <[ncoghlan at gmail.com](mailto:ncoghlan@gmail.com)>

Status: Active

Type: Process

Created: 05-Jul-2001

History: 05-Jul-2001, 01-Aug-2013

Source: <https://github.com/python/peps/blob/main/peps/pep-0008.rst>

Introduction (#introduction)

This document gives coding conventions for the Python code comprising the standard library in the main Python distribution. Please see the companion informational PEP describing style guidelines for the C code in the C implementation of Python ([../pep-0007/](https://peps.python.org/pep-0007/)).

Last modified: 2025

PEP 8 and PEP 257 ([../pep-0257/](https://peps.python.org/pep-0257/)) (Docstring Conventions) were adapted from Guido's 2004 Python Style Guide essay, with some additions from Barry's style guide [2] (#id6).

2004-00:19 UTC

This style guide evolves over time as additional conventions are identified and past conventions are rendered obsolete by changes in the language itself.

Many projects have their own coding style guidelines. In the event of any conflicts, such as project-specific guides take precedence for that project.

Foolish Consistency is the Hobgoblin of Little Minds (#a-foolish-consistency-is-a-hobgoblin-of-little-minds)

One of Guido's key insights is that code is read much more often than it is written. The guidelines provided here are intended to improve the readability of code and make it consistent across the wide spectrum of Python code. As PEP 20 ([../pep-0020/](https://peps.python.org/pep-0020/)) says, "readability counts".

This guide is about consistency. Consistency with this style guide is important. Consistency within a project is more important. Consistency within one module or function is most important.

However, never, know when to be inconsistent – sometimes style guide recommendations just aren't applicable. When in doubt, use your best judgment. Look at other examples and decide what looks best. And don't hesitate to ask!

rticular: do not break backwards compatibility just to comply with this PEP!

e other good reasons to ignore a particular guideline:

- . When applying the guideline would make the code less readable, even for someone who is used to reading code that follows this PEP.
- . To be consistent with surrounding code that also breaks it (maybe for historic reasons) – although this is also an opportunity to clean up someone else’s mess (in true XP style).
- . Because the code in question predates the introduction of the guideline and there is no other reason to be modifying that code.
- . When the code needs to remain compatible with older versions of Python that don’t support the feature recommended by the style guide.

File Lay-out (#code-lay-out)

Indentation (#indentation)

4 spaces per indentation level.

Continuation lines should align wrapped elements either vertically using Python’s implicit joining inside parentheses, brackets and braces, or using a *hanging indent* [1] (#fn-hi).

When using a hanging indent the following should be considered; there should be no comments on the first line and further indentation should be used to clearly distinguish it as a continuation line:

Correct:

Aligned with opening delimiter.

```
o = long_function_name(var_one, var_two,
                       var_three, var_four)
```

Add 4 spaces (an extra level of indentation) to distinguish arguments from function name.

```
f long_function_name(
    var_one, var_two, var_three,
    var_four):
    print(var_one)
```

Hanging indents should add a level.

```
o = long_function_name(
    var_one, var_two,
    var_three, var_four)
```

Wrong:

Arguments on first line forbidden when not using vertical alignment.

```
o = long_function_name(var_one, var_two,
    var_three, var_four)
```

Further indentation required as indentation is not distinguishable.

```
f long_function_name(
    var_one, var_two, var_three,
    var_four):
    print(var_one)
```

4-space rule is optional for continuation lines.

onal:

*Hanging indents *may* be indented to other than 4 spaces.*

```
o = long_function_name(
var_one, var_two,
var_three, var_four)
```

When the conditional part of an `if`-statement is long enough to require that it be written across multiple lines, it's worth noting that the combination of a two character keyword (`if`), plus a single space, plus an opening parenthesis creates a natural 4-space indent for the subsequent lines of the multiline conditional. This can produce a visual conflict with an indented suite of code nested inside the `if`-statement, which would also naturally be indented to 4 spaces. This PEP takes no explicit position on how (or whether) to further visually distinguish such conditional lines from the nested suite inside the `if`-statement. Possible options in this situation include, but are not limited to:

No extra indentation.

```
(this_is_one_thing and
 that_is_another_thing):
    do_something()
```

Add a comment, which will provide some distinction in editors supporting syntax highlighting.

```
(this_is_one_thing and
 that_is_another_thing):
    # Since both conditions are true, we can frobnicate.
    do_something()
```

Add some extra indentation on the conditional continuation line.

```
(this_is_one_thing
    and that_is_another_thing):
    do_something()
```

(see the discussion of whether to break before or after binary operators below.)

Closing brace/bracket/parenthesis on multiline constructs may either line up under the

non-whitespace character of the last line of list, as in:

```
_list = [
    1, 2, 3,
    4, 5, 6,
]
sult = some_function_that_takes_arguments(
    'a', 'b', 'c',
    'd', 'e', 'f',
)
```

may be lined up under the first character of the line that starts the multiline construct,
:

```
_list = [
    1, 2, 3,
    4, 5, 6,

sult = some_function_that_takes_arguments(
    'a', 'b', 'c',
    'd', 'e', 'f',
```

; or Spaces? (#tabs-or-spaces)

es are the preferred indentation method.

should be used solely to remain consistent with code that is already indented with

on disallows mixing tabs and spaces for indentation.

imum Line Length (#maximum-line-length)

: all lines to a maximum of 79 characters.

lowing long blocks of text with fewer structural restrictions (docstrings or comments),
ine length should be limited to 72 characters.

ing the required editor window width makes it possible to have several files open side
de, and works well when using code review tools that present the two versions in
cent columns.

default wrapping in most tools disrupts the visual structure of the code, making it
e difficult to understand. The limits are chosen to avoid wrapping in editors with the
ow width set to 80, even if the tool places a marker glyph in the final column when
pping lines. Some web based tools may not offer dynamic line wrapping at all.

e teams strongly prefer a longer line length. For code maintained exclusively or arily by a team that can reach agreement on this issue, it is okay to increase the line th limit up to 99 characters, provided that comments and docstrings are still wrapped characters.

Python standard library is conservative and requires limiting lines to 79 characters (and trings/comments to 72).

preferred way of wrapping long lines is by using Python's implied line continuation e parentheses, brackets and braces. Long lines can be broken over multiple lines by iping expressions in parentheses. These should be used in preference to using a slash for line continuation.

slashes may still be appropriate at times. For example, long, multiple `with-` :ments could not use implicit continuation before Python 3.10, so backslashes were ptable for that case:

```
with open('/path/to/some/file/you/want/to/read') as file_1, \
      open('/path/to/some/file/being/written', 'w') as file_2:
    file_2.write(file_1.read())
```

the previous discussion on multiline if-statements (`#multiline-if-statements`) for further ghts on the indentation of such multiline `with`-statements.)

her such case is with `assert` statements.

be sure to indent the continued line appropriately.

ould a Line Break Before or After a Binary Operator? (`#should-a-line-break-before-or-after-a-operator`)

decades the recommended style was to break after binary operators. But this can hurt ability in two ways: the operators tend to get scattered across different columns on creen, and each operator is moved away from its operand and onto the previous line. , the eye has to do extra work to tell which items are added and which are subtracted:

```
wrong:
operators sit far away from their operands
income = (gross_wages +
          taxable_interest +
          (dividends - qualified_dividends) -
          ira_deduction -
          student_loan_interest)
```

olve this readability problem, mathematicians and their publishers follow the opposite convention. Donald Knuth explains the traditional rule in his *Computers and Typesetting*: “Although formulas within a paragraph always break after binary operations and functions, displayed formulas always break before binary operations” [3] (#id7).

Following the tradition from mathematics usually results in more readable code:

Correct:
easy to match operators with operands

```
income = (gross_wages
          + taxable_interest
          + (dividends - qualified_dividends)
          - ira_deduction
          - student_loan_interest)
```

In Python code, it is permissible to break before or after a binary operator, as long as the convention is consistent locally. For new code Knuth’s style is suggested.

Blank Lines (#blank-lines)

Surround top-level function and class definitions with two blank lines.

Method definitions inside a class are surrounded by a single blank line.

Blank lines may be used (sparingly) to separate groups of related functions. Blank lines may be omitted between a bunch of related one-liners (e.g. a set of dummy implementations).

Use blank lines in functions, sparingly, to indicate logical sections.

Python accepts the control-L (i.e. ^L) form feed character as whitespace; many tools treat these characters as page separators, so you may use them to separate pages of related sections of your file. Note, some editors and web-based code viewers may not recognize control-L as a form feed and will show another glyph in its place.

Source File Encoding (#source-file-encoding)

Files in the core Python distribution should always use UTF-8, and should not have an encoding declaration.

In the standard library, non-UTF-8 encodings should be used only for test purposes. Use ASCII characters sparingly, preferably only to denote places and human names. If using non-ASCII characters as data, avoid noisy Unicode characters like `zalgo` and byte markers.

Identifiers in the Python standard library MUST use ASCII-only identifiers, and SHOULD use English words wherever feasible (in many cases, abbreviations and technical terms are used which aren't English).

Python source projects with a global audience are encouraged to adopt a similar policy.

Imports (#imports)

Imports should usually be on separate lines:

```
# Correct:  
import os  
import sys
```

```
# Wrong:  
import sys, os
```

It's okay to say this though:

```
# Correct:  
from subprocess import Popen, PIPE
```

Imports are always put at the top of the file, just after any module comments and docstrings, and before module globals and constants.

Imports should be grouped in the following order:

1. Standard library imports.
2. Related third party imports.
3. Local application/library specific imports.

You should put a blank line between each group of imports.

Absolute imports are recommended, as they are usually more readable and tend to be better behaved (or at least give better error messages) if the import system is incorrectly configured (such as when a directory inside a package ends up on `sys.path`):

```
import mypkg.sibling  
from mypkg import sibling  
from mypkg.sibling import example
```

However, explicit relative imports are an acceptable alternative to absolute imports, especially when dealing with complex package layouts where using absolute imports would be unnecessarily verbose:

```
from . import sibling
from .sibling import example
```

Standard library code should avoid complex package layouts and always use absolute imports.

When importing a class from a class-containing module, it's usually okay to spell this:

```
from myclass import MyClass
from foo.bar.yourclass import YourClass
```

If this spelling causes local name clashes, then spell them explicitly:

```
import myclass
import foo.bar.yourclass
```

and use `myclass.MyClass` and `foo.bar.yourclass.YourClass`.

Wildcard imports (`from <module> import *`) should be avoided, as they make it unclear which names are present in the namespace, confusing both readers and many automated tools. There is one defensible use case for a wildcard import, which is to republish an internal interface as part of a public API (for example, overwriting a pure Python implementation of an interface with the definitions from an optional accelerator module and exactly which definitions will be overwritten isn't known in advance).

When republishing names this way, the guidelines below regarding public and internal interfaces still apply.

Module Level Dunder Names (#module-level-dunder-names)

Module level “dunders” (i.e. names with two leading and two trailing underscores) such as `__all__`, `__author__`, `__version__`, etc. should be placed after the module docstring but before any import statements *except* from `__future__` imports. Python mandates that re-exports must appear in the module before any other code except docstrings:

```

"This is the example module.

is module does stuff.
"

from __future__ import barry_as_FLUFL

all__ = ['a', 'b', 'c']
version__ = '0.1'
author__ = 'Cardinal Biggles'

port os
port sys

```

String Quotes (#string-quotes)

Python, single-quoted strings and double-quoted strings are the same. This PEP does not make a recommendation for this. Pick a rule and stick to it. When a string contains single or double quote characters, however, use the other one to avoid backslashes in the string. It improves readability.

For triple-quoted strings, always use double quote characters to be consistent with the string convention in PEP 257 ([../pep-0257/](https://peps.python.org/pep-0257/)).

Whitespace in Expressions and Statements (#whitespace-in-expressions-and-statements)

Peeves (#pet-peeves)

Eliminate extraneous whitespace in the following situations:

Immediately inside parentheses, brackets or braces:

```

# Correct:
spam(ham[1], {eggs: 2})

# Wrong:
spam( ham[ 1 ], { eggs: 2 } )

```

Between a trailing comma and a following close parenthesis:

```

# Correct:
foo = (0,)

# Wrong:
bar = (0, )

```

Immediately before a comma, semicolon, or colon:

```
# Correct:
if x == 4: print(x, y); x, y = y, x

# Wrong:
if x == 4 : print(x , y) ; x , y = y , x
```

However, in a slice the colon acts like a binary operator, and should have equal amounts on either side (treating it as the operator with the lowest priority). In an extended slice, both colons must have the same amount of spacing applied.

Exception: when a slice parameter is omitted, the space is omitted:

```
# Correct:
ham[1:9], ham[1:9:3], ham[:9:3], ham[1::3], ham[1:9:]
ham[lower:upper], ham[lower:upper:], ham[lower::step]
ham[lower+offset : upper+offset]
ham[: upper_fn(x) : step_fn(x)], ham[:: step_fn(x)]
ham[lower + offset : upper + offset]

# Wrong:
ham[lower + offset:upper + offset]
ham[1: 9], ham[1 :9], ham[1:9 :3]
ham[lower : : step]
ham[ : upper]
```

Immediately before the open parenthesis that starts the argument list of a function call:

```
# Correct:
spam(1)

# Wrong:
spam (1)
```

Immediately before the open parenthesis that starts an indexing or slicing:

```
# Correct:
dct['key'] = lst[index]

# Wrong:
dct ['key'] = lst [index]
```

More than one space around an assignment (or other) operator to align it with another:

```
# Correct:
x = 1
y = 2
long_variable = 3
```

```
# Wrong:
x          = 1
y          = 2
long_variable = 3
```

Recommendations (#other-recommendations)

Avoid trailing whitespace anywhere. Because it's usually invisible, it can be confusing: e.g. a backslash followed by a space and a newline does not count as a line continuation marker. Some editors don't preserve it and many projects (like CPython itself) have pre-commit hooks that reject it.

Always surround these binary operators with a single space on either side: assignment (=), augmented assignment (+=, -= etc.), comparisons (==, <, >, !=, <=, >=, in, not in, is, is not), Booleans (and, or, not).

If operators with different priorities are used, consider adding whitespace around the operators with the lowest priority(ies). Use your own judgment; however, never use more than one space, and always have the same amount of whitespace on both sides of a binary operator:

```
# Correct:
i = i + 1
submitted += 1
x = x*2 - 1
hypot2 = x*x + y*y
c = (a+b) * (a-b)
```

```
# Wrong:
i=i+1
submitted +=1
x = x * 2 - 1
hypot2 = x * x + y * y
c = (a + b) * (a - b)
```

Function annotations should use the normal rules for colons and always have spaces around the -> arrow if present. (See Function Annotations (#function-annotations) below for more about function annotations.):

```
# Correct:
def munge(input: AnyStr): ...
def munge() -> PosInt: ...
```

```
# Wrong:  
def munge(input:AnyStr): ...  
def munge()->PosInt: ...
```

Don't use spaces around the = sign when used to indicate a keyword argument, or when used to indicate a default value for an *unannotated* function parameter:

```
# Correct:  
def complex(real, imag=0.0):  
    return magic(r=real, i=imag)
```

```
# Wrong:  
def complex(real, imag = 0.0):  
    return magic(r = real, i = imag)
```

When combining an argument annotation with a default value, however, do use spaces around the = sign:

```
# Correct:  
def munge(sep: AnyStr = None): ...  
def munge(input: AnyStr, sep: AnyStr = None, limit=1000): ...
```

```
# Wrong:  
def munge(input: AnyStr=None): ...  
def munge(input: AnyStr, limit = 1000): ...
```

Compound statements (multiple statements on the same line) are generally discouraged:

```
# Correct:  
if foo == 'blah':  
    do_blah_thing()  
do_one()  
do_two()  
do_three()
```

Rather not:

```
# Wrong:  
if foo == 'blah': do_blah_thing()  
do_one(); do_two(); do_three()
```

While sometimes it's okay to put an if/for/while with a small body on the same line, never do this for multi-clause statements. Also avoid folding such long lines!

Rather not:

```
# Wrong:
if foo == 'blah': do_blah_thing()
for x in lst: total += x
while t < 10: t = delay()
```

Definitely not:

```
# Wrong:
if foo == 'blah': do_blah_thing()
else: do_non_blah_thing()

try: something()
finally: cleanup()

do_one(); do_two(); do_three(long, argument,
                             list, like, this)

if foo == 'blah': one(); two(); three()
```

When to Use Trailing Commas (#when-to-use-trailing-commas)

Trailing commas are usually optional, except they are mandatory when making a tuple of multiple elements. For clarity, it is recommended to surround the latter in (technically redundant) parentheses:

Correct:

```
LES = ('setup.cfg',)
```

Wrong:

```
LES = 'setup.cfg',
```

Even though trailing commas are redundant, they are often helpful when a version control system is used, when a list of values, arguments or imported items is expected to be extended over time. The pattern is to put each value (etc.) on a line by itself, always adding a trailing comma, and add the close parenthesis/bracket/brace on the next line. However it does not make sense to have a trailing comma on the same line as the closing delimiter (except in the above case of singleton tuples):

Correct:

```
LES = [
    'setup.cfg',
    'tox.ini',
]
initialize(FILES,
           error=True,
           )
```

Wrong:

```
LES = ['setup.cfg', 'tox.ini',]
italize(FILES, error=True,)
```

Comments (#comments)

Comments that contradict the code are worse than no comments. Always make a priority of keeping the comments up-to-date when the code changes!

Comments should be complete sentences. The first word should be capitalized, unless it is an identifier that begins with a lower case letter (never alter the case of identifiers!).

Block comments generally consist of one or more paragraphs built out of complete sentences, with each sentence ending in a period.

Comments should use one or two spaces after a sentence-ending period in multi-sentence comments, except after the final sentence.

Remember that your comments are clear and easily understandable to other speakers of the language you are writing in.

For non-coders from non-English speaking countries: please write your comments in English, unless you are 120% sure that the code will never be read by people who don't speak your language.

Block Comments (#block-comments)

Block comments generally apply to some (or all) code that follows them, and are indented to the same level as that code. Each line of a block comment starts with a # and a single space (unless it is indented text inside the comment).

Paragraphs inside a block comment are separated by a line containing a single #.

Inline Comments (#inline-comments)

Use inline comments sparingly.

An inline comment is a comment on the same line as a statement. Inline comments should be separated by at least two spaces from the statement. They should start with a # and a single space.

Redundant comments are unnecessary and in fact distracting if they state the obvious. Don't do

```
= x + 1                # Increment x
```

sometimes, this is useful:

```
= x + 1                # Compensate for border
```

Documentation Strings (#documentation-strings)

Conventions for writing good documentation strings (a.k.a. “docstrings”) are immortalized in PEP 257 ([../pep-0257/](https://peps.python.org/pep-0257/)).

Write docstrings for all public modules, functions, classes, and methods. Docstrings are not necessary for non-public methods, but you should have a comment that describes what the method does. This comment should appear after the `def` line.

PEP 257 ([../pep-0257/](https://peps.python.org/pep-0257/)) describes good docstring conventions. Note that most importantly, the `"""` that ends a multiline docstring should be on a line by itself:

```
"""Return a foobang

Optional plotz says to frobnicate the bizbaz first.
"""
```

For one liner docstrings, please keep the closing `"""` on the same line:

```
"""Return an ex-parrot."""
```

Naming Conventions (#naming-conventions)

Naming conventions of Python’s library are a bit of a mess, so we’ll never get this completely consistent – nevertheless, here are the currently recommended naming standards. New modules and packages (including third party frameworks) should be conformant to these standards, but where an existing library has a different style, internal consistency is preferred.

Overriding Principle (#overriding-principle)

Names that are visible to the user as public parts of the API should follow conventions that reflect usage rather than implementation.

Descriptive: Naming Styles (#descriptive-naming-styles)

There are a lot of different naming styles. It helps to be able to recognize what naming

is being used, independently from what they are used for.

Following naming styles are commonly distinguished:

`b` (single lowercase letter)

`B` (single uppercase letter)

`lowercase`

`lower_case_with_underscores`

`UPPERCASE`

`UPPER_CASE_WITH_UNDERSCORES`

`CapitalizedWords` (or `CapWords`, or `CamelCase` – so named because of the bumpy look of its letters [4] (#id8)). This is also sometimes known as `StudlyCaps`.

Note: When using acronyms in `CapWords`, capitalize all the letters of the acronym. Thus `HTTPServerError` is better than `HttpServerError`.

`mixedCase` (differs from `CapitalizedWords` by initial lowercase character!)

`Capitalized_Words_With_Underscores` (ugly!)

There's also the style of using a short unique prefix to group related names together. This is not used much in Python, but it is mentioned for completeness. For example, the `stat()` function returns a tuple whose items traditionally have names like `st_mode`, `st_size`, `st_mtime` and so on. (This is done to emphasize the correspondence with the members of the POSIX system call struct, which helps programmers familiar with that.)

The `XML` library uses a leading `X` for all its public functions. In Python, this style is generally considered unnecessary because attribute and method names are prefixed with an object, and function names are prefixed with a module name.

In addition, the following special forms using leading or trailing underscores are recognized (these can generally be combined with any case convention):

`_single_leading_underscore`: weak "internal use" indicator. E.g. `from M import *` does not import objects whose names start with an underscore.

`single_trailing_underscore_`: used by convention to avoid conflicts with Python keyword, e.g. :

```
tkinter.Toplevel(master, class_='ClassName')
```

`__double_leading_underscore`: when naming a class attribute, invokes name mangling (inside class `FooBar`, `__boo` becomes `_FooBar__boo`; see below).

`__double_leading_and_trailing_underscore__`: “magic” objects or attributes that live in user-controlled namespaces. E.g. `__init__`, `__import__` or `__file__`. Never invent such names; only use them as documented.

criptive: Naming Conventions (#prescriptive-naming-conventions)

is to Avoid (#names-to-avoid)

or use the characters ‘l’ (lowercase letter el), ‘O’ (uppercase letter oh), or ‘I’ (uppercase r eye) as single character variable names.

me fonts, these characters are indistinguishable from the numerals one and zero. n tempted to use ‘l’, use ‘L’ instead.

Compatibility (#ascii-compatibility)

ifiers used in the standard library must be ASCII compatible as described in the policy on ([../pep-3131/#policy-specification](#)) of PEP 3131 ([../pep-3131/](#)).

age and Module Names (#package-and-module-names)

ules should have short, all-lowercase names. Underscores can be used in the module e if it improves readability. Python packages should also have short, all-lowercase es, although the use of underscores is discouraged.

n an extension module written in C or C++ has an accompanying Python module that ides a higher level (e.g. more object oriented) interface, the C/C++ module has a ng underscore (e.g. `_socket`).

Names (#class-names)

s names should normally use the CapWords convention.

aming convention for functions may be used instead in cases where the interface is mented and used primarily as a callable.

that there is a separate convention for builtin names: most builtin names are single ls (or two words run together), with the CapWords convention used only for exception es and builtin constants.

Variable Names (#type-variable-names)

es of type variables introduced in PEP 484 ([../pep-0484/](https://peps.python.org/pep-0484/)) should normally use CapWords
erring short names: `T`, `AnyStr`, `Num`. It is recommended to add suffixes `_co` or `_contra`
e variables used to declare covariant or contravariant behavior correspondingly:

```
om typing import TypeVar

_co = TypeVar('VT_co', covariant=True)
_contra = TypeVar('KT_contra', contravariant=True)
```

Exception Names (#exception-names)

use exceptions should be classes, the class naming convention applies here. However,
should use the suffix “Error” on your exception names (if the exception actually is an
).

Global Variable Names (#global-variable-names)

s hope that these variables are meant for use inside one module only.) The
entions are about the same as those for functions.

ules that are designed for use via `from M import *` should use the `__all__` mechanism
event exporting globals, or use the older convention of prefixing such globals with an
underscore (which you might want to do to indicate these globals are “module non-
ic”).

Function and Variable Names (#function-and-variable-names)

tion names should be lowercase, with words separated by underscores as necessary
improve readability.

ible names follow the same convention as function names.

dCase is allowed only in contexts where that’s already the prevailing style (e.g.
ading.py), to retain backwards compatibility.

Function and Method Arguments (#function-and-method-arguments)

ys use `self` for the first argument to instance methods.

ys use `cls` for the first argument to class methods.

unction argument’s name clashes with a reserved keyword, it is generally better to
nd a single trailing underscore rather than use an abbreviation or spelling corruption.

`__class__` is better than `class`. (Perhaps better is to avoid such clashes by using a `__` prefix.)

Method Names and Instance Variables (#method-names-and-instance-variables)

Follow the function naming rules: lowercase with words separated by underscores as necessary to improve readability.

Use one leading underscore only for non-public methods and instance variables.

To avoid name clashes with subclasses, use two leading underscores to invoke Python's name mangling rules.

Python mangles these names with the class name: if class `Foo` has an attribute named `__a`, it cannot be accessed by `Foo.__a`. (An insistent user could still gain access by calling `Foo.__dict__['__a']`.) Generally, double leading underscores should be used only to avoid name conflicts with attributes in classes designed to be subclassed.

There is some controversy about the use of `__` names (see below).

Constants (#constants)

Constants are usually defined on a module level and written in all capital letters with underscores separating words. Examples include `MAX_OVERFLOW` and `TOTAL`.

Designing for Inheritance (#designing-for-inheritance)

Designers decide whether a class's methods and instance variables (collectively: "attributes") should be public or non-public. If in doubt, choose non-public; it's easier to make it public than to make a public attribute non-public.

Public attributes are those that you expect unrelated clients of your class to use, with your commitment to avoid backwards incompatible changes. Non-public attributes are those that are not intended to be used by third parties; you make no guarantees that non-public attributes won't change or even be removed.

Don't use the term "private" here, since no attribute is really private in Python (without a generally unnecessary amount of work).

Another category of attributes are those that are part of the "subclass API" (often called "protected" in other languages). Some classes are designed to be inherited from, either to extend or modify aspects of the class's behavior. When designing such a class, take care to make explicit decisions about which attributes are public, which are part of the subclass

and which are truly only to be used by your base class.

this in mind, here are the Pythonic guidelines:

Public attributes should have no leading underscores.

If your public attribute name collides with a reserved keyword, append a single trailing underscore to your attribute name. This is preferable to an abbreviation or corrupted spelling. (However, notwithstanding this rule, 'cls' is the preferred spelling for any variable or argument which is known to be a class, especially the first argument to a class method.)

Note 1: See the argument name recommendation above for class methods.

For simple public data attributes, it is best to expose just the attribute name, without complicated accessor/mutator methods. Keep in mind that Python provides an easy path to future enhancement, should you find that a simple data attribute needs to grow functional behavior. In that case, use properties to hide functional implementation behind simple data attribute access syntax.

Note 1: Try to keep the functional behavior side-effect free, although side-effects such as caching are generally fine.

Note 2: Avoid using properties for computationally expensive operations; the attribute notation makes the caller believe that access is (relatively) cheap.

If your class is intended to be subclassed, and you have attributes that you do not want subclasses to use, consider naming them with double leading underscores and no trailing underscores. This invokes Python's name mangling algorithm, where the name of the class is mangled into the attribute name. This helps avoid attribute name collisions should subclasses inadvertently contain attributes with the same name.

Note 1: Note that only the simple class name is used in the mangled name, so if a subclass chooses both the same class name and attribute name, you can still get name collisions.

Note 2: Name mangling can make certain uses, such as debugging and `__getattr__()`, less convenient. However the name mangling algorithm is well documented and easy to perform manually.

Note 3: Not everyone likes name mangling. Try to balance the need to avoid accidental name clashes with potential use by advanced callers.

Public and Internal Interfaces (#public-and-internal-interfaces)

Backwards compatibility guarantees apply only to public interfaces. Accordingly, it is important that users be able to clearly distinguish between public and internal interfaces.

Documented interfaces are considered public, unless the documentation explicitly declares them to be provisional or internal interfaces exempt from the usual backwards compatibility guarantees. All undocumented interfaces should be assumed to be internal.

To better support introspection, modules should explicitly declare the names in their public API using the `__all__` attribute. Setting `__all__` to an empty list indicates that the module has no public API.

When `__all__` is set appropriately, internal interfaces (packages, modules, classes, functions, attributes or other names) should still be prefixed with a single leading underscore.

An interface is also considered internal if any containing namespace (package, module or class) is considered internal.

Imported names should always be considered an implementation detail. Other modules should not rely on indirect access to such imported names unless they are an explicitly documented part of the containing module's API, such as `os.path` or a package's `__init__` module that exposes functionality from submodules.

Programming Recommendations (#programming-recommendations)

Code should be written in a way that does not disadvantage other implementations of Python (PyPy, Jython, IronPython, Cython, Psyco, and such).

For example, do not rely on CPython's efficient implementation of in-place string concatenation for statements in the form `a += b` or `a = a + b`. This optimization is fragile even in CPython (it only works for some types) and isn't present at all in other implementations that don't use refcounting. In performance sensitive parts of the library, the `''.join()` form should be used instead. This will ensure that concatenation occurs in linear time across various implementations.

Comparisons to singletons like `None` should always be done with `is` or `is not`, never the equality operators.

Also, beware of writing `if x` when you really mean `if x is not None` – e.g. when testing whether a variable or argument that defaults to `None` was set to some other

value. The other value might have a type (such as a container) that could be false in a boolean context!

Use `is not` operator rather than `not ... is`. While both expressions are functionally identical, the former is more readable and preferred:

```
# Correct:  
if foo is not None:
```

```
# Wrong:  
if not foo is None:
```

When implementing ordering operations with rich comparisons, it is best to implement all six operations (`__eq__`, `__ne__`, `__lt__`, `__le__`, `__gt__`, `__ge__`) rather than relying on other code to only exercise a particular comparison.

To minimize the effort involved, the `functools.total_ordering()` decorator provides a tool to generate missing comparison methods.

PEP 207 ([../pep-0207/](https://peps.python.org/pep-0207/)) indicates that reflexivity rules *are* assumed by Python. Thus, the interpreter may swap `y > x` with `x < y`, `y >= x` with `x <= y`, and may swap the arguments of `x == y` and `x != y`. The `sort()` and `min()` operations are guaranteed to use the `<` operator and the `max()` function uses the `>` operator. However, it is best to implement all six operations so that confusion doesn't arise in other contexts.

Always use a `def` statement instead of an assignment statement that binds a lambda expression directly to an identifier:

```
# Correct:  
def f(x): return 2*x
```

```
# Wrong:  
f = lambda x: 2*x
```

The first form means that the name of the resulting function object is specifically `'f'` instead of the generic `'<lambda>'`. This is more useful for tracebacks and string representations in general. The use of the assignment statement eliminates the sole benefit a lambda expression can offer over an explicit `def` statement (i.e. that it can be embedded inside a larger expression)

Derive exceptions from `Exception` rather than `BaseException`. Direct inheritance from `BaseException` is reserved for exceptions where catching them is almost always the wrong thing to do.

Design exception hierarchies based on the distinctions that code *catching* the exceptions is likely to need, rather than the locations where the exceptions are raised. Aim to answer the question “What went wrong?” programmatically, rather than only stating that “A problem occurred” (see PEP 3151 ([../pep-3151/](https://peps.python.org/pep-3151/)) for an example of this lesson being learned for the builtin exception hierarchy)

Class naming conventions apply here, although you should add the suffix “Error” to your exception classes if the exception is an error. Non-error exceptions that are used for non-local flow control or other forms of signaling need no special suffix.

Use exception chaining appropriately. `raise x from y` should be used to indicate explicit replacement without losing the original traceback.

When deliberately replacing an inner exception (using `raise x from None`), ensure that relevant details are transferred to the new exception (such as preserving the attribute name when converting `KeyError` to `AttributeError`, or embedding the text of the original exception in the new exception message).

When catching exceptions, mention specific exceptions whenever possible instead of using a bare `except:` clause:

```
try:
    import platform_specific_module
except ImportError:
    platform_specific_module = None
```

A bare `except:` clause will catch `SystemExit` and `KeyboardInterrupt` exceptions, making it harder to interrupt a program with Control-C, and can disguise other problems. If you want to catch all exceptions that signal program errors, use `except Exception:` (bare `except` is equivalent to `except BaseException:`).

A good rule of thumb is to limit use of bare ‘except’ clauses to two cases:

1. If the exception handler will be printing out or logging the traceback; at least the user will be aware that an error has occurred.
2. If the code needs to do some cleanup work, but then lets the exception propagate upwards with `raise`. `try...finally` can be a better way to handle this case.

When catching operating system errors, prefer the explicit exception hierarchy introduced in Python 3.3 over introspection of `errno` values.

Additionally, for all try/except clauses, limit the `try` clause to the absolute minimum

amount of code necessary. Again, this avoids masking bugs:

```
# Correct:
try:
    value = collection[key]
except KeyError:
    return key_not_found(key)
else:
    return handle_value(value)

# Wrong:
try:
    # Too broad!
    return handle_value(collection[key])
except KeyError:
    # Will also catch KeyError raised by handle_value()
    return key_not_found(key)
```

When a resource is local to a particular section of code, use a `with` statement to ensure it is cleaned up promptly and reliably after use. A `try/finally` statement is also acceptable.

Context managers should be invoked through separate functions or methods whenever they do something other than acquire and release resources:

```
# Correct:
with conn.begin_transaction():
    do_stuff_in_transaction(conn)

# Wrong:
with conn:
    do_stuff_in_transaction(conn)
```

The latter example doesn't provide any information to indicate that the `__enter__` and `__exit__` methods are doing something other than closing the connection after a transaction. Being explicit is important in this case.

Be consistent in return statements. Either all return statements in a function should return an expression, or none of them should. If any return statement returns an expression, any return statements where no value is returned should explicitly state this as `return None`, and an explicit return statement should be present at the end of the function (if reachable):

```
# Correct:

def foo(x):
    if x >= 0:
        return math.sqrt(x)
    else:
        return None

def bar(x):
    if x < 0:
        return None
    return math.sqrt(x)
```

```
# Wrong:

def foo(x):
    if x >= 0:
        return math.sqrt(x)

def bar(x):
    if x < 0:
        return
    return math.sqrt(x)
```

Use `''.startswith()` and `''.endswith()` instead of string slicing to check for prefixes or suffixes.

`startswith()` and `endswith()` are cleaner and less error prone:

```
# Correct:
if foo.startswith('bar'):
```

```
# Wrong:
if foo[:3] == 'bar':
```

Object type comparisons should always use `isinstance()` instead of comparing types directly:

```
# Correct:
if isinstance(obj, int):
```

```
# Wrong:
if type(obj) is type(1):
```

For sequences, (strings, lists, tuples), use the fact that empty sequences are false:

```
# Correct:
if not seq:
if seq:
```

```
# Wrong:  
if len(seq):  
if not len(seq):
```

Don't write string literals that rely on significant trailing whitespace. Such trailing whitespace is visually indistinguishable and some editors (or more recently, `reindent.py`) will trim them.

Don't compare boolean values to `True` or `False` using `==`:

```
# Correct:  
if greeting:
```

```
# Wrong:  
if greeting == True:
```

Worse:

```
# Wrong:  
if greeting is True:
```

Use of the flow control statements `return`/`break`/`continue` within the finally suite of a `try...finally`, where the flow control statement would jump outside the finally suite, is discouraged. This is because such statements will implicitly cancel any active exception that is propagating through the finally suite:

```
# Wrong:  
def foo():  
    try:  
        1 / 0  
    finally:  
        return 42
```

Function Annotations (#function-annotations)

With the acceptance of PEP 484 ([../pep-0484/](https://peps.python.org/pep-0484/)), the style rules for function annotations have changed.

Function annotations should use PEP 484 ([../pep-0484/](https://peps.python.org/pep-0484/)) syntax (there are some formatting recommendations for annotations in the previous section).

The experimentation with annotation styles that was recommended previously in this PEP is no longer encouraged.

However, outside the `stdlib`, experiments within the rules of PEP 484 ([../pep-0484/](https://peps.python.org/pep-0484/)) are

now encouraged. For example, marking up a large third party library or application with PEP 484 ([../pep-0484/](https://peps.python.org/pep-0484/)) style type annotations, reviewing how easy it was to add those annotations, and observing whether their presence increases code understandability.

The Python standard library should be conservative in adopting such annotations, but their use is allowed for new code and for big refactorings.

For code that wants to make a different use of function annotations it is recommended to put a comment of the form:

```
# type: ignore
```

near the top of the file; this tells type checkers to ignore all annotations. (More fine-grained ways of disabling complaints from type checkers can be found in PEP 484 ([../pep-0484/](https://peps.python.org/pep-0484/)).)

Like linters, type checkers are optional, separate tools. Python interpreters by default should not issue any messages due to type checking and should not alter their behavior based on annotations.

Users who don't want to use type checkers are free to ignore them. However, it is expected that users of third party library packages may want to run type checkers over those packages. For this purpose PEP 484 ([../pep-0484/](https://peps.python.org/pep-0484/)) recommends the use of stub files: .pyi files that are read by the type checker in preference of the corresponding .py files. Stub files can be distributed with a library, or separately (with the library author's permission) through the typeshed repo [5] (#id9).

Variable Annotations (#variable-annotations)

PEP 526 ([../pep-0526/](https://peps.python.org/pep-0526/)) introduced variable annotations. The style recommendations for them are similar to those on function annotations described above:

Annotations for module level variables, class and instance variables, and local variables should have a single space after the colon.

There should be no space before the colon.

If an assignment has a right hand side, then the equality sign should have exactly one space on both sides:

```

# Correct:

code: int

class Point:
    coords: Tuple[int, int]
    label: str = '<unknown>'

# Wrong:

code:int # No space after colon
code : int # Space before colon

class Test:
    result: int=0 # No spaces around equality sign

```

Although the PEP 526 ([../pep-0526/](https://peps.python.org/pep-0526/)) is accepted for Python 3.6, the variable annotation syntax is the preferred syntax for stub files on all versions of Python (see PEP 484 ([../pep-0484/](https://peps.python.org/pep-0484/)) for details).

notes

[2]

Hanging indentation is a type-setting style where all the lines in a paragraph are indented except the first line. In the context of Python, the term is used to describe a style where the opening parenthesis of a parenthesized statement is the last non-whitespace character of the line, with subsequent lines being indented until the closing parenthesis.

references (#references)

[1]

Barry's GNU Mailman style guide <http://barry.warsaw.us/software/STYLEGUIDE.txt>
(<http://barry.warsaw.us/software/STYLEGUIDE.txt>)

[3]

Donald Knuth's *The TeXBook*, pages 195 and 196.

[4]

http://www.wikipedia.com/wiki/Camel_case (http://www.wikipedia.com/wiki/Camel_case)

[5]

Typedshed repo <https://github.com/python/timeshed> (<https://github.com/python/timeshed>)

copyright (#copyright)

This document has been placed in the public domain.