AuthXException

class authx.exceptions.AuthXException

Bases: `Exception`

Base AuthXException Exception.

The base exception for all AuthX exceptions.

class authx.exceptions.BadConfigurationError

Bases: `AuthXException`

Exception raised when AuthX configuration contains wrong parameters.

Raised when AuthX configuration contains wrong parameters.

class authx.exceptions.JWTDecodeError

Bases: `AuthXException`

Exception raised when decoding JSON Web Token fails.

Raised when decoding JSON Web Token fails.

class authx.exceptions.NoAuthorizationError

Bases: `AuthXException`

Exception raised when no token can be parsed from request.

Raised when no token can be parsed from request.

class authx.exceptions.CSRFError

Bases: `AuthXException`

Exception raised when CSRF protection failed.

Raised when CSRF protection failed.

class authx.exceptions.TokenError

Bases: `AuthXException`

Base Exception for token related errors.

Raised when token is invalid.

class authx.exceptions.MissingTokenError

Bases: `TokenError`

Exception raised when no token can be parsed from request.

Raised when no token can be parsed from request.

`class` authx.exceptions.MissingCSRFTokenError

Bases: `MissingTokenError`

Exception raised when no CSRF token can be parsed from request.

Raised when no CSRF token can be parsed from request.

`class` authx.exceptions.TokenTypeError

Bases: `TokenError`

Exception raised when a specific token type is expected.

Raised when token type is invalid.

`class` authx.exceptions.RevokedTokenError

Bases: `TokenError`

Exception raised when a revoked token has been used.

Raised when token is invalid.

`class` authx.exceptions.TokenRequiredError

Bases: `TokenError`

Exception raised when no token was used in request.

Raised when token is required.

`class` authx.exceptions.FreshTokenRequiredError

Bases: `TokenError`

Exception raised when a not fresh token was used in request.

Raised when fresh token is required.

`class` authx.exceptions.AccessTokenRequiredError

Bases: `TokenTypeError`

Exception raised when an `access` token is missing from request.

Raised when access token is required.

`class` authx.exceptions.RefreshTokenRequiredError

Bases: `TokenTypeError`

Exception raised when an `refresh` token is missing from request.

Raised when refresh token is required.

class authx.exceptions.InvalidToken

```
InvalidToken(errors)
```

Bases: `Exception`

When a token is invalid for all identity providers.

Initialize InvalidToken Exception.

PARAMETER	DESCRIPTION
`errors`	list of errors **TYPE:** `list[str]`

Source code in `authx/exceptions.py`

```
def __init__(self, errors: str) -> None:
    """Initialize InvalidToken Exception.

    Args:
        errors (list[str]): list of errors
    """
    self.errors = errors
```

attr errors `instance-attribute`

```
errors = errors
```

```
Raised when token is invalid.
```

March 20, 2026 March 19, 2026 GitHub