

ITI 1120

Module 9: Sorting and Searching Algorithms

@2015 Diana Inkpen, University of Ottawa, All rights reserved

General Concepts:

1. Sorting and searching algorithms on data structures.

General Objective: Efficient sorting and searching algorithms.

Result:

1. Problem resolutions that require traveling efficiently through data structures.

Theme 1. Sorting and searching algorithms on data structures

Sub-theme: Linear search

```
def find(x, k):  
    '''(list, int) -> bool  
    Returns True if k is in the list, otherwise False"  
>>>a = [10, 28, -5, 6, 31, 25, 10, -7, 10]  
>>>find(a, 25)  
True  
'''
```

```
find = False  
for val in x:  
    if val == k:  
        find = True    #the element is found  
        break          # thus we stop the loop  
return find
```

Sous-thème: Find the position of an element in a list

```
def whereIsK(x, k):  
    '''(list, int) -> int  
        Returns the position of k in the list x,  
        and -1 if k is not found  
    '''  
    position = -1  
    index = 0  
    while index < len(x) and (position == -1):  
        if x[index] == k:  
            position = index  
            break #we found the first occurrence of k  
        index = index + 1  
    return position
```

```
>>>a = [28, -5, 6, 31, 25, 10, 6, -7, 10]  
>>>whereIsK(a, 6)  
2
```

Sub-theme: Direct access using dictionaries

Works if the searched value is a key.

```
def findD(d, k):  
    '''(dict, str) -> bool  
    Returns True if k is in the dictionary, and False  
    otherwise"  
    >>>d1 ={'marie':100, 'jean': 86, 'nadia': 98}  
    >>>findD(d1, 'nadia')  
    True  
    '''  
  
    find = k in d    # check if the key k exists  
    return find
```

Sub-theme: Binary search in a sorted list

Overall if the value v we look for is small, we just need to look in the left side of the list. If the value is big, we look in the right side. If v is equal to the value in the middle, we stop. Otherwise we continue to search in half of the side just searched...

```
>>> binary _search([1, 3, 4, 5, 7, 9, 10], 9)
5
```

If $v = 9$, thus v is not equal to the value in the middle, 5. We look the half right side [7,9,10]. the new middle has the value 9. We have a hit!.

If $v = 10$, we continue to search in the right half [10] that we will hit in the middle.

If $v = 8$ we continue to search in the left half [7], we do not find it in the middle, we stop (when the list is empty) and returns -1 to specify that we did not find it.

Binary search in a sorted list

```
def binary_search(L, v):  
    """ (list, int) -> int  
    Returns the position of v in the sorted list L,  
    or -1 if v is not in L. """  
    position = -1  
    # i and j delimitate the section searched  
    i = 0  
    j = len(L) - 1  
    while i != j + 1:  
        m = (i + j) // 2 # find the middle  
        if L[m] == v:    # if found return the position  
            position = m  
            break  
        elif L[m] < v:  # look on the right  
            i = m + 1  
        else:           # look on the left  
            j = m - 1  
    return position
```

Merge two sorted lists

```
def merge(l1, l2):  
    ''' (list, list) -> list  
    takes 2 sorted lists and returns a new list with  
    the elements of the 2 lists in increasing order  
>>>merge([1,3,8], [2,3,10,12])  
[1, 2, 3, 3, 8, 10, 12]  
    '''  
  
    i,j = 0,0  
    l3 = []  
    while (i < len(l1)) and (j < len(l2)):  
        if l1[i] <= l2[j]:  
            l3.append(l1[i])  
            i = i + 1  
        else:  
            l3.append(l2[j])  
            j = j + 1
```

Merge two sorted lists (suite)

```
# one of the 2 lists is done (or both)
# test if l1 is done
while (i < len(l1)):
    l3.append(l1[i])
    i = i + 1
# test if l2 is done
while (j < len(l2)):
    l3.append(l2[j])
    j = j + 1
return l3
```


Sub-theme: Search algorithms Complexity

If the list has N elements, what is the maximum number of steps in the worst case?

- Simple search in a list

N

$O(N)$ (O denotes the complexity order)

- Binary search in a sorted list

$N/2 + N/4 + \dots + 1$

$O(\log_2 N)$

- Search of a key in a dictionary

$O(1)$

Sub-theme: Algorithms to sort out a list

Sorting = Ordering a list elements in an ascending order


- Simple sort (bubble sort)
- Sort by Insertion
- Sort by Selection
- Sort by merging (merge sort)

Sub-theme: Simple sort (bubble sort)


```
def bubbleSort(alist):  
    ''' (list)-> None  
    sort the list by switching consecutive elements that  
    are not in order. Repete if exchanges already occured  
    '''  
    exchanges = True  
    while exchanges:  
        exchanges = False  
        for i in range(len(alist)-1):  
            if alist[i] > alist[i+1]:  
                exchanges = True  
                alist[i], alist[i+1] = alist[i+1], alist[i]  
  
alist = [54,26,93,17,77,31,44,55,20]  
bubbleSort(alist)  
print(alist)
```

Sub-theme: Sorting by Insertion

- General idea: Insert a value in the good position in the list already sorted on the left. The first element is in the right position for the moment.




- Insert the second element in the good position in the list with an element [0:1] (insert 6 in the list [3] to get [3,6])



- Insert the third element in the list of two elements [0:2] (Insert 4 in the list [3,6] to get [3,4,6])



- Continue until the end of the list, for the last element. (Insert 2 in the list [3,4,6] to get [2,3,4,6]. Then 7 and after 9)



Sorting by Insertion.

Without changing the initial list. We return a new list.

```
def sort_by_insertion(L):  
    """ (list) -> list  
    Produce a new list L2 with the elements of L  
    in ascending order  
>>> L = [3, 4, 7, -1, 2, 5]  
>>> L2 = sort_by_insertion (L)  
>>> L2  
[-1, 2, 3, 4, 5, 7]  
>>> L  
[3, 4, 7, -1, 2, 5]    """  
  
    i = 0  
    L2 = []  
    while i != len(L):  
        insert(L2, L[i])  
        i = i + 1  
    return L2
```

Sorting by Insertion(suite) Without changing the initial list.

```
def insert(L, val):
    """ (list, int) -> None
    Precondition: L is already sorted
    Insert val in the correct position in L.
    >>> L = [1,3,6]
    >>> insert(L, 2)
    >>> L
    [1,2,3,6]
    """
    # find where to insert val. Start at the end of L and
    # search an element of smaller value
    i = len(L)
    while i != 0 and L[i - 1] >= val:
        i = i - 1
    L.insert(i, val)
```

Sorting by Insertion

The initial list is modified.

```
def sort_by_insertion(L):  
    """ (list) -> None  
    Sort the list L in ascending order  
>>> L = [3, 4, 7, -1, 2, 5]  
>>> sort_by_insertion (L)  
>>> L  
[-1, 2, 3, 4, 5, 7]  
    """  
  
    i = 0  
    while i != len(L):  
        insert(L, i)  
        i = i + 1
```


Sorting by Insertion (suite)

The initial list is modified.

```
def insert(L, b):
    """ (list, int) -> None
    Precondition: L[0:b] is already sorted
    Insert L[b] in the correct position in L[0:b + 1].
    >>> L = [3, 4, -1, 7, 2, 5]
    >>> insert(L, 2)
    >>> L
    [-1, 3, 4, 7, 2, 5] """
    # find or insert L[b]
    # start at the end of L[b] and search an element
    i = b # of smaller value
    while i != 0 and L[i - 1] >= L[b]:
        i = i - 1
    # move L[b] to index i
    value = L[b] # move the values after i on the right.
    del L[b]
    L.insert(i, value)
```


Sub-theme: Sorting by Selection

- General idea: select the smallest element (minimum) and put it at the proper position, on the left. The left side is sorted out and continue to increase until the list is sorted out.



- First of all, find the position ★ that contains the minimum



- Secondly, switch that position with the first element



- Continue with the list starting with the second element, 3-rd,



Sorting by Selection.

The initial list is modified.

```
def sort_by_selection(L):  
    """ (list) -> None  
    Sort the elements of L in ascending order  
    >>> L = [3, 4, 7, -1, 2, 5]  
    >>> sort_by_selection (L)  
    >>> L  
    [-1, 2, 3, 4, 5, 7]  
    """  
    i = 0  
    while i != len(L):  
        # move the minimum to the left  
        min = find_min(L, i)  
        L[i], L[min] = L[min], L[i]  
        i = i + 1
```


Sorting by Selection (find_min)

```
def find_min(L, b):  
    """ (list, int) -> int  
    Precondition: L[b:] is not empty.  
    Returns the index of the minimal value in L[b:].  
    >>> find_min([3, -1, 7, 5], 0)  
    1  
    >>> find_min([3, -1, 7, 5], 2)  
    3  
    """  
    min = b # the index of the temporary minimum  
    i = b + 1  
    while i != len(L):  
        if L[i] < L[min]:  
            # we found a smaller element than the temporary  
            # minimum  
            min = i  
        i = i + 1  
    return min
```

Su-theme: Sorting by merging (merge sort)

```
def mergesort(L):  
    """ (list) -> None  
    Sort elements of L.  
    >>> L = [3, 4, 7, -1, 2, 5]  
    >>> mergesort(L)  
    >>> L  
    [-1, 2, 3, 4, 5, 7]  
    """
```

```
# Produce a temporary list. Each element of the list  
# produces a one element List. We can start the  
# process of merging  
temp = []  
for i in range(len(L)):  
    temp.append([L[i]])
```



Sorting by merging (merge sort) (suite)

```
# The two lists to be merged are temp[i] and temp[i+1].
# There is at least 2 lists to merge, we merge
# them and we repeat the process.
i = 0
while i < len(temp) - 1:
    L1 = temp[i]
    L2 = temp[i + 1]
    newL = merge(L1, L2)
    temp.append(newL)
    i = i + 2
# Copy the result in L.
if len(temp) != 0:
    L[:] = temp[-1][:]
```

Sub-theme: Sorting algorithms complexity

If the list has N elements, what is the maximum number of steps in the worst cases? (O = magnitude order)

- Simple sort (bubble sort)

$$(N-1) + (N-1) + \dots + (N-1) = (N-1)(N-1) = N^2 - 2N + 1$$

$$O(N^2)$$

- Sorting by Selection and sorting by Insertion

$$N + (N-1) + (N-2) + \dots + 1 = N(N+1)/2 = (N^2 + N)/2$$

$$O(N^2)$$

- Sort by merging

$$O(N \log_2 N)$$

Sub-theme: Execution time Measurement

```
# generate a list of 10000 random alues elements
L = random.sample(range(10000), 10000)

print(« SORTING ALGORITHM:")
    copy = L[:]
    t1 = time.perf_counter()
    sorting_algo(copy)
    t2 = time.perf_counter()
    print(t2-t1) # Execution time

# We replace sorting_algo with our algorithms
# and with the predefined function sort()

BUBBLE SORT:
29.11057368348544
SORTING BY SELECTION:
18.468290476188596
SORTING BY INSERTION:
7.289117465590792
MERGE SORT:
0.09519784972807344
PYTHON SORT:
0.003839320149005232
```

Question

If the list has $N = 10,000$ elements, how many operations (multiplications) are processed in the following function?

```
def my_fonction(a):  
    s = 0  
    for x in a:  
        for y in a:  
            s += x*y  
    return s
```

Pssibles responses (choose one):

- a) 10,000
- b) 100,000
- c) 100,000,000
- d) 1000

Question – *Solution*:

Correcte response: c)

Explanation: The outside loop is being processed 10,000 and for each of its execution, the inside loop is processed 10,000. Donc $10,000 * 10,000 = 100,000,000$

Conclusion

- Algorithms to visit data structures de données.
 - Searching algorithms.
 - Sorting algorithms.
 - Complexity and execution time.