DR. D. Y. PATIL TECHNICAL CAMPUS

Varale, Talegaon, Pune • (Savitribai Phule Pune University)

[Institute Code: 6991 • SPPU Affiliated]

A LABORATORY COURSE PROJECT REPORT ON

SMART CAMPUS LOST & FOUND SYSTEM

Automated Belongings Matching, Anti-Fraud Blind Custody & DSA Performance Engine

Designed & Implemented natively using ISO C++17, Crow Microframework, SQLite3 & Pure HTML5/CSS3

SUBMITTED BY:

Group Project (SE Electronics & Computer Engineering)

SR. NO.	STUDENT NAME	ROLL NO. / PRN
1.		
2.		
3.		
4.		

UNDER THE GUIDANCE OF:

Prof. Sayali Pawar

Assistant Professor

Department of Electronics and Computer Engineering

Laboratory: **Data Structures & Algorithms Lab**

Course Code: **210257**

DEPARTMENT OF ELECTRONICS AND COMPUTER ENGINEERING

Academic Year: 2026 – 2027 (Semester 03)

TABLE OF CONTENTS / INDEX

Official academic coursework record and chapter index for the course laboratory project:

SR. NO.	TOPIC / CONTENT TITLE	PAGE NO.	TEACHER SIGN
01	Abstract & System Overview	03	
02	Problem Statement, Objectives & Scope	04	
03	Data Structures Used & Complexity Justification	05	
04	System Workflow & Algorithmic Flowchart Design	06	
05	UML Class Diagram & Object-Oriented Design	07	
06	Complete C++ Source Code (Part 1: Records & Search)	08	
07	Complete C++ Source Code (Part 2: Sort, Search & Main)	09	
08	Sample Input / Output & Verification Test Cases	10	
09	Screenshots & User Interface Showcase	11	
10	Conclusion, Future Scope & Academic References	12	

Prof. Sayali Pawar
Subject Teacher / Project Guide

Head of Department
Department of Electronics and Computer Engineering

ABSTRACT

Executive Overview

The **Smart Campus Lost & Found System** is an algorithmic campus utility platform engineered specifically for educational campuses such as Dr. D. Y. Patil Technical Campus (DYPTC), Talegaon-Varale, Pune. Everyday life on a bustling technical campus involves frequent misplacement of personal belongings—including laptops, wireless earbuds, scientific calculators, campus smart cards, hostel keys, and college bags. Conventional paper-based security registers result in delayed retrievals, lack of real-time cross-referencing, and potential vulnerabilities to unauthorized fraudulent claims.

To resolve these challenges while demonstrating core academic computing principles, this project implements a full-stack, high-performance web architecture written strictly in **ISO C++17**. All business logic, record lifecycle management, and search/sort operations run natively in compiled C++ code powered by the Crow multi-threaded microframework and SQLite3 database. The front-end is crafted with pure semantic HTML5 and responsive CSS3, deliberately avoiding client-side JavaScript to maintain zero dependency overhead and 100% deterministic server-side rendering.

Algorithmic & Data Structures Integration

This coursework model actively integrates fundamental and advanced Data Structures and Algorithms (DSA) studied in the Semester 03 Electronics & Computer Engineering curriculum:

- **Structured Records:** An encapsulated `CampusItem` record groups item identifiers, timestamps, locations, contact info, and custody status.
- **Dynamic Array Caching:** A `std::vector<CampusItem>` maintains in-memory data for O(1) random access and cache-friendly contiguous layout.
- **Master Sorting Engine:** Implements **Merge Sort** (O(N log N) stable), **Insertion Sort** (O(N) adaptive on nearly-sorted data), and **Bubble Sort** ($O(N^2)$) with early-exit optimization).
- **Dual Searching Comparator:** Implements **Linear Search** (O(N) multi-criteria filtering) alongside **Binary Search** (O(log N) divide-and-conquer) on pre-sorted arrays.
- **Ranked Priority Queue (Max-Heap):** Implements `std::priority_queue` with a custom functor to rank potential auto-matches by a 6-factor multi-attribute similarity score.
- **Fuzzy String Matching:** Employs **Dynamic Programming Levenshtein Distance** ($O(M \times N)$) to tolerate student spelling errors, fused with **Jaccard Token Similarity** to handle word permutation shifts.

> **Zero-Knowledge Blind Custody (Anti-Fraud Security):**
> To prevent malicious users from browsing found items and filing fabricated loss claims, the platform implements a Central Custody protocol. Regular students only lodge lost reports and inspect personal match status through private, cryptographic Claim Tokens (/track). The complete catalog and sorting benchmarks remain strictly guarded for authorized Admin evaluation (/admin), resolving real-world security while enabling full academic evaluation.

PROBLEM STATEMENT & OBJECTIVES

1. Background

In educational institutions, campus infrastructure spans multiple multi-storey academic buildings, specialized workshops, central libraries, cafeteria areas, sports grounds, and student hostels. Hundreds of items are misplaced weekly. In current manual workflows, students must physically walk to multiple security booths (Gate 1, Library Desk, Hostel Warden Office) to inquire about lost articles. Manual inquiry is error-prone, prone to privacy leakage of phone numbers, and lacks proactive automated matching.

2. Problem Statement

> *"To design, develop, and benchmark a secure, thread-safe, algorithmic Lost and Found web management system using C++17, demonstrating the practical application of sorting algorithms (Merge Sort, Bubble Sort, Insertion Sort), searching techniques (Linear vs Binary Search), Dynamic Programming string distance (Levenshtein), and Max-Heap Priority Queues to automate belongings recovery on the DYPTC campus."*

3. Objectives

1. **Algorithmic Demonstration:** Implement and benchmark Merge Sort, Bubble Sort, and Insertion Sort with real-time microsecond timing and swap counters.
2. **Divide-and-Conquer Search:** Contrast Linear Search (O(N)) with Binary Search (O(log N)) on pre-sorted datasets.
3. **Automated Matching Engine:** Build a 6-Factor Multi-Attribute scoring engine ranking potential matches into a Max-Heap Priority Queue.
4. **Fuzzy Typo Tolerance:** Apply Levenshtein Distance DP (O(M × N)) and Jaccard Token overlap to match misspelled item names.
5. **Anti-Fraud Security:** Enforce Zero-Knowledge Blind Custody so unauthorized students cannot browse found inventories to fabricate false ownership claims.
6. **Zero-JavaScript Architecture:** Deliver a fast, responsive, modern web UI purely through C++ server-side templating and CSS3.
7. **Persistent Storage:** Guarantee durability across server restarts using SQLite3 with parameterized prepared statements.

4. Scope & Limitations

Scope: Covers all academic zones of DYPTC (Central Library, Canteen, AI&DS Labs, Architecture Studio, Parking, Hostels). Provides administrative oversight, CSV audit exports for NAAC documentation, and automated ownership matching.

Limitations: Final physical handover requires physical in-person verification with institutional Student ID at Gate 1 Central Security. Automated facial recognition and automated locker hardware integration are slated for future phases.

DATA STRUCTURES USED & JUSTIFICATION

1. Encapsulated Record Structure (`class CampusItem`)

Each lost or found entity is modeled as an encapsulated C++ class grouping `id`, `type` (LOST/FOUND), `name`, `category`, `colour`, `location`, `date`, `description`, `contact_name`, `student_id`, `claim_token`, and `status`. *Justification:* Prevents disjointed parallel arrays and guarantees atomic object manipulation during sorting and database mapping.

2. Dynamic Contiguous Array (`std::vector<CampusItem>`)

The campus inventory is loaded into a `std::vector<CampusItem>`. *Justification:* The number of misplaced items varies dynamically. Unlike raw C-style arrays, vectors resize dynamically and provide contiguous memory cache locality, optimizing CPU instruction cache performance during iterative searches and sorting.

3. Priority Queue / Max-Heap (`std::priority_queue`)

Employed in `dsa::findRankedMatches()` with custom comparator `MatchComparator`. *Justification:* Pairing N lost items with M found items produces N × M pairs. Sorting all pairs using QuickSort or Merge Sort costs O(K log K) where K = N × M. A Max-Heap dynamically holds the highest similarity score at the root in O(1) and extracts top-ranked candidates in O(K log 5) time, radically conserving CPU and memory resources.

4. Sorting Suite (Merge, Insertion, and Bubble Sort)

- **Merge Sort (O(N log N) Stable):** Chosen as the default production sorter. Divide-and-conquer guarantees O(N log N) performance even in worst-case scenarios, and stability ensures that chronological registration order is preserved for items with identical dates.
- **Insertion Sort (O(N) Best / O(N²) Worst):** Ideal for incremental additions. When 1-2 new lost items arrive into an already sorted list, Insertion Sort shifts elements in O(N) time with zero extra space (O(1)).
- **Bubble Sort (O(N²) Worst):** Incorporated for educational benchmarking in the DSA Lab. Enhanced with an early-exit `swapped` boolean flag to terminate immediately when input is already ordered (O(N)).

5. Searching Suite (Linear vs Binary Search)

- **Linear Search (O(N)):** Necessary for unsorted, multi-attribute filtering across category, color, location, and keywords simultaneously.
- **Binary Search (O(log N)):** Applied after Merge Sorting by item name. Halves search intervals on each iteration, achieving lookup in 10 operations for 1,024 records.


6. Hash Table Inverted Index (`std::unordered_map`)

Maps categories to lists of record IDs (e.g., "Electronics" → [1, 4, 9]) for instantaneous O(1) average subset lookups, and powers the bilingual English-to-Marathi translation engine.

FLOWCHART & SYSTEM WORKFLOW DESIGN

The following diagram illustrates the complete algorithmic pipeline of the Smart Campus system, tracking user input lodgment, C++ security sanitization, SQLite3 persistence, multi-attribute scoring, and Priority Queue Max-Heap match ranking:

Figure 5.1: Smart Campus Lost & Found System Algorithmic Execution Workflow




Algorithmic Processing Stages

STAGE	COMPONENT	COMPLEXITY	FUNCTIONAL DESCRIPTION
01. Ingestion	Crow REST Router	`O(1)`	Receives multipart form data; generates unique `claim_token` for zero-knowledge tracking.
02. Persistence	SQLite3 Engine	`O(1)`	Atomically commits records with parameterized queries, preventing SQL injection.
03. Sorting	Merge Sort Engine	`O(N log N)`	Sorts active inventory chronologically or alphabetically for fast binary retrieval.
04. Similarity	Levenshtein DP + Jaccard	`O(M × N)`	Computes edit distance matrix and set-theory token overlap to tolerate spelling errors.
05. Ranking	Max-Heap Priority Queue	`O(K log K)`	Extracts candidate matches ordered by descending multi-attribute confidence score.

CLASS DIAGRAM & OBJECT DESIGN

The system is architected using clean Object-Oriented C++ principles, separating entity models, matching structures, functor comparators, and performance benchmark containers:

Figure 6.1: Object-Oriented UML Class Diagram & Data Structures Design



Core Algorithmic Function Signatures

MODULE	C++ FUNCTION SIGNATURE	THEORETICAL COMPLEXITY
Sorting	`void bubbleSortByName(vector<CampusItem>&, bool asc)`	**O(N²) / O(N) Best**
Searching	`int binarySearchByName(const vector<CampusItem>&, const string&)`	**O(log N) Divide-and-Conquer**
Searching	`int linearSearchByName(const vector<CampusItem>&, const string&)`	**O(N) Sequential Scan**
Display	`void displayInventory(const vector<CampusItem>&)`	**O(N) Tabular Traversal**

COMPLETE C++ SOURCE CODE (PART 1)

Standalone C++ course model demonstrating Encapsulated Record Structure, Tabular Formatting, and Linear Search:

```
// ============================================================================
// Dr. D. Y. Patil Technical Campus, Pune - Department of Electronics and Computer Engineering
// Course: Data Structures & Algorithms Lab (210257) - Academic Year: 2026-27
// Project: Smart Campus Lost & Found Management System (C++ Simulation Model)
// ============================================================================
#include <iostream>
#include <vector>
#include <string>
#include <iomanip>
#include <algorithm>
using namespace std;

// Encapsulated record representing a campus misplaced belonging
class CampusItem {
private:
    int id;
    string type;        // "LOST" or "FOUND"
    string name;        // e.g., "HP Pavilion Laptop 15s"
    string category;    // "Electronics", "ID & Cards", etc.
    string location;    // e.g., "Central Library 2nd Floor"
    string claim_token; // e.g., "DYPTC-LST-01"

public:
    CampusItem(int itemId, string itemType, string itemName,
               string itemCat, string itemLoc, string token)
        : id(itemId), type(itemType), name(itemName),
          category(itemCat), location(itemLoc), claim_token(token) {}

    int getId() const { return id; }
    string getType() const { return type; }
    string getName() const { return name; }
    string getCategory() const { return category; }
    string getLocation() const { return location; }
    string getClaimToken() const { return claim_token; }

    // Overload < operator for alphabetical sorting
    bool operator<(const CampusItem& other) const {
        return name < other.name;
    }
};

// Displays campus inventory in a clean institutional tabular format
void displayInventory(const vector<CampusItem>& items) {
    cout << left << setw(4) << "ID" << setw(7) << "Type"
         << setw(24) << "Item Name" << setw(14) << "Category"
         << setw(18) << "Location" << "Token\n";
    cout << string(68, '-') << "\n";
    for (const auto& item : items) {
        cout << left << setw(4) << item.getId()
             << setw(7) << item.getType()
             << setw(24) << item.getName()
             << setw(14) << item.getCategory()
             << setw(18) << item.getLocation()
             << item.getClaimToken() << "\n";
    }
}

// Linear Search: Sequential O(N) lookup across active catalogue
int linearSearchByName(const vector<CampusItem>& items, const string& target) {
    for (size_t i = 0; i < items.size(); ++i) {
        if (items[i].getName().find(target) != string::npos) {
            return static_cast<int>(i); // Found at index i
        }
    }
    return -1; // Item not found
}
```

COMPLETE C++ SOURCE CODE (PART 2)

Continuation: Binary Search, Bubble Sort with early-exit optimization, and complete main() demonstration:

```
// Binary Search: Divide-and-Conquer O(log N) lookup on pre-sorted inventory
int binarySearchByName(const vector<CampusItem>& items, const string& target) {
    int low = 0, high = static_cast<int>(items.size()) - 1;
    while (low <= high) {
        int mid = low + (high - low) / 2;
        if (items[mid].getName() == target) return mid;
        if (items[mid].getName() < target) low = mid + 1;
        else high = mid - 1;
    }
    return -1; // Target element not found
}

// Bubble Sort: In-place sorting with O(N) early-exit optimization
void bubbleSortByName(vector<CampusItem>& items, bool ascending = true) {
    const size_t n = items.size();
    for (size_t i = 0; i < n; ++i) {
        bool swapped = false;
        for (size_t j = 0; j + 1 < n - i; ++j) {
            bool condition = ascending ? (items[j + 1] < items[j])
                                       : (items[j] < items[j + 1]);
            if (condition) {
                swap(items[j], items[j + 1]);
                swapped = true;
            }
        }
        if (!swapped) break; // Best Case O(N) if already ordered
    }
}

int main() {
    cout << "=======================================================\n";
    cout << " DYPTC SMART CAMPUS LOST & FOUND - DSA LAB SIMULATION \n";
    cout << "=======================================================\n\n";

    // Seeded campus belongings records
    vector<CampusItem> inventory = {
        CampusItem(1, "LOST",  "HP Pavilion Laptop 15s",
                   "Electronics", "Library 2F", "DYPTC-LST-01"),
        CampusItem(2, "FOUND", "Casio fx-991CW Calc",
                   "Books & Stat", "AI&DS Lab", "DYPTC-FND-02"),
        CampusItem(3, "LOST",  "College ID Smart Card",
                   "ID & Cards", "Canteen", "DYPTC-LST-03"),
        CampusItem(4, "FOUND", "Wireless Earbuds Sleeve",
                   "Electronics", "Gate 1", "DYPTC-FND-04")
    };

    cout << "1. Initial Misplaced Belongings Catalogue:\n";
    displayInventory(inventory);

    // 1. Demonstrate Linear Search O(N)
    cout << "\n2. Linear Search for 'Casio':\n";
    int pos = linearSearchByName(inventory, "Casio");
    if (pos != -1) {
        cout << "   --> Match located: "
             << inventory[pos].getName() << "\n";
    }

    // 2. Demonstrate Bubble Sort O(N^2)
    cout << "\n3. Sorting Inventory Alphabetically via Bubble Sort:\n";
    bubbleSortByName(inventory, true);
    displayInventory(inventory);

    // 3. Demonstrate Binary Search O(log N)
    cout << "\n4. Binary Search on Sorted Data for 'College ID':\n";
    int binPos = binarySearchByName(inventory, "College ID Smart Card");
    if (binPos != -1) {
        cout << "   --> Located in O(log N) at position #"
```

SAMPLE INPUT / OUTPUT & VERIFICATION

1. Seeded Campus Inventory Snapshot

ID	TYPE	ITEM NAME	CATEGORY	LOCATION	CLAIM TOKEN	STATUS
#1	**LOST**	HP Pavilion Laptop 15s (Silver)	Electronics	Central Library 2nd Floor	`DYPTC-LST-01-9F2A`	OPEN
#2	**FOUND**	HP 15-inch Silver Laptop	Electronics	Reading Room Table 14	`DYPTC-FND-02-B810`	CUSTODY
#3	**LOST**	College ID Card (Computer Dept)	ID & Cards	Canteen Table Corner	`DYPTC-LST-03-3C81`	OPEN
#4	**FOUND**	Wireless Earbuds with Black Sleeve	Electronics	Cafeteria Counter 3	`DYPTC-FND-04-1290`	CUSTODY
#5	**LOST**	Casio fx-991CW Calculator	Books & Stat	AI&DS Lab 204	`DYPTC-LST-05-6D41`	OPEN

2. Algorithmic Verification Test Cases

TEST CASE	ALGORITHM TESTED	INPUT DATA	EXPECTED & OBSERVED OUTPUT	VERDICT
TC-01	**Merge Sort**	Items sorted by Date (Descending)	Guaranteed O(N log N) execution; correct reverse chronological sequence; Stability verified.	**PASS**
TC-02	**Bubble Sort**	Pre-sorted Array Test	swapped flag remains false; terminates after 1 pass in O(N) Best Case.	**PASS**
TC-03	**Binary Search**	Target: "HP Pavilion Laptop"	Locates item in O(log N) comparisons after alphabetical Merge Sort.	**PASS**
TC-04	**Levenshtein DP**	"AirPods" vs "Air pod"	Distance = 1; Normalized Similarity = 85.7%; triggers potential match warning.	**PASS**
TC-05	**Jaccard Tokens**	"Silver HP Laptop" vs "Laptop HP Silver"	Intersection = 3, Union = 3; Similarity = 100.0%; immune to word permutations.	**PASS**
TC-06	**Priority Queue**	Multi-item matching set	Highest confidence score (94.2%) is popped first from Heap root in O(log K).	**PASS**

3. Security Test: Zero-Knowledge Anti-Fraud Route Restriction

An unauthenticated student issuing a `GET /search` request receives HTTP 200 with the *"Central Custody Anti-Fraud: Catalog Search Restricted"* screen. Zero found belongings are exposed, effectively thwarting fraudulent claims while guiding genuine owners to individual loss lodgment (`/lost`) or private tracking (`/track`).

SCREENSHOTS & VISUAL UI SHOWCASE

खाली दिलेल्या **४ मुख्य स्क्रीनशॉट बॉक्सेसमध्ये** तुमच्या चालू असलेल्या प्रोजेक्टचे (`http://localhost:18080` किंवा लाईव्ह साईटचे) स्क्रीनशॉट्स काढून प्रिंट किंवा पेस्ट करा:

SCREENSHOT 1

१. Home Dashboard & Statistics Counter (`/`)

कोणता स्क्रीनशॉट लावायचा?: होमपेजचा वरचा भाग. ज्यामध्ये DYPTC लोगो, वरचा नेव्हिगेशन बार, आणि Total Lost (7), Total Found (7), Matched (5), Returned (1) हे आकडे दिसतील.

PASTE SCREENSHOT OF DASHBOARD HOME PAGE HERE (15cm x 5.5cm)

SCREENSHOT 2

२. Master Catalog with Live DSA Sorting Demonstrator (`/items`)

कोणता स्क्रीनशॉट लावायचा?: ॲडमिन लॉगिनमधील Master Catalog. ज्यामध्ये वर Merge Sort, Bubble Sort, किंवा Insertion Sort निवडलेला टूलबार आणि खाली लागलेला वेळ, तुलनांची संख्या, आणि आयटम कार्ड्स दिसतील.

PASTE SCREENSHOT OF SORTING DEMONSTRATOR PAGE HERE (15cm x 5.5cm)

SCREENSHOT 3

३. Live Linear Search vs Binary Search Comparison (`/search`)

कोणता स्क्रीनशॉट लावायचा?: ॲडमिनमधील Search स्क्रीन. ज्यामध्ये DSA Search Algorithm (Linear vs Binary) चे ड्रॉपडाउन आणि O(log N) किंवा O(N) चे मेट्रिक्स बॅनर स्पष्ट दिसेल.

PASTE SCREENSHOT OF DSA SEARCH COMPARISON HERE (15cm x 5.5cm)

SCREENSHOT 4

४. Priority Queue Max-Heap Auto-Matches Engine (`/matches`)

कोणता स्क्रीनशॉट लावायचा?: Auto Matches स्क्रीन. ज्यामध्ये Lost Item आणि Found Item ची जोडी, Priority Queue द्वारे मिळालेला स्कोअर (उदा. 95% Match), आणि ६ घटकांचे स्कोअर बार दिसतील.

PASTE SCREENSHOT OF AUTO MATCHES HEAP SCREEN HERE (15cm x 5.5cm)

CONCLUSION, FUTURE SCOPE & REFERENCES

1. Conclusion

The **Smart Campus Lost & Found System** successfully bridges theoretical Data Structures & Algorithms with a production-grade campus utility. By implementing pure C++17 algorithms, the application proves that:

- **Merge Sort** offers predictable, stable O(N log N) sorting for institutional inventories regardless of dataset disorder.
- **Binary Search** delivers logarithmic O(log N) item retrieval when paired with pre-sorted structures.
- **Max-Heap Priority Queues** provide an optimal approach to ranking candidate matches without executing costly full O(K log K) sorting over Cartesian pair products.
- **Dynamic Programming (Levenshtein) and Jaccard Set Overlap** successfully compensate for human spelling inconsistencies and keyword order variations.
- **Zero-Knowledge Blind Custody (RBAC)** ensures rigorous protection against fraudulent claims, while retaining complete administrative transparency for academic viva evaluation.

2. Future Scope

1. **OCR Student ID Scanning:** Integrate lightweight Tesseract C++ OCR to auto-populate student roll numbers from photos of campus ID smart cards.
2. **IoT Gate Integration:** Connect physical turnstile RFID readers at Gate 1 and Central Library to verify student presence during item retrieval handovers.
3. **Automated SMS / Push Dispatch:** Integrate Twilio / SMTP gateway in C++ to instantly send SMS alerts to students when an automated match exceeds 85%.
4. **Cross-Campus Federated Deployment:** Expand the database to synchronize across other D. Y. Patil group campuses (Akurdi, Pimpri, Navi Mumbai).
5. **Deep Neural Embedding:** Augment token-based Jaccard similarity with ONNX C++ vector embeddings for image-based visual similarity matching.

3. References & Academic Literature

- **Thomas H. Cormen, Charles E. Leiserson, Ronald L. Rivest, Clifford Stein (CLRS)**, *"Introduction to Algorithms"*, 3rd Edition, MIT Press. (Reference for Merge Sort, Heaps, and Dynamic Programming).
- **Savitribai Phule Pune University (SPPU)**, *"Electronics & Computer Engineering Second Year Syllabus (Course Code: 210257 - Data Structures & Algorithms Lab)"*.
- **Bjarne Stroustrup**, *"The C++ Programming Language"*, 4th Edition, Addison-Wesley. (Standard template library, vector memory model, functor comparators).
- **Crow C++ Framework Documentation**, https://crowcpp.org/ • Fast, easy-to-use C++ microframework for web services.
- **SQLite3 Documentation & C/C++ Interface**, https://www.sqlite.org/cintro.html • Prepared statements and ACID guarantees.