



INTERNATIONAL TELECOMMUNICATION UNION  
**TELECOMMUNICATION  
STANDARDIZATION SECTOR**  
STUDY PERIOD 2017-2020

## **FOCUS GROUP ON AUTONOMOUS NETWORKS (FG-AN)**

**AN-I-163**

**Original: English**

**Question(s):** N/A

Virtual, 3-5 November 2021

### **INPUT DOCUMENT**

**Title:** Team “RAN-RIC-xApp” presentation – Build-a-thon – Activity-4- ORAN Control Loop Instantiation

**Contact:** Deena Mukundan

Email: [deenamukund@gmail.com](mailto:deenamukund@gmail.com)

**Contact:** Divyani R Achari

Email: [divyaniraj1d@gmail.com](mailto:divyaniraj1d@gmail.com)

**Keywords:** Build-a-thon, Model, Control Loop, xApp

**Abstract:** This contribution is a report on activities of team “RAN-RIC-xApp” towards the Build-a-thon hosted by ITU FG AN in ITU AI/ML in 5G Challenge (2021). It will cover the results obtained so far, and the open problems faced by the team.


## 1. Introduction

As discussed in [Build-a-thon FG AN], the “RAN-RIC-xApp” team registered for the Build-a-thon problem statement and worked to produce proof of concept (PoC) demo. This document is the report from the build-a-thon activity from team “RAN-RIC-xApp” done as part of the ITU AI/ML in 5G Challenge.

## 2. Problem statement

1. Goal-1 According to the given requirements fetch model from Acumos
2. Goal-2 Deploy the model as xApp in ORAN. A pre-trained model might be used for this purpose

## 3. Solution Workflow



**Note: E2 Indication is for future reference, currently data is not monitored via RIC Indication. In future, data needs to be monitored and sent to predict xApp.**

### Brief Work Summary:-

- RIC is UP and Running, RAN (E2-SIM in this case) is registered/associated with RIC
- RIC receives policy update from A1 for triggering closed loop PRB Allocation
- Fetch model based on the A1 Policy details
- Based on RAN data monitored, predict PRB utilisation [test data was used for POC instead of actual data from E2]
- Compute the PRB to be allocated and send E2 control message. PRB's are always reserved for Emergency Slide and additionally resources can be reallocated based on situational considerations
- Continuously monitor, evaluate and improve decision

Work Flow as defined in above figure :-

- Points 1&2 show E2 SIM is up and association with RIC is setup
- Point 3 nRT RIC receives A1 policy update to trigger closed loop monitoring
- Point 4 A1-mediator sends A1 Policy REQ to prbpred xApp
- Point 5a, Point 5b show the model is fetched from model store as per policy guidelines and prbpred instructs DataMon/Alloc xApp to start monitoring the data
- Point 6,7,8 shows the messaging done for subscribing to E2 for data
- Point 9 shows Data reception from E2 node. The received metrics are stored in metrics DB as in Point 10
- Upon timer expiry as in Point 11, request for Prediction is sent to prbpred xApp as in Point 12.
- prbpred uses ML model to predict the future utilisation. Based on new data model retraining may be done. Predicted values may be send to Datamon/Alloc xApp as in Points 13,14.
- DataMon/Alloc xApp computes the PRB to be allocated and sends E2 control message towards E2 as in Point 15

#### 4. Activity Results

##### Disclaimer:

The pre-trained model, model specific implementation and PRB allocation ALG1 developed by Team “AUTOMATO” as part of this build-a-thon is re-used in the below xApps. Please refer References [5] & [6] for details on report from Team “AUTOMATO”. The credit for the model implementation, design of closed loop working and PRB allocation scheme goes to Team “AUTOMATO”.

The primary focus of “RAN-RIC-xApp” team was as below: -

- 1) Develop understanding on ORAN-RIC Platform and bring up a fully functional setup
- 2) Understand, explore xApp deployment onto RIC Platform
- 3) Explore implementing different xApp variants (both reactive and proactive)
- 4) Explore messaging communication between xApp’s and RIC components

As part of this following points was achieved: -

- 1) ORAN-RIC platform was brought up with Dawn release content
- 2) Understanding of XApp onboarding/deployment process and RIC platform components was achieved

The below xApps are developed based on xApp Framework for Python. Separate xApp-descriptor files were defined detailing on the configuration, RX & TX messages supported.

a. prbpred xApp – Implementation Details

This xApp is responsible to receive A1\_POLICY\_REQ, save the policy details. Fetch the model from modelStore and save it. Based on timer trigger predict the future PRB utilisation and respond to alloc xApp for further processing.

i. Upon Initialization does following

1. registers for PRB\_PRED\_REQ (PRB Prediction Request) and A1\_POLICY\_REQ (A1 Policy Request)
2. queries A1-mediator and gets the Policy details

- ii. As part of step 8,9 in the sequence diagram mentioned in Reference [4]. A specific policy was created which gives info on model and model version info to be used.

- iii. Based on the policy details xApp fetches the model from model store and stores it locally
- iv. Upon reception of PRB\_PRED\_REQ, based on the model fetched performs prediction of PRB utilisation for each slice and sends response to Alloc xApp
- v. Following are the message types handled by this xApp  
Outgoing Message types: - "A1\_POLICY\_RESP",  
"PRB\_PRED\_RSP", "A1\_POLICY\_QUERY"  
Incoming Message Types - "PRB\_PRED\_REQ", "A1\_POLICY\_REQ"  
xApp Descriptor Details

```
{
  "xapp_name": "prbpredxapp",
  "version": "0.0.2",
  "containers": [
    {
      "name": "prbpredxapp",
      "image": {
        "registry": "nexus3.o-ran-sc.org:10002",
        "name": "o-ran-sc/ric-app-prbpred",
        "tag": "0.0.2"
      }
    }
  ],
  "messaging": {
    "ports": [
      {
        "name": "http",
        "container": "prbpredxapp",
        "port": 10003,
        "description": "http service"
      },
      {
        "name": "rmr-data",
        "container": "prbpredxapp",
        "port": 4560,
        "rxMessages": [
          "A1_POLICY_REQ",
          "PRB_PRED_REQ"
        ],
        "txMessages": [ "A1_POLICY_RESP",
          "PRB_PRED_RSP", "A1_POLICY_QUERY" ],
        "policies": [20008],
        "description": "rmr receive data port "
      },
      {
        "name": "rmr-route",
        "container": "prbpredxapp",
        "port": 4561,
        "description": "rmr route port "
      }
    ]
  },
  "rmr": {
    "protPort": "tcp:4560",
    "maxSize": 2072,
    "numWorkers": 1,
    "txMessages": [
      "PRB_PRED_RSP",
      "A1_POLICY_RESP",
      "A1_POLICY_QUERY"
    ],
    "rxMessages": [
```

```
        "PRB_PRED_REQ",  
        "A1_POLICY_REQ"  
    ],  
    "policies": [20008]  
  }  
}
```

b. Allocator xApp – Implementation Details

- i. Upon Initialization registers with subscription mgr. for E2 information  
And starts timer to trigger PRB\_PRED\_REQ periodically.
- ii. Based on predicted future PRB utilisation computes PRB to be allocated for emergency slice
- iii. A simple algorithm for PRB allocation (ALG1 from References [5] & [6]) is used here. In addition, some PRB's are shown as reserved for Emergency/High priority events.

Below are the details: -

Assumption taken is total no of PRB's in the system is 100

Slice #1 and Slice#2 have been configured with 35 PRB's each.

30 PRB's are reserved for Emergency/High priority events

Based on the predicted PRB utilisation received for each slice, the actual Value of PRB utilised is computed.

Utilised\_PRB\_slice1 = PRB\_ALLOC\_SLICE1\*(slice1\_utilisation/100)

Utilised\_PRB\_slice2= PRB\_ALLOC\_SLICE2\*(slice2\_utilisation/100)

$\text{total\_prb\_avail} = \text{Total\_PRB} - (\text{Utilised\_PRB\_slice1} + \text{Utilised\_PRB\_slice2})$

As this is Emergency event, the reserved PRB's are also made available.

- iv. Alloc xApp sends the E2 control message to allocate the available PRB's from the above calculation.

- v. Following are the message types handled by this xApp

Outgoing	Message	types:	-
			"PRB_PRED_REQ", "RIC_HEALTH_CHECK_RESP"
Incoming	Message	Types	-
			"PRB_PRED_RESP", "SUBSCRIPTION_REQ", "RIC_HEALTH_CHECK_REQ"

xApp Descriptor Details

```
"xapp_name": "alloc",  
"version": "0.0.2",  
"containers": [  
  {  
    "name": "alloc",  
    "image": {  
      "registry": "nexus3.o-ran-sc.org:10002",  
      "name": "o-ran-sc/ric-app-alloc",  
      "tag": "0.0.2"  
    }  
  }  
],  
"messaging": {  
  "ports": [  
    {  
      "name": "http",  
      "container": "alloc",  
      "port": 10005,  
      "description": "http service"  
    },  
    {
```

```
        "name": "rmr-data",
        "container": "alloc",
        "port": 4560,
        "txMessages":
["PRB_PRED_REQ", "RIC_HEALTH_CHECK_RESP"],
        "rxMessages": ["PRB_PRED_RESP",
"SUBSCRIPTION_REQ", "RIC_HEALTH_CHECK_REQ"],
        "policies": [],
        "description": "rmr receive data port for alloc"
    },
    {
        "name": "rmr-route",
        "container": "alloc",
        "port": 4561,
        "description": "rmr route port for alloc "
    }
]
},
"rmr": {
    "protPort": "tcp:4560",
    "maxSize": 2072,
    "numWorkers": 1,
    "rxMessages": ["PRB_PRED_RESP"],
    "txMessages": ["PRB_PRED_REQ"],
    "policies": []
},
"controls": {
    "fileStorage": false
},
"db" : {
    "waitForSdl": false
}
}
```

Successful communication between the XApp's and other RIC platform components was achieved as part of this.

- 3) A Model Store was developed to mimic Acumos and had access to the pre-trained model
- 4) E2 SIM setup was brought up and was successfully registered with E2 component in RIC platform

**Note:** In the Dawn release, creation of A1 policy instance doesn't trigger A1 Policy create message towards xApp. This was confirmed by ORAN-RIC team

<https://wiki.o-ran-sc.org/display/IAT/Traffic+Steering+Flows?focusedCommentId=41456537#comment-41456537>

The workflow was modified to send timer-based event from alloc XApp to trigger PRB prediction. Once the A1 mediator sends CREATE/UPDATE messages to xApp when the policy instance is created, the prbpred xApp can store the model information and perform prediction based on the trigger.

Below is the sequence of message flows: -

- 1) RIC Platform is brought up and then E2 SIM process is started. Upon start up, Simulator generates E2 Setup Request For each E2SM that is registered, includes RAN function definition. From the screenshot we can E2 Setup Request/Response. Points 1,2 in from the above fig are covered here

a. RIC Platform Snapshot

NAME	READY	STATUS	RESTARTS	AGE
deployment-ricplt-almediator-b4576889d-dqs2b	1/1	Running	60	41d
deployment-ricplt-alarmmanager-f59846448-76ts1	1/1	Running	36	41d
deployment-ricplt-appmgr-7cfbff4f7d-8gkmh	1/1	Running	36	41d
deployment-ricplt-e2mgr-556748b66f-9tgpx	1/1	Running	6	6d2h
deployment-ricplt-e2term-alpha-7dbd577c8d-dhcb4	1/1	Running	31	24d
deployment-ricplt-jaegeradapter-76ddb9c9-r464v	1/1	Running	41	41d
deployment-ricplt-olmediator-f7dd5fcc8-dt9kq	1/1	Running	36	41d
deployment-ricplt-rtmgr-7455599d58-np94f	1/1	Running	43	41d
deployment-ricplt-submgr-6cd6775cd6-x8z74	1/1	Running	36	41d
deployment-ricplt-vespamgr-757b6cc5dc-4vtzn	1/1	Running	36	41d
deployment-ricplt-xapp-onboarder-5958856fc8-p8bj1	2/2	Running	72	41d
r4-infrastructure-kong-7995f4679b-n65qm	2/2	Running	99	41d
r4-infrastructure-prometheus-alertmanager-5798b78f48-xks4r	2/2	Running	72	41d
r4-infrastructure-prometheus-server-c8ddcdf5-55tf8	1/1	Running	36	41d
ricplt-influxdb-meta-0	0/1	Pending	0	41d
statefulset-ricplt-dbaas-server-0	1/1	Running	36	41d

b. E2 SIM Process Snapshot

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS
f8dfa3da6cae	e2simul:1.0.0	"/bin/sh -c 'kpm_sim..."	5 seconds ago	Up 4 seconds

c. E2 Setup Request containing the gnb-Id and PLMN-id being sent from E2 interface

```
<E2setupRequestIEs>
  <id>3</id>
  <criticality><reject/></criticality>
  <value>
    <GlobalE2node-ID>
      <gNB>
        <global-gNB-ID>
          <plmn-id>37 34 37</plmn-id>
          <gnb-id>
            <gnb-ID>
              10110101110001100111011110001
            </gnb-ID>
          </gnb-id>
        </global-gNB-ID>
      </gNB>
    </GlobalE2node-ID>
  </value>
</E2setupRequestIEs>
<E2setupRequestIEs>
  <id>10</id>
  <criticality><reject/></criticality>
  <value>
    <RANfunctions-List>
      <ProtocolIE-SingleContainer>
        <id>8</id>
        <criticality><reject/></criticality>
        <value>
          <RANfunction-Item>
            <ranFunctionID>0</ranFunctionID>
            <ranFunctionDefinition>
```



```

30 00 00 00 05 4F 49 44 31 32 33 05 00 4B 50 4D
20 6D 6F 6E 69 74 6F 72 01 01 60 00 01 01 07 00
50 65 72 69 6F 64 69 63 20 72 65 70 6F 72 74 01
05 14 01 01 1D 00 4F 2D 44 55 20 4D 65 61 73 75
72 65 6D 65 6E 74 20 43 6F 6E 74 61 69 6E 65 72
20 66 6F 72 20 74 68 65 20 35 47 43 20 63 6F 6E
6E 65 63 74 65 64 20 64 65 70 6C 6F 79 6D 65 6E
74 01 01 01 01 00 01 02 1D 00 4F 2D 44 55 20 4D
65 61 73 75 72 65 6D 65 6E 74 20 43 6F 6E 74 61
69 6E 65 72 20 66 6F 72 20 74 68 65 20 45 50 43
20 63 6F 6E 6E 65 63 74 65 64 20 64 65 70 6C 6F
79 6D 65 6E 74 01 01 01 01 00 01 03 1E 80 4F 2D
43 55 2D 43 50 20 4D 65 61 73 75 72 65 6D 65 6E
74 20 43 6F 6E 74 61 69 6E 65 72 20 66 6F 72 20
74 68 65 20 35 47 43 20 63 6F 6E 6E 65 63 74 65
64 20 64 65 70 6C 6F 79 6D 65 6E 74 01 01 01 01
00 01 04 1E 80 4F 2D 43 55 2D 43 50 20 4D 65 61
73 75 72 65 6D 65 6E 74 20 43 6F 6E 74 61 69 6E
65 72 20 66 6F 72 20 74 68 65 20 45 50 43 20 63
6F 6E 6E 65 63 74 65 64 20 64 65 70 6C 6F 79 6D
65 6E 74 01 01 01 01 00 01 05 1E 80 4F 2D 43 55
2D 55 50 20 4D 65 61 73 75 72 65 6D 65 6E 74 20
43 6F 6E 74 61 69 6E 65 72 20 66 6F 72 20 74 68
65 20 35 47 43 20 63 6F 6E 6E 65 63 74 65 64 20
64 65 70 6C 6F 79 6D 65 6E 74 01 01 01 01 00 01
06 1E 80 4F 2D 43 55 2D 55 50 20 4D 65 61 73 75
72 65 6D 65 6E 74 20 43 6F 6E 74 61 69 6E 65 72
20 66 6F 72 20 74 68 65 20 45 50 43 20 63 6F 6E
6E 65 63 74 65 64 20 64 65 70 6C 6F 79 6D 65 6E
74 01 01 01 01
</ranFunctionDefinition>
<ranFunctionRevision>2</ranFunctionRevision>
</RANfunction-Item>
</value>
</ProtocolIE-SingleContainer>
</RANfunctions-List>
</value>
</E2setupRequestIEs>
</protocolIEs>
</E2setupRequest>

```

d. E2 Mgr. receiving E2 Setup Request

```

{"crit": "INFO", "ts": "1635747069353", "id": "E2Manager", "msg": "#E2SetupRequestNotificationHandler.Handle - E2T Address: 10.110.226.182:38000 - handling E2_SETUP_REQUEST", "mcdc": {"time": "2021-11-01 06:11:09.353"}},
{"crit": "INFO", "ts": "1635747069353", "id": "E2Manager", "msg": "#RnibDataService.GetE2Instance - E2 instance address: 10.110.226.182:38000, state: ACTIVE, associated RANs count: 0, keep Alive ts: 1635747046708612521", "mcdc": {"time": "2021-11-01 06:11:09.353"}},
{"crit": "INFO", "ts": "1635747069355", "id": "E2Manager", "msg": "#RnibDataService.SaveNodeB - nodeBInfo: ran_name: 'gnb_733_b5c67788' global_nb_id: {plmn_id: '3734373' nb_id: '101101011100001100110111000011'} node_type: GNB gnb: {ran_functions: {ran_function_definition: '30000000005494341323030504B5D402060F6E9746F720101600001010700506572696F669320726570672740105101010004F240455204D6561737572656D6567420436F6E7461696E65722066672207468652035474142036265637465624654706C6F796D65674701010100100102D004F240455204D6561737572656D6567420436F6E7461696E657220666722074686520354504320636F796D6563746562465046706C6F796D656747010101001001031B804F24355204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D656747010101001001041E804F24352D35470100465167137572656D6567420436F6E7461696E657220666722074686520354320636F796D6563746562465046706C6F796D65674701010100051E804F243552D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100061E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100071E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100081E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100091E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100101E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100111E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100121E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100131E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100141E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100151E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100161E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100171E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100181E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100191E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100201E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100211E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100221E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100231E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100241E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100251E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100261E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100271E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F796D65674701010100281E804F24352D550204D6561737572656D6567420436F6E7461696E6572206667220746865203547414203626563746562465046706C6F79
```

e. E2 Mgr changing the state as connected and sending response E2 setup response

```

{"crit":"INFO","ts":"1635474069356","id":"E2Manager","msg":{"#ranListManagerInstance.AddNbIdentity RAN name: gnb_734 733 b5c67788 Successfully added nodeb identity","mdc":{"time":"2021-11-01 06:11:09.356"}}}
{"crit":"INFO","ts":"1635474069356","id":"E2Manager","msg":{"#E2AssociationManager.AssociateRan - Associating RAN gnb_734 733 b5c67788 to E2T Instance address: 10.110.226.182:38000","mdc":{"time":"2021-11-01 06:11:09.356"}}}
{"crit":"INFO","ts":"1635474069356","id":"E2Manager","msg":{"[E2 Manager -> Routing Manager] #RoutingManagerClient.send Message - POST url: http://service-ricpl-rtmgr-http:3800/ric/v1/handles/associate-ran-to-e2t, request body: {\"Address\": \"10.110.226.182:38000\", \"ranNameList\": [\"gnb_734 b5c67788\"]}, \"mdc\": {\"time\": \"2021-11-01 06:11:09.356\"}}}
{"crit":"INFO","ts":"1635474069358","id":"E2Manager","msg":{"[Routing Manager -> E2 Manager] #RoutingManagerClient.send Message - success. http status code: 201,\"mdc\":{\"time\":\"2021-11-01 06:11:09.358\"}}}
{"crit":"INFO","ts":"1635474069358","id":"E2Manager","msg":{"#RanConnectStatusChangeManager.ChangeStatus - RAN name: gnb_734 733 b5c67788, currentStatus: UNKNOWN_CONNECTION_STATUS, nextStatus: CONNECTED,\"mdc\":{\"time\":\"2021-11-01 06:11:09.358\"}}}
{"crit":"INFO","ts":"1635474069358","id":"E2Manager","msg":{"#RanConnectStatusChangeManager.setEvent - Connectivity Event for RAN gnb_734 733 b5c67788 is: gnb_734 733 b5c67788 CONNECTED,\"mdc\":{\"time\":\"2021-11-01 06:11:09.358\"}}}
{"crit":"INFO","ts":"1635474069358","id":"E2Manager","msg":{"#RnibDataService.UpdateNodeBInfoOnConnectionStatusInversion - event: gnb_734 733 b5c67788 CONNECTED, nodeBInfo: ran name: \"gnb_734 733 b5c67788\" connection status: CONNECTED global nb id: plmn id: \"3734377\" nb id: \"10101011010001101001101100011\" node type: GNB gnb: ran function definition: \"300000000054f4944313230350405B04D206D6F6E69746F72010600001070056572696F6A6963207265706F727201051040100104F2D4455204D6561737572656D656E74204346F674161696E65720666772207468652035474320636F6E6E657374656474206465706C6F796D656E7401010100102D04D651737572656D656E74204346F674161696E65720666772207468652045572066677220636F6E6E657374656474206465706C6F796D656E7401010100103E1804F2D43552D4350204D6561737572656D656E74204346F674161696E65720666772207468652035474320636F6E6E657374656474206465706C6F796D656E7401010100104E1804F2D43552D4350204D6561737572656D656E74204346F674161696E65720666772207468652045572066677220636F6E6E657374656474206465706C6F796D656E7401010100101E1804F2D43552D4350204D6561737572656D656E74204346F674161696E65720666772207468652045572066677220636F6E6E657374656474206465706C6F796D656E740101010110100101G1804F2D43552D4350204D6561737572656D656E74204346F674161696E65720666772207468652045572066677220636F6E6E657374656474206465706C6F796D656E74010101011 ran function revision:2} gnb type:GNB associated e2t instance address: \"10.110.226.182:38000\" setup from network: true,\"mdc\":{\"time\":\"2021-11-01 06:11:09.358\"}}}
{"crit":"INFO","ts":"1635474069359","id":"E2Manager","msg":{"#RanConnectStatusChangeManager.updateNodeBInfoOnConnectionStatusInversion RAN name: gnb_734 733 b5c67788 - Successfully updated rNib,\"mdc\":{\"time\":\"2021-11-01 06:11:09.359\"}}}

```



```
bn:2] gnb_type:GNB] associated_e2t_instance_address:\10.110.226.182:38000\] setup_from_network:true", "mdc":{"time":  
"2021-11-01 06:11:09.359"}}  
"crit":"INFO","ts":1635747069359,"id":"E2Manager","msg":"#RnibDataService.GetE2TInstance - E2T instance address: 1  
10.226.182:38000, state: ACTIVE, associated RANs count: 0, keep Alive ts: 1635747046708612521", "mdc":{"time":"20  
21-11-01 06:11:09.359"}}  
"crit":"INFO","ts":1635747069359,"id":"E2Manager","msg":"#RnibDataService.SaveE2TInstance - E2T instance address:  
10.110.226.182:38000, podName: e2term, state: ACTIVE, associated RANs count: 1, keep Alive ts: 1635747046708612521"  
"mdc":{"time":"2021-11-01 06:11:09.359"}}  
"crit":"INFO","ts":1635747069359,"id":"E2Manager","msg":"#E2TInstancesManager.AddRansToInstance - RAN [gnb_734_733  
b5c67788] were added successfully to E2T 10.110.226.182:38000", "mdc":{"time":"2021-11-01 06:11:09.359"}}  
"crit":"INFO","ts":1635747069359,"id":"E2Manager","msg":"#E2TAssociationManager.AssociateRan - successfully associ  
ated RAN gnb_734_733_b5c67788 with E2T 10.110.226.182:38000", "mdc":{"time":"2021-11-01 06:11:09.359"}}  
"crit":"INFO","ts":1635747069360,"id":"E2Manager","msg":"#E2SetupRequestNotificationHandler.handleSuccessfulRespon  
se - payload: <E2AP-PDU><successfulOutcome><procedureCode>1</procedureCode><criticality><reject></criticality><val  
ue><E2setupResponse><protocolIEs><E2setupResponseIEs><id>4</id><criticality><reject></criticality><value><GlobalRI  
C-ID><PLMN-Identity>131014</PLMN-Identity><ric-ID>10101010110011001110</ric-ID></GlobalRIC-ID></value></E2setupResp  
onseIEs><E2setupResponseIEs><id>9</id><criticality><reject></criticality><value><RANFunctionsID-List><ProtocolIE-S  
ingleContainer><id>6</id><criticality><ignore></criticality><value><RANfunctionID-Item><ranFunctionID>0</ranFuncti  
onID><ranFunctionRevision>2</ranFunctionRevision></RANfunctionID-Item></value></ProtocolIE-SingleContainer></RANfun  
ctionsID-List></value></E2setupResponseIEs></protocolIEs></E2setupResponse></value></successfulOutcome></E2AP-PDU>"  
"mdc":{"time":"2021-11-01 06:11:09.360"}}  
"crit":"INFO","ts":1635747069360,"id":"E2Manager","msg":"#E2SetupRequestNotificationHandler.handleSuccessfulRespon  
se - RAN name: gnb_734_733_b5c67788 - RIC E2_SETUP_RESP message has been built successfully. Message: &{2ee2 676e62  
3733345f373335f6235633637373838 3c453241507245044553e3c7375636365737366756c4f7574636f64653e3c70726f63656475726564  
3733345f373335f6235633637373838 3c453241507245044553e3c7375636365737366756c4f7574636f64653e3c70726f63656475726564
```

f. E2 Setup Response at E2 SIM end

```
<E2setupResponse>  
  <protocolIEs>  
    <E2setupResponseIEs>  
      <id>4</id>  
      <criticality><reject></criticality>  
      <value>  
        <GlobalRIC-ID>  
          <PLMN-Identity>13 10 14</PLMN-Identity>  
          <ric-ID>  
            10101010110011001110  
          </ric-ID>  
        </GlobalRIC-ID>  
      </value>  
    </E2setupResponseIEs>  
    <E2setupResponseIEs>  
      <id>9</id>  
      <criticality><reject></criticality>  
      <value>  
        <RANFunctionsID-List>  
          <ProtocolIE-SingleContainer>  
            <id>6</id>  
            <criticality><ignore></criticality>  
            <value>  
              <RANfunctionID-Item>  
                <ranFunctionID>0</ranFunctionID>  
                <ranFunctionRevision>2</ranFunctionRevision>  
              </RANfunctionID-Item>  
            </value>  
          </ProtocolIE-SingleContainer>  
        </RANFunctionsID-List>  
      </value>  
    </E2setupResponseIEs>  
  </protocolIEs>  
</E2setupResponse>
```

g. E2 RAN registration can confirmed with response from below CURL command.

```
curl -v --location --request GET "http://10.244.0.128:3800/v1/e2t/list" --header  
'Content-Type: application/json'
```

Result displays the e2Term instance and RAN name associated

```
root@instance-2:~# curl -v --location --request GET "http://10.244.0.128:3800/v1/e2t/list" --header 'Content-Type: appl  
ication/json'  
Note: Unnecessary use of -X or --request, GET is already inferred.  
* Trying 10.244.0.128...  
* TCP_NODELAY set  
* Connected to 10.244.0.128 (10.244.0.128) port 3800 (#0)  
> GET /v1/e2t/list HTTP/1.1  
> Host: 10.244.0.128:3800  
> User-Agent: curl/7.58.0  
> Accept: */*  
> Content-Type: application/json  
>  
< HTTP/1.1 200 OK  
< Content-Type: application/json  
< Date: Mon, 01 Nov 2021 06:12:57 GMT  
< Content-Length: 75  
<  
< Connection #0 to host 10.244.0.128 left intact  
{\"e2tAddress\":\"10.110.226.182:38000\",\"ranNames\":[\"gnb_734_733_b5c67788\"]}root@instance-2:~#
```

h. Fetch the gNB details associated on trigger of GET request from E2mgr

```
curl -v --location --request GET
"http://10.244.0.128:3800/v1/nodeb/gnb_734_733_b5c67788" --header 'Content-
Type: application/json'
```

```
root@instance-254:~# curl -v --location --request GET "http://10.244.0.128:3800/v1/nodeb/gnb_734_733_b5c6f788" --header
Content-Type: application/json"
Note: Unnecessary use of -X or --request, GET is already inferred.
* Trying 10.244.0.128...
* TCP_NODELAY set
* Connected to 10.244.0.128 (10.244.0.128) port 3800 (#0)
> GET /v1/nodeb/gnb_734_733_b5c6f788 HTTP/1.1
Host: 10.244.0.128:3800
User-Agent: curl/7.58.0
Accept: */*
Content-Type: application/json

HTTP/1.1 200 OK
Content-Type: application/json
Date: Mon, 01 Nov 2021 06:16:10 GMT
Content-Length: 1264

{"ranName": "gnb_734_733_b5c6f788", "connectionStatus": "CONNECTED", "globalNbId": {"plmnId": "373437", "nbId": "1011010110001011011110001"}, "nodeType": "GNB", "ranInfo": {"ranFunctions": [{"ranFunctionDefinition": "300000000054F494431323305004B504206D66E69746F722074160001010700056572696F646963207265706F727401051401011D004F2D445E20465671737572656D656E74203436F6E7461696B7220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001021D004F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652045504320636F6E6E6563746564206465706C6F796D656E74010101010001031E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E7401010101000104103001011E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652045504320636F6E6E6563746564206465706C6F796D656E74010101010001051E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001061E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001071E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001081E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001091E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001101E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001111E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001121E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001131E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001141E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001151E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001161E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001171E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001181E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001191E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001201E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001211E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001221E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001231E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001241E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001251E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001261E804F2D445E20465671737572656D656E74203436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656E74010101010001271E804F2D445E20465671737572656D656E74203436
```

- 2) A1- Policy and Policy Instances are created by executing following curl commands
- `curl -X PUT --header "Content-Type: application/json" -d @create1.json http://<a1med_ip>:<a1med_port>/a1-p/policytypes/20008`
  - `curl -X PUT --header "Content-Type: application/json" --data '{"modelVersion": "1.0.0", "modelName": "prb_pred_model.pkl", "modelstoreUrl": "http://<modelstoreIp>:10001/model_store"}' http://<a1med_ip>:<a1med_port>/a1-p/policytypes/20008/policies/tsapolicy145`

Below snapshot shows the policy instance is created with the values supplied in the curl command

```
root@instance-2:~# curl --header "Content-Type: application/json" http://10.244.0.87:10000/ai-p/policytypes/20008/policies/tsapolicy145
{
  "modelVersion": "1.0.0",
  "modelName": "prb_pred_model.pkl",
  "modelstoreUrl": "http://34.72.49.222:10001/model_store"
}
```

- 3) Alloc xApp is deployed

```
root@instance-2:~# kubectl get pods -n ricxapp
```

NAME	READY	STATUS	RESTARTS	AGE
ricxapp-alloc-b9f994b84-x7zxr	1/1	Running	0	8h
ricxapp-prbpredxapp-66bfd5bc55-jhrmn	1/1	Running	0	8h

### Alloc xApp sends REST Subscription request to Subscription Manager

- 4) prbpred xApp is also deployed

Above snapshot shows both xApps being deployed

Prbpred xApp sends query to A1 mediator on the policy details. It receives A1 POLICY REQ from A1 mediator

- a. Emulated Acumos Model Store listening on 10001 port, receives REST REQ for fetching model. Acumos functionality was emulated considering HW requirements in bringing up actual Acumos.

```

my_env) root@instance-2: ~/customapp$ python modelstore.py

      db      .g8""'bgd `7MME' `7MF'\`7MMM.      ,MMF' .g8""'8q. .M""'bgd
;MM:      .dp' `M MM      M MMMb dPM d.p' `YM. ,MI .M'Y
,V'MM.    dM'      MM      M M YM ,M MM dM' `MM 'MMb.
,M `MM MM      MM      M M Mb M' MM MM      MM `YMMNg.
AbmmungMA MM.      MM      M M YM.P' MM MM.      ,MP .`MM
A' VML `Mb.      , YM.      ,M M `YM' MM `Mb.      ,dP' Mb dM
.AMA. .AMMA. `bmmmd' `bmmmd" .JML. `` .JMLL. `bmd" P'Ybmd"

Starting model store 2021-10-31 09:58:03.722292
* Serving Flask app 'modelstore' (lazy loading)
* Environment: production
  WARNING: This is a development server. Do not use it in a production deployment.
  Use a production WSGI server instead.
* Debug mode: off
* Running on all addresses.
  WARNING: This is a development server. Do not use it in a production deployment.
* Running on http://10.128.0.4:10001/ (Press CTRL+C to quit)
Received req2021-10-31 10:02:05.442191
34.72.49.222 - - [31/Oct/2021 10:02:05] "GET /model_store/1.0.0/prb_pred_model.pkl HTTP/1.1" 200 -
[connected, host fingerprint: ssh-rsa 0 5D:BB:9E:6A:26:75:A8:A0:87F8:1A:12:30:B78A:5D:B1:4A:4B:21:F6:E7FC3:95:59:6
7:FC:A7:E8:27:D4:DF

```

- b. Below Snapshot shows REST Req being sent to model store with the details received from A1 policy request. Model is successfully downloaded to prbpred container.

```

31-Oct-21 10:02:04 - pred_xapp created@@@
31-Oct-21 10:02:04 - AIPolicyInterface
31-Oct-21 10:02:04 - send ai_policy_query:: Sent AI policy query (AI_POLICY_QUERY)={ 'policy_type_id': '20008' }
{"ts": 1635674525435, "crit": "DEBUG", "id": "ricxappframe.xapp_frame", "mdc": {}, "msg": "run: invoking msg handle
r on type 20000"}
31-Oct-21 10:02:05 - request_handler.resp_handler:: Handler processing AI_POLICY_REQ request
31-Oct-21 10:02:05 - request_handler.resp_handler:: Handler verified policy request: {'operation': 'CREATE', 'polic
y_type_id': '20008', 'policy_instance_id': 'tsapolicy145', 'payload': {'modelVersion': '1.0.0', 'modelname': 'prb_p
red_model.pkl', 'modelstoreUrl': 'http://34.72.49.222:10001/model_store'}}
31-Oct-21 10:02:05 - AIPolicyInterface::request handler received payload {'modelVersion': '1.0.0', 'modelname': 'p
rb_pred_model.pkl', 'modelstoreUrl': 'http://34.72.49.222:10001/model_store'}
31-Oct-21 10:02:05 - store_model_info:: Fetch model from model store {'modelVersion': '1.0.0', 'modelname': 'prb_p
red_model.pkl', 'modelstoreUrl': 'http://34.72.49.222:10001/model_store'}
31-Oct-21 10:02:05 - pull_model::Sent Download request to model store http://34.72.49.222:10001/model_store/1.0.0/
31-Oct-21 10:02:05 - pull_model::Successfully Downloaded model to ./prbpred/prb_pred_model.pkl
1635674525 1/RMR [INFO] sends: ts=1635674525 src=service-ricxapp-prbpredxapp-rmr.ricxapp:4560 target=service-ricxap
p-alloc-rmr:4560 open=0 succ=0 fail=0 (hard=0 soft=0)
1635674525 1/RMR [INFO] sends: ts=1635674525 src=service-ricxapp-prbpredxapp-rmr.ricxapp:4560 target=service-ricpl
t-almediator-rmr.ricplt:4562 open=1 succ=1 fail=0 (hard=0 soft=0)
/opt/conda/lib/python3.7/site-packages/sklearn/base.py:333: UserWarning: Trying to unpickle estimator GaussianProce
ssRegressor from version 0.24.1 when using version 1.0.1. This might lead to breaking code or invalid results. Use
 it at your own risk. For more info please refer to:
https://scikit-learn.org/stable/modules/model_persistence.html#security-maintainability-limitations
UserWarning,
31-Oct-21 10:02:05 - store_model_info::Saved Model info
31-Oct-21 10:02:05 - request_handler.resp_handler:: AI_POLICY_RESP Response sent: {'policy_type_id': '20008', 'polic
y_instance_id': 'tsapolicy145', 'payload': {'modelVersion': '1.0.0', 'modelname': 'prb_pred_model.pkl', 'modelstor
eUrl': 'http://34.72.49.222:10001/model_store'}, 'handler_id': 'prbpredxapp', 'status': 'OK'}
{"ts": 1635674553708, "crit": "DEBUG", "id": "ricxappframe.xapp_frame", "mdc": {}, "msg": "run: invoking msg handle
r on type 30003"}
31-Oct-21 10:02:33 - predict handler received payload b'1'
31-Oct-21 10:02:33 - Predictor::predict()
31-Oct-21 10:02:33 - Predictor::predict()
/opt/conda/lib/python3.7/site-packages/sklearn/base.py:333: UserWarning: Trying to unpickle estimator GaussianProce
ssRegressor from version 0.24.1 when using version 1.0.1. This might lead to breaking code or invalid results. Use
 it at your own risk. For more info please refer to:
https://scikit-learn.org/stable/modules/model_persistence.html#security-maintainability-limitations
UserWarning,
31-Oct-21 10:02:33 - Predicted value for Slice 1&2 : b'{"prediction": [71.7, 70.6]}'
31-Oct-21 10:02:33 - Sending message to alloc xApp : b'{"prediction": [71.7, 70.6]}'
31-Oct-21 10:02:33 - predict handler: sent message successfully

```

- 5) On Timer expiry Alloc xApp sent PRB\_PRED\_REQ to prbpred xApp and Prbpred xApp receives PRB\_PRED\_REQ, performs prediction of the PRB's and sends message to Alloc XAPP

```
31-Oct-21 10:03:33 - predict handler received payload b'1'
31-Oct-21 10:03:33 - Predictor::predict()
/opt/conda/lib/python3.7/site-packages/sklearn/base.py:333: UserWarning: Trying to unpickle estimator GaussianProcessRegressor from version 0.24.1 when using version 1.0.1. This might lead to breaking code or invalid results. Use at your own risk. For more info please refer to:
https://scikit-learn.org/stable/modules/model_persistence.html#security-maintainability-limitations
UserWarning,
31-Oct-21 10:03:33 - Predictor::predict()
/opt/conda/lib/python3.7/site-packages/sklearn/base.py:333: UserWarning: Trying to unpickle estimator GaussianProcessRegressor from version 0.24.1 when using version 1.0.1. This might lead to breaking code or invalid results. Use at your own risk. For more info please refer to:
https://scikit-learn.org/stable/modules/model_persistence.html#security-maintainability-limitations
UserWarning,
31-Oct-21 10:03:33 - Predicted value for Slice 1&2 : b'{"prediction": [71.7, 70.6]}'
31-Oct-21 10:03:33 - Sending message to alloc xApp : b'{"prediction": [71.7, 70.6]}'
31-Oct-21 10:03:33 - predict handler: sent message successfully
1635674618 1/RMR [INFO] sends: ts=1635674618 src=service-ricxapp-prbpredxapp-rmr.ricxapp:4560 target=service-ricxapp-p-alloc-rmr:4560 open=0 succ=0 fail=0 (hard=0 soft=0)
1635674618 1/RMR [INFO] sends: ts=1635674618 src=service-ricxapp-prbpredxapp-rmr.ricxapp:4560 target=service-ricplmt-almediator-rmr.ricplmt:4562 open=1 succ=2 fail=0 (hard=0 soft=0)
1635674618 1/RMR [INFO] sends: ts=1635674618 src=service-ricxapp-prbpredxapp-rmr.ricxapp:4560 target=service-ricxapp-p-alloc-rmr.ricxapp:4560 open=1 succ=1 fail=0 (hard=0 soft=0)
```

- 6) Alloc xApp receives PRB\_PRED\_RSP from prbpred xApp, computes the PRB to be allocated and sends control message to E2

```
31-Oct-21 10:03:33 - [msg to pred]
31-Oct-21 10:03:33 - [INFO] Message to pred : message sent Successfully
31-Oct-21 10:03:33 - [INFO] Received acknowledgement from pred (PRB_PRED_RSP): {'payload': b'{"prediction": [71.7, 70.6]}', 'payload length': 28, 'message type': 30002, 'subscription id': -1, 'transaction id': b'aaec35103a3111ec832aeada170f84a', 'message state': 0, 'message status': 'RMR_OK', 'payload max size': 3136, 'meid': b'', 'message source': 'service-ricxapp-prbpredxapp-rmr.ricxapp:4560', 'errno': 0}
31-Oct-21 10:03:33 - Estimated PRB usage of Slice 1:25
31-Oct-21 10:03:33 - Estimated PRB usage of Slice 2:25
31-Oct-21 10:03:33 - PRB allocated to Emergency Slice :50
```

#### 4. Code Repository

[Github] [https://github.com/deenammd/ITUML5GChallenge\\_BuildaThon](https://github.com/deenammd/ITUML5GChallenge_BuildaThon)

#### 5. Open issues

- ricplt-influxdb-meta-0 pod is in pending state in RIC platform. Tried all the suggestion as mentioned in RIC wiki but couldn't succeed
- Not receiving Subscription response from Subscription Manager
- Behaviour of A1 mediator sending A1 POLICY REQ to xApps when policy instance is CREATED/UPDATED is suppressed in Dawn release

#### 6. Future activities

- Build a multivariant timeseries model with monitored data and arrive at proper inference.
- It is recommended that gNode/E2 interface has reserved resources for Emergency situations. Additionally, based on the situation resource reallocation from lower QOS based services should be explored.
- Develop a user friendly webapp to onboard xApp's & trigger policy towards near-RT RIC and support visualisations
- Extend the solution to self-learning Closed Loops with following capabilities: -
  - Continuously perform Collection, Analytics, Decision and Actuation
  - Detect model performance and trigger a switch-over to another better performing model
  - Analyse and trigger different set of data/measurements for data analysis
- Points for future study from FGAN-O-013: -
  - How ML pipelines can be synchronized/managed across the edge and emergency responder devices?



- ii. The split of inference tasks/model functionalities between edge and emergency responder devices

## 8. REFERENCES

1. [1] A. Dandekar, J.Schulz-Zander, H.Wissing, Fraunhofer HHI, “Use case and requirements for orchestration of AI/ML based closed loops to enable autonomous networks”, Fraunhofer HHI, Apr., 2021.
2. [Build-a-thon FG AN] ITU-T FG AN-I-146 “Proposal for a “Build-a-thon” for ITU AI/ML in 5G Challenge (second edition, 2021), aligned with FGAN WG3” <https://extranet.itu.int/sites/itu-t/focusgroups/an/input/FGAN-I-114-R1.docx>
3. [Build-a-thon Challenge] ITU-T AI/ML in 5G Challenge problem statement “ITU-ML5G-PS-014: Build-a-thon (PoC) Network resource allocation for emergency management based on closed loop analysis” <https://challenge.aiforgood.itu.int/match/matchitem/45>
4. [https://github.com/ITU-build-a-thon/challenge-resources/blob/main/intro\\_tutorial.pdf](https://github.com/ITU-build-a-thon/challenge-resources/blob/main/intro_tutorial.pdf)
5. FGAN-153 “Team AUTOMATO” [https://extranet.itu.int/sites/itu-t/focusgroups/an/\\_layouts/15/WopiFrame.aspx?sourcedoc=%7B85757552-DFBE-479A-A816-003AE91C2B22%7D&file=FGAN-I-155.docx&action=default](https://extranet.itu.int/sites/itu-t/focusgroups/an/_layouts/15/WopiFrame.aspx?sourcedoc=%7B85757552-DFBE-479A-A816-003AE91C2B22%7D&file=FGAN-I-155.docx&action=default)
6. Pre-trained model and repository [https://github.com/krcmehmet/ITUChallenge\\_BuildaThon\\_Activity4](https://github.com/krcmehmet/ITUChallenge_BuildaThon_Activity4)
7. Near Realtime RIC <https://wiki.o-ran-sc.org/display/GS/Near+Realtime+RIC+Installation>
8. <https://wiki.o-ran-sc.org/display/ORANSdk/App+Writing+Guide>
9. <https://github.com/o-ran-sc>
10. <https://lists.o-ran-sc.org/g/main/topics>
11. [https://docbox.etsi.org/ISG/ZSM/Open/Drafts/009-3ed111\\_Cla\\_AdvTop/ZSM-009-3\\_Cla\\_AdvTopv010](https://docbox.etsi.org/ISG/ZSM/Open/Drafts/009-3ed111_Cla_AdvTop/ZSM-009-3_Cla_AdvTopv010)

## Appendix-1 Steps to recreate demo setup

### 1) Near Realtime RIC Installation

#### System requirements: -

VM Minimum Requirements for RIC 22 –  
OS: Ubuntu 18.04 LTS (Bionic Beaver)  
CPU(s): 4  
RAM: 16 GB  
Storage: 160 GB

The following are the steps to be followed to set up the RIC platform –

1. Obtaining the deployment scripts and charts
  - `sudo -i`
  - `git clone http://gerrit.o-ran-sc.org/r/it/dep -b bronze`
  - `cd dep`
  - `git submodule update --init --recursive --remote`
2. Change the repository value in the values.yaml file in the /ric-dep/helm/infrastructure/subcharts/kong/. Refer to the following link <https://gerrit.o-ran-sc.org/r/c/ric-plt/ric-dep/+6502/1/helm/infrastructure/subcharts/kong/values.yaml>
3. Generation of cloud-init script
  - `cd tools/k8s/bin`
  - `./gen-cloud-init.sh`
4. Installation of Kubernetes, Helm, Docker
  - `./k8s-1node-cloud-init-k_1_16-h_2_17-d_cur.sh`
  - `sudo -i`
  - `kubectl get gods --all-namespaces` (There should be 9 pods running in kube-system namespace.)
5. Helm3 installation steps
  - `curl -fsSL -o get_helm.sh https://raw.githubusercontent.com/helm/helm/master/scripts/get-helm-3`
  - `chmod 700 get_helm.sh`
  - `./get_helm.sh`
6. Deploy RIC using Recipe
  - `cd dep/bin`
  - `./deploy-ric-platform -f ../RECIPE_EXAMPLE/PLATFORM/example_recipe_oran_dawn_release.yaml`
  - `kubectl get pods -n ricplt` (There should be ~16 pods running in the ricplt namespace)

RIC platform pods



## 2) E2 Simulator setup

### 1. Install dependencies

- `sudo apt-get update`
- `sudo apt-get install -y build-essential git cmake libsctp-dev lksctp-tools autoconf automake libtool bison flex libboost-all-dev`  
`sudo apt-get clean`
- `sudo apt-get clean`

### 2. Build and Deploy E2Simulator

- `clone sim/e2-interface`
- `mkdir build`
- `cd build`
- `cmake ..`
- `make package`
- `cmake .. -DDEV_PKG=1`
- `make package`
- In the root directory of e2sim: Follow directions in README to produce the deb files
- Since the deb files are not yet pushed to package cloud, we need to copy them
- `cp e2sim*.deb ../e2sm_examples/kpm_e2sm`
- `cd ../e2sm_examples/kpm_e2sm`
- Edit the Dockerfile at the bottom to have IP address of service-ricplt-e2term-sctp-alpha service
- `docker build .`
- `docker tag <image id> e2simul:1.0.0`
- `docker run -d e2simul:1.0.0`

## 3) XApp installation steps

- `docker run --rm -u 0 -it -d -p 8090:8080 -e DEBUG=1 -e STORAGE=local -e STORAGE_LOCAL_ROOTDIR=/charts -v $(pwd)/charts:/charts chartmuseum/chartmuseum:latest`
- `export CHART_REPO_URL=http://0.0.0.0:8090`
- `cd appmgr/xapp_orchestrator/dev/xapp_onboarder`
- `pip3 uninstall xapp_onboarder`
- `pip3 install ./`
- `dms_cli onboard --config_file_path=config.json --shcema_file_path=/root/dep/bin/appmgr/xapp_orchestrator/dev/docs/xapp_onboarder/guide/embedded-schema.json`
- `curl -X GET http://localhost:8090/api/charts | jq .`
- `dms_cli install --xapp_chart_name=<app-name> --version=1.0.0 --namespace=ricxapp`
- `kubectl get pods -n ricxapp` ( xapp should be up and running)

For specific details on onboarding prbrpred and alloc x-app please refer README in [https://github.com/deenammd/ITUML5GChallenge\\_BuildaThon](https://github.com/deenammd/ITUML5GChallenge_BuildaThon)