

ITU ML5G Build-a-thon

Demonstrate POC done as part of
Activity-4 –ORAN Control Loop
Instantiation

Team -RAN-RIC-xApp
Deena Mukundan
Divyani Achari

GOALS

Goal-1 On reception of Emergency Intent According to the given requirements fetch model from Acumos.

Goal-2 Deploy the model as xApp in ORAN. A pre-trained model might be used for this purpose -

Build-a-thon Activity-4

Achievements


Brought up ORAN-RIC platform with Dawn release content and attained hands-on knowledge on RIC Platform

Implemented & Deployed 2 custom xApps in RIC platform that interacts with RIC platform components and amongst each other

Implemented capability to dynamically fetch model from a remote model store based on A1 policy configured

Brought up E2 SIM process and registered with RIC E2 components

Workflow- Network Resource Allocation



- RIC is UP and Running, RAN(E2-SIM in this case) is registered/associated with RIC
- RIC receives policy update from A1 for triggering closed loop PRB Allocation
- Fetch model based on the A1 Policy details
- Based on RAN data monitored, predict PRB utilisation [test data was used for POC instead of actual data from E2]
- Compute the PRB to be allocated and send E2 control message. PRB's are always reserved for Emergency Slide and additionally resources can be reallocated based on situational considerations
- Continuously monitor, evaluate and improve decision

Note: E2 Indication is for future reference, currently data is not received via RIC Indication. In future, based on subscription E2 interface will receive data via RIC Indication.

Credit Note: The pre-trained model, model specific implementation and PRB allocation ALG1 developed by Team “AUTOMATO” as part of this build-a-thon is re-used for this POC

xApp POC Implementation Details

Prbpred- xApp is developed as Reactive xApp


- i. Upon Initialization does following :-
 - i. Registers for PRB_PRED_REQ (PRB Prediction Request) and A1_POLICY_REQ (A1 Policy Request)
 - ii. xApp provides details of the policy supported in xApp-descriptor and registers handler function to receive A1_POLICY_REQ
 - iii. Queries A1-mediator and gets the Policy details
 - iv. As part of step 4,5a in the sequence diagram mentioned in Reference [4]. A specific policy was created which gives info on model and model version info to be used.
- ii. Based on the policy details xApp fetches the model from remote model store by constructing the URL based on the information received and stores it locally
- iii. Upon reception of PRB_PRED_REQ, based on the model fetched performs prediction of PRB utilisation for each slice and sends response to Alloc xApp
- iv. Following are the message types handled by this xApp
 - i. Outgoing Message types: - "A1_POLICY_RESP", "PRB_PRED_RSP", "A1_POLICY_QUERY"
 - ii. Incoming Message Types - "PRB_PRED_REQ", "A1_POLICY_REQ"

alloc xApp – is developed as proactive xApp

- i. Is as Proactive xApp
- ii. Upon Initialization does following:-
 - i. registers with subscription mgr. for E2 information
 - ii. And starts timer to trigger PRB_PRED_REQ periodically.
- iii. Based on predicted future PRB utilisation computes PRB to be allocated for emergency slice
- iv. Emergency slice has reserved PRB's, in addition the remaining unutilised PRB's are allocated
- v. Alloc xApp sends the E2 control message to allocate the available PRB's from the computation
- vi. Following are the message types handled by this xApp
 - i. Outgoing Message types: - "PRB_PRED_REQ", "RIC_HEALTH_CHECK_RESP"
 - ii. Incoming Message Types - "PRB_PRED_RESP", "SUBSCRIPTION_REQ", "RIC_HEALTH_CHECK_REQ"

In the Dawn release, creation of A1 policy instance doesn't trigger A1 Policy create message towards xApp. This was confirmed by ORAN-RIC team <https://wiki.o-ran-sc.org/display/IAT/Traffic+Steering+Flows?focusedCommentId=41456537#comment-41456537>. Hence the workflow was modified to send timer-based event from alloc XApp to trigger PRB prediction.

On-boarding and Deploying xApps



xApp Onboarding Instructions through DMS CLI

```
docker run --rm -u 0 -it -d -p 9090:8080 -e DEBUG=1 -e STORAGE=local -e
STORAGE_LOCAL_ROOTDIR=/charts -v $(pwd)/charts:/charts chartmuseum/chartmuseum:latest
export CHART_REPO_URL=http://0.0.0.0:9090
dms_cli onboard --config_file_path=config.json --
shcema_file_path=/root/appmgr/xapp_orchestrator/dev/docs/xapp_onboarder/guide/embedded-
schema.json
dms_cli install --xapp_chart_name=prbpredxapp --version=0.0.2 --namespace=ricxapp
dms_cli install --xapp_chart_name=alloc --version=0.0.2 --namespace=ricxapp
```

Reference : <https://wiki.o-ran-sc.org/display/RICA/On-boarding+and+Deploying+xApps>

- 1.To onboard an xApp, the xApp descriptor and its schema will be submitted to the xApp onboarder. (ADD LINK TO API DOC)
- 2.xApp onboarder generates helm charts and distributes them to the local helm repo in the RIC platform instance
- 3.Operator triggers xApp deployment
- 4.(OPTIONAL)Through RIC dashboard, download an values.yaml file that contains the default xApp configuration parameters
- 5.(OPTIONAL) Modify the xApp configuration parameters, upload the new configuration to appmgr
- 6.Appmgr combines the xApp helm charts from local helm repo and the new configuration
- 7.Appmgr creates an xApp instance

Prbpred-xAppDescriptor

```
{
  "xapp_name": "prbpredxapp",
  "version": "0.0.2",
  "containers": [
    {
      "name": "prbpredxapp",
      "image": {
        "registry": "nexus3.o-ran-sc.org:10002",
        "name": "o-ran-sc/ric-app-prbpred",
        "tag": "0.0.2"
      }
    }
  ],
  "messaging": {
    "ports": [
      {
        "name": "http",
        "container": "prbpredxapp",
        "port": 10003,
        "description": "http service"
      },
      {
        "name": "rmr-data",
        "container": "prbpredxapp",
        "port": 4560,
        "rxMessages": [
          "A1_POLICY_REQ",
          "PRB_PRED_REQ"
        ],
        "txMessages": [
          "A1_POLICY_RESP", "PRB_PRED_RSP", "A1_POLICY_QUERY"
        ],
        "policies": [20008],
        "description": "rmr receive data port "
      },
      {
        "name": "rmr-route",
        "container": "prbpredxapp",
        "port": 4561,
        "description": "rmr route port "
      }
    ]
  },
  "rmr": {
    "protPort": "tcp:4560",
    "maxSize": 2072,
    "numWorkers": 1,
    "txMessages": [
      "PRB_PRED_RSP",
      "A1_POLICY_RESP",
      "A1_POLICY_QUERY"
    ],
    "rxMessages": [
      "PRB_PRED_REQ",
      "A1_POLICY_REQ"
    ],
    "policies": [20008]
  }
}
```

Container Info

Services port

RMR Messages

Policy Info

alloc-xAppDescriptor

```
{
  "xapp_name": "alloc",
  "version": "0.0.2",
  "containers": [
    {
      "name": "alloc",
      "image": {
        "registry": "nexus3.o-ran-sc.org:10002",
        "name": "o-ran-sc/ric-app-alloc",
        "tag": "0.0.2"
      }
    }
  ],
  "messaging": {
    "ports": [
      {
        "name": "http",
        "container": "alloc",
        "port": 10005,
        "description": "http service"
      },
      {
        "name": "rmr-data",
        "container": "alloc",
        "port": 4560,
        "txMessages": ["PRB_PRED_REQ", "RIC_HEALTH_CHECK_RESP"],
        "rxMessages": ["PRB_PRED_RSP", "SUBSCRIPTION_REQ", "RIC_HEALTH_CHECK_REQ"],
        "policies": [],
        "description": "rmr receive data port for alloc"
      },
      {
        "name": "rmr-route",
        "container": "alloc",
        "port": 4561,
        "description": "rmr route port for alloc"
      }
    ]
  },
  "rmr": {
    "protPort": "tcp:4560",
    "maxSize": 2072,
    "numWorkers": 1,
    "rxMessages": ["PRB_PRED_RESP"],
    "txMessages": ["PRB_PRED_REQ"],
    "policies": []
  },
  "controls": {
    "fileStorage": false
  },
  "db": {
    "waitForSdl": false
  }
}
```

Metadata

Internal
configuration of
xApp

Interactions With RIC Components

As part of this POC, direct/in-direct interactions with below mentioned RIC Platform Components was explored

A1-Mediator

This component listens for policy type and policy instance requests sent via HTTP (the "northbound" interface) and publishes those requests to running xApps via RMR messages (the "southbound" interface).

E2 manager

The E2 manager controls E2 connection establishment and provides REST APIs to manage these connections.

E2 Term

The E2 termination component establishes E2 SCTP connections and routes messages received/sent over E2 to/from RMR.


Subscription Manager

Subscription Manager is responsible for managing E2 subscriptions from xApps to the E2 Node (eNodeB or gNodeB). xApp can make subscriptions to E2 Node through Subscription Manager. xApp can subscribe REPORT, INSERT, CONTROL and POLICY type services from E2 Node.

Routing Manager

Routing Manager is responsible for distributing routing policies among the other platform components and xApps.

Messaging Interface



xApp can make subscriptions to E2 Node through Subscription Manager


xApp can subscribe REPORT, INSERT, CONTROL and POLICY type services from E2 Node

Subscribed messages from E2 Node are transported to RIC inside RIC Indication message. RIC Indication message is transported to xApp inside RMR message in Payload field of the RMR message.

Subscription Manager allocates unique E2 instance id for every E2 subscription during subscription procedure.

Subscribed messages are routed to xApps based on InstanceId in E2 Indication message.

xApp- E2 Subscription Flow



Screen shots from demo Setup

3. E2 Setup Procedure :Setup request from E2 SIM

1. RIC Platform Snapshot

NAME	READY	STATUS	RESTARTS	
deployment-ricplt-almediator-b4576889d-dqs2b	1/1	Running	60	
deployment-ricplt-alarmanager-f59846448-76ts1	1/1	Running	36	
deployment-ricplt-appmgr-7cfbfff7d-8gkmh	1/1	Running	36	
deployment-ricplt-e2mgr-556748b66f-9tgp	1/1	Running	6	6d2b
deployment-ricplt-e2term-alpha-7dbd577c8d-dhcb4	1/1	Running	31	24d
deployment-ricplt-jaegeradapter-76ddbf9c9-r464v	1/1	Running	41	41d
deployment-ricplt-olmediator-f7dd5fcc8-dt9kq	1/1	Running	36	41d
deployment-ricplt-rtmgi-7455599f-f3-v9:tfss Snapshot	1/1	Running	43	41d
deployment-ricplt-submgr-6cd6775cd6-x8z74	1/1	Running	36	41d
deployment-ricplt-vespamgr-757b6cc5dc-4vtzn	1/1	Running	36	41d
deployment-ricplt-xapp-onboarder-5958856fc8-p8bjl	2/2	Running	72	41d
r4-infrastructure-kong-7995f4679b-n65qm	2/2	Running	99	41d
r4-infrastructure-prometheus-alertmanager-5798b78f48-xks4r	2/2	Running	72	41d
r4-infrastructure-prometheus-server-c8ddcdf5f5-55tf8	1/1	Running	36	41d
ricplt-influxdb-meta-0	0/1	Pending	0	41d
statefulset-ricplt-dbaas-server-0	1/1	Running	36	41d

GNB & PLMN Id

2. E2 SIM Process Snapshot

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS
f8dfa3da6cae	e2simul:1.0.0	"/bin/sh -c 'kpm_sim_...	5 seconds ago	Up 4 seconds

```
<E2setupRequestIEs>
  <id>3</id>
  <criticality><reject/></criticality>
  <value>
    <GlobalE2node-ID>
      <gNB>
        <global-gNB-ID>
          <plmn-id>37 34 37</plmn-id>
          <gNB-ID>
            <gNB-ID>
              10110101110001100111011110001
            </gNB-ID>
          </gNB-ID>
        </global-gNB-ID>
      </gNB>
    </GlobalE2node-ID>
  </value>
</E2setupRequestIEs>
<E2setupRequestIEs>
  <id>10</id>
  <criticality><reject/></criticality>
  <value>
    <RANfunctions-List>
      <ProtocolIE-SingleContainer>
        <id>8</id>
        <criticality><reject/></criticality>
        <value>
          <RANfunction-Item>
            <ranFunctionID>0</ranFunctionID>
            <ranFunctionDefinition>
              30 00 00 00 05 4F 49 44 31 32 33 05 00 4B 50 4D
              20 6D 6F 6E 69 74 6F 72 01 01 60 00 01 01 07 00
              50 65 72 69 6F 64 69 63 20 72 65 70 6F 72 74 01
              05 14 01 01 1D 00 4F 2D 44 55 20 4D 65 61 73 75
              20 66 6F 72 20 74 68 65 20 35 47 43 20 63 6F 6E
              6E 65 63 74 65 64 20 64 65 70 6C 6F 79 6D 65 6E
              74 01 01 01 01 00 01 02 1D 00 4F 2D 44 55 20 4D
              65 61 73 75 72 65 6D 65 6E 74 20 43 6F 6E 74 61
              69 6E 65 72 20 66 6F 72 20 74 68 65 20 45 50 43
              20 63 6F 6E 6E 65 63 74 65 64 20 64 65 70 6C 6F
              43 55 2D 43 50 20 4D 65 61 73 75 72 65 6D 65 6E
              74 20 43 6F 6E 74 61 69 6E 65 72 20 66 6F 72 20
              74 68 65 20 35 47 43 20 63 6F 6E 6E 65 63 74 65
              64 20 64 65 70 6C 6F 79 6D 65 6E 74 01 01 01 01
              00 01 04 1E 80 4F 2D 43 55 2D 43 50 20 4D 65 61
              73 75 72 65 6D 65 6E 74 20 43 6F 6E 74 61 69 6E
              65 72 20 66 6F 72 20 74 68 65 20 45 50 43 20 63
              6F 6E 6E 65 63 74 65 64 20 64 65 70 6C 6F 79 6D
              65 6E 74 01 01 01 01 00 01 05 1E 80 4F 2D 43 55
              2D 55 50 2D 4D 65 61 73 75 72 65 6D 65 6E 74 20
              43 6F 6E 74 61 69 6E 65 72 20 66 6F 72 20 74 68
              65 20 35 47 43 20 63 6F 6E 6E 65 63 74 65 64 20
              64 65 70 6C 6F 79 6D 65 6E 74 01 01 01 01 00 01
              06 1E 80 4F 2D 43 55 2D 55 50 2D 4D 65 61 73 75
              72 65 6D 65 6E 74 20 43 6F 6E 74 61 69 6E 65 72
              20 66 6F 72 20 74 68 65 20 45 50 43 20 63 6F 6E
              6E 65 63 74 65 64 20 64 65 70 6C 6F 79 6D 65 6E
              74 01 01 01 01
            </ranFunctionDefinition>
            <ranFunctionRevision>2</ranFunctionRevision>
          </RANfunction-Item>
        </value>
      </ProtocolIE-SingleContainer>
    </RANfunctions-List>
  </value>
</E2setupRequestIEs>
</E2setupRequest>
```

Screenshots of E2 Setup Procedure as seen from E2 Mgr

E2 Mgr Setup Procedure

- GetE2TInstance from
- Saves NodeB data in RNIB Data service
- Creates a POST Request towards Routing Mgr to Associates RAN to E2-TAssociationManager
- On success of response connection status is moved from UNKNOWN_CONNECTION_STATUS-> CONNECTED
- Sends Builds E2Setup Success response Msg

4. E2 Mgr receiving E2 Setup Request

```

0 "crit":"INFO","ts":"1635747069355","id":"E2Manager","msg":{"E2SetupRequestNotificationHandler.Handle - E2T Address:
1 10.126.182.38000 - handling E2 SETUP REQUEST","mdc":{"time":"2021-11-01 06:11:09.353"}}
2 "crit":"INFO","ts":"1635747069355","id":"E2Manager","msg":{"#RnibDataService.GetE2TInstanceAddress: 1
3 10.126.182.38000, state: ACTIVE, associated RAMs count: 0, keep Alive ts: 163574704708612521","mdc":{"time":"20
4 21-11-01 06:11:09.353"}}
5 "crit":"INFO","ts":"1635747069355","id":"E2Manager","msg":{"#RnibDataService.SaveNodeB - nodeInfo: ran_name=:gnb_73
6 733_b5c6f7788" global_nb_id:{plmn_id:"373437"} nb_id:"10110110110001101101100011"} node_type:GNB_gnb
7 ran_functions:(ran_function_definition:\`3000000000054E94431323305004B50D206D6F6E69746F720101600001010700506572696F
8 693027265706F724701051401101D004F424455204D65173757265D60567420436F6E7461696E657220666F7220746865203547420636F6
9 6E65374656240645706C6F796D6567470101101201D004F424455204D65173757265D60567420436F6E7461696E657220666F7220746865
10 7468652045504320636F6E657474656420645706C6F796D6567470101101001013E804F424355204350204D65173757265D60567420436
11 3E6F7461696E657220666F7220746865204574320636F6E65374656240645706C6F796D656747010110100101E804F424355204350
12 204D65173757265D60567420436F6E7461696E657220666F72207468652045504320636F6E65374656240645706C6F796D6567470101
13 101000105E804F42435520550204D65173757265D60567420436F6E7461696E657220666F7220746865203547420636F6E65374656240645
14 20645706C6F796D6567470101101001001E804F42435520550204D65173757265D60567420436F6E7461696E657220666F7220746865
15 2045504320636F6E65374656240645706C6F796D6567470101101011"} ran_function_revision:2 gnb_type:GNB associated_e
16 2t_instance_address:"10.126.182.38000" setup_from_network:true","mdc":{"time":"2021-11-01 06:11:09.355"}}
17 "crit":"INFO","ts":"1635747069356","id":"E2Manager","msg":{"#RnibDataService.AddNbIdentity - nbIdentity: inventory na
18 me:"gnb_734_733_b5c6f7788" global_nb_id:{plmn_id:"373437"} nb_id:"10110110110001101101100011"},"mdc":{"ti
19 me":"2021-11-01 06:11:09.356"}}

```

5. E2 Mgr changing the state as connected and sending response E2 setup response

```

{"ts":1635747069356,"id":"E2Manager","msg":"#RanInstManagerInstance.AddNodeIdentity RAN name: gnb-734 733 b5c6f7788 - Successfully added node identity", "mdc":{"time":"2021-11-01 06:11:09.356"}}
{"crit":"INFO","ts":1635747069356,"id":"E2Manager","msg":"#E2TAssociationManager.AssociateRan - Associating RAN gnb 734 733 b5c6f7788 to E2T instance address: 10.110.226.182:38000","mdc":{"time":"2021-11-01 06:11:09.356"}}
{"crit":"INFO","ts":1635747069356,"id":"E2Manager","msg":"#RoutingManagerClient.sendMessage - POST url: http://service-riplt-rtmgr-http:3800/ric/v1/handles/associate-ran-to-e2t, request body: {\\\"E2Address\\\":\\\"10.110.226.182:38000\\\",\\\"ranNameList\\\":[\\\"gnb 734 733 b5c6f7788\\\"]}, \\\"mdc\\\":{\\\"time\\\":\\\"2021-11-01 06:11:09.356\\\"}}
{"crit":"INFO","ts":1635747069358,"id":"E2Manager","msg":"#RoutingManagerClient.sendMessage - success, http status code: 201,\"mdc\":{\"time\":\"2021-11-01 06:11:09.358\"}}
{"crit":"INFO","ts":1635747069358,"id":"E2Manager","msg":"#RanConnectStatusChangeManager.ChangeStatus - RAN name: gnb 734 733 b5c6f7788, currentStatus: UNKNOWN CONNECTION STATUS, nextStatus: CONNECTED\", \"mdc\":{\"time\":\"2021-11-01 06:11:09.358\"}}
{"crit":"INFO","ts":1635747069358,\"id\":\"E2Manager\",\"msg\":\"#RanConnectStatusChangeManager.setEvent - Connectivity Event for RAN gnb 734 733 b5c6f7788 is: gnb 734 733 b5c6f7788 CONNECTED\", \"mdc\":{\"time\":\"2021-11-01 06:11:09.358\"}}
{"crit\":\"INFO\",\"ts\":1635747069358,\"id\":\"E2Manager\",\"msg\":\"#RnibDataService.UpdateNodeInfoOnConnectionStatusInversion - event: gnb 734 733 b5c6f7788 CONNECTED, nodeInfo: ran name: \\\"gnb 734 733 b5c6f7788\\\" connection status: CONNECTED global nb id: {plmn id: \\\"373437\\\" nb id: \\\"1011010111000101001101110001\\\"} node type: GNB gnb: {ran functions: {ran function definition: \\\"300000000054F9443132300504B504D2066GF69E6746F72010100000101007005672696F64693027267057072740105140101110004F2D4455204D656173757265D6567420436F6E7461696E657220666F7220746865205474320636F6E6E6563746564206465706C6F796D65677401010101000102D1D004F2D4455204D656173757265D6567420436F6E7461696E657220666F7220746865205474320636F6E6E6563746564206465706C6F796D65677401010101000103B804F2D435204D656173757265D6567420436F6E7461696E657220666F72207468652035474320636F6E6E6563746564206465706C6F796D656774010101000104E804F2D435204D656173757265D6567420436F6E7461696E657220666F722074686520504320636F6E6E6563746564206465706C6F796D656774010101000105E180F2D435204D656173757265D6567420436F6E7461696E657220666F722074686520504320636F6E6E6563746564206465706C6F796D656774010101000106E1804F2D435204D656173757265D6567420436F6E7461696E657220666F722074686520504320636F6E6E6563746564206465706C6F796D65677401010101\" ran function revision: 2} gnb type: GNB) associated e2t_instance_address: \\\"10.110.226.182:38000\\\" setup from network: true\", \"mdc\":{\"time\":\"2021-11-01 06:11:09.358\"}}
{"crit":"INFO","ts":1635747069359,\"id\":\"E2Manager\",\"msg\":\"#RanConnectStatusChangeManager.updateNodeInfoOnConnectionStatusInversion - RAN names: gnb 734 733 b5c6f7788 - Successfully updated \\\"nb\", \"mdc\":{\"time\":\"2021-11-01 06:11:09.359\"}}
{"crit\":\"INFO\",\"ts\":1635747069359,\"id\":\"E2Manager\",\"msg\":\"#RnibDataService.GetE2TInstance - E2T instance address: 10.110.226.182:38000, state: ACTIVE, associated RANs count: 0, keep Alive ts: 1635747046708612521\", \"mdc\":{\"time\":\"2021-11-01 06:11:09.359\"}}
{"crit\":\"INFO\",\"ts\":1635747069359,\"id\":\"E2Manager\",\"msg\":\"#RnibDataService.SaveE2TInstance - E2T instance address: 10.110.226.182:38000, podName: e2term, state: ACTIVE, associated RANs count: 1, keep Alive ts: 1635747046708612521\", \"mdc\":{\"time\":\"2021-11-01 06:11:09.359\"}}
{"crit\":\"INFO\",\"ts\":1635747069359,\"id\":\"E2Manager\",\"msg\":\"#E2TInstancesManager.AddRansToInstance - RAN gnb 734 733 b5c6f7788) were added successfully to E2T 10.110.226.182:38000\", \"mdc\":{\"time\":\"2021-11-01 06:11:09.359\"}}
{"crit\":\"INFO\",\"ts\":1635747069359,\"id\":\"E2Manager\",\"msg\":\"#E2TAssociationManager.AssociateRan - successfully associated RAN gnb 734 733 b5c6f7788 with E2T 10.110.226.182:38000\", \"mdc\":{\"time\":\"2021-11-01 06:11:09.359\"}}
{"crit\":\"INFO\",\"ts\":1635747069360,\"id\":\"E2Manager\",\"msg\":\"#E2SetupRequestNotificationHandler.handleSuccessfulResponse - payload: <E2AP-PDU>{successfulOutcome}<procedureCode></procedureCode><criticality><reject></criticality><value><E2setupResponse><protocolIEs><E2setupResponseIEs><id>4</id><criticality><reject></criticality><value><GlobalRAN-ID><plmn-identity>131014</plmn-identity><ric-ID>1010101010011001110</ric-ID></GlobalRAN-ID><value><E2setupResponseIEs><E2setupResponseIEs><id>9</id><criticality><reject></criticality><value><RANFunctionsID-List><SingleContainer><id>6</id><criticality><ignore></criticality><value><RANFunctionID-Item><ranFunctionID>0</ranFunctionID><ranFunctionRevision>2</ranFunctionRevision></RANFunctionID-Item><value></ProtocolIE-SingleContainer></RANFunctionsID-List><value><E2setupResponseIEs></protocolIEs><E2setupResponse><value><successfulOutcome><E2AP-PDU></mdc\":{\"time\":\"2021-11-01 06:11:09.360\"}}
{"crit\":\"INFO\",\"ts\":1635747069360,\"id\":\"E2Manager\",\"msg\":\"#E2SetupRequestNotificationHandler.handleSuccessfulResponse - RAN name: gnb 734 733 b5c6f7788 - R3-IC2 SETUP RESP message has been built successfully. Message: <2ee2 676e62 02733345f3733335f623563367373838 - CA53421502d504455367373563365737366756c4f7574636f6d653e3c70276f63655475726543\\\""}

```

E2 RAN registration can confirmed with response from below CURL command

6. E2 Setup Response at E2 SIM end

E2 SETUP RESPONSE- ricid

```
<E2setupResponse>
<protocolIEs>
  <E2setupResponseIEs>
    <id>4</id>
    <criticality><reject></criticality>
    <value>
      <GlobalRIC-ID>
        <pLMN-Identity>13 10 11</pLMN-Identity>
        <ric-ID>
          10101010110011001110
        </ric-ID>
        </GlobalRIC-ID>
      </value>
    </E2setupResponseIEs>
  <E2setupResponseIEs>
    <id>9</id>
    <criticality><reject></criticality>
    <value>
      <RANfunctionsID-List>
        <ProtocolIE-SingleContainer>
          <id>6</id>
          <criticality><ignore></criticality>
          <value>
            <RANfunctionID-Item>
              <ranFunctionID>0</ranFunctionID>
              <ranFunctionRevision>2</ranFunctionRevision>
            </RANfunctionID-Item>
          </value>
        </ProtocolIE-SingleContainer>
      </RANfunctionsID-List>
    </value>
  </E2setupResponseIEs>
</protocolIEs>
</E2setupResponse>
```

```
7. curl -v --location --request GET "http://<E2Mgr ip>/v1/e2t/list" --  
header 'Content-Type: application/json'
```

Result displays the e2Term instance and RAN name associated

```
root@instance-2:~# curl -v --location --request GET "http://10.244.0.128:3800/v1/e2t/list" --header 'Content-Type: application/json'
Note: Unnecessary use of -X or --request, GET is already inferred.
  Trying 10.244.0.128...
  TCP_NODELAY set
  Connected to 10.244.0.128 (10.244.0.128) port 3800 (#0)
  GET /v1/e2t/list HTTP/1.1
  Host: 10.244.0.128:3800
  User-Agent: curl/7.58.0
  Accept: */*
  Content-Type: application/json

  HTTP/1.1 200 OK
  Content-Type: application/json
  Date: Mon, 01 Nov 2021 06:12:57 GMT
  Content-Length: 75

  Connection #0 to host 10.244.0.128 left intact
{"e2tAddress":"10.110.226.182:38000","ranNames":["qnb 734 733 b5c67788"]}]root@instance-2:~#
```

8. Fetch the gNB details associated on trigger of GET request from E2mgr

```
curl -v --location --request GET "http://<E2Mgr
ip>/v1/nodeb/gnb_734_733_b5c67788" --header 'Content-Type:
application/json'
```

[illegible]

A1 Policy and Policy Instances

- 9 A1- Policy and Policy Instances are created by executing following curl commands ..Indicating an emergency and defines the model to be used here.
- A1-Policy
 - curl -X PUT --header "Content-Type: application/json" -d @create1.json http://<a1med_ip>: <a1med_port>:/a1-p/policytypes/20008

A1 Policy Instance creation

- curl -X PUT --header "Content-Type: application/json" --data '{"modelVersion": "1.0.0", "modelname": "prb_pred_model.pkl", "modelstoreUrl": "http:// <modelstore IP >/model_store"}' http://<a1med_ip>: <a1med_port>/a1-p/policytypes/20008/policies/tsapolicy145

Below snapshot shows the policy instance is created with the values supplied in the curl command

```
root@instance-2:~# curl --header "Content-Type: application/json" http://10.244.0.87:10000/a1-p/policytypes/20008/policies/tsapolicy145
{
  "modelVersion": "1.0.0",
  "modelname": "prb_pred_model.pkl",
  "modelstoreUrl": "http://34.72.49.222:10001/model_store"
}
```

Policy Schema Used

```
{
  "name": "tsapolicy",
  "description": "tsa parameters",
  "policy_type_id": 20008,
  "create_schema": {
    "$schema": "http://json-schema.org/draft-07/schema#",
    "type": "object",
    "properties": {
      "modelname": {
        "type": "string"
      },
      "modelVersion": {
        "type": "string",
        "default": 0.0
      },
      "modelstoreUrl": {
        "type": "string"
      }
    },
    "additionalProperties": false
  }
}
```

xApp Screenshots & Model store

10. Alloc xApp is deployed

```
root@instance-2:~# kubectl get pods -n ricxapp
NAME                                READY   STATUS    RESTARTS   AGE
ricxapp-alloc-b9f994b84-x7zxr       1/1     Running   0           8h
ricxapp-prbpredxapp-66bfd5bc55-jhrmn 1/1     Running   0           8h
```

11. Emulated Acumos Model Store listening on 10001 port, receives REST REQ for fetching model. Acumos functionality was emulated considering HW requirements in bringing up Acumos.

Model Fetch Request

```
(my_env) root@instance-2:~/customxapp python modelstore.py

db      .g8""bgd `7MME' `7MF'`7MMM. ,MMF' .g8""8g. .M""bgd
;MM:    .dp'   `M   MM   M   NMMb dPMM .dp'   YM. ,MI   "Y
,V`MM.  dm'   `    MM   M   M YM ,M MM dm'   `MM `MMb.
,M `MM   MM   MM   M   Mb M' MM MM   MM   `YMMNg.
AbmmmgMA MM.   MM   M   YM.P' MM MM.   ,MP   `MM
A"      VML `Mb. , ' YM. ,M   M `YM' MM `Mb. ,dp' Mb   dm
AMA.    .AMMA. `Lmmmd' `bmmmdm' .JML. ``.JMML. ``Emmd" P"YEmmd"

Starting model store 2021-10-31 09:58:03.722292
* Serving Flask app 'modelstore' (lazy loading)
* Environment: production
  WARNING: This is a development server. Do not use it in a production deployment.
  Use a production WSGI server instead.
* Debug mode: off
* Running on all addresses.
  WARNING: This is a development server. Do not use it in a production deployment.
* Running on http://10.128.0.4:10001/ (Press CTRL+C to quit)
Received req2021-10-31 10:02:05.442191
34.72.49.222 - - [31/Oct/2021 10:02:05] "GET /model_store/1.0.0/prb_pred_model.pkl HTTP/1.1" 200 -
[FC:AT:E8:27:04:DF]
```

12. Below Snapshot shows REST Req being sent to model store with the details received from A1 policy request. Model store URL being constructed based on the A1 policy request. Model is successfully downloaded to prbpred container.

A1 Policy REQ

```

31-Oct-21 10:02:04 - pred xapp created@@@
31-Oct-21 10:02:04 - A1PolicyInterface
31-Oct-21 10:02:04 - send a1 policy query (A1_POLICY_QUERY)= {"policy_type_id": "20008"}
{"ts": 1635674525435, "crit": "DEBUG", "id": "ricxappframe.xapp_frame", "mdc": {}, "msg": "run: invoking msg handle
on type 20010"}
31-Oct-21 10:02:05 - request handler.resp handler:: Handler processing A1_POLICY_REQ request
31-Oct-21 10:02:05 - request handler.resp handler:: Handler verified policy
type id: '20008', 'policy_instance_id': 'tsapolicy145', 'payload': {'modelVersion': '1.0.0', 'modelName': 'prb
pred_model.pkl', 'modelstoreUrl': 'http://34.72.49.222:10001/model_store/1.0.0/'}, 'handler_id': 'prbpred'
31-Oct-21 10:02:05 - A1PolicyInterface::request handler received payload {'modelVersion': '1.0.0', 'modelName': 'p
rb_pred_model.pkl', 'modelstoreUrl': 'http://34.72.49.222:10001/model_store/1.0.0/'}, 'handler_id': 'prbpred'
31-Oct-21 10:02:05 - store model info: Fetch model from model store http://34.72.49.222:10001/model_store/1.0.0/
31-Oct-21 10:02:05 - pull_model::Sent Download request to model store http://34.72.49.222:10001/model_store/1.0.0/
31-Oct-21 10:02:05 - pull_model::Successfully Downloaded model to ./prbpred/prb_pred_model.pkl
1635674525 1/RMR [INFO] sends: ts=1635674525 src=service-ricxapp-prbpredxapp-rmr.ricxapp:4560 target=service-ricxap
p-alloc-rmr:4560 open=0 succ=0 fail=0 (hard=0 soft=0)
1635674525 1/RMR [INFO] sends: ts=1635674525 src=service-ricxapp-prbpredxapp-rmr.ricxapp:4560 target=service-ricpl
t-almediator-rmr.ricplt:4562 open=1 succ=1 fail=0 (hard=0 soft=0)
/opt/conda/lib/python3.7/site-packages/sklearn/base.py:333: UserWarning: Trying to unpickle estimator GaussianProce
ssRegressor from version 0.24.1 when using version 1.0.1. This might lead to breaking code or invalid results. Use
at your own risk. For more info please refer to:
https://scikit-learn.org/stable/modules/model_persistence.html#security-maintainability-limitations
UserWarning:
31-Oct-21 10:02:05 - store_model info::Saved Model info
31-Oct-21 10:02:05 - request handler.resp handler:: A1_POLICY_RESP Response sent: {"policy_type_id": "20008", "poli
cy_instance_id": "tsapolicy145", "payload": {"modelVersion": "1.0.0", "modelName": "prb_pred_model.pkl", "modelstor
eUrl": "http://34.72.49.222:10001/model_store/1.0.0/"}, "handler_id": "prbpred", "status": "OK"}
{"ts": 1635674553708, "crit": "DEBUG", "id": "ricxappframe.xapp_frame", "mdc": {}, "msg": "run: invoking msg handle
on type 20003"}
31-Oct-21 10:02:33 - predict handler received payload b'1'
31-Oct-21 10:02:33 - Predictor::predict()
/opt/conda/lib/python3.7/site-packages/sklearn/base.py:333: UserWarning: Trying to unpickle estimator GaussianProce
ssRegressor from version 0.24.1 when using version 1.0.1. This might lead to breaking code or invalid results. Use
at your own risk. For more info please refer to:
https://scikit-learn.org/stable/modules/model_persistence.html#security-maintainability-limitations
UserWarning:
31-Oct-21 10:02:33 - Predicted value for Slice 1&2 : b'{"prediction": [71.7, 70.6]}'
31-Oct-21 10:02:33 - Sending message to alloc xApp : b'{"prediction": [71.7, 70.6]}'
31-Oct-21 10:02:33 - predict handler: sent message successfully

```

Model Fetched Successfully

Sent PRB_PRED_REQ to alloc xApp

13. On Timer expiry Alloc xApp sent PRB_PRED_REQ to prbpred xApp and prbpred xApp receives PRB_PRED_REQ, performs prediction of the PRB's and sends message to Alloc XAPP

PRB prediction per Slice

```

31-Oct-21 10:03:33 - predict handler received payload b'1'
31-Oct-21 10:03:33 - Predictor::predict()
/opt/conda/lib/python3.7/site-packages/sklearn/base.py:333: UserWarning: Trying to unpickle estimator GaussianProce
ssRegressor from version 0.24.1 when using version 1.0.1. This might lead to breaking code or invalid results. Use
at your own risk. For more info please refer to:
https://scikit-learn.org/stable/modules/model_persistence.html#security-maintainability-limitations
UserWarning:
31-Oct-21 10:03:33 - Predictor::predict()
/opt/conda/lib/python3.7/site-packages/sklearn/base.py:333: UserWarning: Trying to unpickle estimator GaussianProce
ssRegressor from version 0.24.1 when using version 1.0.1. This might lead to breaking code or invalid results. Use
at your own risk. For more info please refer to:
https://scikit-learn.org/stable/modules/model_persistence.html#security-maintainability-limitations
UserWarning:
31-Oct-21 10:03:33 - Predicted value for Slice 1&2 : b'{"prediction": [71.7, 70.6]}'
31-Oct-21 10:03:33 - Sending message to alloc xApp : b'{"prediction": [71.7, 70.6]}'
31-Oct-21 10:03:33 - predict handler: sent message successfully
1635674618 1/RMR [INFO] sends: ts=1635674618 src=service-ricxapp-prbpredxapp-rmr.ricxapp:4560 target=service-ricxap
p-alloc-rmr:4560 open=0 succ=0 fail=0 (hard=0 soft=0)
1635674618 1/RMR [INFO] sends: ts=1635674618 src=service-ricxapp-prbpredxapp-rmr.ricxapp:4560 target=service-ricpl
t-almediator-rmr.ricplt:4562 open=1 succ=2 fail=0 (hard=0 soft=0)
1635674618 1/RMR [INFO] sends: ts=1635674618 src=service-ricxapp-prbpredxapp-rmr.ricxapp:4560 target=service-ricxap
p-alloc-rmr.ricxapp:4560 open=1 succ=1 fail=0 (hard=0 soft=0)

```

14. Alloc xApp receives PRB_PRED_RSP from prbpred xApp, computes the PRB to be allocated

Alloc xApp sends PRB Allocation to E2

```

31-Oct-21 10:03:33 - [msg to prbpred]
31-Oct-21 10:03:33 - [INFO] Message to prbpred: message sent Successfully
31-Oct-21 10:03:33 - [INFO] Received acknowledgement from prbpred (PRB_PRED_RSP): {'payload': b'{"prediction": [71.7, 7
0.6]}'}, 'payload length': 28, 'message type': 30002, 'subscription id': -1, 'transaction id': b'aaec35103a311ec832
beadad170f84a', 'message state': 0, 'message status': 'RMR_OK', 'payload max size': 3136, 'meid': b'', 'message sou
rce': 'service-ricxapp-prbpredxapp-rmr.ricxapp:4560', 'errno': 0}
31-Oct-21 10:03:33 - Estimated PRB usage of Slice 1:25
31-Oct-21 10:03:33 - Estimated PRB usage of Slice 2:25
31-Oct-21 10:03:33 - PRB allocated to Emergency SLice :50

```

Proposed Future Work

- Build a multivariant timeseries model with monitored data and arrive at proper inference.
- It is recommended that gNode/E2 interface has reserved resources for Emergency situations. Additionally, based on the situation resource reallocation from lower QOS based services should be explored.
- Develop a user friendly webapp to onboard xApp's & trigger policy towards near-RT RIC and support visualisations
- Extend the solution to self learning Closed Loops with following capabilities :-
 - Continuously perform Collection, Analytics, Decision and Actuation
 - Detect model performance and trigger a switch-over to another better performing model
- Analyse and trigger different set of data/measurements for data analysis
- Points for future study from FGAN-O-013 :=
 - 1) How ML pipelines can be synchronized/managed across the edge and emergency responder devices ?
 - 2) The split of inference tasks/model functionalities between edge and emergency responder devices

Open Issues

- a. ricplt-influxdb-meta-0 pod is in pending state in RIC platform. Tried all the suggestion as mentioned in RIC wiki but couldn't succeed
- b. Not receiving Subscription response from Subscription Manager
- c. Behaviour on A1 mediator sending A1 POLICY REQ when policy instance is CREATED/UPDATED to xApps is suppressed in Dawn release

Special Thanks

Thoralf Czichy - Nokia

Abukar Mohamed - Nokia

REFERENCES

1. A. Dandekar, J.Schulz-Zander, H.Wissing, Fraunhofer HHI, "Use case and requirements for orchestration of AI/ML based closed loops to enable autonomous networks", Fraunhofer HHI, Apr. 2021.
2. [Build-a-thon FG AN] ITU-T FG AN-I-146 "Proposal for a "Build-a-thon" for ITU AI/ML in 5G Challenge (second edition, 2021), aligned with FGAN WG3" <https://extranet.itu.int/sites/itu-t/focusgroups/an/input/FGAN-I-114-R1.docx>
3. [Build-a-thon Challenge] ITU-T AI/ML in 5G Challenge problem statement "ITU-ML5G-PS-014: Build-a-thon (PoC) Network resource allocation for emergency management based on closed loop analysis" <https://challenge.aiforgood.itu.int/match/matchitem/45>
4. https://github.com/ITU-build-a-thon/challenge-resources/blob/main/intro_tutorial.pdf
5. FGAN-153 "Team AUTOMATO" https://extranet.itu.int/sites/itu-t/focusgroups/an/_layouts/15/WopiFrame.aspx?sourcedoc=%7B85757552-DFBE-479A-A816-003AE91C2B22%7D&file=FGAN-I-155.docx&action=default
6. Pre-trained model and repository https://github.com/krcmehmet/ITUChallenge_BuildaThon_Activity4
7. Near Realtime RIC <https://wiki.o-ran-sc.org/display/GS/Near+Realtime+RIC+Installation>
8. <https://wiki.o-ran-sc.org/display/ORANSdk/App+Writing+Guide>
9. <https://github.com/o-ran-sc/code-repository>
10. <https://lists.o-ran-sc.org/g/main/topics>
11. https://docbox.etsi.org/ISG/ZSM/Open/Drafts/009-3ed111_Cla_AdvTop/ZSM-009-3_Cla_AdvTopv010