## Reformatting string and character data

FUNCTIONS FOR MANIPULATING DATA IN POSTGRESQL



**Brian Piccolo**Sr. Director, Digital Strategy



#### **Topics**

- Reformatting string and character data.
- Parsing string and character data.
- Determine string length and character position.
- Truncating and padding string data.

#### The string concatenation operator

```
SELECT
first_name,
last_name,
first_name || ' ' || last_name AS full_name
FROM customer
```

```
+-----+
| first_name | last_name | full_name |
|------|
| MARY | SMITH | MARY SMITH |
| LINDA | WILLIAMS |
+-----+
```

#### String concatenation with functions

```
SELECT
  CONCAT(first_name,' ', last_name) AS full_name
FROM customer;
```

```
+-----+
| first_name | last_name | full_name |
|------|
| MARY | SMITH | MARY SMITH |
| LINDA | WILLIAMS |
+------
```

#### String concatenation with a non-string input

```
SELECT
  customer_id || ': '
   || first_name || ' '
   || last_name AS full_name
FROM customer;
```

#### Changing the case of string

```
SELECT
   UPPER(email)
FROM customer;
```



#### Changing the case of string

```
SELECT
  LOWER(title)
FROM film;
```

#### Changing the case of string

```
SELECT
   INITCAP(title)
FROM film;
```

#### Replacing characters in a string

```
SELECT description FROM film;
```

```
description
A Epic Drama of a Feminist And a Mad Scientist...
A Astounding Epistle of a Database Administrator...
A Astounding Reflection of a Lumberjack And a Car...
A Fanciful Documentary of a Frisbee And a Lumberjack...
A Fast-Paced Documentary of a Pastry Chef And a...
```

#### Replacing characters in a string

#### Manipulating string data with REVERSE

```
SELECT
  title,
  REVERSE(title)
FROM
  film AS f;
```

## Let's practice!

FUNCTIONS FOR MANIPULATING DATA IN POSTGRESQL



## Parsing string and character data

FUNCTIONS FOR MANIPULATING DATA IN POSTGRESQL



**Brian Piccolo**Sr. Director, Digital Strategy



#### Determining the length of a string

```
SELECT
    title,
    CHAR_LENGTH(title)
FROM film;
```

#### Determining the length of a string

```
SELECT
    title,
    LENGTH(title)
FROM film;
```

#### Finding the position of a character in a string

```
SELECT
    email,
    POSITION('@' IN email)
FROM customer;
```

#### Finding the position of a character in a string

```
SELECT
    email,
    STRPOS(email, '@')
FROM customer;
```

#### Parsing string data

```
SELECT
   LEFT(description, 50)
FROM film;
```

#### Parsing string data

```
SELECT
   RIGHT(description, 50)
FROM film;
```

```
SELECT
   SUBSTRING(description, 10, 50)
FROM
  film AS f;
```

```
SELECT
   SUBSTRING(email FROM 0 FOR POSITION('@' IN email))
FROM
 customer;
 SUBSTRING(email FROM 0 FOR POSITION('@' IN email)) |
     _____
 MARY.SMITH
```

PATRICIA.JOHNSON

LINDA.WILLIAMS

```
SELECT
    SUBSTRING(email FROM POSITION('@' IN email)+1 FOR CHAR_LENGTH(email))
FROM
    customer;
```

```
+-----+
| SUBSTRING(email FROM POSITION('@' IN email)+1 FOR CHAR_LENGTH(email)) |
|-------|
| sakilacustomer.org | |
| sakilacustomer.org | |
| sakilacustomer.org | |
| the sakilacustomer.org | |
| sakilacustomer.org | |
| the sakilacustomer.org |
```

```
SELECT
   SUBSTR(description, 10, 50)
FROM
  film AS f;
```

## Let's practice!

FUNCTIONS FOR MANIPULATING DATA IN POSTGRESQL



# Truncating and padding string data

FUNCTIONS FOR MANIPULATING DATA IN POSTGRESQL



**Brian Piccolo**Sr. Director, Digital Strategy



```
TRIM([leading | trailing | both] [characters] from string)
```

- First parameter: [leading | trailing | both]
- Second parameter: [characters]
- Third parameter: from string









#### Padding strings with character data

```
SELECT LPAD('padded', 10, '#');
```

```
+----+
| LPAD |
|-----|
| ####padded |
+----+
```

#### Padding strings with whitespace

SELECT LPAD('padded', 10);

```
SELECT LPAD('padded', 5);
```

#### Padding strings with whitespace

```
SELECT RPAD('padded', 10, '#');
```

```
+----+
| RPAD |
|-----|
| padded#### |
|----+
```



## Let's practice!

FUNCTIONS FOR MANIPULATING DATA IN POSTGRESQL

