

# Recursive Types

Advanced Compiler Construction and Program Analysis

**Lecture 10**

Innopolis University, Spring 2022

# The topics of this lecture are covered in detail in...

Benjamin C. Pierce.

## **Types and Programming Languages**

MIT Press 2002


### **IV Recursive Types 265**

#### **20 *Recursive Types* 267**

- 20.1 Examples 268
- 20.2 Formalities 275
- 20.3 Subtyping 279
- 20.4 Notes 279

#### **21 *Metatheory of Recursive Types* 281**

- 21.1 Induction and Coinduction 282
- 21.2 Finite and Infinite Types 284
- 21.3 Subtyping 286
- 21.4 A Digression on Transitivity 288
- 21.5 Membership Checking 290
- 21.6 More Efficient Algorithms 295
- 21.7 Regular Trees 298
- 21.8  $\mu$ -Types 299
- 21.9 Counting Subexpressions 304
- 21.10 Digression: An Exponential Algorithm 309
- 21.11 Subtyping Iso-Recursive Types 311
- 21.12 Notes 312



## A list of natural numbers

Previously, we have implemented lists using built-in support for `List[T]`. Ignoring the generic part, can we define a list of numbers as a type alias?

```
NatList = <nil: Unit, cons: {..., ...}>
```

## A list of natural numbers

Previously, we have implemented lists using built-in support for `List[T]`. Ignoring the generic part, can we define a list of numbers as a type alias?

```
NatList = <nil: Unit, cons: {Nat, ...}>
```

## A list of natural numbers

Previously, we have implemented lists using built-in support for `List[T]`. Ignoring the generic part, can we define a list of numbers as a type alias?

```
NatList = <nil: Unit, cons: {Nat,  
NatList}>
```

## A list of natural numbers: unrolling definition


```
NatList = <nil: Unit, cons: {Nat,  
NatList}>
```

## A list of natural numbers: unrolling definition

```
NatList = <nil: Unit, cons: {Nat,  
NatList}>  
      <nil: •, cons: •>
```

# A list of natural numbers: unrolling definition


```
NatList = <nil: Unit, cons: {Nat,  
NatList}>
```






# A list of natural numbers: unrolling definition

NatList = <nil: Unit, cons: {Nat, NatList}>



## A list of natural numbers: unrolling definition

```
NatList = <nil: Unit, cons: {Nat, NatList}>
```



# A list of natural numbers: unrolling definition

NatList = <nil: Unit, cons: {Nat, NatList}>

<nil: •, cons: •>

Unit

{ •, • }

Nat

<nil: •, cons: •>

Unit

{ •, • }

Nat

...

## A list of natural numbers: fixpoint combinator

```
letrec factorial : Nat → Nat  
      = λn. if n == 0 then 1 else n * factorial (n-  
1)
```

## A list of natural numbers: fixpoint combinator

```
letrec factorial : Nat → Nat
  = λn. if n == 0 then 1 else n * factorial (n-1)
```

```
let factorial : Nat → Nat
  = fix λf.
    λn. if n == 0 then 1 else n * f (n-1)
```

## A list of natural numbers: fixpoint combinator

```
letrec factorial : Nat → Nat
  = λn. if n == 0 then 1 else n * factorial (n-1)
```

```
let factorial : Nat → Nat
  = fix λf.
    λn. if n == 0 then 1 else n * f (n-1)
```

```
NatList = <nil: Unit, cons: {Nat, NatList}>
```

## A list of natural numbers: fixpoint combinator

```
letrec factorial : Nat → Nat
  = λn. if n == 0 then 1 else n * factorial (n-1)
```

```
let factorial : Nat → Nat
  = fix λf.
    λn. if n == 0 then 1 else n * f (n-1)
```

```
NatList = <nil: Unit, cons: {Nat, NatList}>
```

```
NatList = μX. <nil: Unit, cons: {Nat, X}>
```

## A list of natural numbers: examples

`NatList` =  $\mu X.$  `<nil: Unit, cons: {Nat, X}>`



## A list of natural numbers: examples

```
NatList =  $\mu$ X. <nil: Unit, cons: {Nat, X}>
```

```
let nil : NatList =  
  <nil = unit> as NatList
```

## A list of natural numbers: examples

```
NatList =  $\mu$ X. <nil: Unit, cons: {Nat, X}>
```

```
let nil : NatList =  
  <nil = unit> as NatList
```

```
let cons : Nat → NatList → NatList =  
   $\lambda$ n:Nat.  $\lambda$ l:NatList. <cons = {n, l}> as  
NatList
```

## A list of natural numbers: examples

```
NatList =  $\mu X.$  <nil: Unit, cons: {Nat, X}>
```

```
let nil : NatList =  
  <nil = unit> as NatList
```

```
let cons : Nat  $\rightarrow$  NatList  $\rightarrow$  NatList =  
   $\lambda n:Nat. \lambda l:NatList.$  <cons = {n, l}> as  
NatList
```

```
let isnil : NatList  $\rightarrow$  Bool =  
   $\lambda l:NatList.$  case l of  
    <nil = _>  $\Rightarrow$  true  
    <cons = {n, l}>  $\Rightarrow$  false
```

## A list of natural numbers: exercise

`NatList` = `<nil: Unit, cons: {Nat, NatList}>`

`NatList` = `μX. <nil: Unit, cons: {Nat, X}>`

**Exercise 10.1.** Assuming `plus : Nat → Nat → Nat`,  
implement recursive function

`sumList : NatList → Nat`

# Hungry functions

`Hungry` =  $\mu X.$  `Nat`  $\rightarrow$  `X`

# Hungry functions

`Hungry =  $\mu X.$  Nat  $\rightarrow$  X`

```
let g : Hungry =  
    fix ( $\lambda f$ :Nat $\rightarrow$ Hungry. $\lambda x$ :Nat.f)  
in g 0 1 2 3 4 5
```

# Streams

`Stream =  $\mu X.$  Unit  $\rightarrow$  {Nat, X}`

# Streams

`Stream =  $\mu X.$  Unit  $\rightarrow$  {Nat, X}`

`let head : Stream  $\rightarrow$  Nat =  
  $\lambda s$ :Stream.(s unit).1`



# Streams

`Stream =  $\mu X.$  Unit  $\rightarrow$  {Nat, X}`

`let head : Stream  $\rightarrow$  Nat =  
  $\lambda s$ :Stream.(s unit).1`

`let tail : Stream  $\rightarrow$  Stream =  
  $\lambda s$ :Stream.(s unit).2`

# Streams

`Stream =  $\mu X.$  Unit  $\rightarrow$  {Nat, X}`

`let head : Stream  $\rightarrow$  Nat =  
  $\lambda s : \text{Stream}.$  (s unit).1`

`let tail : Stream  $\rightarrow$  Stream =  
  $\lambda s : \text{Stream}.$  (s unit).2`

`letrec upfrom : Nat  $\rightarrow$  Stream =  
  $\lambda n : \text{Nat}.$   $\lambda \_ : \text{Unit}.$  {n, upfrom (succ n)}`

## Streams: exercise

$\text{Stream} = \mu X. \text{Unit} \rightarrow \{\text{Nat}, X\}$

**Exercise 10.2.** Assuming  $\text{plus} : \text{Nat} \rightarrow \text{Nat} \rightarrow \text{Nat}$ ,  
define a stream of Fibonacci numbers (1, 1, 2, 3, 5, 8, ...):

$\text{fib} : \text{Stream}$

# Processes

Process =  $\mu X. \text{Nat} \rightarrow \{\text{Nat}, X\}$

# Processes

`Process` =  $\mu X. \text{Nat} \rightarrow \{\text{Nat}, X\}$

```
letrec sumProcessFrom : Nat → Process =  
  λacc:Nat. λn:Nat.  
    let newacc = plus acc n  
    in {newacc, sumProcessFrom  
newacc}
```

# Processes

`Process =  $\mu X.$  Nat  $\rightarrow$  {Nat, X}`

`letrec sumProcessFrom : Nat  $\rightarrow$  Process =  
  $\lambda$ acc:Nat. $\lambda$ n:Nat.`

`let newacc = plus acc n  
      in {newacc, sumProcessFrom  
newacc}`

`let sumProcess : Process  
 = sumProcessFrom 0`

# Purely Functional Objects

Counter =  $\mu X.$  {get: Nat, inc: Unit  $\rightarrow$  X}

# Purely Functional Objects

`Counter =  $\mu X.$  {get: Nat, inc: Unit  $\rightarrow$  X}`

`letrec newCounter : {x: Nat}  $\rightarrow$  Counter =  
  $\lambda$ rep:{x: Nat}.  
 { get = rep.x  
 , inc =  $\lambda\_:$ Unit.  
 newCounter {x = succ  
(rep.x)}  
 }`



# Well-typed fixed point combinator

Untyped fixed point:

$$\text{fix} = \lambda f. (\lambda x. f \ (x \ x)) (\lambda x. f \ (x \ x))$$

# Well-typed fixed point combinator

Untyped fixed point:

$$\text{fix} = \lambda f. (\lambda x. f \ (x \ x)) (\lambda x. f \ (x \ x))$$

Simply-typed fixed point for type T:

$$\begin{aligned} \text{fix}^T &= \lambda f: T \rightarrow T. \\ &\quad (\lambda x: (\mu X. X \rightarrow T). f \ (x \ x)) \\ &\quad (\lambda x: (\mu X. X \rightarrow T). f \ (x \ x)) \end{aligned}$$

# Well-typed fixed point combinator

Untyped fixed point:

$$\text{fix} = \lambda f. (\lambda x. f \ (x \ x)) (\lambda x. f \ (x \ x))$$

Simply-typed fixed point for type T:

$$\begin{aligned} \text{fix}^T &= \lambda f: T \rightarrow T. \\ &\quad (\lambda x: (\mu X. X \rightarrow T). f \ (x \ x)) \\ &\quad (\lambda x: (\mu X. X \rightarrow T). f \ (x \ x)) \end{aligned}$$

**Corollary:** recursive types break normalization property

# Two approaches to recursive types

How is the recursive type related to its one-step unfolding?

`NatList` vs `<nil: Unit, cons: NatList>`

# Two approaches to recursive types

How is the recursive type related to its one-step unfolding?

`NatList` vs `<nil: Unit, cons: NatList>`

1. **Equi-recursive** approach says that those types are definitionally equal, as they stand for the same infinite tree.

# Two approaches to recursive types


How is the recursive type related to its one-step unfolding?

`NatList` vs `<nil: Unit, cons: NatList>`

1. **Equi-recursive** approach says that those types are definitionally equal, as they stand for the same infinite tree.
2. **Iso-recursive** approach says that those types are distinct, but isomorphic (there explicit coercions between the two).

# Two approaches to recursive types


How is the recursive type related to its one-step unfolding?



1. **Equi-recursive** approach says that those types are definitionally equal, as they stand for the same infinite tree.
2. **Iso-recursive** approach says that those types are distinct, but isomorphic (there explicit coercions between the two).

# Two approaches to recursive types



How is the recursive type related to its one-step unfolding?



1. **Equi-recursive** is typically easier to reason from the programmer's perspective, but harder to implement.
2. **Iso-recursive** is easier to implement. Also, coercions (folding/unfolding) can be introduced by the typechecker.



# Iso-recursive types



# Iso-recursive types

$t ::= \dots$  *terms*  
     $\text{fold}[T] \ t$  *folding*  
     $\text{unfold}[T] \ t$  *unfolding*

$v ::= \dots$  *values*  
     $\text{fold}[T] \ v$  *folding*

$T ::= \dots$  *types*  
     $X$  *type variable*  
     $\mu X. T$  *recursive type*

$\text{unfold}[S](\text{fold}[T] \ v_1) \rightarrow v_1$

$$\frac{\Gamma \vdash t : [X \mapsto U]T \quad U = \mu X. T}{\Gamma \vdash \text{fold}[U] \ t : U}$$

$$\frac{\Gamma \vdash t : U \quad U = \mu X. T}{\Gamma \vdash \text{unfold}[U] \ t : [X \mapsto U]T}$$

# Iso-recursive types: using coercions implicitly

```
NatList =  $\mu$ X. <nil: Unit, cons: {Nat, X}>
```

```
NLBody = <nil: Unit, cons: NatList>
```

# Iso-recursive types: using coercions implicitly

```
NatList =  $\mu$ X. <nil: Unit, cons: {Nat, X}>
```

```
NLBody = <nil: Unit, cons: NatList>
```

```
let nil : NatList =  
  fold[NatList] (<nil = unit> as NLBody)
```

# Iso-recursive types: using coercions implicitly

```
NatList =  $\mu$ X. <nil: Unit, cons: {Nat, X}>
```

```
NLBody = <nil: Unit, cons: NatList>
```

```
let nil : NatList =  
    fold[NatList] (<nil = unit> as NLBody)
```

```
let cons : Nat → NatList → NatList =  
     $\lambda$ n:Nat. $\lambda$ l:NatList.  
        fold[NatList] (<cons = {n, l}> as NLBody)
```

# Iso-recursive types: using coercions implicitly

```
NatList =  $\mu$ X. <nil: Unit, cons: {Nat, X}>
```

```
NLBody = <nil: Unit, cons: NatList>
```

```
let nil : NatList =  
    fold[NatList] (<nil = unit> as NLBody)
```

```
let cons : Nat → NatList → NatList =  
     $\lambda$ n:Nat.  $\lambda$ l:NatList.  
        fold[NatList] (<cons = {n, l}> as NLBody)
```

```
let isnil : NatList → Bool =  
     $\lambda$ l:NatList. case unfold[NatList] l of  
        <nil =  $\_$ >  $\Rightarrow$  true  
    | <cons = { $\_$ ,  $\_$ >  $\Rightarrow$  false
```

# Recursive types and subtyping

Even  $<:$  Nat

What should be the relationship between the following types?

$\mu X. \text{Nat} \rightarrow (\text{Even} \times X)$                       and  
 $\mu X. \text{Even} \rightarrow (\text{Nat} \times X)$

# Subtyping of iso-recursive types

$$\frac{\Sigma, X <: Y \vdash S <: T}{\Sigma \vdash \mu X.S <: \mu Y.T}$$

$$\Sigma, X <: Y \vdash X <: Y$$



# Generating functions

**Definition 10.4.** A function  $F \in P(U) \rightarrow P(U)$  is *monotone* if  $X \subseteq Y$  implies  $F(X) \subseteq F(Y)$ .

# Generating functions

**Definition 10.4.** A function  $F \in P(U) \rightarrow P(U)$  is **monotone** if  $X \subseteq Y$  implies  $F(X) \subseteq F(Y)$ .

**Definition 10.5.** Let  $X$  be a subset of  $U$ .

1.  $X$  is  **$F$ -closed** if  $F(X) \subseteq X$ .
2.  $X$  is  **$F$ -consistent** if  $X \subseteq F(X)$ .
3.  $X$  is a **fixed point of  $F$**  if  $X = F(X)$ .

# Generating functions: example

$$G(\emptyset) = \{c\}$$

**G-closed sets**

**G-consistent sets**

$$G(\{a\}) = \{c\}$$

$$G(\{b\}) = \{c\}$$

$$G(\{c\}) = \{b, c\}$$

$$G(\{a,b\}) = \{c\}$$

$$G(\{a,c\}) = \{b,c\}$$

$$G(\{b,c\}) = \{a,b,c\}$$

$$G(\{a,b,c\}) = \{a,b,c\}$$

# Generating functions: example

$$G(\emptyset) = \{c\}$$

$$G(\{a\}) = \{c\}$$

$$G(\{b\}) = \{c\}$$

$$G(\{c\}) = \{b, c\}$$

$$G(\{a, b\}) = \{c\}$$

$$G(\{a, c\}) = \{b, c\}$$

$$G(\{b, c\}) = \{a, b, c\}$$

$$G(\{a, b, c\}) = \{a, b, c\}$$

## **G-closed sets**

$$\{a, b, c\}$$

## **G-consistent sets**

$$\emptyset$$

$$\{c\}$$

$$\{b, c\}$$

$$\{a, b, c\}$$

# Least and greatest fixpoints

## Theorem 10.6.

1. The intersection of all  $F$ -closed sets  
is the least fixed point of  $F$ . (we will write  $\mu F$ )
2. The union of all  $F$ -consistent sets  
is the greatest fixed point of  $F$ . (we will write  $\nu F$ )

# Least and greatest fixpoints

## Theorem 10.6.

1. The intersection of all  $F$ -closed sets  
is the least fixed point of  $F$ . (we will write  $\mu F$ )
2. The union of all  $F$ -consistent sets  
is the greatest fixed point of  $F$ . (we will write  $\nu F$ )

## Corollary.

1. *Principle of induction.* If  $X$  is  $F$ -closed, then  $\mu F \subseteq X$ .
2. *Principle of coinduction.* If  $X$  is  $F$ -consistent, then  $X \subseteq \nu F$ .

# Summary

- ❑ Structural recursive types
- ❑ Equi-recursive vs Iso-recursive
- ❑ Formal definitions for iso-recursive types
- ❑ Recursive types and subtyping
- ❑ Least and greatest fixed points

**See you next time!**