

# Theoretical computer science

Tutorial - week 14

April 22, 2021


**INNOVATION**  
**UNIVERSITY**

# Agenda

- Announcements
- Rice theorem implication
- Static Analysis

# Recap from the lecture

Our long  
journey in  
the outer  
space...



# Common questions about programs

- Termination
- Memory requirements
- Null pointer dereference, division by zero, overflow
- Initialization before access
- ...

# Rice's theorem

**Any non-trivial property of the behavior of programs (semantic) in a Turing-complete language is undecidable!**


Examples:

- The class of partial computable functions that return  $0$  for every input, and its complement.
- The class of partial computable functions that return  $0$  for at least one input, and its complement.
- The class of partial computable functions that are constant, and its complement.



# Testing

- Spots bugs with failing tests
- Check if software **runs as expected**
- Effective at finding
  - software regression
  - security vulnerabilities (fuzzing)
- Provide rough idea about quality of software with coverage information



# Software quality matters (Embedded SW)

PRIYA GANAPATI GEAR 12.31.08 05:47 PM

## ZUNE FREEZE RESULT OF LEAP YEAR: MICROSOFT



# Software quality matters (ZUNE)

```
1 while (year > 365) {  
2   if (IsLeapYear(year)) {  
3     if (days > 366) {  
4       days -= 366;  
5       year += 1;  
6     }  
7   } else {  
8     days -= 365;  
9     year += 1;  
10  }  
11 }
```



December 31, 2008

Suggested solution: wait for tomorrow



# Edsger W. Dijkstra

*“Testing can only prove the presence  
of bugs, not their absence.”*




# Software quality matters (Safety critical)

On the night of the 25th of February, 1991, a Patriot missile system operating in Dhahran, Saudi Arabia, failed to track and intercept an incoming Scud. The Iraqi missile impacted into an army barracks, killing 28 U.S. soldiers and injuring another 98.



February 25, 1991

# Software quality matters (Safety critical)



# Software quality matters (Patriot)

- [illegible]


Suggested solution: reboot every 10 hours

# What is Static Analysis?


## Program as a Data

- Discovers **properties** of a program (or a program point) by reasoning **statically** the program (without running the program)
- Discovered properties can be:
  - the program terminates.
  - arrays are always accessed within their bounds.
  - a variable **p** at line 10 cannot have a null pointer.
  - a variable **p** at line 10 cannot be a dangling reference.


# Goal: exploring program states



# Goal: exploring abstract states



# Goal: exploring abstract states





# Soundness & Completeness

- Soundness: Catch all violations
  - Over-approximate behavior
  - May result in false positives
- Completeness: Only catch actual violations
  - Under-approximate behavior
  - May result in false negatives

# Static Analysis

## Program as a Data


- Discovers **properties** of a program (or a program point) by reasoning **statically** the program (without running the program)
- Discovered properties can be:
  - the program terminates.
  - arrays are always accessed within their bounds.
  - a variable **p** at line 10 cannot have a null pointer.
  - a variable **p** at line 10 cannot be a dangling reference.

# Abstract Syntax Trees

- Tree representation of the syntactic structure of source code.
  - Parsers convert concrete syntax into abstract syntax, and deal with resulting ambiguities.
- Records only the semantically relevant information.
  - Abstract: doesn't represent every detail (like parentheses); these can be inferred from the structure.

# Abstract Syntax Trees

```
int result = 1;  
int i = 2;  
while (i < n) {  
    result *= i;  
    i++;  
}  
return result;
```




That is what your IDE and compiler are doing


# Type analysis (checking)

```
f(a,b,c,d) = if b = 1 then
  if a[1](0) then
    c(1)
  else
    c(d)
else
  if a[b](0) then
    c(b)
  else
    f(a, b - 1, c, d)
```


## Example



# Type analysis (checking)



# Sign analysis



1<sup>st</sup> iteration

$x_1 = [f \mapsto +, n \mapsto \perp]$

$x_2 = [f \mapsto +, n \mapsto +]$

$x_3 = [f \mapsto +, n \mapsto +]$

$x_4 = [f \mapsto +, n \mapsto +]$

$x_5 = [f \mapsto +, n \mapsto ?]$

$x_6 = [f \mapsto +, n \mapsto +]$

2<sup>nd</sup> iteration

$x_1 = [f \mapsto +, n \mapsto \perp]$

$x_2 = [f \mapsto +, n \mapsto +]$

$x_3 = [f \mapsto +, n \mapsto ?]$

$x_4 = [f \mapsto ?, n \mapsto ?]$


$x_5 = [f \mapsto ?, n \mapsto ?]$

$x_6 = [f \mapsto +, n \mapsto ?]$

# Liveness analysis

A variable is live at a particular point in the program if its value at that point will be used in the future (dead, otherwise).

- dead code elimination





# Wrap up

- What have you learnt?
- What for this could be useful?