

# Compiler Construction: Practical Introduction

## Lecture 7 Semantic Analysis


Eugene Zouev  
Spring Semester 2022  
Innopolis University

# Main Topics

- Why and for semantic analysis is?
- Examples: standard conversions, initialization semantics, user-defined conversions, calculating constant expressions
- Source code optimizations: the general idea
- Examples: eliminating repeated calculations, replacing slow instructions, excluding redundant calculations, constant propagation etc.


# Compilation: An Ideal Picture

*A program written by a human  
(or by another program)*



*Coming back to the  
today's topic*

# Where We Are Today



# What Is Semantic Analysis For?

```
void f(int p)
{
    int a, b;
    *a = 777;
    return xyz*a+b*f;
}

...
f();
int x = f(1,2);
```

# What Is Semantic Analysis For?

```
void f(int p)
{
    int a, b;
    *a = 777;
    return xyz*a+b*f;
}

...
f();
int x = f(1,2);
```

Syntactically  
perfect program!..

# What Is Semantic Analysis For?

```
void f(int p)
{
    int a, b;
    *a = 777;
    return xyz*a+b*f;
}
...
f();
int x = f(1,2);
```

Illegal operation (dereferencing)  
for the object of type **int**

Using uninitialized variables **a** and **b**

Undeclared variable **xyz**

Illegal operand types for operator **\***

Returning a value in **void** function

Illegal number of arguments in  
calls to function **f**

Illegal position for call to function **f**

**Syntactically  
perfect program!...**

# What Is Semantic Analysis For?

## Some remarks

1. Errors like "undeclared identifier" are typically detected on syntax analysis stage - while building symbol tables and/or program tree.
2. Errors like "uninitialized variable" usually are not detected by all compilers because it requires deeper control flow and data flow analysis.
3. Analysis of the code snippet `...xyz*a...` typically results in a message like "illegal operand types for \* operator". Formally that's true but in fact the reason is that `xyz` is not declared - this is an example of an **induced error**.

*Наведенные ошибки*



# Semantic Analysis

- Typically semantic analysis runs on the program tree built on previous compilation stages (while syntax analysis).
- Semantic analysis is typically implemented as a series of tree traverses with some actions related to the source language semantics.
- The more complex semantics is the more passes (traverses) are needed.
  - For relatively simple languages semantic analysis can be done **together** with syntax analysis while building the program tree.
  - Usually, the last tree walk implements target code generation - either an intermediate representation (like C--) or assembler code.
  - Often, before code generation, some **additional stages** after semantic analysis are necessary like building CFG & SSA representations...

# Semantic Analysis

- One or several semantic actions are performed on each tree walk.
- What's the result of each tree walk?
  - Either a modified program tree with **the same node types**; perhaps complex nodes get replaced for simpler ones.

**Example is the C# compiler:** after each tree walk the tree consists of the same node types.

- Or a modified program tree **with different node types** that are more primitive but are "closer" to the target architecture.

**Example is the Scala compiler:** node types representing source program constructs get replaced for more primitive nodes ("ICode"), and the JVM (or MSIL) code is generated from ICode finally.

# Semantic Analysis

The result of each tree walk is typically twofold:

- The tree changes its structure: some nodes/subtrees are added or removed, some nodes/subtrees get replaced for other nodes/subtrees...
- Tree nodes are annotated ("decorated" 😊) by attributes reflecting various semantic features; the attributes are deduced during the analysis process.

=> The Abstract Syntax Tree (AST) is converted to the **Annotated Syntax Tree (AAST)**.

(An alternative solution is **attribute grammars**.)

# Semantic Analysis: Actions


## Four categories of actions while semantic analysis:

- Semantic checks
  - Operand types consistency in expressions
  - Checking correctness for function calls (including destructors)
- Semantic conversions
  - Replacing conversions for function calls
  - Replacing infix operators for operator function calls
  - Inserting necessary type conversions
  - Template instantiating
- Identification of hidden semantics
  - Implicit destructor calls
  - Temporary objects
- Optimizations (!)

# AAST example (a fragment)


From the prev  
lecture

```
class C { ... };  
float f(const char* s)  
{  
    C c(s); return c.m;  
}
```



- Structural links
- Type information
- Attributes


# AAST example (a fragment)



```
class C { ... };
float f(const char* s)
{
    C c(s); return c.m;
}
```

- Semantic links
- Scopes

# AAST example (a fragment)




```
class C { ... };
float f(const char* s)
{
    C c(s); return c.m;
}
```

• Hidden semantics

# Semantic Analysis: Example 1

## Standard conversions

```
int a = 3;  
double d = 7.55;  
float x = a + d;
```






# Semantic Analysis: Example 1

## Standard conversions

```
int a = 3;  
double d = 7.55;  
float x = a + d;
```





...

```
float x = (float)((double)a + d);
```


# Semantic Analysis: Example 1

## Standard conversions

```
int a = 3;  
double d = 7.55;  
float x = a + d;
```




```
...  
float x = (float)((double)a + d);
```



# Semantic Analysis: Example 2

## Class declaration

```
class C {  
    public:  
    int a, b;  
};
```



# Semantic Analysis: Example 2


## Class declaration

```
class C {  
    public:  
    int a, b;  
};
```



```
class C {  
    public:  
    C() { a = 0; b = 0; }  
    C(const C& c) { a = c.a; b = c.b; }  
    ...  
    int a, b;  
};
```

Automatically generated:  
Default constructor  
Copy constructor  
Move constructor  
Copy assignment operator  
...




# Semantic Analysis: Example 2

## Class declaration

```
class C {  
  public:  
    int a, b;  
};
```

```
class C {  
  public:  
    C() { a = 0; b = 0; }  
    C(const C& c) { a = c.a; b = c.b; }  
    ...  
    int a, b;  
};
```

Automatically generated:  
Default constructor  
Copy constructor  
Move constructor  
Copy assignment operator  
...



# Semantic Analysis: Example 3

## Initialization semantics

```
class C { ... };  
...  
C c1;  
C c2(1);  
C c3(c2);  
C c4 = 7;  
C c5 = c1;
```

# Semantic Analysis: Example 3

## Initialization semantics

```
class C { ... };  
...  
C c1;  
C c2(1);  
C c3(c2);  
C c4 = 7;  
C c5 = c1;
```

- Allocate memory for c1 object;
- Call default constructor of C for c1.

# Semantic Analysis: Example 3

## Initialization semantics

```
class C { ... };
```

```
...
```

```
C c1;
```

```
C c2(1);
```

```
C c3(c2);
```

```
C c4 = 7;
```

```
C c5 = c1;
```

- Allocate memory for c1 object;
- Call **default constructor** of C for c1.

- Allocate memory for c2 object;
- Call **C(int)** constructor for c2.



# Semantic Analysis: Example 3

## Initialization semantics

```
class C { ... };
```

```
...
```

```
C c1;
```

```
C c2(1);
```

```
C c3(c2);
```

```
C c4 = 7;
```

```
C c5 = c1;
```

- Allocate memory for c1 object;
- Call **default constructor** of C for c1.

- Allocate memory for c2 object;
- Call **C(int)** constructor for c2.

- Allocate memory for c3 object;
- Call **copy constructor** for c3.

# Semantic Analysis: Example 3

## Initialization semantics

```
class C { ... };
```

```
...
```

```
C c1;
```

```
C c2(1);
```

```
C c3(c2);
```

```
C c4 = 7;
```

```
C c5 = c1;
```

- Allocate memory for c1 object;
- Call **default constructor** of C for c1.

- Allocate memory for c2 object;
- Call **C(int)** constructor for c2.

- Allocate memory for c3 object;
- Call **copy constructor** for c3.

- Allocate memory for c4 object;
- Create temporary object tmp;
- Call **C(int)** constructor for tmp;
- Call **copy constructor** for c4.

# Semantic Analysis: Example 3


## Initialization semantics

```
class C { ... };
```

```
...
```

```
C c2(1);
```

...






# Semantic Analysis: Example 3

## Initialization semantics

```
class C { ... };
```

```
...  
C c2(1);
```



# Semantic Analysis: Example 4

## User-defined conversions

```
class C {  
    private:  
        bool m;  
    public:  
        operator bool() { return m; }  
};  
  
...  
C c;  
  
...  
if ( c ) ...
```

# Semantic Analysis: Example 4

## User-defined conversions

```
class C {  
    private:  
        bool m;  
    public:  
        operator bool() { return m; }  
};  
  
...  
C c;  
  
...  
if ( c ) ... ← if ( (bool)c ) ...
```

# Semantic Analysis: Example 4

## User-defined conversions


```
class C {  
private:  
    bool m;  
public:  
    operator bool() { return m; }  
};  
  
...  
C c;  
  
...  
if ( c ) ...
```

if ( (bool)c ) ...

if ( c.operator bool() ) ...

# Semantic Analysis: Example 4

if ( c ) ...







# Semantic Analysis: Example 4

if ( c ) ...

if ( (bool)c ) ...




# Semantic Analysis: Example 4



# Semantic Analysis: Example 5

## Functional objects ("functors")

```
class C {  
public:  
    int operator()(int a,int b)  
    { return a+b; }  
};  
...  
C c1;  
...  
int res = c1(5,7);
```



# Semantic Analysis: Example 5


Functional objects (“functors”)

...c1(5,7)...

# Semantic Analysis: Example 5

Functional objects ("functors")

...c1(5,7)...




...C::operator()(&c1,5,7)...


# Semantic Analysis: Example 5

Functional objects ("functors")

...c1(5,7)...



...C::operator()(&c1,5,7)...



# Semantic Analysis: Example 6


Hidden semantics: destructor call

```
class C {  
    ...  
};  
void f() {  
    C c;  
    ...  
}
```

# Semantic Analysis: Example 6

Hidden semantics: destructor call

```
class C {  
    ...  
};  
void f() {  
    C c;  
    ...  
}
```




*The call to `C`'s destructor  
is assumed here!*




# Semantic Analysis: Example 6

Hidden semantics: destructor call



# Semantic Analysis: Example 6

## Hidden semantics: destructor call



# Semantic Analysis: Example 7

Calculating constant expressions

```
const int Factor = 10;  
int A[Factor*7-1];
```

