

# ***Publisher's Guide: Users, Roles and Permissions***

## **User Manual**

**Version: 1.0**

**May 29, 2011**

---

## Table of Contents

|          |  |           |
|----------|--|-----------|
| <b>1</b> | <b>ABOUT THIS DOCUMENT .....</b>                         | <b>10</b> |
| 1.1      | SCOPE .....  | 10        |
| 1.2      | WHO SHOULD READ THIS DOCUMENT? .....                     | 10        |
| 1.3      | ASSUMPTIONS .....  | 10        |
| 1.4      | RELATED INFORMATION .....                                | 10        |
| 1.5      | VERSION HISTORY .....                                    | 10        |
| <b>2</b> | <b>GLOSSARY .....</b>                                    | <b>11</b> |
| <b>3</b> | <b>UNDERSTANDING USERS, ROLES, AND PERMISSIONS .....</b> | <b>12</b> |
| 3.1      | ROLES AND PERMISSIONS: OVERVIEW .....                    | 12        |
| 3.1.1    | Introduction .....                                       | 12        |
| 3.1.2    | Server Infrastructure .....                              | 12        |
| 3.2      | USERS: OVERVIEW .....                                    | 13        |
| 3.2.1    | Introduction .....                                       | 13        |
| 3.2.2    | Server Infrastructure .....                              | 14        |
|          | Partner .....  | 14        |
|          | Account Owner .....                                      | 14        |
|          | Kaltura Session (KS) .....                               | 14        |
|          | Partner User ID (puser_id) .....                         | 15        |
|          | Kaltura User (kuser) .....                               | 15        |
|          | User Login Data .....                                    | 15        |
| 3.3      | PERMISSION TYPES .....                                   | 16        |
|          | Normal Permissions .....                                 | 16        |
|          | Special and Plugin Permissions .....                     | 16        |
|          | Partner Group Permissions .....                          | 16        |
| <b>4</b> | <b>APIS FOR USERS, ROLES, AND PERMISSIONS .....</b>      | <b>18</b> |

---

|        |                                |    |
|--------|--------------------------------|----|
| 4.1    | USERSERVICE .....              | 18 |
| 4.1.1  | addAction.....                 | 19 |
| 4.1.2  | updateAction .....             | 20 |
| 4.1.3  | getAction.....                 | 21 |
| 4.1.4  | getByLoginIdAction .....       | 22 |
| 4.1.5  | deleteAction.....              | 23 |
| 4.1.6  | listAction .....               | 23 |
| 4.1.7  | notifyBan.....                 | 24 |
| 4.1.8  | loginAction .....              | 24 |
| 4.1.9  | loginByLoginIdAction .....     | 26 |
| 4.1.10 | updateLoginDataAction .....    | 27 |
| 4.1.11 | resetPasswordAction.....       | 28 |
| 4.1.12 | setInitialPasswordAction ..... | 29 |
| 4.1.13 | enableLoginAction .....        | 31 |
| 4.1.14 | disableLoginAction .....       | 32 |
| 4.2    | USERROLESERVICE .....          | 33 |
| 4.2.1  | addAction.....                 | 33 |
| 4.2.2  | getAction.....                 | 34 |
| 4.2.3  | updateAction .....             | 35 |
| 4.2.4  | deleteAction.....              | 35 |
| 4.2.5  | listAction .....               | 36 |
| 4.2.6  | cloneAction .....              | 37 |
| 4.3    | PERMISSIONSERVICE .....        | 37 |
| 4.3.1  | addAction.....                 | 38 |
| 4.3.2  | getAction.....                 | 39 |
| 4.3.3  | updateAction .....             | 39 |

---

|           |  |           |
|-----------|--|-----------|
| 4.3.4     | deleteAction .....   | 40        |
| 4.3.5     | listAction .....   | 41        |
| 4.3.6     | getCurrentPermissions .....                                | 41        |
| 4.4       | PERMISSIONITEMSERVICE .....                                | 42        |
| 4.4.1     | addAction .....  | 42        |
| 4.4.2     | getAction .....  | 43        |
| 4.4.3     | updateAction .....   | 44        |
| 4.4.4     | deleteAction .....   | 44        |
| 4.4.5     | listAction .....   | 45        |
| <b>5</b>  | <b>ADDING A USER .....</b>                                 | <b>47</b> |
| 5.1       | USE CASE .....   | 47        |
| 5.2       | SAMPLE CODE .....  | 47        |
| <b>6</b>  | <b>CREATING A NEW ROLE BASED ON AN EXISTING ROLE .....</b> | <b>49</b> |
| 6.1       | USE CASE .....   | 49        |
| 6.2       | SAMPLE CODE .....  | 49        |
| <b>7</b>  | <b>MODIFYING A PERMISSION .....</b>                        | <b>51</b> |
| 7.1       | USE CASE .....   | 51        |
| 7.2       | SAMPLE CODE .....  | 51        |
| <b>8</b>  | <b>LISTING AN ACCOUNT'S PERMISSION ITEMS .....</b>         | <b>53</b> |
| 8.1       | USE CASE .....   | 53        |
| 8.2       | SAMPLE CODE .....  | 53        |
| <b>9</b>  | <b>APPLYING A ROLE TO A USER .....</b>                     | <b>55</b> |
| 9.1       | USE CASE .....   | 55        |
| 9.2       | SAMPLE CODE .....  | 55        |
| <b>10</b> | <b>UNDERSTANDING SERVER DATA FLOWS .....</b>               | <b>57</b> |
| <b>11</b> | <b>UNDERSTANDING APPLICATION DATA FLOWS .....</b>          | <b>58</b> |

---

|           |  |           |
|-----------|--|-----------|
| 11.1      | KMC .....  | 58        |
| 11.2      | ADMIN CONSOLE .....                                | 58        |
| 11.3      | KALTURA MEDIASPACE .....                           | 58        |
| <b>12</b> | <b>APPENDIX A: SYSTEM DEFAULTS .....</b>           | <b>59</b> |
| 12.1      | MAPPING ROLES TO PERMISSION NAMES .....            | 59        |
| 12.1.1    | Understanding Default Roles .....                  | 59        |
| 12.1.2    | Partner (0) Roles .....                            | 59        |
| 12.1.3    | Template Partner (99) Roles .....                  | 59        |
| 12.1.4    | Admin Console Partner (-2) Roles .....             | 63        |
| 12.2      | MAPPING PERMISSION NAMES TO PERMISSION ITEMS ..... | 64        |
| 12.2.1    | CUSTOM_DATA_FIELD_DELETE .....                     | 64        |
| 12.2.2    | CUSTOM_DATA_FIELD_UPDATE .....                     | 64        |
| 12.2.3    | CUSTOM_DATA_FIELD_ADD .....                        | 65        |
| 12.2.4    | KMC_READ_ONLY .....                                | 66        |
| 12.2.5    | KMC_ACCESS .....                                   | 67        |
| 12.2.6    | AUDIT_TRAIL_ADD .....                              | 67        |
| 12.2.7    | AUDIT_TRAIL_BASE .....                             | 67        |
| 12.2.8    | ANALYTICS_SEND_DATA .....                          | 68        |
| 12.2.9    | SEARCH_SERVICE .....                               | 68        |
| 12.2.10   | WIDGET_ADMIN .....                                 | 69        |
| 12.2.11   | ANALYTICS_SEND_DATA .....                          | 69        |
| 12.2.12   | WIDGET_ADMIN .....                                 | 69        |
| 12.2.13   | ANALYTICS_BASE .....                               | 69        |
| 12.2.14   | ADMIN_WHITE_BRANDING .....                         | 70        |
| 12.2.15   | ADMIN_PUBLISHER_MANAGE .....                       | 70        |
| 12.2.16   | ADMIN_ROLE_DELETE .....                            | 70        |

---

|         |                                   |    |
|---------|-----------------------------------|----|
| 12.2.17 | ADMIN_ROLE_ADD .....              | 70 |
| 12.2.18 | ADMIN_ROLE_UPDATE .....           | 71 |
| 12.2.19 | ADMIN_USER_DELETE.....            | 71 |
| 12.2.20 | ADMIN_USER_ADD .....              | 71 |
| 12.2.21 | ADMIN_USER_UPDATE .....           | 72 |
| 12.2.22 | ADMIN_BASE .....                  | 72 |
| 12.2.23 | CUSTOM_DATA_PROFILE_DELETE .....  | 73 |
| 12.2.24 | CUSTOM_DATA_PROFILE_UPDATE .....  | 73 |
| 12.2.25 | CUSTOM_DATA_PROFILE_ADD .....     | 74 |
| 12.2.26 | CUSTOM_DATA_PROFILE_BASE .....    | 74 |
| 12.2.27 | TRANSCODING_DELETE.....           | 74 |
| 12.2.28 | TRANSCODING_UPDATE .....          | 75 |
| 12.2.29 | TRANSCODING_ADD .....             | 75 |
| 12.2.30 | TRANSCODING_BASE .....            | 75 |
| 12.2.31 | ACCESS_CONTROL_DELETE.....        | 76 |
| 12.2.32 | ACCESS_CONTROL_UPDATE .....       | 76 |
| 12.2.33 | ACCESS_CONTROL_ADD .....          | 77 |
| 12.2.34 | ACCESS_CONTROL_BASE .....         | 77 |
| 12.2.35 | INTEGRATION_UPDATE_SETTINGS.....  | 77 |
| 12.2.36 | INTEGRATION_BASE .....            | 78 |
| 12.2.37 | ACCOUNT_UPDATE_SETTINGS.....      | 78 |
| 12.2.38 | ACCOUNT_BASE .....                | 78 |
| 12.2.39 | ADVERTISING_UPDATE_SETTINGS ..... | 79 |
| 12.2.40 | ADVERTISING_BASE .....            | 79 |
| 12.2.41 | STUDIO_SELECT_CONTENT .....       | 79 |
| 12.2.42 | STUDIO_BRAND_UICONF .....         | 79 |

---

|         |  |    |
|---------|--|----|
| 12.2.43 | STUDIO_DELETE_UICONF .....                       | 80 |
| 12.2.44 | STUDIO_UPDATE_UICONF .....                       | 80 |
| 12.2.45 | STUDIO_ADD_UICONF .....                          | 80 |
| 12.2.46 | STUDIO_BASE .....                                | 81 |
| 12.2.47 | SYNDICATION_DELETE .....                         | 81 |
| 12.2.48 | SYNDICATION_UPDATE .....                         | 81 |
| 12.2.49 | SYNDICATION_ADD .....                            | 82 |
| 12.2.50 | SYNDICATION_BASE .....                           | 82 |
| 12.2.51 | PLAYLIST_EMBED_CODE .....                        | 82 |
| 12.2.52 | PLAYLIST_DELETE .....                            | 82 |
| 12.2.53 | PLAYLIST_UPDATE .....                            | 83 |
| 12.2.54 | PLAYLIST_ADD .....                               | 83 |
| 12.2.55 | PLAYLIST_BASE .....                              | 84 |
| 12.2.56 | CONTENT_MODERATE_APPROVE_REJECT .....            | 84 |
| 12.2.57 | CONTENT_MODERATE_CUSTOM_DATA .....               | 85 |
| 12.2.58 | CONTENT_MODERATE_METADATA .....                  | 85 |
| 12.2.59 | CONTENT_MODERATE_BASE .....                      | 86 |
| 12.2.60 | LIVE_STREAM_UPDATE .....                         | 87 |
| 12.2.61 | LIVE_STREAM_ADD .....                            | 87 |
| 12.2.62 | CONTENT_MANAGE_SHARE .....                       | 88 |
| 12.2.63 | CONTENT_MANAGE_ANNOTATION .....                  | 88 |
| 12.2.64 | CONTENT_MANAGE_DOWNLOAD .....                    | 88 |
| 12.2.65 | CONTENT_MANAGE_VIRUS_SCAN .....                  | 89 |
| 12.2.66 | CONTENT_MANAGE_DISTRIBUTION_PROFILE_MODIFY ..... | 89 |
| 12.2.67 | CONTENT_MANAGE_DISTRIBUTION_REMOVE .....         | 89 |
| 12.2.68 | CONTENT_MANAGE_DISTRIBUTION_SEND .....           | 90 |

---

|         |   |     |
|---------|---|-----|
| 12.2.69 | CONTENT_MANAGE_ASSIGN_CATEGORIES.....   | 90  |
| 12.2.70 | CONTENT_MANAGE_THUMBNAIL .....          | 91  |
| 12.2.71 | CONTENT_MANAGE_SCHEDULE.....            | 93  |
| 12.2.72 | CONTENT_MANAGE_ACCESS_CONTROL.....      | 93  |
| 12.2.73 | CONTENT_MANAGE_CUSTOM_DATA.....         | 94  |
| 12.2.74 | CONTENT_MANAGE_DELETE .....             | 94  |
| 12.2.75 | CONTENT_MANAGE_RECONVERT.....           | 95  |
| 12.2.76 | CONTENT_MANAGE_EDIT_CATEGORIES .....    | 96  |
| 12.2.77 | CONTENT_MANAGE_EMBED_CODE .....         | 96  |
| 12.2.78 | CONTENT_MANAGE_DISTRIBUTION_BASE .....  | 96  |
| 12.2.79 | CONTENT_MANAGE_DISTRIBUTION_WHERE ..... | 97  |
| 12.2.80 | SYSTEM_ADMIN_USER_MANAGE .....          | 97  |
| 12.2.81 | SYSTEM_ADMIN_PUBLISHER_USAGE.....       | 98  |
| 12.2.82 | SYSTEM_ADMIN_PUBLISHER_ADD.....         | 98  |
| 12.2.83 | SYSTEM_ADMIN_PUBLISHER_REMOVE.....      | 98  |
| 12.2.84 | SYSTEM_ADMIN_PUBLISHER_BLOCK .....      | 98  |
| 12.2.85 | SYSTEM_ADMIN_PUBLISHER_CONFIG .....     | 99  |
| 12.2.86 | SYSTEM_ADMIN_PUBLISHER_KMC_ACCESS ..... | 99  |
| 12.2.87 | SYSTEM_ADMIN_PUBLISHER_BASE.....        | 99  |
| 12.2.88 | SYSTEM_ADMIN_BASE .....                 | 100 |
| 12.2.89 | CONTENT_MANAGE_BASE.....                | 100 |
| 12.2.90 | CONTENT_MANAGE_METADATA .....           | 102 |
| 12.2.91 | CONTENT_INGEST_FEED.....                | 103 |
| 12.2.92 | CONTENT_MANAGE_MIX.....                 | 103 |
| 12.2.93 | CONTENT_INGEST_UPLOAD.....              | 103 |
| 12.2.94 | CONTENT_INGEST_BULK_UPLOAD .....        | 105 |



---

|          |   |     |
|----------|---|-----|
| 12.2.95  | ALWAYS_ALLOWED_ACTIONS.....                   | 105 |
| 12.2.96  | BATCH_BASE.....                               | 107 |
| 12.2.97  | BASE_USER_SESSION_PERMISSION.....             | 114 |
| 12.2.98  | SYSTEM_ADMIN_SYSTEM_MONITOR.....              | 121 |
| 12.2.99  | SYSTEM_ADMIN_DEVELOPERS_TAB .....             | 121 |
| 12.2.100 | SYSTEM_ADMIN_BATCH_CONTROL.....               | 121 |
| 12.2.101 | SYSTEM_ADMIN_BATCH_CONTROL_INPROGRESS.....    | 122 |
| 12.2.102 | SYSTEM_ADMIN_BATCH_CONTROL_FAILED .....       | 123 |
| 12.2.103 | SYSTEM_ADMIN_BATCH_CONTROL_SETUP.....         | 123 |
| 12.2.104 | SYSTEM_ADMIN_STORAGE .....                    | 123 |
| 12.2.105 | SYSTEM_ADMIN_VIRUS_SCAN.....                  | 123 |
| 12.2.106 | SYSTEM_ADMIN_EMAIL_INGESTION .....            | 124 |
| 12.2.107 | SYSTEM_ADMIN_CONTENT_DISTRIBUTION_BASE .....  | 124 |
| 12.2.108 | SYSTEM_ADMIN_CONTENT_DISTRIBUTION_MODIFY..... | 125 |
| 12.2.109 | SYSTEM_ADMIN_PERMISSIONS_MANAGE .....         | 126 |
| 12.2.110 | SYSTEM_INTERNAL.....                          | 127 |
| 12.2.111 | SYSTEM_ADMIN_ENTRY_INVESTIGATION.....         | 127 |
| 12.2.112 | SYSTEM_FILESYNC.....                          | 128 |
| 12.2.113 | ADMIN_PERMISSION_ADD .....                    | 128 |
| 12.2.114 | ADMIN_PERMISSION_UPDATE .....                 | 129 |
| 12.2.115 | ADMIN_PERMISSION_DELETE .....                 | 129 |
| 12.2.116 | SHORT_LINK_BASE .....                         | 129 |
| 12.2.117 | SHORT_LINK_MODIFY.....                        | 130 |

## 1 ABOUT THIS DOCUMENT

### 1.1 SCOPE

This document describes:

- The roles and permissions infrastructure
- How to use Kaltura server APIs to define and modify roles and permissions in Kaltura applications

This document does not address:

- The Users and Roles pages in Kaltura applications, such as the Kaltura Management Console (KMC), the Kaltura Administration Console, and Kaltura MediaSpace
- Content-based permissions

### 1.2 WHO SHOULD READ THIS DOCUMENT?

This document is intended for Kaltura employees, partners, community members, and customers.

### 1.3 ASSUMPTIONS

To understand this document, you need to be familiar with:

- Kaltura terminology
- Kaltura server API architecture, including services, actions, and objects
- PHP programming language

### 1.4 RELATED INFORMATION

- <http://www.kaltura.org/>
- Understanding API Services (TBD)

### 1.5 VERSION HISTORY

| Date      | Version | Owner       | Change History |
|-----------|---------|-------------|----------------|
| May, 2011 | 1.0     | Dor Itzhaki | Created        |

## 2 GLOSSARY

| Term                           | Definition   |
|--------------------------------|--|
| Kaltura Administration Console | An application for administering the Kaltura system, including administration of multiple Kaltura accounts. The Admin Console typically is accessed by Kaltura system administrators and the IT team.  |
| Kaltura MediaSpace             | A fully customizable video portal  |
| KMC                            | Kaltura Management Console. An application for content management, application creation and configuration, content monetization, distribution and syndication, and account management and reporting. The KMC is accessed by Kaltura partner administrators and the various users of a Kaltura account. |
| KS                             | Kaltura session. A unique string that identifies the session creator. The KS is used to authenticate Kaltura API calls.  |
| kuser                          | Kaltura user   |
| Partner                        | An individual or organization with a Kaltura system account  |
| Partner ID                     | A numeric identifier that uniquely identifies a partner in the Kaltura database  |
| Publisher                      | See Partner.   |
| puser ID                       | Partner user identifier  |

## 3 UNDERSTANDING USERS, ROLES, AND PERMISSIONS

### 3.1 ROLES AND PERMISSIONS: OVERVIEW

#### 3.1.1 Introduction

Roles and permissions enable organizations to define a user's ability to perform actions based on the user's responsibilities.

A publisher uses the roles and permissions infrastructure to specify actions that a user is allowed to perform.

#### 3.1.2 Server Infrastructure

##### API actions and API object properties

- An API action is not allowed unless a user has specific permission to execute it.
- All API actions have permission items.
- Only some API object properties have permission items.
- An API object parameter is allowed by default. When an object parameter does require a permission, a code comment specifies the permission item settings. The comment is included in the code of the class that defines the object, in the parameter's comment section. The comment format is `@requiresPermission`, followed by the applicable permission item settings. For example: `* @requiresPermission insert,update`

##### Permission Item, Permission, and Role: Overview

*Permission Item* — enables very granular settings for accessing a specific API and object property.

*Permission* — defines a functional flow by grouping the granular permission items.

*Role* —groups functional flows into usable users roles.

##### Permission Item

A permission item:

- Consists of an API action or an API object property
- Defines a specific API action, such as:
  - `baseEntry->list`

- category->add
- liveStream->delete

or

Defines a specific API object property, such as:

- KalturaBaseEntry::startDate
- KalturaBaseEntry::accessControlProfileId
- Can allow the following, when applied to an API object property:
  - Read
  - Update
  - Insert
- Is internal to the Kaltura server

### **Permission**

A permission:

- May have different meanings in different applications
- May be used by an application to enable access to a functionality, such as creating a player or uploading content
- Consists of a set of permission items

### **Role**

A user may be associated with a role.

A role is a set of permissions.

**Note:** A user currently can have only one role. Although the server supports multiple roles per user, the API currently blocks multiple role functionality.

## **3.2 USERS: OVERVIEW**

### **3.2.1 Introduction**

Roles and permissions apply to users of the Kaltura system.

A user is an individual who logs on to a Kaltura account. The user typically accesses the Kaltura server, a

Kaltura application or widget, or a Kaltura plugin.

## 3.2.2 Server Infrastructure

### Partner

A partner is an individual or organization with a Kaltura system account.

A partner defines roles and permissions that apply to its users.

A user may be associated with multiple partner accounts.

### Account Owner

Each Kaltura account must have a user who is defined as the account owner.

An account owner:

- Cannot be deleted
- Receives account administrator emails
- Has full control of account permissions and roles
- May assign full control of account permissions and roles to additional users
- May be changed to a different user after the user is assigned full control of account permissions and roles

**Note:** An account may have only one account owner.

### Kaltura Session (KS)

#### **KS Definition**

The Kaltura system uses a Kaltura Session (KS) identifier to identify and authenticate a user.

The KS:

- Is the string identifier generated by Kaltura or the client application using a shared secret for web session authentication
- Is generated using elements such as:
  - Partner ID
  - User ID
  - Session type

The session type is one of the following:

- ADMIN – Can access all the entries of the partner
- USER – Can access only entries created by the user

### Source for Roles and Permissions

The user's role determines permissions when the KS contains a user ID and a role is assigned to the user.

The KS session type determines permissions when one of the following occurs:

- The KS does not contain a user ID.
- The user is not assigned a role.

### Partner User ID (puser\_id)

A puser ID uniquely identifies the user for a specific partner.

### Kaltura User (kuser)

A kuser:

- Is an object that represents a person who uses the Kaltura system
- Contains metadata about the user, such as name, email, and location
- Is identified by a partner user ID (puser\_id), which must be unique among one partner's users
- May be associated with more than one partner.

**Note:** When a kuser is associated with multiple partners, the user has multiple kuser objects, one for each partner. All of the multiple kuser objects use the same `user_login_data` record for system logins.

### User Login Data

Information about Kaltura user (kuser) logons is stored in the `user_login_data` database table.

The user login data includes:

- Email
- Name
- Password
- Last partner whose account the user logged on to
  - Number of bad login retries

- Password expiry date

One data record may relate to multiple kusers. This enables a user to use a single ID and password for multiple partner accounts.

### 3.3 PERMISSION TYPES

The Kaltura system provides the following types of permission:

- Normal Permissions
- Special and Plugin Permissions
- Partner Group Permissions

A permission type may be one of the following:

- A user-level permission, which is associated with an individual user through a user role
- A partner-level permission, which applies only to a partner and is not associated with an individual user. A user role does not contain partner-level permissions.

#### Normal Permissions

*Normal* permissions, which are described in this document, are user-level permissions.

Normal permissions group permission items, which may be included in a user role. The user role is assigned to an individual user.

A user role may only contain normal permissions.

#### Special and Plugin Permissions

*Special* and *plugin* permissions are partner-level permissions.

Special and plugin permissions may define:

- A feature, such as access to a specific plugin (for example, virus scan)
- A special service, such as analytics

**Note:** A normal permission that specifies access to an API action or object property that relates to a plugin usually applies only if the plugin is included in a partner-level special permission.

#### Partner Group Permissions

*Partner group* permissions are partner-level permissions.

Partner group permissions include permission items.



Partner group permissions have a special `partnerGroup` parameter.

The `partnerGroup` parameter is a comma-separated list of partner IDs.

**Note:** When the value of `partnerGroup` is an asterisk (\*), the parameter applies to all partners.

When a user is allowed to perform an action based on the user's role and the user's partner has a partner group permission, the user is allowed to perform the action on all the partners listed in `partnerGroup`.

## 4 APIs FOR USERS, ROLES, AND PERMISSIONS

You can use Kaltura APIs to define and modify users, roles, and permissions.

### 4.1 USERSERVICE

A service API class that manages partner users.

#### Remarks

`userId` is the unique identifier in the partner's system.

The `partnerId`, `userId` couple constitutes a unique key in Kaltura's database.

#### Extends

`KalturaBaseUserService`

**Note:** `AdminUserService` also extends `KalturaBaseUserService` (for backward compatibility).

Do not use `AdminUserService`, which is deprecated.

#### Actions

| Name                               | Description   |
|------------------------------------|---|
| <code>addAction</code>             | Adds a new user to an existing account in the Kaltura database.                                       |
| <code>updateAction</code>          | Updates an existing user object.  |
| <code>getAction</code>             | Retrieves a user object for a specified user ID.  |
| <code>getByLoginIdAction</code>    | Retrieves a user object for a user's login ID and partner ID.   |
| <code>deleteAction</code>          | Deletes a user from a partner account.  |
| <code>listAction</code>            | Lists user objects that are associated with an account.   |
| <code>notifyBan</code>             | Notifies that a user is banned from an account.   |
| <code>loginAction</code>           | Logs a user into a partner account with a partner ID, a partner user ID (puser), and a user password. |
| <code>loginByLoginIdAction</code>  | Logs a user into a partner account with a user login ID and a user password.                          |
| <code>updateLoginDataAction</code> | Updates a user's login data:  |

| Name                     | Description   |
|--------------------------|---|
|                          | <ul style="list-style-type: none"> <li>Email</li> <li>Password</li> <li>Name</li> </ul>                 |
| resetPasswordAction      | Resets a user's password and sends the user an email containing a link for setting up the new password. |
| setInitialPasswordAction | Sets a user's password.   |
| enableLoginAction        | Enables a user to log into a partner account using an email address and a password.                     |
| disableLoginAction       | Disables a user's ability to log into a partner account using an email address and a password.          |

### 4.1.1 addAction

Adds a new user to an existing account in the Kaltura database.

```
function addAction(KalturaUser $user)
```

#### Parameters

| Name | Input/Output | Type        | Description  |
|------|--------------|-------------|--------------|
| user | Input        | KalturaUser | The new user |

#### Return Value

| Type        | Description           |
|-------------|-----------------------|
| KalturaUser | The added user object |

## Errors

| Name                               | Description  |
|------------------------------------|--|
| DUPLICATE_USER_BY_ID               | A user with the ID [ <i>user-&gt;id</i> ] already exists in system.  |
| PROPERTY_VALIDATION_CANNOT_BE_NULL | The property [ <i>property_name</i> ] cannot be NULL.  |
| INVALID_FIELD_VALUE                | The value in field [ <i>field_name</i> ] is not valid.   |
| UNKNOWN_PARTNER_ID                 | The partner ID [ <i>partner_id</i> ] is not recognized.  |
| ADMIN_LOGIN_USERS_QUOTA_EXCEEDED   | The permitted number of user logins has been reached. No more logins are permitted for this partner account.   |
| PASSWORD_STRUCTURE_INVALID         | <p>The password you entered is not valid. Passwords must:</p> <ul style="list-style-type: none"> <li>• Contain between 8 and 14 characters</li> <li>• Not contain your name</li> <li>• Contain at least one lowercase letter (a-z)</li> <li>• Contain at least one digit (0-9)</li> <li>• Contain at least one of the following symbols:<br/>%~!@#\$%^*+=+?[]{}</li> <li>• Not contain the following characters: &lt; or &gt;</li> </ul> |
| DUPLICATE_USER_BY_LOGIN_ID         | A loginable user with the email [ <i>login_email</i> ] already exists in system.   |

### 4.1.2 updateAction

Updates an existing user object.

```
public function updateAction($userId, KalturaUser $user)
```

#### Remarks

You also can use this action to update the `userId`.

## Parameters

| Name   | Input/Output | Type        | Description  |
|--------|--------------|-------------|--|
| userId | Input        | String      | The user's unique identifier in the partner's system |
| user   | Input        | KalturaUser | The updated user                                     |

## Return Value

| Type        | Description             |
|-------------|-------------------------|
| KalturaUser | The updated user object |

## Errors

| Name                                   | Description   |
|--|---|
| INVALID_USER_ID                        | The user ID is not valid.                                 |
| CANNOT_DELETE_OR_BLOCK_ROOT_ADMIN_USER | An account owner user cannot be deleted.                  |
| USER_ROLE_NOT_FOUND                    | The user role cannot be located.                          |
| ACCOUNT_OWNER_NEEDS_PARTNER_ADMIN_ROLE | The account owner must have a partner administrator role. |

## 4.1.3 getAction

Retrieves a user object for a specified user ID.

```
public function getAction($userId)
```

## Parameters

| Name   | Input/Output | Type   | Description  |
|--------|--------------|--------|--|
| userId | Input        | String | The user's unique identifier in the partner's system |

## Return Value

| Type        | Description               |
|-------------|---------------------------|
| KalturaUser | The specified user object |

## Errors

| Name            | Description               |
|-----------------|---------------------------|
| INVALID_USER_ID | The user ID is not valid. |

## 4.1.4 getByLoginIdAction

Retrieves a user object for a user's login ID and partner ID.

```
public function getByLoginIdAction($loginId)
```

## Remarks

A login ID is the email address used by a user to log into the system.

## Parameters

| Name    | Input/Output | Type   | Description   |
|---------|--------------|--------|---|
| loginId | Input        | String | The user's email address that identifies the user for login |

## Return Value

| Type        | Description  |
|-------------|--|
| KalturaUser | The user object represented by the login and partner IDs |

## Errors

| Name                 | Description                     |
|----------------------|---------------------------------|
| LOGIN_DATA_NOT_FOUND | The login ID cannot be located. |

| Name           | Description                 |
|----------------|-----------------------------|
| USER_NOT_FOUND | The user cannot be located. |

### 4.1.5 deleteAction

Deletes a user from a partner account.

```
public function deleteAction($userId)
```

#### Parameters

| Name   | Input/Output | Type   | Description  |
|--------|--------------|--------|--|
| userId | Input        | String | The user's unique identifier in the partner's system |

#### Return Value

| Type        | Description             |
|-------------|-------------------------|
| KalturaUser | The deleted user object |

#### Errors

| Name            | Description               |
|-----------------|---------------------------|
| INVALID_USER_ID | The user ID is not valid. |

### 4.1.6 listAction

Lists user objects that are associated with an account.

```
public function listAction(KalturaUserFilter $filter = null,
    KalturaFilterPager $pager = null)
```

#### Remarks

Blocked users are listed unless you use a filter to exclude them.

Deleted users are not listed unless you use a filter to include them.

## Parameters

| Name   | Input/Output        | Type               | Description  |
|--------|---------------------|--------------------|--|
| filter | Input<br>(optional) | KalturaUserFilter  | A filter used to exclude specific types of users       |
| pager  | Input<br>(optional) | KalturaFilterPager | A limit for the number of records to display on a page |

## Return Value

| Type                    | Description              |
|-------------------------|--------------------------|
| KalturaUserListResponse | The list of user objects |

### 4.1.7 notifyBan

Notifies that a user is banned from an account.

```
public function notifyBan($userId)
```

## Parameters

| Name   | Input/Output | Type   | Description  |
|--------|--------------|--------|--|
| userId | Input        | String | The user's unique identifier in the partner's system |

## Errors

| Name            | Description               |
|-----------------|---------------------------|
| INVALID_USER_ID | The user ID is not valid. |

### 4.1.8 loginAction

Logs a user into a partner account with a partner ID, a partner user ID (puser), and a user password.

```
public function loginAction($partnerId, $userId, $password, $expiry =
```



```
86400, $privileges = '*')
```

## Remarks

The action enables a user to generate a KS.

The KS enables the user to execute API actions.

## Parameters

| Name       | Input/Output | Type    | Description  |
|------------|--------------|---------|--|
| partnerId  | Input        | Integer | The identifier of the partner account  |
| userId     | Input        | String  | The user's unique identifier in the partner's system   |
| password   | Input        | String  | The user's password  |
| expiry     | Input        | Integer | The requested time (in seconds) before the generated KS expires.<br>By default, a KS expires after 24 hours. |
| privileges | Input        | String  | Special privileges   |

## Return Value

| Type   | Description   |
|--------|---------------|
| String | The user's KS |

## Errors

| Name                   | Description   |
|------------------------|---|
| USER_NOT_FOUND         | The user cannot be located.   |
| USER_WRONG_PASSWORD    | The user password is incorrect.   |
| INVALID_PARTNER_ID     | The partner ID [ <i>partner_id</i> ] is not valid.  |
| LOGIN_RETRIES_EXCEEDED | You tried logging in too many times. Your account is locked and will not be available for 24 hours. |

| Name             | Description             |
|------------------|-------------------------|
| LOGIN_BLOCKED    | Your account is locked. |
| PASSWORD_EXPIRED | Your password expired.  |
| USER_IS_BLOCKED  | The user is blocked.    |

### 4.1.9 loginByLoginIdAction

Logs a user into a partner account with a user login ID and a user password.

```
public function loginByLoginIdAction($loginId, $password, $partnerId =
null, $expiry = 86400, $privileges = '*')
```

#### Remarks

The action enables a user to generate a KS.

The KS enables the user to execute API actions.

| Name       | Input/Output        | Type    | Description  |
|------------|---------------------|---------|--|
| loginId    | Input               | String  | The user's email address that identifies the user for login  |
| password   | Input               | String  | The user's password  |
| partnerId  | Input<br>(Optional) | Integer | The identifier of the partner account  |
| expiry     | Input               | Integer | The requested time (in seconds) before the generated KS expires.<br>By default, a KS expires after 24 hours. |
| privileges | Input               | String  | Special privileges   |

#### Return Value

| Type   | Description   |
|--------|---------------|
| String | The user's KS |

## Errors

| Name                   | Description   |
|------------------------|---|
| USER_NOT_FOUND         | The user cannot be located.   |
| USER_WRONG_PASSWORD    | The user password is incorrect.   |
| INVALID_PARTNER_ID     | The partner ID [ <i>name</i> ] is not valid.  |
| LOGIN_RETRIES_EXCEEDED | You tried logging in too many times. Your account is locked and will not be available for 24 hours. |
| LOGIN_BLOCKED          | Your account is locked.   |
| PASSWORD_EXPIRED       | Your password expired.  |
| USER_IS_BLOCKED        | The user is blocked.  |

### 4.1.10 updateLoginDataAction

Updates a user's login data:

- Email
- Password
- Name

```
public function updateLoginDataAction( $oldLoginId , $password ,
$newLoginId = "" , $newPassword = "" , $newFirstName = null, $newLastName =
null)
```

| Name       | Input/Output        | Type   | Description   |
|------------|---------------------|--------|---|
| oldLoginId | Input               | String | The user's current email address that identified the user for login |
| password   | Input               | String | The user's existing password  |
| newLoginId | Input<br>(Optional) | String | The user's email address that will identify the user for login      |

| Name         | Input/Output        | Type   | Description               |
|--------------|---------------------|--------|---------------------------|
| newPassword  | Input<br>(Optional) | String | The user's new password   |
| newFirstName | Input<br>(Optional) | String | The user's new first name |
| newLastName  | Input<br>(Optional) | String | The user's new last name  |

## Errors

| Name                       | Description   |
|----------------------------|---|
| INVALID_FIELD_VALUE        | The value in field <i>[name]</i> is not valid.  |
| LOGIN_DATA_NOT_FOUND       | The login ID cannot be located.   |
| WRONG_OLD_PASSWORD         | The existing password is incorrect.   |
| PASSWORD_STRUCTURE_INVALID | <p>The password you entered is not valid. Passwords must:</p> <ul style="list-style-type: none"> <li>Contain between 8 and 14 characters</li> <li>Not contain your name</li> <li>Contain at least one lowercase letter (a-z)</li> <li>Contain at least one digit (0-9)</li> <li>Contain at least one of the following symbols:<br/>%~!@#\$%^*+=?[]{}</li> <li>Not contain the following characters: &lt; or &gt;</li> </ul> |
| PASSWORD_ALREADY_USED      | The password you chose has already been used.   |
| LOGIN_ID_ALREADY_USED      | The login ID is already in use.   |

### 4.1.11 resetPasswordAction

Resets a user's password and sends the user an email containing a link for setting up the new password.

```
public function resetPasswordAction($email)
```

## Remarks

This action is used in the “Forgot password” feature.

## Parameters

| Name  | Input/Output | Type   | Description                            |
|-------|--------------|--------|--|
| email | Input        | String | The user's email address (login email) |

## Errors

| Name                       | Description  |
|----------------------------|--|
| LOGIN_DATA_NOT_FOUND       | The login ID (login email) cannot be located.  |
| PASSWORD_STRUCTURE_INVALID | <p>The password you entered is not valid. Passwords must:</p> <ul style="list-style-type: none"> <li>Contain between 8 and 14 characters</li> <li>Not contain your name</li> <li>Contain at least one lowercase letter (a-z)</li> <li>Contain at least one digit (0-9)</li> <li>Contain at least one of the following symbols:<br/>%~!@#\$%^*+=+?[]{}</li> <li>Not contain the following characters: &lt; or &gt;</li> </ul> |
| PASSWORD_ALREADY_USED      | The password you chose has already been used.  |
| INVALID_FIELD_VALUE        | The value in field [ <i>field_name</i> ] is not valid.   |
| LOGIN_ID_ALREADY_USED      | The login ID is already in use.  |

## 4.1.12 setInitialPasswordAction

Sets a user's password.

```
public function setInitialPasswordAction($hashKey, $newPassword)
```

## Remarks

The application uses this action internally.

## Context

Called to set a user's password after a `resetPasswordAction` request.

## Parameters

| Name        | Input/Output | Type   | Description                            |
|-------------|--------------|--------|--|
| hashKey     | Input        | String | The hash key used to identify the user |
| newPassword | Input        | String | The new password to set for the user   |

## Errors

| Name                          | Description  |
|-------------------------------|--|
| LOGIN_DATA_NOT_FOUND          | The login ID cannot be located.  |
| PASSWORD_STRUCTURE_INVALID    | <p>The password you entered is not valid. Passwords must:</p> <ul style="list-style-type: none"> <li>Contain between 8 and 14 characters</li> <li>Not contain your name</li> <li>Contain at least one lowercase letter (a-z)</li> <li>Contain at least one digit (0-9)</li> <li>Contain at least one of the following symbols:<br/>%~!@#\$%^*+=?[]{} </li> <li>Not contain the following characters: &lt; or &gt;</li> </ul> |
| NEW_PASSWORD_HASH_KEY_EXPIRED | The specified hash key is expired.   |
| NEW_PASSWORD_HASH_KEY_INVALID | The specified hash key is not valid.   |
| PASSWORD_ALREADY_USED         | The password you chose has already been used.  |
| INTERNAL_SERVERL_ERROR        | An internal server error occurred.   |

### 4.1.13 enableLoginAction

Enables a user to log into a partner account using an email address and a password.

```
public function enableLoginAction($userId, $loginId, $password = null)
```

#### Parameters

| Name     | Input/Output        | Type   | Description   |
|----------|---------------------|--------|---|
| userId   | Input               | String | The user's unique identifier in the partner's system        |
| loginId  | Input               | String | The user's email address that identifies the user for login |
| password | Input<br>(Optional) | String | The user's password   |

#### Return Value

| Type        | Description   |
|-------------|---|
| KalturaUser | The user object represented by the user and login IDs |

#### Errors

| Name                             | Description   |
|----------------------------------|---|
| USER_LOGIN_ALREADY_ENABLED       | The user already is allowed to log in.  |
| USER_NOT_FOUND                   | The user cannot be located.   |
| ADMIN_LOGIN_USERS_QUOTA_EXCEEDED | The permitted number of user logins has been reached. No more logins are permitted for this partner account.  |
| PASSWORD_STRUCTURE_INVALID       | The password you entered is not valid. Passwords must: <ul style="list-style-type: none"> <li>Contain between 8 and 14 characters</li> <li>Not contain your name</li> </ul> |

| Name                  | Description  |
|-----------------------|--|
|                       | <ul style="list-style-type: none"> <li>Contain at least one lowercase letter (a-z)</li> <li>Contain at least one digit (0-9)</li> <li>Contain at least one of the following symbols:<br/>%~!@#\$%^*+=+?[]{}</li> <li>Not contain the following characters: &lt; or &gt;</li> </ul> |
| LOGIN_ID_ALREADY_USED | The login ID is already in use.  |

#### 4.1.14 disableLoginAction

Disables a user's ability to log into a partner account using an email address and a password.

```
public function disableLoginAction($userId = null, $loginId = null)
```

##### Remarks

You may use either a `userId` or a `loginId` parameter for this action.

##### Parameters

| Name                 | Input/Output        | Type   | Description   |
|----------------------|---------------------|--------|---|
| <code>userId</code>  | Input<br>(Optional) | String | The user's unique identifier in the partner's system        |
| <code>loginId</code> | Input<br>(Optional) | String | The user's email address that identifies the user for login |

##### Return Value

| Type                     | Description   |
|--------------------------|---|
| <code>KalturaUser</code> | The user object represented by the user and login IDs |



## Errors

| Name                                | Description   |
|-------------------------------------|---|
| USER_LOGIN_ALREADY_DISABLED         | The user already is not allowed to log in.            |
| PROPERTY_VALIDATION_CANNOT_BE_NULL  | The property [ <i>property_name</i> ] cannot be NULL. |
| USER_NOT_FOUND                      | The user cannot be located.                           |
| CANNOT_DISABLE_LOGIN_FOR_ADMIN_USER | A login cannot be disabled for an ADMIN user.         |

## 4.2 USERROLESERVICE

A service API class that creates and manages user roles.

### Extends

KalturaBaseService

### Actions

| Name         | Description   |
|--------------|---|
| addAction    | Adds a new user role object to the account.                             |
| getAction    | Retrieves a user role object using its ID.                              |
| updateAction | Updates an existing user role object.                                   |
| deleteAction | Deletes an existing user role object.                                   |
| listAction   | Lists user role objects that are associated with an account.            |
| cloneAction  | Creates a new user role object that is a duplicate of an existing role. |

### 4.2.1 addAction

Adds a new user role object to the account.

```
public function addAction(KalturaUserRole $userRole)
```

## Parameters

| Name     | Input/Output | Type            | Description |
|----------|--------------|-----------------|-------------|
| userRole | Input        | KalturaUserRole | A new role  |

## Return Value

| Type            | Description                |
|-----------------|----------------------------|
| KalturaUserRole | The added user role object |

## Errors

| Name                               | Description  |
|------------------------------------|--|
| PROPERTY_VALIDATION_CANNOT_BE_NULL | The property [ <i>name</i> ] cannot be NULL.             |
| PROPERTY_VALIDATION_NOT_UPDATABLE  | The property [ <i>name</i> ] cannot be updated.          |
| PERMISSION_NOT_FOUND               | A permission associated with the role cannot be located. |

## 4.2.2 getAction

Retrieves a user role object using its ID.

```
public function getAction($userId)
```

## Parameters

| Name   | Input/Output | Type    | Description                  |
|--------|--------------|---------|------------------------------|
| userId | Input        | Integer | The user's unique identifier |

## Return Value

| Type            | Description                    |
|-----------------|--------------------------------|
| KalturaUserRole | The retrieved user role object |

## Errors

| Name              | Description                         |
|-------------------|-------------------------------------|
| INVALID_OBJECT_ID | The object identifier is not valid. |

### 4.2.3 updateAction

Updates an existing user role object.

```
public function updateAction($userId, KalturaUserRole $userRole)
```

#### Parameters

| Name     | Input/Output | Type            | Description  |
|----------|--------------|-----------------|--|
| userId   | Input        | Integer         | The user role's unique identifier                  |
| userRole | Input        | KalturaUserRole | The role object that contains parameters to update |

#### Return Value

| Type            | Description                  |
|-----------------|------------------------------|
| KalturaUserRole | The updated user role object |

## Errors

| Name                 | Description  |
|----------------------|--|
| INVALID_OBJECT_ID    | The object identifier is not valid.                      |
| PERMISSION_NOT_FOUND | A permission associated with the role cannot be located. |

### 4.2.4 deleteAction

Deletes an existing user role object.

```
public function deleteAction($userId)
```

## Parameters

| Name   | Input/Output | Type    | Description                       |
|--------|--------------|---------|-----------------------------------|
| roleId | Input        | Integer | The user role's unique identifier |

## Return Value

| Type            | Description                  |
|-----------------|------------------------------|
| KalturaUserRole | The deleted user role object |

## Errors

| Name               | Description   |
|--------------------|---|
| INVALID_OBJECT_ID  | The object identifier is not valid.                 |
| ROLE_IS_BEING_USED | The role is in use. The action cannot be completed. |

## 4.2.5 listAction

Lists user role objects that are associated with an account.

```
public function listAction(KalturaUserRoleFilter $filter = null,
    KalturaFilterPager $pager = null)
```

## Remarks

Blocked user roles are listed unless you use a filter to exclude them.

Deleted user roles are not listed unless you use a filter to include them.

## Parameters

| Name   | Input/Output     | Type                  | Description  |
|--------|------------------|-----------------------|--|
| filter | Input (Optional) | KalturaUserRoleFilter | A filter used to exclude specific types of user roles  |
| pager  | Input (Optional) | KalturaFilterPager    | A limit for the number of records to display on a page |

#### Return Value

| Type                        | Description                   |
|-----------------------------|-------------------------------|
| KalturaUserRoleListResponse | The list of user role objects |

### 4.2.6 cloneAction

Creates a new user role object that is a duplicate of an existing role.

```
public function cloneAction($roleId)
```

#### Parameters

| Name   | Input/Output | Type    | Description                       |
|--------|--------------|---------|-----------------------------------|
| roleId | Input        | Integer | The user role's unique identifier |

#### Return Value

| Type            | Description                    |
|-----------------|--------------------------------|
| KalturaUserRole | The duplicate user role object |

#### Errors

| Name              | Description                         |
|-------------------|-------------------------------------|
| INVALID_OBJECT_ID | The object identifier is not valid. |

## 4.3 PERMISSIONSERVICE

A service API class that creates and manages user permissions.

#### Extends

KalturaBaseService

## Actions

| Name                  | Description   |
|-----------------------|---|
| addAction             | Adds a new permission object to the account.                  |
| getAction             | Retrieves a permission object using its ID.                   |
| updateAction          | Updates an existing permission object.                        |
| deleteAction          | Deletes an existing permission object.                        |
| listAction            | Lists permission objects that are associated with an account. |
| getCurrentPermissions | Retrieves a list of permissions that apply to the current KS. |

### 4.3.1 addAction

Adds a new permission object to the account.

```
public function addAction(KalturaPermission $permission)
```

#### Parameters

| Name       | Input/Output | Type              | Description        |
|------------|--------------|-------------------|--------------------|
| permission | Input        | KalturaPermission | The new permission |

#### Return Value

| Type              | Description                 |
|-------------------|-----------------------------|
| KalturaPermission | The added permission object |

#### Errors

| Name                               | Description                                     |
|------------------------------------|---|
| PROPERTY_VALIDATION_CANNOT_BE_NULL | The property [ <i>name</i> ] cannot be NULL.    |
| PROPERTY_VALIDATION_NOT_UPDATABLE  | The property [ <i>name</i> ] cannot be updated. |

### 4.3.2 getAction

Retrieves a permission object using its ID.

```
public function getAction($permissionName)
```

#### Parameters

| Name           | Input/Output | Type   | Description                         |
|----------------|--------------|--------|-------------------------------------|
| permissionName | Input        | String | The name assigned to the permission |

#### Return Value

| Type              | Description                     |
|-------------------|---------------------------------|
| KalturaPermission | The retrieved permission object |

#### Errors

| Name              | Description                         |
|-------------------|-------------------------------------|
| INVALID_OBJECT_ID | The object identifier is not valid. |

### 4.3.3 updateAction

Updates an existing permission object.

```
public function updateAction($permissionName, KalturaPermission  
$permission)
```

#### Parameters

| Name           | Input/Output | Type              | Description                         |
|----------------|--------------|-------------------|-------------------------------------|
| permissionName | Input        | String            | The name assigned to the permission |
| permission     | Input        | KalturaPermission | The updated permission              |

## Return Value

| Type              | Description                   |
|-------------------|-------------------------------|
| KalturaPermission | The updated permission object |

## Errors

| Name              | Description                         |
|-------------------|-------------------------------------|
| INVALID_OBJECT_ID | The object identifier is not valid. |

## 4.3.4 deleteAction

Deletes an existing permission object.

```
public function deleteAction($permissionName)
```

## Parameters

| Name           | Input/Output | Type   | Description                         |
|----------------|--------------|--------|-------------------------------------|
| permissionName | Input        | String | The name assigned to the permission |

## Return Value

| Type              | Description                   |
|-------------------|-------------------------------|
| KalturaPermission | The deleted permission object |

## Errors

| Name              | Description                         |
|-------------------|-------------------------------------|
| INVALID_OBJECT_ID | The object identifier is not valid. |



### 4.3.5 listAction

Lists permission objects that are associated with an account.

```
public function listAction(KalturaPermissionFilter $filter = null,
    KalturaFilterPager $pager = null)
```

#### Remarks

Blocked permissions are listed unless you use a filter to exclude them.

Deleted permissions are not listed unless you use a filter to include them.

#### Parameters

| Name   | Input/Output        | Type                    | Description  |
|--------|---------------------|-------------------------|--|
| filter | Input<br>(Optional) | KalturaPermissionFilter | A filter used to exclude specific types of permissions |
| pager  | Input<br>(Optional) | KalturaFilterPager      | A limit for the number of records to display on a page |

#### Return Value

| Type                          | Description                    |
|-------------------------------|--------------------------------|
| KalturaPermissionListResponse | The list of permission objects |

### 4.3.6 getCurrentPermissions

Retrieves a list of permissions that apply to the current KS.

```
public function getCurrentPermissions()
```

#### Remarks

The data is extracted from the KS as follows:

- The data is taken from the user's role when there is a `userId`.
- The data is taken according to the `sessionType` in the following cases:
  - There is no `userId`.

- The user is not associated with a role.

#### Return Value

| Type   | Description  |
|--------|--|
| String | A comma-separated list of current permission names |

## 4.4 PERMISSIONITEMSERVICE

A service API class that creates and manages permission items.

#### Extends

KalturaBaseService

#### Actions

| Name         | Description  |
|--------------|--|
| addAction    | Adds a new permission item object to the account.                  |
| getAction    | Retrieves a permission item object using its ID.                   |
| updateAction | Lists permission item objects that are associated with an account. |
| deleteAction | Deletes an existing permission item object.                        |
| listAction   | Lists permission item objects that are associated with an account. |

### 4.4.1 addAction

Adds a new permission item object to the account.

```
public function addAction(KalturaPermissionItem $permissionItem)
```

#### Remarks

This action is available only to Kaltura system administrators.

#### Parameters

| Name           | Input/Output | Type                  | Description             |
|----------------|--------------|-----------------------|-------------------------|
| permissionItem | Input        | KalturaPermissionItem | The new permission item |

#### Return Value

| Type                  | Description                      |
|-----------------------|----------------------------------|
| KalturaPermissionItem | The added permission item object |

#### Errors

| Name                               | Description                                     |
|------------------------------------|---|
| PROPERTY_VALIDATION_CANNOT_BE_NULL | The property [ <i>name</i> ] cannot be NULL.    |
| PROPERTY_VALIDATION_NOT_UPDATABLE  | The property [ <i>name</i> ] cannot be updated. |

### 4.4.2 getAction

Retrieves a permission item object using its ID.

```
public function getAction($permissionItemId)
```

#### Parameters

| Name             | Input/Output | Type    | Description                             |
|------------------|--------------|---------|---|
| permissionItemId | Input        | Integer | The permission item's unique identifier |

#### Return Value

| Type                  | Description                          |
|-----------------------|--------------------------------------|
| KalturaPermissionItem | The retrieved permission item object |

#### Errors

| Name              | Description                         |
|-------------------|-------------------------------------|
| INVALID_OBJECT_ID | The object identifier is not valid. |

### 4.4.3 updateAction

Updates an existing permission item object.

```
public function updateAction($permissionItemId, KalturaPermissionItem
    $permissionItem)
```

#### Remarks

This action is available only to Kaltura system administrators.

#### Parameters

| Name             | Input/Output | Type                  | Description                             |
|------------------|--------------|-----------------------|---|
| permissionItemId | Input        | Integer               | The permission item's unique identifier |
| permissionItem   | Input        | KalturaPermissionItem | The updated permission item             |

#### Return Value

| Type                  | Description                        |
|-----------------------|------------------------------------|
| KalturaPermissionItem | The updated permission item object |

#### Errors

| Name              | Description                         |
|-------------------|-------------------------------------|
| INVALID_OBJECT_ID | The object identifier is not valid. |

### 4.4.4 deleteAction

Deletes an existing permission item object.

```
public function deleteAction($permissionItemId)
```

#### Remarks

This action is available only to Kaltura system administrators.

## Parameters

| Name             | Input/Output | Type    | Description                             |
|------------------|--------------|---------|---|
| permissionItemId | Input        | Integer | The permission item's unique identifier |

## Return Value

| Type                  | Description                        |
|-----------------------|------------------------------------|
| KalturaPermissionItem | The deleted permission item object |

## Errors

| Name              | Description                         |
|-------------------|-------------------------------------|
| INVALID_OBJECT_ID | The object identifier is not valid. |

## 4.4.5 listAction

Lists permission item objects that are associated with an account.

```
public function listAction(KalturaPermissionItemFilter $filter = null,
    KalturaFilterPager $pager = null)
```

## Parameters

| Name   | Input/Output     | Type                        | Description   |
|--------|------------------|-----------------------------|---|
| filter | Input (Optional) | KalturaPermissionItemFilter | A filter used to exclude specific types of permission items |
| pager  | Input (Optional) | KalturaFilterPager          | A limit for the number of records to display on a page      |

#### Return Value

| Type                              | Description                         |
|-----------------------------------|-------------------------------------|
| KalturaPremissionItemListResponse | The list of permission item objects |

## 5 ADDING A USER

### 5.1 USE CASE

To add a user to a partner account:

1. Log on to the Kaltura system.
2. A KS is generated to identify and authenticate the user.
3. Send the following API request to the server: `UserService->addAction`
  - Specify the user parameters as a `KalturaUser` object.
4. The server processes the API request and returns the new user object.

### 5.2 SAMPLE CODE

```
/** Include the KalturaClient class */
require_once('KalturaClient.php');

/** Initiate a new KalturaClient object with the partner details */
$partnerId = <PARTNER_ID_HERE>; // replace with your partner ID
$config = new KalturaConfiguration($partnerId);
$config->serviceUrl = 'http://www.kaltura.com/'; // set serviceUrl if different
$client = new KalturaClient($config);

/** Set user login variables and call user->loginByLoginId action */
$loginId = '<USER_LOGIN_EMAIL_HERE>'; // replace with user's login email
$password = '<USER_LOGIN_PASSWORD_HERE>'; // replace with user's login password
$ks = $client->user->loginByLoginId($loginId, $password, $partnerId);

/** Set the client to use the KS that is returned */
$client->setKs($ks);

/** Create a new KalturaUser object to be added */
$newUser = new KalturaUser();
$newUser->id = 'NEW_USER_ID';
```

```
$newUser->firstName = 'first name';  
$newUser->lastName = 'last name';  
$newUser->email = 'new_user@kaltura.com';  
$newUser->isAdmin = true;  
$newUser->roleIds = 30; // must match an existing user role ID  
  
/** Call the user->add action with the new user object */  
$addedUser = $client->user->add($newUser);
```



## 6 CREATING A NEW ROLE BASED ON AN EXISTING ROLE

### 6.1 USE CASE

To create a new role from an existing role:

1. Log on to the Kaltura system.
2. A KS is generated to identify and authenticate the user.
3. Send the following API request to the server: UserRoleService->cloneAction
  - Specify the user role to copy.
4. The server processes the API request and returns the duplicate user role object.

### 6.2 SAMPLE CODE

```
/** Include the KalturaClient class */
require_once('KalturaClient.php');

/** Initiate a new KalturaClient object with the partner details */
$partnerId = <PARTNER_ID_HERE>; // replace with your partner ID
$config = new KalturaConfiguration($partnerId);
$config->serviceUrl = 'http://www.kaltura.com/'; // set serviceUrl if different
$client = new KalturaClient($config);

/** Set user login variables and call user->loginByLoginId action */
$loginId = '<USER_LOGIN_EMAIL_HERE>'; // replace with user's login email
$password = '<USER_LOGIN_PASSWORD_HERE>'; // replace with user's login password
$ks = $client->user->loginByLoginId($loginId, $password, $partnerId);

/** Set the client to use the KS that is returned */
$client->setKs($ks);

/** Set the original user role ID */
$originalRoleId = <ORIGINAL_USER_ROLE_ID>; // must match an existing user role ID
```

```
/** Call the userRole->clone action */  
$duplicatedRole = $client->userRole->cloneAction($originalRoleId);
```

## 7 MODIFYING A PERMISSION

### 7.1 USE CASE

To modify a permission:

1. Log on to the Kaltura system.
2. A KS is generated to identify and authenticate the user.
3. Send the following API request to the server: `PermissionService->updateAction`
  - Specify the following:
    - The current permission name
    - The properties to update as a `KalturaPermission` object
4. The server processes the API request and returns the updated permission object.

### 7.2 SAMPLE CODE

```
/** Include the KalturaClient class */
require_once('KalturaClient.php');

/** Initiate a new KalturaClient object with the partner details */
$partnerId = <PARTNER ID HERE>; // replace with your partner ID
$config = new KalturaConfiguration($partnerId);
$config->serviceUrl = 'http://www.kaltura.com/'; // set serviceUrl if different
$client = new KalturaClient($config);

/** Set user login variables and call user->loginByLoginId action */
$loginId = '<USER LOGIN EMAIL HERE>'; // replace with user's login email
$password = '<USER LOGIN PASSWORD HERE>'; // replace with user's login password
$ks = $client->user->loginByLoginId($loginId, $password, $partnerId);

/** Set the client to use the KS that is returned */
```

```
$client->setKs($ks);

/** Set the existing permission's name */
$permissionName = '<PERMISSION_NAME_HERE>'; // must match an existing permission name

/** Set a KalturaPermission object with the required parameters to update */
$updatePermission = new KalturaPermission();
$updatePermission->name = 'NEW_PERMISSION_NAME';
$updatePermission->permissionItemsIds = '<LIST_OF_PERMISSION_ITEM_IDS>'; // must match existing permission item IDs

/** Call the permission->update action */
$updatePermission = $client->permission->update($permissionName, $updatePermission);
```

## 8 LISTING AN ACCOUNT'S PERMISSION ITEMS

### 8.1 USE CASE

To list the permission items that are associated with an account:

1. Log on to the Kaltura system.
2. A KS is generated to identify and authenticate the user.
3. Send the following API request to the server: `PermissionItemService->listAction`
  - You may specify:
    - A filter
    - A limit on the number of records to display on a page
4. The server processes the API request and returns the list of permission item objects.

### 8.2 SAMPLE CODE

```
/** Include the KalturaClient class */
require_once('KalturaClient.php');

/** Initiate a new KalturaClient object with the partner details */
$partnerId = <PARTNER_ID_HERE>; // replace with your partner ID
$config = new KalturaConfiguration($partnerId);
$config->serviceUrl = 'http://www.kaltura.com/'; // set serviceUrl if different
$client = new KalturaClient($config);

/** Set user login variables and call user->loginByLoginId action */
$loginId = '<USER_LOGIN_EMAIL_HERE>'; // replace with user's login email
$password = '<USER_LOGIN_PASSWORD_HERE>'; // replace with user's login password
$ks = $client->user->loginByLoginId($loginId, $password, $partnerId);

/** Set the client to use the KS that is returned */
```

```
$client->setKs($ks);

/** Set a KalturaPermissionItemFilter object - optional */
$filter = new KalturaPermissionItemFilter();
$filter->typeIn = KalturaPermissionItemType::API_ACTION_ITEM; // example of listing only action permission items

/** Set a KalturaFilterPager object - optional */
$pager = new KalturaFilterPager();
$pager->pageIndex = 1; // get only page 1
$pager->pageSize = 20; // page size must be 20

/** Call the permissionItem->list action */
$permissionItemList = $client->permissionItem->listAction($filter, $pager);
```

## 9 APPLYING A ROLE TO A USER

### 9.1 USE CASE

To apply a role to a user:

1. Log on to the Kaltura system.
2. A KS is generated to identify and authenticate the user.
3. Send the following API request to the server: UserService->updateAction
  - Specify the following:
    - The user role ID
    - A KalturaUser object with a parameter that specifies the new user role identifier
4. The server processes the API request and returns the user role object.

### 9.2 SAMPLE CODE

```
/** Include the KalturaClient class */
require_once('KalturaClient.php');

/** Initiate a new KalturaClient object with the partner details */
$partnerId = <PARTNER ID HERE>; // replace with your partner ID
$config = new KalturaConfiguration($partnerId);
$config->serviceUrl = 'http://www.kaltura.com/'; // set serviceUrl if different
$client = new KalturaClient($config);

/** Set user login variables and call user->loginByLoginId action */
$loginId = '<USER LOGIN EMAIL HERE>'; // replace with user's login email
$password = '<USER LOGIN PASSWORD HERE>'; // replace with user's login password
$ks = $client->user->loginByLoginId($loginId, $password, $partnerId);

/** Set the client to use the KS that is returned */
```

```
$client->setKs($ks);

/** Set the existing user's ID */
$userId = 'user_id'; // must match an existing user ID

/** Create a new KalturaUser object and set the roleIds parameter to the required user role ID */
$updateUser = new KalturaUser();
$updateUser->roleIds = '<NEW_ROLE_ID_HERE>'; // must match an existing user role ID

/** Call the user->update action */
$updateUser = $client->user->update($userId, $updateUser);
```



## 10 UNDERSTANDING SERVER DATA FLOWS

This section describes the basic data flow of the Kaltura server for users, roles, and permissions.

1. A user logs into the system using a unique email and password or the account's user/admin secret.
2. A successful login request generates a KS string that is returned to the user. The KS holds elements that identify the user, such as `partnerId`, `userId`, and `sessionType`.
3. The user uses the KS to issue an API request.
4. The server receives the API request for a specific service and action.
5. The server decodes the KS, identifies the user, and checks for the role associated with the user.
6. The server checks for the permissions contained in the user's role.
7. The server checks for the permission items contained in the user's permissions.
8. The server grants access to the requested service and action only if a suitable permission item is found for the user.
9. A request to insert or update a new object property that requires special permission succeeds only if the user has the insert or update permission for the property. The request fails if the user does not have the permission.
10. The response includes an object property that requires special permission only if the user has the permission item that allows reading the property.

## 11 UNDERSTANDING APPLICATION DATA FLOWS

### 11.1 KMC

This section describes the basic data flow of the KMC for users, roles, and permissions.

1. A user logs into the KMC.
2. Using an API request, the KMC requests a list of permissions associated with the user from the server.
3. The KMC displays and hides specific UI objects according to the user's permissions.

### 11.2 ADMIN CONSOLE

This section describes the basic data flow of the Admin Console for users, roles, and permissions.

1. A user logs into the Admin Console.
2. Using an API request, the Admin Console requests a list of permissions associated with the user from the server.
3. According to the user's permissions, the Admin Console:
  - Displays and hides specific UI objects
  - Enables and blocks Admin Console actions

### 11.3 KALTURA MEDIASPACE

TBD

## 12 APPENDIX A: SYSTEM DEFAULTS

This section describes the system defaults for:

Mapping Roles to Permission Names

Mapping Permission Names to Permission Items

### 12.1 MAPPING ROLES TO PERMISSION NAMES

Understanding Default Roles defines the default roles.

The other sections list the roles and permissions included in each default role.

#### 12.1.1 Understanding Default Roles

The Kaltura system provides the following types of default roles:

- Partner (0) Roles  
Every partner may use the roles but cannot edit them.
- Template Partner (99) Roles  
The roles are copied to every partner when the partner is created. Every partner may use and edit the roles.
- Admin Console Partner (-2) Roles  
Only an Admin Console partner may use and edit the roles.

#### 12.1.2 Partner (0) Roles

| Role                    | Permissions                                      |
|-------------------------|--|
| Basic User Session Role | BASE_USER_SESSION_PERMISSION                     |
| Publisher Administrator | All permissions allowed for the current partner. |

#### 12.1.3 Template Partner (99) Roles

| Role    | Permissions |
|---------|-------------|
| Manager | KMC_ACCESS  |

| Role | Permissions   |
|------|---|
|      | KMC_READ_ONLY<br>CONTENT_INGEST_UPLOAD<br>CONTENT_INGEST_BULK_UPLOAD<br>CONTENT_INGEST_FEED<br>CONTENT_MANAGE_DISTRIBUTION_BASE<br>CONTENT_MANAGE_DISTRIBUTION_WHERE<br>CONTENT_MANAGE_DISTRIBUTION_SEND<br>CONTENT_MANAGE_DISTRIBUTION_REMOVE<br>CONTENT_MANAGE_DISTRIBUTION_PROFILE_MODIFY<br>CONTENT_MANAGE_VIRUS_SCAN<br>CONTENT_MANAGE_MIX<br>CONTENT_MANAGE_BASE<br>CONTENT_MANAGE_METADATA<br>CONTENT_MANAGE_ASSIGN_CATEGORIES<br>CONTENT_MANAGE_THUMBNAIL<br>CONTENT_MANAGE_SCHEDULE<br>CONTENT_MANAGE_ACCESS_CONTROL<br>CONTENT_MANAGE_CUSTOM_DATA<br>CONTENT_MANAGE_DELETE<br>CONTENT_MANAGE_RECONVERT<br>CONTENT_MANAGE_EDIT_CATEGORIES<br>CONTENT_MANAGE_ANNOTATION<br>CONTENT_MANAGE_SHARE<br>CONTENT_MANAGE_DOWNLOAD<br>LIVE_STREAM_ADD<br>LIVE_STREAM_UPDATE<br>CONTENT_MODERATE_BASE<br>CONTENT_MODERATE_METADATA<br>CONTENT_MODERATE_CUSTOM_DATA |

| Role | Permissions   |
|------|---|
|      | CONTENT_MODERATE_APPROVE_REJECT<br>PLAYLIST_BASE<br>PLAYLIST_ADD<br>PLAYLIST_UPDATE<br>PLAYLIST_DELETE<br>SYNDICATION_BASE<br>SYNDICATION_ADD<br>SYNDICATION_UPDATE<br>SYNDICATION_DELETE<br>STUDIO_BASE<br>STUDIO_ADD_UICONF<br>STUDIO_UPDATE_UICONF<br>STUDIO_DELETE_UICONF<br>ACCOUNT_BASE<br>INTEGRATION_BASE<br>ACCESS_CONTROL_BASE<br>ACCESS_CONTROL_ADD<br>ACCESS_CONTROL_UPDATE<br>ACCESS_CONTROL_DELETE<br>TRANSCODING_BASE<br>TRANSCODING_ADD<br>TRANSCODING_UPDATE<br>TRANSCODING_DELETE<br>CUSTOM_DATA_PROFILE_BASE<br>CUSTOM_DATA_PROFILE_ADD<br>CUSTOM_DATA_PROFILE_UPDATE<br>CUSTOM_DATA_PROFILE_DELETE<br>CUSTOM_DATA_FIELD_ADD<br>CUSTOM_DATA_FIELD_UPDATE |

| Role              | Permissions  |
|-------------------|--|
|                   | CUSTOM_DATA_FIELD_DELETE<br>ANALYTICS_BASE<br>WIDGET_ADMIN<br>SEARCH_SERVICE<br>ANALYTICS_SEND_DATA<br>AUDIT_TRAIL_BASE<br>AUDIT_TRAIL_ADD<br>ADVERTISING_BASE<br>ADVERTISING_UPDATE_SETTINGS<br>PLAYLIST_EMBED_CODE<br>STUDIO_BRAND_UICONF<br>STUDIO_SELECT_CONTENT<br>CONTENT_MANAGE_EMBED_CODE<br>PLAYLIST_EMBED_CODE |
| Content Uploader  | KMC_ACCESS<br>KMC_READ_ONLY<br>CONTENT_INGEST_UPLOAD<br>CONTENT_INGEST_BULK_UPLOAD<br>CONTENT_MANAGE_BASE  |
| Content Moderator | KMC_ACCESS<br>KMC_READ_ONLY<br>CONTENT_MODERATE_APPROVE_REJECT<br>CONTENT_MODERATE_BASE<br>CONTENT_MODERATE_METADATA<br>CONTENT_MODERATE_CUSTOM_DATA   |
| Player Designer   | KMC_ACCESS<br>KMC_READ_ONLY<br>STUDIO_BASE   |

| Role | Permissions  |
|------|--|
|      | STUDIO_ADD_UICONF<br>STUDIO_UPDATE_UICONF<br>STUDIO_DELETE_UICONF<br>STUDIO_BRAND_UICONF |

### 12.1.4 Admin Console Partner (-2) Roles

| Role                     | Permissions   |
|--------------------------|---|
| System Administrator     | All   |
| Support Manager          | SYSTEM_ADMIN_BASE<br>SYSTEM_ADMIN_PUBLISHER_BASE<br>SYSTEM_ADMIN_PUBLISHER_KMC_ACCESS<br>SYSTEM_ADMIN_PUBLISHER_CONFIG<br>SYSTEM_ADMIN_PUBLISHER_BLOCK<br>SYSTEM_ADMIN_PUBLISHER_ADD<br>SYSTEM_ADMIN_PUBLISHER_USAGE<br>SYSTEM_ADMIN_DEVELOPERS_TAB<br>SYSTEM_ADMIN_BATCH_CONTROL<br>SYSTEM_ADMIN_CONTENT_DISTRIBUTION_BASE<br>SYSTEM_ADMIN_CONTENT_DISTRIBUTION_MODIFY |
| Publishers Administrator | SYSTEM_ADMIN_BASE<br>SYSTEM_ADMIN_PUBLISHER_BASE<br>SYSTEM_ADMIN_PUBLISHER_KMC_ACCESS<br>SYSTEM_ADMIN_PUBLISHER_CONFIG<br>SYSTEM_ADMIN_PUBLISHER_BLOCK<br>SYSTEM_ADMIN_PUBLISHER_ADD<br>SYSTEM_ADMIN_PUBLISHER_USAGE<br>SYSTEM_ADMIN_DEVELOPERS_TAB   |

| Role  | Permissions       |
|-------|-------------------|
| Guest | SYSTEM_ADMIN_BASE |

## 12.2 MAPPING PERMISSION NAMES TO PERMISSION ITEMS

This section lists:

- Permission name (section title)
- Partner identifier
- Permission Items

A permission item may be:

- An API action, which includes a service and action
- An API parameter, which includes an object and property

### 12.2.1 CUSTOM DATA FIELD DELETE

**Partner ID**

0

**Permission Items: API Actions**

| Service                  | Actions |
|--------------------------|---------|
| metadata_metadataprofile | delete  |
|                          | update  |

### 12.2.2 CUSTOM DATA FIELD UPDATE

**Partner ID**

0

**Permission Items: API Actions**



---

| Service                  | Actions |
|--------------------------|---------|
| metadata_metadataprofile | update  |

### 12.2.3 CUSTOM DATA FIELD ADD

**Partner ID**

0

## Permission Items: API Actions

| Service                  | Actions |
|--------------------------|---------|
| metadata_metadataprofile | add     |
|                          | update  |

## 12.2.4 KMC READ ONLY

### Partner ID

0

## Permission Items: API Actions

| Service                                 | Actions           |
|---|-------------------|
| metadata_metadataprofile                | list              |
| metadata_metadata                       | list              |
| contentdistribution_distributionprofile | list              |
| contentdistribution_entrydistribution   | list              |
| uiconf                                  | list              |
|   | listtemplates     |
| user                                    | get               |
| partner                                 | getinfo           |
|   | getusage          |
| playlist                                | list              |
| mixing                                  | getmixesbymediaid |
| baseentry                               | list              |
|   | get               |
|   | getcontextdata    |
| report                                  | getgraphs         |

| Service       | Actions                   |
|---------------|---------------------------|
| flavorparams  | list                      |
| flavorasset   | getbyentryid              |
|               | getwebplayablebyentryid   |
|               | getflavorassetswithparams |
| thumbasset    | getbyentryid              |
| accesscontrol | list                      |
| category      | list                      |
| userrole      | get                       |
| permission    | list                      |

## 12.2.5 KMC ACCESS

**Partner ID**

0

## 12.2.6 AUDIT TRAIL ADD

**Partner ID**

0

**Permission Items: API Actions**

| Service          | Actions |
|------------------|---------|
| audit_audittrail | add     |

## 12.2.7 AUDIT TRAIL BASE

**Partner ID**

0

**Permission Items: API Actions**

| Service          | Actions |
|------------------|---------|
| audit_audittrail | list    |
|                  | get     |

## 12.2.8 ANALYTICS SEND DATA

**Partner ID**

0

**Permission Items: API Actions**

| Service | Actions        |
|---------|----------------|
| stats   | collect        |
|         | kmccollect     |
|         | reportkceerror |

## 12.2.9 SEARCH SERVICE

**Partner ID**

0

**Permission Items: API Actions**

| Service | Actions       |
|---------|---------------|
| search  | search        |
|         | getmediainfo  |
|         | searchurl     |
|         | externallogin |

## 12.2.10 WIDGET\_ADMIN

**Partner ID**

0

**Permission Items: API Actions**

| Service | Actions |
|---------|---------|
| widget  | add     |
|         | clone   |
|         | get     |
|         | update  |
|         | list    |

## 12.2.11 ANALYTICS\_SEND\_DATA

**Partner ID**

0

## 12.2.12 WIDGET\_ADMIN

**Partner ID**

0

## 12.2.13 ANALYTICS\_BASE

**Partner ID**

0

**Permission Items: API Actions**

| Service | Actions   |
|---------|-----------|
| report  | getgraphs |
|         | gettotal  |

| Service  | Actions              |
|----------|----------------------|
|          | gettable             |
|          | geturlforreportascsv |
| category | list                 |

## 12.2.14 ADMIN WHITE BRANDING

Partner ID

0

## 12.2.15 ADMIN PUBLISHER MANAGE

Partner ID

0

## 12.2.16 ADMIN ROLE DELETE

Partner ID

0

Permission Items: API Actions

| Service  | Actions |
|----------|---------|
| userrole | delete  |

## 12.2.17 ADMIN ROLE ADD

Partner ID

0

---

**Permission Items: API Actions**

| Service  | Actions |
|----------|---------|
| userrole | add     |
|          | clone   |

## 12.2.18 ADMIN\_ROLE\_UPDATE

**Partner ID**

0

**Permission Items: API Actions**

| Service  | Actions |
|----------|---------|
| userrole | update  |

## 12.2.19 ADMIN\_USER\_DELETE

**Partner ID**

0

**Permission Items: API Actions**

| Service | Actions |
|---------|---------|
| user    | delete  |

## 12.2.20 ADMIN\_USER\_ADD

**Partner ID**

0

**Permission Items: API Actions**

| Service | Actions |
|---------|---------|
| user    | add     |

## 12.2.21 ADMIN USER UPDATE

**Partner ID**

0

**Permission Items: API Actions**

| Service | Actions         |
|---------|-----------------|
| user    | update          |
|         | updatelogindata |
|         | enablelogin     |
|         | disablelogin    |

## 12.2.22 ADMIN BASE

**Partner ID**

0

**Permission Items: API Actions**

| Service  | Actions      |
|----------|--------------|
| user     | get          |
|          | list         |
|          | notifyban    |
|          | getbyloginid |
| partner  | getinfo      |
| userrole | get          |



| Service        | Actions           |
|----------------|-------------------|
|                | list              |
| permission     | get               |
|                | list              |
| permissionitem | get               |
|                | list              |
| uiconf         | getavailabletypes |

## 12.2.23 CUSTOM DATA PROFILE DELETE

**Partner ID**

0

**Permission Items: API Actions**

| Service                  | Actions |
|--------------------------|---------|
| metadata_metadataprofile | delete  |

## 12.2.24 CUSTOM DATA PROFILE UPDATE

**Partner ID**

0

**Permission Items: API Actions**

| Service                  | Actions                  |
|--------------------------|--------------------------|
| metadata_metadataprofile | update                   |
|                          | updatedefinitionfromfile |
|                          | updateviewsfromfile      |
|                          | revert                   |

## 12.2.25 CUSTOM DATA PROFILE ADD

**Partner ID**

0

**Permission Items: API Actions**

| Service                  | Actions     |
|--------------------------|-------------|
| metadata_metadataprofile | add         |
|                          | addfromfile |

## 12.2.26 CUSTOM DATA PROFILE BASE

**Partner ID**

0

**Permission Items: API Actions**

| Service                  | Actions    |
|--------------------------|------------|
| metadata_metadataprofile | list       |
|                          | get        |
|                          | listfields |

## 12.2.27 TRANSCODING DELETE

**Partner ID**

0

**Permission Items: API Actions**

| Service           | Actions |
|-------------------|---------|
| conversionprofile | delete  |
| flavorparams      | delete  |

## 12.2.28 TRANSCODING UPDATE

Partner ID

0

Permission Items: API Actions

| Service           | Actions            |
|-------------------|--------------------|
| conversionprofile | update             |
|                   | addflavorparams    |
|                   | removeflavorparams |
| flavorparams      | update             |

## 12.2.29 TRANSCODING ADD

Partner ID

0

Permission Items: API Actions

| Service           | Actions |
|-------------------|---------|
| conversionprofile | add     |
| flavorparams      | add     |

## 12.2.30 TRANSCODING BASE

Partner ID

0

**Permission Items: API Actions**

| Service           | Actions                  |
|-------------------|--------------------------|
| conversionprofile | get                      |
|                   | list                     |
| flavorparams      | get                      |
|                   | list                     |
|                   | getbyconversionprofileid |
|                   | getdefault               |
| thumbparams       | list                     |

## 12.2.31 ACCESS CONTROL DELETE

**Partner ID**

0

**Permission Items: API Actions**

| Service       | Actions |
|---------------|---------|
| accesscontrol | delete  |

## 12.2.32 ACCESS CONTROL UPDATE

**Partner ID**

0

**Permission Items: API Actions**

| Service       | Actions |
|---------------|---------|
| accesscontrol | update  |

---

### 12.2.33 ACCESS CONTROL ADD

**Partner ID**

0

**Permission Items: API Actions**

| Service       | Actions |
|---------------|---------|
| accesscontrol | add     |

### 12.2.34 ACCESS CONTROL BASE

**Partner ID**

0

**Permission Items: API Actions**

| Service       | Actions |
|---------------|---------|
| accesscontrol | get     |
|               | list    |

### 12.2.35 INTEGRATION UPDATE SETTINGS

**Partner ID**

0

**Permission Items: API Actions**

| Service | Actions |
|---------|---------|
| partner | update  |

---

## 12.2.36 INTEGRATION BASE

**Partner ID**

0

**Permission Items: API Actions**

| Service | Actions |
|---------|---------|
| partner | getinfo |

**Permission Items: API Parameters**

| Object         | Properties            |
|----------------|-----------------------|
| KalturaPartner | secret<br>adminSecret |

## 12.2.37 ACCOUNT UPDATE SETTINGS

**Partner ID**

0

**Permission Items: API Actions**

| Service | Actions |
|---------|---------|
| partner | update  |

## 12.2.38 ACCOUNT BASE

**Partner ID**

0

**Permission Items: API Actions**

| Service  | Actions  |
|----------|----------|
| user     | list     |
| partner  | getinfo  |
|          | getusage |
| userrole | list     |

## 12.2.39 ADVERTISING UPDATE SETTINGS

**Partner ID**

0

## 12.2.40 ADVERTISING BASE

**Partner ID**

0

## 12.2.41 STUDIO SELECT CONTENT

**Partner ID**

0

**Permission Items: API Actions**

| Service  | Actions |
|----------|---------|
| playlist | list    |

## 12.2.42 STUDIO BRAND UICONF

**Partner ID**

0

---

## 12.2.43 STUDIO DELETE UICONF

**Partner ID**

0

**Permission Items: API Actions**

| Service | Actions |
|---------|---------|
| uiconf  | delete  |

## 12.2.44 STUDIO UPDATE UICONF

**Partner ID**

0

**Permission Items: API Actions**

| Service | Actions |
|---------|---------|
| uiconf  | update  |

## 12.2.45 STUDIO ADD UICONF

**Partner ID**

0

**Permission Items: API Actions**

| Service | Actions |
|---------|---------|
| uiconf  | add     |
|         | clone   |



## 12.2.46 STUDIO BASE

**Partner ID**

0

**Permission Items: API Actions**

| Service | Actions       |
|---------|---------------|
| uiconf  | get           |
|         | list          |
|         | listtemplates |

## 12.2.47 SYNDICATION DELETE

**Partner ID**

0

**Permission Items: API Actions**

| Service         | Actions |
|-----------------|---------|
| syndicationfeed | delete  |

## 12.2.48 SYNDICATION UPDATE

**Partner ID**

0

**Permission Items: API Actions**

| Service         | Actions |
|-----------------|---------|
| syndicationfeed | update  |

## 12.2.49 SYNDICATION\_ADD

Partner ID

0

Permission Items: API Actions

| Service         | Actions |
|-----------------|---------|
| syndicationfeed | add     |

## 12.2.50 SYNDICATION\_BASE

Partner ID

0

Permission Items: API Actions

| Service         | Actions           |
|-----------------|-------------------|
| syndicationfeed | get               |
|                 | list              |
|                 | getentrycount     |
|                 | requestconversion |

## 12.2.51 PLAYLIST\_EMBED\_CODE

Partner ID

0

## 12.2.52 PLAYLIST\_DELETE

Partner ID

0

**Permission Items: API Actions**

| Service  | Actions |
|----------|---------|
| playlist | delete  |

## 12.2.53 PLAYLIST\_UPDATE

**Partner ID**

0

**Permission Items: API Actions**

| Service   | Actions |
|-----------|---------|
| playlist  | update  |
| media     | list    |
| mixing    | list    |
| data      | list    |
| baseentry | list    |

## 12.2.54 PLAYLIST\_ADD

**Partner ID**

0

**Permission Items: API Actions**

| Service  | Actions |
|----------|---------|
| playlist | add     |
|          |         |
| media    | list    |
| mixing   | list    |
| data     | list    |

| Service   | Actions |
|-----------|---------|
| baseentry | list    |

## 12.2.55 PLAYLIST BASE

**Partner ID**

0

**Permission Items: API Actions**

| Service   | Actions             |
|-----------|---------------------|
| playlist  | get                 |
|           | list                |
|           | execute             |
|           | executefromcontent  |
|           | executefromfilters  |
|           | getstatsfromcontent |
| media     | list                |
| mixing    | list                |
| data      | list                |
| baseentry | list                |

## 12.2.56 CONTENT MODERATE APPROVE REJECT

**Partner ID**

0

#### Permission Items: API Actions

| Service   | Actions |
|-----------|---------|
| media     | reject  |
|           | approve |
| baseentry | reject  |
|           | approve |

## 12.2.57 CONTENT MODERATE CUSTOM DATA

#### Partner ID

0

#### Permission Items: API Actions

| Service           | Actions        |
|-------------------|----------------|
| metadata_metadata | add            |
|                   | addfromfile    |
|                   | addfromurl     |
|                   | delete         |
|                   | update         |
|                   | updatefromfile |

## 12.2.58 CONTENT MODERATE METADATA

#### Partner ID

0

#### Permission Items: API Actions

| Service            | Actions |
|--------------------|---------|
| document_documents | update  |

| Service   | Actions       |
|-----------|---------------|
| media     | update        |
|           | anonymousrank |
| mixing    | anonymousrank |
| data      | update        |
| baseentry | update        |
|           | anonymousrank |
| document  | update        |

#### Permission Items: API Parameters

| Object           | Properties                  |
|------------------|-----------------------------|
| KalturaBaseEntry | name<br>tags<br>description |

## 12.2.59 CONTENT MODERATE BASE

#### Partner ID

0

#### Permission Items: API Actions

| Service                                 | Actions |
|---|---------|
| metadata_metadataprofile                | list    |
| contentdistribution_distributionprofile | list    |
| playlist                                | list    |
| media                                   | list    |
|   | flag    |

| Service           | Actions   |
|-------------------|-----------|
|                   | listflags |
| livestream        | list      |
| mixing            | list      |
| data              | list      |
| baseentry         | list      |
|                   | count     |
|                   | flag      |
|                   | listflags |
| conversionprofile | list      |
| flavorparams      | list      |
| category          | list      |

## 12.2.60 LIVE STREAM UPDATE

**Partner ID**

0

**Permission Items: API Actions**

| Service    | Actions |
|------------|---------|
| livestream | update  |
| baseentry  | update  |

## 12.2.61 LIVE STREAM ADD

**Partner ID**

0

---

**Permission Items: API Actions**

| Service    | Actions |
|------------|---------|
| livestream | add     |

## 12.2.62 CONTENT MANAGE SHARE

**Partner ID**

0

## 12.2.63 CONTENT MANAGE ANNOTATION

**Partner ID**

0

**Permission Items: API Actions**

| Service               | Actions |
|-----------------------|---------|
| annotation_annotation | update  |
|                       | delete  |
|                       | list    |
|                       | add     |
|                       | get     |

## 12.2.64 CONTENT MANAGE DOWNLOAD

**Partner ID**

0

**Permission Items: API Actions**

| Service     | Actions        |
|-------------|----------------|
| flavorasset | getdownloadurl |



| Service   | Actions          |
|-----------|------------------|
| xinternal | xaddbulkdownload |

## 12.2.65 CONTENT MANAGE VIRUS SCAN

Partner ID

0

## 12.2.66 CONTENT MANAGE DISTRIBUTION PROFILE MODIFY

Partner ID

0

Permission Items: API Actions

| Service                                 | Actions      |
|---|--------------|
| metadata_metadataprofile                | list         |
|   | listfields   |
| contentdistribution_distributionprofile | add          |
|   | update       |
|   | updatestatus |
|   | delete       |
| flavorparams                            | list         |

## 12.2.67 CONTENT MANAGE DISTRIBUTION REMOVE

Partner ID

0

#### Permission Items: API Actions

| Service                               | Actions      |
|---------------------------------------|--------------|
| contentdistribution_entrydistribution | submitdelete |

## 12.2.68 CONTENT MANAGE DISTRIBUTION SEND

#### Partner ID

0

#### Permission Items: API Actions

| Service                               | Actions           |
|---------------------------------------|-------------------|
| contentdistribution_entrydistribution | submitadd         |
|                                       | submitupdate      |
|                                       | submitfetchreport |
|                                       | retrysubmit       |

## 12.2.69 CONTENT MANAGE ASSIGN CATEGORIES

#### Partner ID

0

#### Permission Items: API Actions

| Service            | Actions |
|--------------------|---------|
| document_documents | update  |
| media              | update  |
| data               | update  |
| baseentry          | update  |
| category           | get     |
|                    | list    |

| Service  | Actions |
|----------|---------|
| document | update  |

#### Permission Items: API Parameters

| Object           | Properties                                   |
|------------------|--|
| KalturaBaseEntry | categories<br>categoriesIds<br>categoriesIds |

## 12.2.70 CONTENT MANAGE THUMBNAIL

#### Partner ID

0

#### Permission Items: API Actions

| Service            | Actions                        |
|--------------------|--------------------------------|
| document_documents | update                         |
| media              | update                         |
|                    | updatethumbnail                |
|                    | updatethumbnailjpeg            |
|                    | updatethumbnailfromurl         |
|                    | updatethumbnailfromsourceentry |
| livestream         | updateofflinethumbnailjpeg     |
|                    | updateofflinethumbnailfromurl  |
| data               | update                         |
| baseentry          | update                         |
|                    | updatethumbnailjpeg            |

| Service     | Actions                        |
|-------------|--------------------------------|
|             | updatethumbnailfromurl         |
|             | updatethumbnailfromsourceentry |
| thumbparams | add                            |
|             | get                            |
|             | update                         |
|             | delete                         |
|             | list                           |
|             | getbyconversionprofileid       |
|             | getdefault                     |
| thumbasset  | get                            |
|             | getbyentryid                   |
|             | servebyentryid                 |
|             | serve                          |
|             | setasdefault                   |
|             | generatebyentryid              |
|             | generate                       |
|             | regenerate                     |
|             | addfromurl                     |
|             | addfromimage                   |
|             | delete                         |
|             | deletebyentryid                |
| document    | list                           |
|             | update                         |

## 12.2.71 CONTENT MANAGE SCHEDULE

**Partner ID**

0

**Permission Items: API Actions**

| Service            | Actions |
|--------------------|---------|
| document_documents | update  |
| media              | update  |
| data               | update  |
| baseentry          | update  |
| document           | update  |

**Permission Items: API Parameters**

| Object           | Properties           |
|------------------|----------------------|
| KalturaBaseEntry | startDate<br>endDate |

## 12.2.72 CONTENT MANAGE ACCESS CONTROL

**Partner ID**

0

**Permission Items: API Actions**

| Service            | Actions |
|--------------------|---------|
| document_documents | update  |
| media              | update  |
| data               | update  |
| baseentry          | update  |

| Service  | Actions |
|----------|---------|
| document | update  |

**Permission Items: API Parameters**

| Object           | Properties      |
|------------------|-----------------|
| KalturaBaseEntry | accessControlId |

## 12.2.73 CONTENT MANAGE CUSTOM DATA

**Partner ID**

0

**Permission Items: API Actions**

| Service           | Actions        |
|-------------------|----------------|
| metadata_metadata | list           |
|                   | add            |
|                   | addfromfile    |
|                   | addfromurl     |
|                   | delete         |
|                   | update         |
|                   | updatefromfile |

## 12.2.74 CONTENT MANAGE DELETE

**Partner ID**

0

## Permission Items: API Actions

| Service            | Actions |
|--------------------|---------|
| document_documents | delete  |
| media              | delete  |
| livestream         | delete  |
| mixing             | delete  |
| data               | delete  |
| baseentry          | delete  |
| flavorasset        | delete  |
| document           | delete  |

## 12.2.75 CONTENT MANAGE RECONVERT

### Partner ID

0

## Permission Items: API Actions

| Service            | Actions           |
|--------------------|-------------------|
| document_documents | convert           |
|                    | convertpptoswf    |
| media              | convert           |
|                    | requestconversion |
| mixing             | requestflattening |
| flavorasset        | convert           |
|                    | reconvert         |
| syndicationfeed    | requestconversion |
| document           | convertpptoswf    |

## 12.2.76 CONTENT MANAGE EDIT CATEGORIES

**Partner ID**

0

**Permission Items: API Actions**

| Service  | Actions |
|----------|---------|
| category | add     |
|          | get     |
|          | update  |
|          | delete  |

## 12.2.77 CONTENT MANAGE EMBED CODE

**Partner ID**

0

**Permission Items: API Actions**

| Service             | Actions |
|---------------------|---------|
| shortlink_shortlink | list    |
|                     | add     |
|                     | update  |

## 12.2.78 CONTENT MANAGE DISTRIBUTION BASE

**Partner ID**

0



#### Permission Items: API Actions

| Service                                  | Actions          |
|--|------------------|
| contentdistribution_distributionprovider | list             |
| contentdistribution_distributionprofile  | get              |
|  | list             |
|  | listbypartner    |
| contentdistribution_entrydistribution    | get              |
|  | list             |
|  | validate         |
|  | serverreturndata |
|  | serveentdata     |

## 12.2.79 CONTENT MANAGE DISTRIBUTION WHERE

#### Partner ID

0

#### Permission Items: API Actions

| Service                               | Actions |
|---------------------------------------|---------|
| contentdistribution_entrydistribution | add     |
|                                       | update  |
|                                       | delete  |

## 12.2.80 SYSTEM ADMIN USER MANAGE

#### Partner ID

-2

## 12.2.81 SYSTEM ADMIN PUBLISHER USAGE

Partner ID

-2

Permission Items: API Actions

| Service                     | Actions  |
|-----------------------------|----------|
| systempartner_systempartner | getusage |

## 12.2.82 SYSTEM ADMIN PUBLISHER ADD

Partner ID

-2

## 12.2.83 SYSTEM ADMIN PUBLISHER REMOVE

Partner ID

-2

Permission Items: API Actions

| Service                     | Actions      |
|-----------------------------|--------------|
| systempartner_systempartner | updatestatus |

## 12.2.84 SYSTEM ADMIN PUBLISHER BLOCK

Partner ID

-2

Permission Items: API Actions

| Service                     | Actions      |
|-----------------------------|--------------|
| systempartner_systempartner | updatestatus |

## 12.2.85 SYSTEM ADMIN PUBLISHER CONFIG

**Partner ID**

-2

**Permission Items: API Actions**

| Service                     | Actions             |
|-----------------------------|---------------------|
| systempartner_systempartner | updatestatus        |
|                             | updateconfiguration |

## 12.2.86 SYSTEM ADMIN PUBLISHER KMC ACCESS

**Partner ID**

-2

**Permission Items: API Actions**

| Service                     | Actions         |
|-----------------------------|-----------------|
| systempartner_systempartner | getadminsession |

## 12.2.87 SYSTEM ADMIN PUBLISHER BASE

**Partner ID**

-2

**Permission Items: API Actions**

| Service                     | Actions          |
|-----------------------------|------------------|
| systempartner_systempartner | get              |
|                             | list             |
|                             | getconfiguration |
|                             | getpackages      |

## 12.2.88 SYSTEM ADMIN BASE

Partner ID

-2

Permission Items: API Actions

| Service | Actions      |
|---------|--------------|
| session | impersonate  |
| user    | list         |
|         | getbyloginid |

## 12.2.89 CONTENT MANAGE BASE

Partner ID

0

Permission Items: API Actions

| Service                  | Actions               |
|--------------------------|-----------------------|
| metadata_metadataprofile | list                  |
| metadata_metadata        | list                  |
|                          | get                   |
| document_documents       | get                   |
|                          | list                  |
|                          | serve                 |
|                          | servebyflavorparamsid |
| media                    | get                   |
|                          | list                  |
|                          | count                 |

| Service           | Actions                   |
|-------------------|---------------------------|
| livestream        | get                       |
|                   | list                      |
| mixing            | get                       |
|                   | list                      |
|                   | count                     |
|                   | getmixesbymediaid         |
|                   | getreadymediaentries      |
| data              | get                       |
|                   | list                      |
|                   | serve                     |
| baseentry         | list                      |
|                   | count                     |
|                   | get                       |
|                   | getcontextdata            |
|                   | getbyids                  |
| notification      | getclientnotification     |
| conversionprofile | list                      |
| flavorparams      | list                      |
| flavorasset       | get                       |
|                   | getbyentryid              |
|                   | getwebplayablebyentryid   |
|                   | getflavorassetswithparams |
|                   | list                      |
| category          | get                       |

| Service  | Actions               |
|----------|-----------------------|
|          | list                  |
| document | get                   |
|          | list                  |
|          | serve                 |
|          | servebyflavorparamsid |

#### Permission Items: API Parameters

| Object                      | Properties |
|-----------------------------|------------|
| KalturaLiveStreamAdminEntry | *          |

## 12.2.90 CONTENT MANAGE METADATA

#### Partner ID

0

#### Permission Items: API Actions

| Service            | Actions |
|--------------------|---------|
| document_documents | update  |
| media              | update  |
| data               | update  |
| baseentry          | update  |
| document           | update  |

## Permission Items: API Parameters

| Object           | Properties                  |
|------------------|-----------------------------|
| KalturaBaseEntry | name<br>tags<br>description |

### 12.2.91 CONTENT INGEST FEED

Partner ID

0

### 12.2.92 CONTENT MANAGE MIX

Partner ID

0

## Permission Items: API Actions

| Service | Actions              |
|---------|----------------------|
| mixing  | add                  |
|         | update               |
|         | clone                |
|         | appendmediaentry     |
|         | requestflattening    |
|         | getmixesbymediaid    |
|         | getreadymediaentries |

### 12.2.93 CONTENT INGEST UPLOAD

Partner ID

0

## Permission Items: API Actions

| Service            | Actions                        |
|--------------------|--------------------------------|
| document_documents | addfromuploadedfile            |
|                    | addfromentry                   |
|                    | addfromflavorasset             |
|                    | upload                         |
| media              | addfromurl                     |
|                    | addfromsearchresult            |
|                    | addfromuploadedfile            |
|                    | addfromrecordedwebcam          |
|                    | addfromentry                   |
|                    | addfromflavorasset             |
|                    | upload                         |
| data               | add                            |
| baseentry          | addfromuploadedfile            |
|                    | upload                         |
| conversionprofile  | list                           |
| upload             | upload                         |
|                    | getuploadedfiletokenbyfilename |
| uploadtoken        | add                            |
|                    | get                            |
|                    | upload                         |
|                    | list                           |
|                    | delete                         |
| document           | addfromuploadedfile            |



| Service | Actions |
|---------|---------|
|         | upload  |

## 12.2.94 CONTENT INGEST BULK UPLOAD

Partner ID

0

Permission Items: API Actions

| Service           | Actions |
|-------------------|---------|
| bulkupload        | add     |
|                   | get     |
|                   | delete  |
|                   | list    |
| conversionprofile | list    |

## 12.2.95 ALWAYS ALLOWED ACTIONS

Partner ID

0

Permission Items: API Actions

| Service             | Actions               |
|---------------------|-----------------------|
| document_documents  | serve                 |
|                     | servebyflavorparamsid |
| shortlink_shortlink | goto                  |
| session             | start                 |
|                     | startwidgetsession    |

| Service   | Actions            |
|-----------|--------------------|
|           | end                |
|           | impersonate        |
| uiconf    | get                |
| user      | login              |
|           | loginbyloginid     |
|           | updatelogindata    |
|           | resetpassword      |
|           | setinitialpassword |
| widget    | get                |
| partner   | register           |
|           | getsecrets         |
| adminuser | updatepassword     |
|           | resetpassword      |
|           | login              |
|           | setinitialpassword |
| search    | search             |
|           | getmediainfo       |
|           | searchurl          |
|           | externallogin      |
| playlist  | execute            |
| media     | flag               |
| baseentry | flag               |
| stats     | collect            |
|           | kmccollect         |

| Service    | Actions               |
|------------|-----------------------|
|            | reportkceerror        |
| system     | ping                  |
| thumbasset | servebyentryid        |
|            | serve                 |
| permission | getcurrentpermissions |
| document   | serve                 |
|            | servebyflavorparamsid |

## 12.2.96 BATCH\_BASE

### Partner ID

-1

### Permission Items: API Actions

| Service           | Actions                |
|-------------------|------------------------|
| metadata_metadata | update                 |
| media             | addfromuploadedfile    |
|                   | upload                 |
|                   | addfrombulk            |
| baseentry         | addfromuploadedfile    |
| jobs              | abortmail              |
|                   | abortbulkupload        |
|                   | abortconvertcollection |
|                   | abortprovisionprovide  |
|                   | abortprovisiondelete   |
|                   | abortconvert           |

| Service | Actions                 |
|---------|-------------------------|
|         | abortpostconvert        |
|         | abortextractmedia       |
|         | abortstorageexport      |
|         | abortstoragedelete      |
|         | abortimport             |
|         | abortpull               |
|         | abortnotification       |
|         | abortconvertprofile     |
|         | abortremoteconvert      |
|         | deletemail              |
|         | deletebulkupload        |
|         | deleteconvertcollection |
|         | deleteprovisionprovide  |
|         | deleteprovisiondelete   |
|         | deleteconvert           |
|         | deletepostconvert       |
|         | deleteextractmedia      |
|         | deletestorageexport     |
|         | deletestoragedelete     |
|         | deleteimport            |
|         | deletepull              |
|         | deletenotification      |
|         | deleteconvertprofile    |
|         | deleteremoteconvert     |

| Service | Actions                    |
|---------|----------------------------|
|         | retrymail                  |
|         | retrybulkupload            |
|         | retryconvertcollection     |
|         | retryprovisionprovide      |
|         | retryprovisiondelete       |
|         | retryconvert               |
|         | retrypostconvert           |
|         | retryextractmedia          |
|         | retrystorageexport         |
|         | retrystoragedelete         |
|         | retryimport                |
|         | retrypull                  |
|         | retrynotification          |
|         | retryconvertprofile        |
|         | retryremoteconvert         |
|         | getpullstatus              |
|         | getimportstatus            |
|         | getpostconvertstatus       |
|         | getextractmediastatus      |
|         | getstorageexportstatus     |
|         | getstoragedeletestatus     |
|         | getbulkuploadstatus        |
|         | getconvertcollectionstatus |
|         | getprovisionprovidestatus  |

| Service | Actions                        |
|---------|--------------------------------|
|         | getprovisiondeletestatus       |
|         | getconvertstatus               |
|         | getnotificationstatus          |
|         | getconvertprofilestatus        |
|         | getremoteconvertstatus         |
|         | getmailstatus                  |
| batch   | getqueuesize                   |
|         | checkfileexists                |
|         | getexclusivepulljobs           |
|         | updateexclusivepulljob         |
|         | freeexclusivepulljob           |
|         | getexclusiveimportjobs         |
|         | updateexclusiveimportjob       |
|         | freeexclusiveimportjob         |
|         | cleanexclusivejobs             |
|         | addbulkuploadresult            |
|         | getbulkuploadlastresult        |
|         | updatebulkuploadresults        |
|         | addmediainfo                   |
|         | getexclusivepostconvertjobs    |
|         | updateexclusivepostconvertjob  |
|         | freeexclusivepostconvertjob    |
|         | getexclusiveextractmediajobs   |
|         | updateexclusiveextractmediajob |

| Service | Actions                             |
|---------|-------------------------------------|
|         | freeexclusiveextractmediajob        |
|         | getexclusivestorageexportjobs       |
|         | getexclusivestoragedeletejobs       |
|         | updateexclusivestorageexportjob     |
|         | updateexclusivestoragedeletejob     |
|         | freeexclusivestorageexportjob       |
|         | freeexclusivestoragedeletejob       |
|         | getexclusivebulkuploadjobs          |
|         | getexclusiveconvertcollectionjobs   |
|         | getexclusiveprovisionprovidejobs    |
|         | getexclusiveprovisiondeletejobs     |
|         | updateexclusivebulkuploadjob        |
|         | updateexclusiveconvertcollectionjob |
|         | updateexclusiveprovisionprovidejob  |
|         | updateexclusiveprovisiondeletejob   |
|         | freeexclusivebulkuploadjob          |
|         | freeexclusiveconvertcollectionjob   |
|         | freeexclusiveprovisionprovidejob    |
|         | freeexclusiveprovisiondeletejob     |
|         | getexclusiveconvertjobs             |
|         | updateexclusiveconvertjob           |
|         | freeexclusiveconvertjob             |
|         | getexclusivenotificationjobs        |
|         | updateexclusivenotificationjob      |

| Service | Actions                                     |
|---------|---|
|         | freeexclusivenotificationjob                |
|         | getexclusivemailjobs                        |
|         | updateexclusivemailjob                      |
|         | freeexclusivemailjob                        |
|         | freeexclusiveconvertprofilejob              |
|         | freeexclusiveconvertprofilejob              |
|         | getexclusivebulkdownloadjobs                |
|         | updateexclusivebulkdownloadjob              |
|         | freeexclusivebulkdownloadjob                |
|         | getexclusivecapturethumbjobs                |
|         | updateexclusivecapturethumbjob              |
|         | freeexclusivecapturethumbjob                |
|         | logconversion                               |
|         | resetjobexecutionattempts                   |
|         | updateexclusiveconvertjobsubtype            |
|         | updateexclusiveconvertprofilejob            |
|         | getexclusivealmostdoneconvertjobs           |
|         | getexclusivealmostdoneconvertprofilejobs    |
|         | getexclusivealmostdonebulkuploadjobs        |
|         | getexclusivealmostdoneconvertcollectionjobs |
|         | getexclusivealmostdoneprovisionprovidejobs  |
|         | getexclusivealmostdoneprovisiondeletejobs   |
|         | getexclusivealmostdoneremoteconvertjobs     |
|         | getexclusivealmostdonebulkdownloadjobs      |



| Service                          | Actions                                   |
|----------------------------------|---|
| batchcontrol                     | configloaded                              |
|                                  | reportstatus                              |
|                                  | getcommand                                |
|                                  | setcommandresult                          |
|                                  | getfullstatus                             |
| emailgestionprofile              | getbyemailaddress                         |
|                                  | addmediaentry                             |
| filesync_filesync                | sync                                      |
| metadata_metadatabatch           | getexclusiveimportmetadatabatch           |
|                                  | updateexclusiveimportmetadatabatch        |
|                                  | freeexclusiveimportmetadatabatch          |
|                                  | getexclusiveimportmetadatabatch           |
|                                  | updateexclusiveimportmetadatabatch        |
|                                  | freeexclusiveimportmetadatabatch          |
|                                  | gettransformmetadatabatch                 |
|                                  | upgrademetadatabatch                      |
| metadata_metadata                | invalidate                                |
| multicenters_filesyncimportbatch | updateexclusivefilesyncimportbatch        |
|                                  | freeexclusivefilesyncimportbatch          |
|                                  | getexclusivefilesyncimportbatch           |
|                                  | getexclusivealmostdonefilesyncimportbatch |
| virusscan_virusscanbatch         | updateexclusivevirusscanbatch             |
|                                  | freeexclusivevirusscanbatch               |
|                                  | getexclusivevirusscanbatch                |

| Service                                      | Actions   |
|--|---|
| contentdistribution_contentdistributionbatch | getexclusivedistributionssubmitjobs               |
|  | updateexclusivedistributionssubmitjob             |
|  | freeexclusivedistributionssubmitjob               |
|  | getexclusivealmostdonedistributionssubmitjobs     |
|  | getexclusivedistributionupdatejobs                |
|  | updateexclusivedistributionupdatejob              |
|  | freeexclusivedistributionupdatejob                |
|  | getexclusivealmostdonedistributionupdatejobs      |
|  | getexclusivedistributiondeletejobs                |
|  | updateexclusivedistributiondeletejob              |
|  | freeexclusivedistributiondeletejob                |
|  | getexclusivealmostdonedistributiondeletejobs      |
|  | getexclusivedistributionfetchreportjobs           |
|  | updateexclusivedistributionfetchreportjob         |
|  | freeexclusivedistributionfetchreportjob           |
|  | getexclusivealmostdonedistributionfetchreportjobs |
|  | createrequiredjobs                                |
|  | updatesunstatus                                   |

## 12.2.97 BASE USER SESSION PERMISSION

Partner ID

0

## Permission Items: API Actions

| Service                  | Actions               |
|--------------------------|-----------------------|
| metadata_metadataprofile | list                  |
|                          | get                   |
|                          | listfields            |
| metadata_metadata        | list                  |
|                          | add                   |
|                          | addfromfile           |
|                          | addfromurl            |
|                          | delete                |
|                          | get                   |
|                          | update                |
|                          | updatefromfile        |
| document_documents       | addfromuploadedfile   |
|                          | convert               |
|                          | addfromentry          |
|                          | addfromflavorasset    |
|                          | get                   |
|                          | update                |
|                          | delete                |
|                          | list                  |
|                          | upload                |
|                          | convertpptoswf        |
|                          | serve                 |
|                          | servebyflavorparamsid |

| Service               | Actions            |
|-----------------------|--------------------|
| annotation_annotation | update             |
|                       | delete             |
|                       | list               |
|                       | add                |
|                       | get                |
| shortlink_shortlink   | get                |
|                       | list               |
|                       | goto               |
| session               | start              |
|                       | startwidgetsession |
|                       | end                |
|                       | impersonate        |
| uiconf                | get                |
|                       | list               |
| user                  | login              |
|                       | loginbyloginid     |
|                       | updatelogindata    |
|                       | resetpassword      |
|                       | setinitialpassword |
| widget                | add                |
|                       | clone              |
|                       | get                |
| partner               | register           |
|                       | getsecrets         |

| Service   | Actions               |
|-----------|-----------------------|
| adminuser | updatepassword        |
|           | resetpassword         |
|           | login                 |
|           | setinitialpassword    |
| search    | search                |
|           | getmediainfo          |
|           | searchurl             |
|           | externallogin         |
| playlist  | get                   |
|           | list                  |
|           | execute               |
| media     | addfromurl            |
|           | addfromsearchresult   |
|           | addfromuploadedfile   |
|           | addfromrecordedwebcam |
|           | get                   |
|           | convert               |
|           | addfromentry          |
|           | addfromflavorasset    |
|           | update                |
|           | upload                |
|           | delete                |
|           | list                  |
|           | count                 |

| Service    | Actions                        |
|------------|--------------------------------|
|            | updatethumbnail                |
|            | updatethumbnailjpeg            |
|            | updatethumbnailfromurl         |
|            | updatethumbnailfromsourceentry |
|            | requestconversion              |
|            | flag                           |
|            | anonymousrank                  |
| livestream | get                            |
|            | list                           |
|            | updateofflinethumbnailjpeg     |
|            | updateofflinethumbnailfromurl  |
| mixing     | add                            |
|            | get                            |
|            | update                         |
|            | delete                         |
|            | list                           |
|            | count                          |
|            | clone                          |
|            | appendmediaentry               |
|            | requestflattening              |
|            | getmixesbymediaid              |
|            | getreadymediaentries           |
|            | anonymousrank                  |
| data       | add                            |

| Service      | Actions                        |
|--------------|--------------------------------|
|              | get                            |
|              | update                         |
|              | delete                         |
|              | list                           |
|              | serve                          |
| baseentry    | addfromuploadedfile            |
|              | list                           |
|              | count                          |
|              | get                            |
|              | getcontextdata                 |
|              | update                         |
|              | upload                         |
|              | getbyids                       |
|              | delete                         |
|              | updatethumbnailjpeg            |
|              | updatethumbnailfromurl         |
|              | updatethumbnailfromsourceentry |
|              | flag                           |
|              | anonymousrank                  |
| stats        | collect                        |
|              | kmccollect                     |
|              | reportkceerror                 |
| system       | ping                           |
| notification | getclientnotification          |

| Service     | Actions                        |
|-------------|--------------------------------|
| flavorasset | getbyentryid                   |
|             | getwebplayablebyentryid        |
| thumbasset  | get                            |
|             | getbyentryid                   |
|             | servebyentryid                 |
|             | serve                          |
|             | generate                       |
|             | addfromurl                     |
|             | addfromimage                   |
| category    | get                            |
|             | list                           |
| upload      | upload                         |
|             | getuploadedfiletokenbyfilename |
| uploadtoken | add                            |
|             | get                            |
|             | upload                         |
|             | list                           |
|             | delete                         |
| permission  | getcurrentpermissions          |
| document    | addfromuploadedfile            |
|             | get                            |
|             | update                         |
|             | delete                         |
|             | list                           |



| Service    | Actions               |
|------------|-----------------------|
|            | upload                |
|            | convertpptoswf        |
|            | serve                 |
|            | servebyflavorparamsid |
| thumbasset | list                  |

#### Permission Items: API Parameters

| Object           | Properties   |
|------------------|--|
| KalturaBaseEntry | categories<br>categoriesIds<br>name<br>tags<br>description |

## 12.2.98 SYSTEM ADMIN SYSTEM MONITOR

Partner ID

-2

## 12.2.99 SYSTEM ADMIN DEVELOPERS TAB

Partner ID

-2

## 12.2.100 SYSTEM ADMIN BATCH CONTROL

Partner ID

-2

## Permission Items: API Actions

| Service      | Actions              |
|--------------|----------------------|
| jobs         | addmailjob           |
|              | listbatchjobs        |
|              | abortjob             |
|              | retryjob             |
|              | deletejob            |
|              | addconvertprofilejob |
| batchcontrol | setscheduleconfig    |
|              | setworkerconfig      |
|              | stopschedule         |
|              | stopworker           |
|              | startworker          |
|              | kill                 |
|              | getcommand           |
|              | setcommandresult     |
|              | getfullstatus        |
|              | listschedulers       |
|              | listworkers          |
|              | listcommands         |

## 12.2.101 SYSTEM ADMIN BATCH CONTROL INPROGRESS

Partner ID

-2

## 12.2.102 SYSTEM ADMIN BATCH CONTROL FAILED

Partner ID

-2

## 12.2.103 SYSTEM ADMIN BATCH CONTROL SETUP

Partner ID

-2

## 12.2.104 SYSTEM ADMIN STORAGE

Partner ID

-2

Permission Items: API Actions

| Service                       | Actions       |
|-------------------------------|---------------|
| flavorparams                  | list          |
| storageprofile_storageprofile | listbypartner |
|                               | updatestatus  |
|                               | get           |
|                               | update        |
|                               | add           |

## 12.2.105 SYSTEM ADMIN VIRUS SCAN

Partner ID

-2

Permission Items: API Actions

| Service                    | Actions |
|----------------------------|---------|
| virusscan_virusscanprofile | add     |

| Service | Actions |
|---------|---------|
|         | delete  |
|         | get     |
|         | list    |
|         | update  |
|         | scan    |

## 12.2.106 SYSTEM ADMIN EMAIL INGESTION

**Partner ID**

-2

**Permission Items: API Actions**

| Service               | Actions           |
|-----------------------|-------------------|
| emailingestionprofile | add               |
|                       | get               |
|                       | update            |
|                       | delete            |
|                       | getbyemailaddress |
|                       | addmediaentry     |

## 12.2.107 SYSTEM ADMIN CONTENT DISTRIBUTION BASE

**Partner ID**

-2

## Permission Items: API Actions

| Service   | Actions         |
|---|-----------------|
| contentdistribution_distributionprovider              | list            |
| contentdistribution_distributionprofile               | get             |
|   | list            |
|   | listbypartner   |
| contentdistribution_entrydistribution                 | list            |
| contentdistribution_genericdistributionprovideraction | get             |
|   | list            |
|   | getbyproviderid |
| contentdistribution_genericdistributionprovider       | get             |
|   | list            |

## 12.2.108 SYSTEM ADMIN CONTENT DISTRIBUTION MODIF

Y

Partner ID

-2

## Permission Items: API Actions

| Service                                 | Actions      |
|---|--------------|
| metadata_metadataprofile                | list         |
|   | listfields   |
| contentdistribution_distributionprofile | add          |
|   | update       |
|   | updatestatus |
|   | delete       |

| Service   | Actions                     |
|---|-----------------------------|
| flavorparams  | list                        |
| contentdistribution_genericdistributionprovider       | add                         |
|   | update                      |
|   | delete                      |
| contentdistribution_genericdistributionprovideraction | add                         |
|   | addmrsstransform            |
|   | addmrsstransformfromfile    |
|   | addmrssvalidate             |
|   | addmrssvalidatefromfile     |
|   | addresultstransform         |
|   | addresultstransformfromfile |
|   | update                      |
|   | updatebyproviderid          |
|   | delete                      |
|   | deletebyproviderid          |

## 12.2.109 SYSTEM ADMIN PERMISSIONS MANAGE

Partner ID

-2

Permission Items: API Actions

| Service  | Actions |
|----------|---------|
| userrole | add     |
|          | delete  |
|          | get     |

| Service        | Actions |
|----------------|---------|
|                | list    |
|                | update  |
|                | clone   |
| permission     | add     |
|                | delete  |
|                | update  |
|                | get     |
|                | list    |
| permissionitem | add     |
|                | delete  |
|                | update  |

## 12.2.110 SYSTEM INTERNAL

Partner ID

-2

Permission Items: API Actions

| Service   | Actions          |
|---|------------------|
| kalturainternaltools_kalturainternaltoolssystemhelper | fromsecurestring |
|   | iptocountry      |
|   | getremoteaddress |

## 12.2.111 SYSTEM ADMIN ENTRY INVESTIGATION

Partner ID

-2

#### Permission Items: API Actions

| Service                               | Actions      |
|---------------------------------------|--------------|
| contentdistribution_entrydistribution | list         |
| flavorparams                          | list         |
| thumbparams                           | list         |
| flavorasset                           | getbyentryid |
|                                       | reconvert    |
| thumbasset                            | getbyentryid |
|                                       | regenerate   |
| adminconsole_entryadmin               | get          |
|                                       | gettracks    |
| adminconsole_flavorparamsoutput       | list         |
|                                       | list         |
| adminconsole_mediainfo                | list         |
| filesync_filesync                     | list         |

### 12.2.112 SYSTEM FILESYNC

#### Partner ID

-2

#### Permission Items: API Actions

| Service           | Actions |
|-------------------|---------|
| filesync_filesync | list    |

### 12.2.113 ADMIN PERMISSION ADD

#### Partner ID



0

**Permission Items: API Actions**

| Service    | Actions |
|------------|---------|
| permission | add     |

## 12.2.114 ADMIN PERMISSION UPDATE

**Partner ID**

0

**Permission Items: API Actions**

| Service    | Actions |
|------------|---------|
| permission | update  |

## 12.2.115 ADMIN PERMISSION DELETE

**Partner ID**

0

**Permission Items: API Actions**

| Service    | Actions |
|------------|---------|
| permission | delete  |

## 12.2.116 SHORT LINK BASE

**Partner ID**

0

**Permission Items: API Actions**

| Service             | Actions |
|---------------------|---------|
| shortlink_shortlink | get     |
|                     | list    |
|                     | add     |
|                     | update  |
|                     | delete  |

## 12.2.117 SHORT LINK MODIFY

**Partner ID**

0

**Permission Items: API Actions**

| Service             | Actions |
|---------------------|---------|
| shortlink_shortlink | add     |
|                     | update  |
|                     | delete  |