

The Reference

Contents

1 Data structures	2	4.2 SCC (struct)	10	5.15 Modular Inverse Using Phi	16
1.1 Dsu	2	4.3 SCC Nodes (kosajaru)	10	5.16 N Choose K Count	16
1.2 Dsu (Python)	2	4.4 Check Bipartite	11	5.17 Permutation Count	16
1.3 Ordered Set Gnu Pbds	2	4.5 Count SCC (kosajaru)	11	5.18 Polynomial	16
1.4 Segtree Rmaxq Rmaxu	2	4.6 Dijkstra	11	5.19 Power Sum	17
1.5 Segtree Rminq Pau	3	4.7 Floyd Warshall	11	5.20 Sieve List Primes	17
1.6 Segtree Rminq Rsu	3	4.8 Kruskal (Python)	11		
1.7 Segtree Rsq Rsu	4	4.9 Lowest Common Ancestor Sparse Table . . .	12	6 Searching	17
1.8 Sparse Table Rminq	5	4.10 Topological Sorting	12	6.1 Ternary Search Recursive	17
2 Dynamic programming	5	5 Math	13	7 Strings	17
2.1 Edit Distance	5	5.1 Combinatorics With Repetitions	13	7.1 Rabin Karp	17
2.2 Knapsack Dp Values 01	5	5.2 Count Divisors Memo	13	7.2 String Psum	17
2.3 Money Sum Bottom Up	5	5.3 Euler Phi	13	7.3 Trie Naive	17
2.4 Tsp	6	5.4 Factorial Factorization	14		
3 Extras	6	5.5 Factorial	14	8 Trees	18
3.1 Bigint	6	5.6 Factorization With Primes	14	8.1 Binary Lifting	18
3.2 Binary To Gray	9	5.7 Factorization	14	8.2 Maximum Distances	18
3.3 Get Permutation Cicles	9	5.8 Fast Exp	14	8.3 Tree Diameter	19
4 Graphs	9	5.9 Gcd Using Factorization	14		
4.1 2 SAT (struct)	9	5.10 Gcd	15	9 Settings and macros	19
		5.11 Integer Mod	15	9.1 .vimrc	19
		5.12 Is Prime	15	9.2 degug.cpp	20
		5.13 Lcm Using Factorization	15	9.3 .bashrc	20
		5.14 Lcm	16	9.4 macro.cpp	21

1 Data structures

1.1 Dsu

```
struct DSU {
    vector<int> ps;
    vector<int> size;
    DSU(int N) : ps(N + 1), size(N + 1, 1) { iota(ps.begin(), ps.end(), 0); }
    int find_set(int x) { return ps[x] == x ? x : ps[x] = find_set(ps[x]); }
    bool same_set(int x, int y) { return find_set(x) == find_set(y); }
    void union_set(int x, int y) {
        if (same_set(x, y)) return;

        int px = find_set(x);
        int py = find_set(y);

        if (size[px] < size[py]) swap(px, py);

        ps[py] = px;
        size[px] += size[py];
    }
};
```

1.2 Dsu (Python)

```
class DSU:
    def __init__(self, n):
        self.n = n
        self.p = [x for x in range(0, n + 1)]
        self.size = [0 for i in range(0, n + 1)]

    def find_set(self, x): # log n
        if self.p[x] == x:
            return x
        else:
            self.p[x] = self.find_set(self.p[x])
            return self.p[x]

    def same_set(self, x, y): # log n
        return bool(self.find_set(x) == self.find_set(y))

    def union_set(self, x, y): # log n
        px = self.find_set(x)
        py = self.find_set(y)

        if px == py:
            return

        size_x = self.size[px]
        size_y = self.size[py]

        if size_x > size_y:
            self.p[py] = self.p[px]
            self.size[px] += self.size[py]
        else:
            self.p[px] = self.p[py]
            self.size[py] += self.size[px]
```

1.3 Ordered Set Gnu Pbds

```
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
template <typename T>
// using ordered_set = tree<T, null_type, less<T>, rb_tree_tag,
// tree_order_statistics_node_update>;

// if you want to find the elements less or equal :p
using ordered_set = tree<T, null_type, less_equal<T>, rb_tree_tag,
                        tree_order_statistics_node_update>;
```

1.4 Segtree Rmaxq Rmaxu

```
template <typename T = ll>
struct SegTree {
    int N;
    T nu, nq;
    vector<T> st, lazy;
    SegTree(const vector<T> &xs)
        : N(len(xs)),
          nu(numeric_limits<T>::min()),
          nq(numeric_limits<T>::min()),
          st(4 * N + 1, nu),
          lazy(4 * N + 1, nu) {
        for (int i = 0; i < len(xs); ++i) update(i, i, xs[i]);
    }

    void update(int l, int r, T value) { update(1, 0, N - 1, l, r, value); }

    T query(int l, int r) { return query(1, 0, N - 1, l, r); }

    void update(int node, int nl, int nr, int ql, int qr, T v) {
        propagation(node, nl, nr);

        if (ql > nr or qr < nl) return;

        st[node] = max(st[node], v);
        if (ql <= nl and nr <= qr) {
            if (nl < nr) {
                lazy[left(node)] = max(lazy[left(node)], v);
                lazy[right(node)] = max(lazy[right(node)], v);
            }
            return;
        }
        update(left(node), nl, mid(nl, nr), ql, qr, v);
        update(right(node), mid(nl, nr) + 1, nr, ql, qr, v);

        st[node] = max(st[left(node)], st[right(node)]);
    }

    T query(int node, int nl, int nr, int ql, int qr) {
        propagation(node, nl, nr);

        if (ql > nr or qr < nl) return nq;

        if (ql <= nl and nr <= qr) return st[node];
```

```

    T x = query(left(node), nl, mid(nl, nr), ql, qr);
    T y = query(right(node), mid(nl, nr) + 1, nr, ql, qr);

    return max(x, y);
}

void propagation(int node, int nl, int nr) {
    if (lazy[node] != nu) {
        st[node] = max(st[node], lazy[node]);

        if (nl < nr) {
            lazy[left(node)] = max(lazy[left(node)], lazy[node]);
            lazy[right(node)] = max(lazy[right(node)], lazy[node]);
        }

        lazy[node] = nu;
    }
}

int left(int p) { return p << 1; }
int right(int p) { return (p << 1) + 1; }
int mid(int l, int r) { return (r - l) / 2 + 1; }
};

int main() {
    int n;
    cin >> n;
    vector<array<int, 3>> xs(n);
    for (int i = 0; i < n; ++i) {
        for (int j = 0; j < 3; ++j) {
            cin >> xs[i][j];
        }
    }
    vi aux(n, 0);
    SegTree<int> st(aux);
    for (int i = 0; i < n; ++i) {
        int a = min(i + xs[i][1], n);
        int b = min(i + xs[i][2], n);
        st.update(i, i, st.query(i, i) + xs[i][0]);
        int cur = st.query(i, i);
        st.update(a, b, cur);
    }

    cout << st.query(0, n) << '\n';
}

```

1.5 Segtree Rminq Pau

```

template <typename T = ll>
struct SegTree {
    int n;
    T nu, nq;
    vector<T> st;
    SegTree(const vector<T> &v)
        : n(len(v)), nu(0), nq(numeric_limits<T>::max()), st(n * 4 + 1, nu) {
        for (int i = 0; i < n; ++i) update(i, v[i]);
    }
    void update(int p, T v) { update(1, 0, n - 1, p, v); }

```

```

    T query(int l, int r) { return query(1, 0, n - 1, l, r); }

    void update(int node, int nl, int nr, int p, T v) {
        if (p < nl or p > nr) return;

        if (nl == nr) {
            st[node] = v;
            return;
        }

        update(left(node), nl, mid(nl, nr), p, v);
        update(right(node), mid(nl, nr) + 1, nr, p, v);

        st[node] = min(st[left(node)], st[right(node)]);
    }

    T query(int node, int nl, int nr, int ql, int qr) {
        if (ql <= nl and qr >= nr) return st[node];
        if (nl > qr or nr < ql) return nq;
        if (nl == nr) return st[node];

        return min(query(left(node), nl, mid(nl, nr), ql, qr),
                    query(right(node), mid(nl, nr) + 1, nr, ql, qr));
    }

    int left(int p) { return p << 1; }
    int right(int p) { return (p << 1) + 1; }
    int mid(int l, int r) { return (r - l) / 2 + 1; }
};

```

1.6 Segtree Rminq Rsu

```

template <typename t = ll>
struct SegTree {
    int n;
    t nu;
    t nq;
    vector<t> st, lazy;
    SegTree(const vector<t> &xs)
        : n(len(xs)),
          nu(0),
          nq(numeric_limits<t>::max()),
          st(4 * n, nu),
          lazy(4 * n, nu) {
        for (int i = 0; i < len(xs); ++i) update(i, i, xs[i]);
    }

    SegTree(int n) : n(n), st(4 * n, nu), lazy(4 * n, nu) {}

    void update(int l, int r, ll value) { update(1, 0, n - 1, l, r, value); }

    t query(int l, int r) { return query(1, 0, n - 1, l, r); }

    void update(int node, int nl, int nr, int ql, int qr, ll v) {
        propagation(node, nl, nr);

        if (ql > nr or qr < nl) return;

```

```

    if (ql <= nl and nr <= qr) {
        st[node] += (nr - nl + 1) * v;

        if (nl < nr) {
            lazy[left(node)] += v;
            lazy[right(node)] += v;
        }

        return;
    }

    update(left(node), nl, mid(nl, nr), ql, qr, v);
    update(right(node), mid(nl, nr) + 1, nr, ql, qr, v);

    st[node] = min(st[left(node)], st[right(node)]);
}

t query(int node, int nl, int nr, int ql, int qr) {
    propagation(node, nl, nr);

    if (ql > nr or qr < nl) return nq;

    if (ql <= nl and nr <= qr) return st[node];

    t x = query(left(node), nl, mid(nl, nr), ql, qr);
    t y = query(right(node), mid(nl, nr) + 1, nr, ql, qr);

    return min(x, y);
}

void propagation(int node, int nl, int nr) {
    if (lazy[node]) {
        st[node] += lazy[node];

        if (nl < nr) {
            lazy[left(node)] += lazy[node];
            lazy[right(node)] += lazy[node];
        }

        lazy[node] = nu;
    }
}

int left(int p) { return p << 1; }
int right(int p) { return (p << 1) + 1; }
int mid(int l, int r) { return (r - l) / 2 + 1; }
};

```

1.7 Segtree Rsq Rsu

```

template <typename T = ll>
struct SegTree {
    int N;
    vector<T> st, lazy;
    T nu = 0;
    T nq = 0;
    SegTree(const vector<T> &xs) : N(len(xs)), st(4 * N, nu), lazy(4 * N, nu) {
        for (int i = 0; i < len(xs); ++i) update(i, i, xs[i]);
    }
};

```

```

}

SegTree(int n) : N(n), st(4 * N, nu), lazy(4 * N, nu) {}

void update(int l, int r, ll value) { update(1, 0, N - 1, l, r, value); }

T query(int l, int r) { return query(1, 0, N - 1, l, r); }

void update(int node, int nl, int nr, int ql, int qr, ll v) {
    propagation(node, nl, nr);

    if (ql > nr or qr < nl) return;

    if (ql <= nl and nr <= qr) {
        st[node] += (nr - nl + 1) * v;

        if (nl < nr) {
            lazy[left(node)] += v;
            lazy[right(node)] += v;
        }

        return;
    }

    update(left(node), nl, mid(nl, nr), ql, qr, v);
    update(right(node), mid(nl, nr) + 1, nr, ql, qr, v);

    st[node] = st[left(node)] + st[right(node)];
}

T query(int node, int nl, int nr, int ql, int qr) {
    propagation(node, nl, nr);

    if (ql > nr or qr < nl) return nq;

    if (ql <= nl and nr <= qr) return st[node];

    T x = query(left(node), nl, mid(nl, nr), ql, qr);
    T y = query(right(node), mid(nl, nr) + 1, nr, ql, qr);

    return x + y;
}

void propagation(int node, int nl, int nr) {
    if (lazy[node]) {
        st[node] += (nr - nl + 1) * lazy[node];

        if (nl < nr) {
            lazy[left(node)] += lazy[node];
            lazy[right(node)] += lazy[node];
        }

        lazy[node] = nu;
    }
}

int left(int p) { return p << 1; }
int right(int p) { return (p << 1) + 1; }

```

```
int mid(int l, int r) { return (r - l) / 2 + 1; }
};
```

1.8 Sparse Table Rminq

```
/*
    Sparse table implementation for rmq.
    build: O(NlogN)
    query: O(1)
*/
int fastlog2(ll x) {
    ull i = x;
    return i ? __builtin_clzll(1) - __builtin_clzll(i) : -1;
}
template <typename T>
class SparseTable {
public:
    int N;
    int K;
    vector<vector<T>> st;
    SparseTable(vector<T> vs)
        : N((int)vs.size()), K(fastlog2(N) + 1), st(K + 1, vector<T>(N + 1)) {
        copy(vs.begin(), vs.end(), st[0].begin());

        for (int i = 1; i <= K; ++i)
            for (int j = 0; j + (1 << i) <= N; ++j)
                st[i][j] = min(st[i - 1][j], st[i - 1][j + (1 << (i - 1))]);
    }
    T RMQ(int l, int r) { // [l, r], 0 indexed
        int i = fastlog2(r - l + 1);
        return min(st[i][l], st[i][r - (1 << i) + 1]);
    }
};
```

2 Dynamic programming

2.1 Edit Distance

```
int edit_distance(const string &a, const string &b) {
    int n = a.size();
    int m = b.size();
    vector<vi> dp(n + 1, vi(m + 1, 0));

    int ADD = 1, DEL = 1, CHG = 1;
    for (int i = 0; i <= n; ++i) {
        dp[i][0] = i * DEL;
    }
    for (int i = 1; i <= m; ++i) {
        dp[0][i] = ADD * i;
    }

    for (int i = 1; i <= n; ++i) {
        for (int j = 1; j <= m; ++j) {
            int add = dp[i][j - 1] + ADD;
            int del = dp[i - 1][j] + DEL;
            int chg = dp[i - 1][j - 1] + (a[i - 1] == b[j - 1] ? 0 : 1) * CHG;
            dp[i][j] = min({add, del, chg});
        }
    }
}
```

```
    }
}

return dp[n][m];
}

2.2 Knapsack Dp Values 01

const int MAX_N = 1001;
const int MAX_S = 100001;
array<array<int, MAX_S>, MAX_N> dp;
bool check[MAX_N][MAX_S];
pair<int, vi> knapsack(int S, const vector<pii> &xs) {
    int N = (int)xs.size();

    for (int i = 0; i <= N; ++i) dp[i][0] = 0;

    for (int m = 0; m <= S; ++m) dp[0][m] = 0;

    for (int i = 1; i <= N; ++i) {
        for (int m = 1; m <= S; ++m) {
            dp[i][m] = dp[i - 1][m];
            check[i][m] = false;

            auto [w, v] = xs[i - 1];

            if (w <= m and (dp[i - 1][m - w] + v) >= dp[i][m]) {
                dp[i][m] = dp[i - 1][m - w] + v;
                check[i][m] = true;
            }
        }
    }

    int m = S;
    vi es;

    for (int i = N; i >= 1; --i) {
        if (check[i][m]) {
            es.push_back(i);
            m -= xs[i - 1].first;
        }
    }

    reverse(es.begin(), es.end());

    return {dp[N][S], es};
}
```

2.3 Money Sum Bottom Up

```
/*
    find every possible sum using
    the given values only once.
*/
set<int> money_sum(const vi &xs) {
    using vc = vector<char>;
    using vvc = vector<vc>;
    int _m = accumulate(all(xs), 0);
```

```

int _n = xs.size();
vvc _dp(_n + 1, vc(_m + 1, 0));
set<int> _ans;
_dp[0][xs[0]] = 1;
for (int i = 1; i < _n; ++i) {
    for (int j = 0; j <= _m; ++j) {
        if (j == 0 or _dp[i - 1][j]) {
            _dp[i][j + xs[i]] = 1;
            _dp[i][j] = 1;
        }
    }
}

for (int i = 0; i < _n; ++i)
    for (int j = 0; j <= _m; ++j)
        if (_dp[i][j]) _ans.insert(j);
return _ans;
}

```

2.4 Tsp

```

using vi = vector<int>;
vector<vi> dist;
vector<vi> memo;
/* 0 ( N^2 * 2^N )*/
int tsp(int i, int mask, int N) {
    if (mask == (1 << N) - 1) return dist[i][0];
    if (memo[i][mask] != -1) return memo[i][mask];
    int ans = INT_MAX << 1;
    for (int j = 0; j < N; ++j) {
        if (mask & (1 << j)) continue;
        auto t = tsp(j, mask | (1 << j), N) + dist[i][j];
        ans = min(ans, t);
    }
    return memo[i][mask] = ans;
}

```

3 Extras

3.1 Bigint

```

const int maxn = 1e2 + 14, lg = 15;
const int base = 1000000000;
const int base_digits = 9;
struct bigint {
    vector<int> a;
    int sign;

    int size() {
        if (a.empty()) return 0;
        int ans = (a.size() - 1) * base_digits;
        int ca = a.back();
        while (ca) ans++, ca /= 10;
        return ans;
    }

    bigint operator^(const bigint &v) {
        bigint ans = 1, a = *this, b = v;

```

```

        while (!b.isZero()) {
            if (b % 2) ans *= a;
            a *= a, b /= 2;
        }
        return ans;
    }

    string to_string() {
        stringstream ss;
        ss << *this;
        string s;
        ss >> s;
        return s;
    }

    int sumof() {
        string s = to_string();
        int ans = 0;
        for (auto c : s) ans += c - '0';
        return ans;
    }

    /*</arpa>*/
    bigint() : sign(1) {}

    bigint(long long v) { *this = v; }

    bigint(const string &s) { read(s); }

    void operator=(const bigint &v) {
        sign = v.sign;
        a = v.a;
    }

    void operator=(long long v) {
        sign = 1;
        a.clear();
        if (v < 0) sign = -1, v = -v;
        for (; v > 0; v = v / base) a.push_back(v % base);
    }

    bigint operator+(const bigint &v) const {
        if (sign == v.sign) {
            bigint res = v;

            for (int i = 0, carry = 0; i < (int)max(a.size(), v.a.size()) || carry; ++i) {
                if (i == (int)res.a.size()) res.a.push_back(0);
                res.a[i] += carry + (i < (int)a.size() ? a[i] : 0);
                carry = res.a[i] >= base;
                if (carry) res.a[i] -= base;
            }
            return res;
        }
        return *this - (-v);
    }

    bigint operator-(const bigint &v) const {
        if (sign == v.sign) {
            if (abs() >= v.abs()) {
                bigint res = *this;

```

```

        for (int i = 0, carry = 0; i < (int)v.a.size() || carry; ++i) {
            res.a[i] -= carry + (i < (int)v.a.size() ? v.a[i] : 0);
            carry = res.a[i] < 0;
            if (carry) res.a[i] += base;
        }
        res.trim();
        return res;
    }
    return -(v - *this);
}

void operator+=(int v) {
    if (v < 0) sign = -sign, v = -v;
    for (int i = 0, carry = 0; i < (int)a.size() || carry; ++i) {
        if (i == (int)a.size()) a.push_back(0);
        long long cur = a[i] * (long long)v + carry;
        carry = (int)(cur / base);
        a[i] = (int)(cur % base);
        // asm("divl %%ecx" : "=a"(carry), "=d"(a[i]) :
        // "A"(cur), "c"(base));
    }
    trim();
}

bigint operator*(int v) const {
    bigint res = *this;
    res *= v;
    return res;
}

void operator*=(long long v) {
    if (v < 0) sign = -sign, v = -v;
    if (v > base) {
        *this = *this * (v / base) * base + *this * (v % base);
        return;
    }
    for (int i = 0, carry = 0; i < (int)a.size() || carry; ++i) {
        if (i == (int)a.size()) a.push_back(0);
        long long cur = a[i] * (long long)v + carry;
        carry = (int)(cur / base);
        a[i] = (int)(cur % base);
        // asm("divl %%ecx" : "=a"(carry), "=d"(a[i]) :
        // "A"(cur), "c"(base));
    }
    trim();
}

bigint operator*(long long v) const {
    bigint res = *this;
    res *= v;
    return res;
}

friend pair<bigint, bigint> divmod(const bigint &a1, const bigint &b1) {
    int norm = base / (b1.a.back() + 1);
    bigint a = a1.abs() * norm;

```

```

    bigint b = b1.abs() * norm;
    bigint q, r;
    q.a.resize(a.a.size());

    for (int i = a.a.size() - 1; i >= 0; i--) {
        r *= base;
        r += a.a[i];
        int s1 = r.a.size() <= b.a.size() ? 0 : r.a[b.a.size()];
        int s2 = r.a.size() <= b.a.size() - 1 ? 0 : r.a[b.a.size() - 1];
        int d = ((long long)base * s1 + s2) / b.a.back();
        r -= b * d;
        while (r < 0) r += b, --d;
        q.a[i] = d;
    }

    q.sign = a1.sign * b1.sign;
    r.sign = a1.sign;
    q.trim();
    r.trim();
    return make_pair(q, r / norm);
}

bigint operator/(const bigint &v) const { return divmod(*this, v).first; }

bigint operator%(const bigint &v) const { return divmod(*this, v).second; }

void operator/=(int v) {
    if (v < 0) sign = -sign, v = -v;
    for (int i = (int)a.size() - 1, rem = 0; i >= 0; --i) {
        long long cur = a[i] + rem * (long long)base;
        a[i] = (int)(cur / v);
        rem = (int)(cur % v);
    }
    trim();
}

bigint operator/(int v) const {
    bigint res = *this;
    res /= v;
    return res;
}

int operator%(int v) const {
    if (v < 0) v = -v;
    int m = 0;
    for (int i = a.size() - 1; i >= 0; --i)
        m = (a[i] + m * (long long)base) % v;
    return m * sign;
}

void operator+=(const bigint &v) { *this = *this + v; }
void operator-=(const bigint &v) { *this = *this - v; }
void operator*=(const bigint &v) { *this = *this * v; }
void operator/=(const bigint &v) { *this = *this / v; }

bool operator<(const bigint &v) const {
    if (sign != v.sign) return sign < v.sign;
    if (a.size() != v.a.size()) return a.size() * sign < v.a.size() * v.sign;

```

```

    for (int i = a.size() - 1; i >= 0; i--)
        if (a[i] != v.a[i]) return a[i] * sign < v.a[i] * sign;
    return false;
}

bool operator>(const bigint &v) const { return v < *this; }
bool operator<=(const bigint &v) const { return !(v < *this); }
bool operator>=(const bigint &v) const { return !(*this < v); }
bool operator==(const bigint &v) const {
    return !(*this < v) && !(v < *this);
}
bool operator!=(const bigint &v) const { return *this < v || v < *this; }

void trim() {
    while (!a.empty() && !a.back()) a.pop_back();
    if (a.empty()) sign = 1;
}

bool isZero() const { return a.empty() || (a.size() == 1 && !a[0]); }

bigint operator-() const {
    bigint res = *this;
    res.sign = -sign;
    return res;
}

bigint abs() const {
    bigint res = *this;
    res.sign *= res.sign;
    return res;
}

long long longValue() const {
    long long res = 0;
    for (int i = a.size() - 1; i >= 0; i--) res = res * base + a[i];
    return res * sign;
}

friend bigint gcd(const bigint &a, const bigint &b) {
    return b.isZero() ? a : gcd(b, a % b);
}

friend bigint lcm(const bigint &a, const bigint &b) {
    return a / gcd(a, b) * b;
}

void read(const string &s) {
    sign = 1;
    a.clear();
    int pos = 0;
    while (pos < (int)s.size() && (s[pos] == '-' || s[pos] == '+')) {
        if (s[pos] == '-') sign = -sign;
        ++pos;
    }
    for (int i = s.size() - 1; i >= pos; i -= base_digits) {
        int x = 0;
        for (int j = max(pos, i - base_digits + 1); j <= i; j++)
            x = x * 10 + s[j] - '0';
        a.push_back(x);
    }
}

```

```

    }
    trim();
}

friend istream &operator>>(istream &stream, bigint &v) {
    string s;
    stream >> s;
    v.read(s);
    return stream;
}

friend ostream &operator<<(ostream &stream, const bigint &v) {
    if (v.sign == -1) stream << '-';
    stream << (v.a.empty() ? 0 : v.a.back());
    for (int i = (int)v.a.size() - 2; i >= 0; --i)
        stream << setw(base_digits) << setfill('0') << v.a[i];
    return stream;
}

static vector<int> convert_base(const vector<int> &a, int old_digits,
                                int new_digits) {
    vector<long long> p(max(old_digits, new_digits) + 1);
    p[0] = 1;
    for (int i = 1; i < (int)p.size(); i++) p[i] = p[i - 1] * 10;
    vector<int> res;
    long long cur = 0;
    int cur_digits = 0;
    for (int i = 0; i < (int)a.size(); i++) {
        cur += a[i] * p[cur_digits];
        cur_digits += old_digits;
        while (cur_digits >= new_digits) {
            res.push_back(int(cur % p[new_digits]));
            cur /= p[new_digits];
            cur_digits -= new_digits;
        }
    }
    res.push_back((int)cur);
    while (!res.empty() && !res.back()) res.pop_back();
    return res;
}

typedef vector<long long> vll;

static vll karatsubaMultiply(const vll &a, const vll &b) {
    int n = a.size();
    vll res(n + n);
    if (n <= 32) {
        for (int i = 0; i < n; i++)
            for (int j = 0; j < n; j++) res[i + j] += a[i] * b[j];
        return res;
    }

    int k = n >> 1;
    vll a1(a.begin(), a.begin() + k);
    vll a2(a.begin() + k, a.end());
    vll b1(b.begin(), b.begin() + k);
    vll b2(b.begin() + k, b.end());
}

```



```

vll a1b1 = karatsubaMultiply(a1, b1);
vll a2b2 = karatsubaMultiply(a2, b2);

for (int i = 0; i < k; i++) a2[i] += a1[i];
for (int i = 0; i < k; i++) b2[i] += b1[i];

vll r = karatsubaMultiply(a2, b2);
for (int i = 0; i < (int)a1b1.size(); i++) r[i] -= a1b1[i];
for (int i = 0; i < (int)a2b2.size(); i++) r[i] -= a2b2[i];

for (int i = 0; i < (int)r.size(); i++) res[i + k] += r[i];
for (int i = 0; i < (int)a1b1.size(); i++) res[i] += a1b1[i];
for (int i = 0; i < (int)a2b2.size(); i++) res[i + n] += a2b2[i];
return res;
}

bigint operator*(const bigint &v) const {
    vector<int> a6 = convert_base(this->a, base_digits, 6);
    vector<int> b6 = convert_base(v.a, base_digits, 6);
    vll a(a6.begin(), a6.end());
    vll b(b6.begin(), b6.end());
    while (a.size() < b.size()) a.push_back(0);
    while (b.size() < a.size()) b.push_back(0);
    while (a.size() & (a.size() - 1)) a.push_back(0), b.push_back(0);
    vll c = karatsubaMultiply(a, b);
    bigint res;
    res.sign = sign * v.sign;
    for (int i = 0, carry = 0; i < (int)c.size(); i++) {
        long long cur = c[i] + carry;
        res.a.push_back((int)(cur % 1000000));
        carry = (int)(cur / 1000000);
    }
    res.a = convert_base(res.a, 6, base_digits);
    res.trim();
    return res;
}
};

```

3.2 Binary To Gray

```

string binToGray(string bin) {
    string gray(bin.size(), '0');
    int n = bin.size() - 1;
    gray[0] = bin[0];
    for (int i = 1; i <= n; i++) {
        gray[i] = '0' + (bin[i - 1] == '1') ^ (bin[i] == '1');
    }
    return gray;
}

```

3.3 Get Permutation Cicles

```

/*
 * receives a permutation [0, n-1]
 * returns a vector of cicles
 * for example: [ 1, 0, 3, 4, 2] -> [[0, 1], [2, 3, 4]]
 */
vector<vll> getPermutationCicles(const vll &ps) {

```

```

    ll n = len(ps);
    vector<char> visited(n);
    vector<vll> cicles;
    for (int i = 0; i < n; ++i) {
        if (visited[i]) continue;

        vll cicle;
        ll pos = i;
        while (!visited[pos]) {
            cicle.pb(pos);
            visited[pos] = true;
            pos = ps[pos];
        }

        cicles.push_back(vll(all(cicle)));
    }
    return cicles;
}

```

4 Graphs

4.1 2 SAT (struct)

```

struct SAT2 {
    ll n;
    vll2d adj, adj_t;
    vc used;
    vll order, comp;
    vc assignment;
    bool solvable;
    SAT2(ll _n)
        : n(2 * _n),
          adj(n),
          adj_t(n),
          used(n),
          order(n),
          comp(n, -1),
          assignment(n / 2) {}
    void dfs1(int v) {
        used[v] = true;
        for (int u : adj[v]) {
            if (!used[u]) dfs1(u);
        }
        order.push_back(v);
    }

    void dfs2(int v, int c1) {
        comp[v] = c1;
        for (int u : adj_t[v]) {
            if (comp[u] == -1) dfs2(u, c1);
        }
    }

    bool solve_2SAT() {
        // find and label each SCC
        for (int i = 0; i < n; ++i) {
            if (!used[i]) dfs1(i);

```

```

}
reverse(all(order));
ll j = 0;
for (auto &v : order) {
    if (comp[v] == -1) dfs2(v, j++);
}

assignment.assign(n / 2, false);
for (int i = 0; i < n; i += 2) {
    // x and !x belong to the same SCC
    if (comp[i] == comp[i + 1]) {
        solvable = false;
        return false;
    }

    assignment[i / 2] = comp[i] > comp[i + 1];
}
solvable = true;
return true;
}

void add_disjunction(int a, bool na, int b, bool nb) {
    a = (2 * a) ^ na;
    b = (2 * b) ^ nb;
    int neg_a = a ^ 1;
    int neg_b = b ^ 1;
    adj[neg_a].push_back(b);
    adj[neg_b].push_back(a);
    adj_t[b].push_back(neg_a);
    adj_t[a].push_back(neg_b);
}
};

```

4.2 SCC (struct)

```

struct SCC {
    ll N;
    vll2d adj, tadj;
    vll todo, comps, comp;
    vector<set<ll>> sccadj;
    vchar vis;
    SCC(ll _N) : N(_N), adj(_N), tadj(_N), comp(_N, -1), sccadj(_N), vis(_N) {}

    void add_edge(ll x, ll y) { adj[x].eb(y), tadj[y].eb(x); }

    void dfs(ll x) {
        vis[x] = 1;
        for (auto &y : adj[x])
            if (!vis[y]) dfs(y);
        todo.pb(x);
    }

    void dfs2(ll x, ll v) {
        comp[x] = v;
        for (auto &y : tadj[x])
            if (comp[y] == -1) dfs2(y, v);
    }

    void gen() {
        for (ll i = 0; i < N; ++i)

```

```

            if (!vis[i]) dfs(i);
        reverse(all(todo));
        for (auto &x : todo)
            if (comp[x] == -1) {
                dfs2(x, x);
                comps.pb(x);
            }
    }

    void genSCCGraph() {
        for (ll i = 0; i < N; ++i) {
            for (auto &j : adj[i]) {
                if (comp[i] != comp[j]) {
                    sccadj[comp[i]].insert(comp[j]);
                }
            }
        }
    }
};

```

4.3 SCC Nodes (kosajaru)

```

/*
 * O(n+m)
 * Returns a pair <a, b>
 *     a: number of SCCs
 *     b: vector of size n, where b[i] is the SCC id of node i
 */
void dfs(ll u, vchar &visited, const vll2d &g, vll &scc, bool buildScc, ll id,
        vll &sccid) {
    visited[u] = true;
    sccid[u] = id;
    for (auto &v : g[u])
        if (!visited[v]) dfs(v, visited, g, scc, buildScc, id, sccid);

    // if it's the first pass, add the node to the scc
    if (buildScc) scc.eb(u);
}

pair<ll, vll> kosajaru(vll2d &g) {
    ll n = len(g);
    vll scc;
    vchar vis(n);
    vll sccid(n);
    for (ll i = 0; i < n; i++)
        if (!vis[i]) dfs(i, vis, g, scc, true, 0, sccid);

    // build the transposed graph
    vll2d gt(n);
    for (int i = 0; i < n; ++i)
        for (auto &v : g[i]) gt[v].eb(i);

    // run the dfs on the previous scc order
    ll id = 1;
    vis.assign(n, false);
    for (ll i = len(scc) - 1; i >= 0; i--)
        if (!vis[scc[i]]) {
            dfs(scc[i], vis, gt, scc, false, id++, sccid);

```

```

    }
    return {id - 1, sccid};
}

```

4.4 Check Bipartite

```

// 0(V)
bool checkBipartite(const ll n, const vector<vll> &adj) {
    ll s = 0;
    queue<ll> q;
    q.push(s);
    vll color(n, INF);
    color[s] = 0;
    bool isBipartite = true;
    while (!q.empty() && isBipartite) {
        ll u = q.front();
        q.pop();
        for (auto &v : adj[u]) {
            if (color[v] == INF) {
                color[v] = 1 - color[u];
                q.push(v);
            } else if (color[v] == color[u]) {
                return false;
            }
        }
    }
    return true;
}

```

4.5 Count SCC (kosajaru)

```

void dfs(ll u, vchar &visited, const vll2d &g, vll &scc, bool buildScc) {
    visited[u] = true;
    for (auto &v : g[u])
        if (!visited[v]) dfs(v, visited, g, scc, buildScc);

    // if it's the first pass, add the node to the scc
    if (buildScc) scc.eb(u);
}

ll kosajaru(vll2d &g) {
    ll n = len(g);
    vll scc;
    vchar vis(n);
    for (ll i = 0; i < n; i++)
        if (!vis[i]) dfs(i, vis, g, scc, true);

    // build the transposed graph
    vll2d gt(n);
    for (int i = 0; i < n; ++i)
        for (auto &v : g[i]) gt[v].eb(i);

    // run the dfs on the previous scc order
    ll scccnt = 0;
    vis.assign(n, false);
    for (ll i = len(scc) - 1; i >= 0; i--)
        if (!vis[scc[i]]) dfs(scc[i], vis, gt, scc, false), scccnt++;
    return scccnt;
}

```

```

}

```

4.6 Dijkstra

```

ll __inf = LLONG_MAX >> 5;
vll dijkstra(const vector<vector<pll>> &g, ll n) {
    priority_queue<pll, vector<pll>, greater<pll>> pq;
    vll dist(n, __inf);
    vector<char> vis(n);
    pq.emplace(0, 0);
    dist[0] = 0;
    while (!pq.empty()) {
        auto [d1, v] = pq.top();
        pq.pop();
        if (vis[v]) continue;
        vis[v] = true;

        for (auto [d2, u] : g[v]) {
            if (dist[u] > d1 + d2) {
                dist[u] = d1 + d2;
                pq.emplace(dist[u], u);
            }
        }
    }
    return dist;
}

```

4.7 Floyd Warshall

```

vector<vll> floyd_warshall(const vector<vll> &adj, ll n) {
    auto dist = adj;

    for (int i = 0; i < n; ++i) {
        for (int j = 0; j < n; ++j) {
            for (int k = 0; k < n; ++k) {
                dist[j][k] = min(dist[j][k], dist[j][i] + dist[i][k]);
            }
        }
    }
    return dist;
}

```

4.8 Kruskal (Python)

```

class DSU:
    def __init__(self, n):
        self.n = n
        self.p = [x for x in range(0, n + 1)]
        self.size = [0 for i in range(0, n + 1)]

    def find_set(self, x):
        if self.p[x] == x:
            return x
        else:
            self.p[x] = self.find_set(self.p[x])
            return self.p[x]

```

```

def same_set(self, x, y):
    return bool(self.find_set(x) == self.find_set(y))

def union_set(self, x, y):
    px = self.find_set(x)
    py = self.find_set(y)

    if px == py:
        return

    size_x = self.size[px]
    size_y = self.size[py]

    if size_x > size_y:
        self.p[py] = self.p[px]
        self.size[px] += self.size[py]
    else:
        self.p[px] = self.p[py]
        self.size[py] += self.size[px]

def kruskal(gv, n):
    """
    Receives the list of edges as a list of tuple in the form:
        d, u, v
    d: distance between u and v
    And also n as the total of vertices.
    """
    dsu = DSU(n)

    c = 0
    for e in gv:
        d, u, v = e
        if not dsu.same_set(u, v):
            c += d
            dsu.union_set(u, v)

    return c

```

4.9 Lowest Common Ancestor Sparse Table

```

int fastlog2(ll x) {
    ull i = x;
    return i ? __builtin_clzll(1) - __builtin_clzll(i) : -1;
}

template <typename T>
class SparseTable {
public:
    int N;
    int K;
    vector<vector<T>> st;
    SparseTable(vector<T> vs)
        : N((int)vs.size()), K(fastlog2(N) + 1), st(K + 1, vector<T>(N + 1)) {
        copy(vs.begin(), vs.end(), st[0].begin());

        for (int i = 1; i <= K; ++i)
            for (int j = 0; j + (1 << i) <= N; ++j)
                st[i][j] = min(st[i - 1][j], st[i - 1][j + (1 << (i - 1))]);
    }
};

```

```

}
SparseTable() {}
T RMQ(int l, int r) {
    int i = fastlog2(r - l + 1);
    return min(st[i][l], st[i][r - (1 << i) + 1]);
}
};

class LCA {
public:
    int p;
    int n;
    vi first;
    vector<char> visited;
    vi vertices;
    vi height;
    SparseTable<int> st;

    LCA(const vector<vi> &g)
        : p(0), n((int)g.size()), first(n + 1), visited(n + 1, 0), height(n + 1) {
        build_dfs(g, 1, 1);
        st = SparseTable<int>(vertices);
    }

    void build_dfs(const vector<vi> &g, int u, int hi) {
        visited[u] = true;
        height[u] = hi;
        first[u] = vertices.size();
        vertices.push_back(u);
        for (auto uv : g[u]) {
            if (!visited[uv]) {
                build_dfs(g, uv, hi + 1);
                vertices.push_back(uv);
            }
        }
    }

    int lca(int a, int b) {
        int l = min(first[a], first[b]);
        int r = max(first[a], first[b]);
        return st.RMQ(l, r);
    }
};

```

4.10 Topological Sorting

```

/*
 * O(V)
 * assumes:
 *     * vertices have index [0, n-1]
 * if is a DAG:
 *     * returns a topological sorting
 * else:
 *     * returns an empty vector
 */
enum class state { not_visited, processing, done };
bool dfs(const vector<vll> &adj, ll s, vector<state> &states, vll &order) {
    states[s] = state::processing;
    for (auto &v : adj[s]) {

```

```

    if (states[v] == state::not_visited) {
        if (not dfs(adj, v, states, order)) return false;
    } else if (states[v] == state::processing)
        return false;
    }
    states[s] = state::done;
    order.pb(s);
    return true;
}

vll topologicalSorting(const vector<vll> &adj) {
    ll n = len(adj);
    vll order;
    vector<state> states(n, state::not_visited);
    for (int i = 0; i < n; ++i) {
        if (states[i] == state::not_visited) {
            if (not dfs(adj, i, states, order)) return {};
        }
    }
    reverse(all(order));
    return order;
}

```

5 Math

5.1 Combinatorics With Repetitions

```

void combinations_with_repetition(int n, int k,
                                   function<void(const vector<int> &)> process)
{
    vector<int> v(k, 1);
    int pos = k - 1;

    while (true) {
        process(v);

        v[pos]++;

        while (pos > 0 and v[pos] > n) {
            --pos;
            v[pos]++;
        }

        if (pos == 0 and v[pos] > n) break;

        for (int i = pos + 1; i < k; ++i) v[i] = v[pos];

        pos = k - 1;
    }
}

```

5.2 Count Divisors Memo

```

const ll mod = 1073741824;
const ll maxd = 100 * 100 * 100 + 1;
vector<ll> memo(maxd, -1);
ll countdivisors(ll x) {
    ll ox = x;

```

```

    ll ans = 1;
    for (ll i = 2; i <= x; ++i) {
        if (memo[x] != -1) {
            ans *= memo[x];
            break;
        }
        ll count = 0;
        while (x and x % i == 0) {
            x /= i;
            count++;
        }
        ans *= (count + 1);
    }
    memo[ox] = ans;
    return ans;
}

```

5.3 Euler Phi

```

const ll MAXN = 1e5;
vll list_primes(ll n) { // Nlog * log N
    vll ps;
    bitset<MAXN> sieve;
    sieve.set();
    sieve.reset(1);
    for (ll i = 2; i <= n; ++i) {
        if (sieve[i]) ps.push_back(i);
        for (ll j = i * 2; j <= n; j += i) {
            sieve.reset(j);
        }
    }
    return ps;
}

vector<pll> factorization(ll n, const vll &primes) {
    vector<pll> ans;
    for (auto &p : primes) {
        if (n == 1) break;
        ll cnt = 0;
        while (n % p == 0) {
            cnt++;
            n /= p;
        }
        if (cnt) ans.emplace_back(p, cnt);
    }
    return ans;
}

ll phi(ll n, vector<pll> factors) {
    if (n == 1) return 1;
    ll ans = n;

    for (auto [p, k] : factors) {
        ans /= p;
        ans *= (p - 1);
    }

    return ans;
}

```

```
}
```

5.4 Factorial Factorization

```
// O(logN) greater k that p^k | n
ll E(ll n, ll p) {
    ll k = 0, b = p;
    while (b <= n) {
        k += n / b;
        b *= p;
    }
    return k;
}

// list every prime until MAXN O(Nlog * log N)
const ll MAXN = 1e5;
vll list_primes(ll n) {
    vll ps;
    bitset<MAXN> sieve;
    sieve.set();
    sieve.reset(1);
    for (ll i = 2; i <= n; ++i) {
        if (sieve[i]) ps.push_back(i);
        for (ll j = i * 2; j <= n; j += i) sieve.reset(j);
    }
    return ps;
}

// O(pi(N)*logN)
map<ll, ll> factorial_factorization(ll n, const vll &primes) {
    map<ll, ll> fs;
    for (const auto &p : primes) {
        if (p > n) break;
        fs[p] = E(n, p);
    }
    return fs;
}
```

5.5 Factorial

```
const ll MAX = 18;
vll fv(MAX, -1);
ll factorial(ll n) {
    if (fv[n] != -1) return fv[n];
    if (n == 0) return 1;
    return n * factorial(n - 1);
}
```

5.6 Factorization With Primes

```
// Nlog * log N
const ll MAXN = 1e5;
vll list_primes(ll n) {
    vll ps;
    bitset<MAXN> sieve;
    sieve.set();
    sieve.reset(1);
```

```
    for (ll i = 2; i <= n; ++i) {
        if (sieve[i]) ps.push_back(i);
        for (ll j = i * 2; j <= n; j += i) sieve.reset(j);
    }
    return ps;
}
```

```
// O(pi(sqrt(n)))
map<ll, ll> factorization(ll n, const vll &primes) {
    map<ll, ll> ans;
    for (auto p : primes) {
        if (p * p > n) break;
        ll count = 0;
        for (; n % p == 0; count++, n /= p)
            ;
        if (count) ans[p] = count;
    }
    return ans;
}
```

5.7 Factorization

```
// O(sqrt(n))
map<ll, ll> factorization(ll n) {
    map<ll, ll> ans;
    for (ll i = 2; i * i <= n; i++) {
        ll count = 0;
        for (; n % i == 0; count++, n /= i)
            ;
        if (count) ans[i] = count;
    }
    if (n > 1) ans[n]++;
    return ans;
}
```

5.8 Fast Exp

```
/*
    Fast exponentiation algorithm,
    compute a^n in O(log(n))
*/
ll fexp(ll a, int n) {
    if (n == 0) return 1;
    if (n == 1) return a;
    ll x = fexp(a, n / 2);
    return x * x * (n & 1 ? a : 1);
}
```

5.9 Gcd Using Factorization

```
// O(sqrt(n))
map<ll, ll> factorization(ll n) {
    map<ll, ll> ans;
    for (ll i = 2; i * i <= n; i++) {
        ll count = 0;
        for (; n % i == 0; count++, n /= i)
            ;
```

```

    if (count) ans[i] = count;
}
if (n > 1) ans[n]++;
return ans;
}

ll gcd_with_factorization(ll a, ll b) {
    map<ll, ll> fa = factorization(a);
    map<ll, ll> fb = factorization(b);
    ll ans = 1;
    for (auto fai : fa) {
        ll k = min(fai.second, fb[fai.first]);
        while (k--) ans *= fai.first;
    }
    return ans;
}

```

5.10 Gcd

```
ll gcd(ll a, ll b) { return b ? gcd(b, a % b) : a; }
```

5.11 Integer Mod

```

const ll INF = 1e18;
const ll mod = 998244353;
template <ll MOD = mod>
struct Modular {
    ll value;
    static const ll MOD_value = MOD;

    Modular(ll v = 0) {
        value = v % MOD;
        if (value < 0) value += MOD;
    }
    Modular(ll a, ll b) : value(0) {
        *this += a;
        *this /= b;
    }

    Modular& operator+=(Modular const& b) {
        value += b.value;
        if (value >= MOD) value -= MOD;
        return *this;
    }
    Modular& operator--(Modular const& b) {
        value -= b.value;
        if (value < 0) value += MOD;
        return *this;
    }
    Modular& operator*(Modular const& b) {
        value = (ll)value * b.value % MOD;
        return *this;
    }

    friend Modular mexp(Modular a, ll e) {
        Modular res = 1;
        while (e) {
            if (e & 1) res *= a;

```

```

        a *= a;
        e >>= 1;
    }
    return res;
}
friend Modular inverse(Modular a) { return mexp(a, MOD - 2); }

Modular& operator/=(Modular const& b) { return *this *= inverse(b); }
friend Modular operator+(Modular a, Modular const b) { return a += b; }
Modular operator++(int) { return this->value = (this->value + 1) % MOD; }
Modular operator++() { return this->value = (this->value + 1) % MOD; }
friend Modular operator-(Modular a, Modular const b) { return a -= b; }
friend Modular operator-(Modular const a) { return 0 - a; }
Modular operator--(int) {
    return this->value = (this->value - 1 + MOD) % MOD;
}

Modular operator--() { return this->value = (this->value - 1 + MOD) % MOD; }
friend Modular operator*(Modular a, Modular const b) { return a *= b; }
friend Modular operator/(Modular a, Modular const b) { return a /= b; }
friend std::ostream& operator<<(std::ostream& os, Modular const& a) {
    return os << a.value;
}
friend bool operator==(Modular const& a, Modular const& b) {
    return a.value == b.value;
}
friend bool operator!=(Modular const& a, Modular const& b) {
    return a.value != b.value;
}
};

```

5.12 Is Prime

```

bool isprime(ll n) { // 0(sqrt(n))
    if (n < 2) return false;
    if (n == 2) return true;
    if (n % 2 == 0) return false;
    for (ll i = 3; i * i < n; i += 2)
        if (n % i == 0) return false;
    return true;
}

```

5.13 Lcm Using Factorization

```

map<ll, ll> factorization(ll n) {
    map<ll, ll> ans;
    for (ll i = 2; i * i <= n; i++) {
        ll count = 0;
        for (; n % i == 0; count++, n /= i)
            ;
        if (count) ans[i] = count;
    }
    if (n > 1) ans[n]++;
    return ans;
}

ll lcm_with_factorization(ll a, ll b) {
    map<ll, ll> fa = factorization(a);

```

```

map<ll, ll> fb = factorization(b);
ll ans = 1;
for (auto fai : fa) {
    ll k = max(fai.second, fb[fai.first]);
    while (k--) ans *= fai.first;
}
return ans;
}

```

5.14 Lcm

```

ll gcd(ll a, ll b) { return b ? gcd(b, a % b) : a; }
ll lcm(ll a, ll b) { return a / gcd(a, b) * b; }

```

5.15 Modular Inverse Using Phi

```

map<ll, ll> factorization(ll n) {
    map<ll, ll> ans;
    for (ll i = 2; i * i <= n; i++) {
        ll count = 0;
        for (; n % i == 0; count++, n /= i)
            ;
        if (count) ans[i] = count;
    }
    if (n > 1) ans[n]++;
    return ans;
}

```

```

ll phi(ll n) {
    if (n == 1) return 1;

    auto fs = factorization(n);
    auto res = n;

    for (auto [p, k] : fs) {
        res /= p;
        res *= (p - 1);
    }

    return res;
}

```

```

ll fexp(ll a, ll n, ll mod) {
    if (n == 0) return 1;
    if (n == 1) return a;
    ll x = fexp(a, n / 2, mod);
    return x * x * (n & 1 ? a : 1) % mod;
}

```

```

ll inv(ll a, ll mod) { return fexp(a, phi(mod) - 1, mod); }

```

5.16 N Choose K Count

```

/*
 * O(nm) time, O(m) space
 * equal to n choose k
 * */

```

```

ll binom(ll n, ll k) {
    if (k > n) return 0;
    vll dp(k + 1, 0);
    dp[0] = 1;
    for (ll i = 1; i <= n; i++)
        for (ll j = k; j > 0; j--) dp[j] = dp[j] + dp[j - 1];
    return dp[k];
}

```

5.17 Permutation Count

```

const ll MAX = 18;
vll fv(MAX, -1);
ll factorial(ll n) {
    if (fv[n] != -1) return fv[n];
    if (n == 0) return 1;
    return n * factorial(n - 1);
}

```

```

template <typename T>
ll permutation_count(vector<T> xs) {
    map<T, ll> h;
    for (auto xi : xs) h[xi]++;
    ll ans = factorial((ll)xs.size());
    dbg(ans);
    for (auto [v, cnt] : h) {
        dbg(cnt);
        ans /= cnt;
    }

    return ans;
}

```

5.18 Polynomial

```

using polynomial = vector<ll>;
int degree(const polynomial &xs) { return xs.size() - 1; }
ll horner_evaluate(const polynomial &xs, ll x) {
    ll ans = 0;
    ll n = degree(xs);
    for (int i = n; i >= 0; --i) {
        ans *= x;
        ans += xs[i];
    }
    return ans;
}
polynomial operator+(const polynomial &a, const polynomial &b) {
    int n = degree(a);
    int m = degree(b);
    polynomial r(max(n, m) + 1, 0);

    for (int i = 0; i <= n; ++i) r[i] += a[i];
    for (int j = 0; j <= m; ++j) r[j] += b[j];
    while (!r.empty() and r.back() == 0) r.pop_back();
    if (r.empty()) r.push_back(0);
    return r;
}
polynomial operator*(const polynomial &p, const polynomial &q) {

```



```

int n = degree(p);
int m = degree(q);
polynomial r(n + m + 1, 0);
for (int i = 0; i <= n; ++i)
    for (int j = 0; j <= m; ++j) r[i + j] += (p[i] * q[j]);
return r;
}

```

5.19 Power Sum

```

// calculates  $K^0 + K^1 + \dots + K^n$ 
ll fastpow(ll a, int n) {
    if (n == 1) return a;
    ll x = fastpow(a, n / 2);
    return x * x * (n & 1 ? a : 1);
}
ll powersum(ll n, ll k) { return (fastpow(n, k + 1) - 1) / (n - 1); }

```

5.20 Sieve List Primes

```

// list every prime until MAXN
const ll MAXN = 1e5;
vll list_primes(ll n) { // Nlog * log N
    vll ps;
    bitset<MAXN> sieve;
    sieve.set();
    sieve.reset(1);
    for (ll i = 2; i <= n; ++i) {
        if (sieve[i]) ps.push_back(i);
        for (ll j = i * 2; j <= n; j += i) {
            sieve.reset(j);
        }
    }
    return ps;
}

```

6 Searching

6.1 Ternary Search Recursive

```

const double eps = 1e-6;

// IT MUST BE AN UNIMODAL FUNCTION
double f(int x) { return x * x + 2 * x + 4; }

double ternary_search(double l, double r) {
    if (fabs(f(l) - f(r)) < eps) return f((l + (r - l) / 2.0));

    auto third = (r - l) / 3.0;
    auto m1 = l + third;
    auto m2 = r - third;

    // change the signal to find the maximum point.
    return m1 < m2 ? ternary_search(m1, r) : ternary_search(l, m2);
}

```

7 Strings

7.1 Rabin Karp

```

vi rabin_karp(string const &s, string const &t) {
    ll p = 31;
    ll m = 1e9 + 9;
    int S = s.size(), T = t.size();

    vll p_pow(max(S, T));
    p_pow[0] = 1;
    for (int i = 1; i < (int)p_pow.size(); i++) p_pow[i] = (p_pow[i - 1] * p) % m;

    vll h(T + 1, 0);
    for (int i = 0; i < T; i++)
        h[i + 1] = (h[i] + (t[i] - 'a' + 1) * p_pow[i]) % m;
    ll h_s = 0;
    for (int i = 0; i < S; i++) h_s = (h_s + (s[i] - 'a' + 1) * p_pow[i]) % m;

    vi occurrences;
    for (int i = 0; i + S - 1 < T; i++) {
        ll cur_h = (h[i + S] + m - h[i]) % m;
        // IT DON'T CONSIDERE CONLIIONS !
        if (cur_h == h_s * p_pow[i] % m) occurrences.push_back(i);
    }
    return occurrences;
}

```

7.2 String Psum

```

struct strPsum {
    ll n;
    ll k;
    vector<vll> psum;
    strPsum(const string &s) : n(s.size()), k(100), psum(k, vll(n + 1)) {
        for (ll i = 1; i <= n; ++i) {
            for (ll j = 0; j < k; ++j) {
                psum[j][i] = psum[j][i - 1];
            }
            psum[s[i - 1]][i]++;
        }
    }

    ll qtd(ll l, ll r, char c) { // [0,n-1]
        return psum[c][r + 1] - psum[c][l];
    }
}

```

7.3 Trie Naive

```

// time:  $O(n^2)$  memory:  $O(n^2)$ 
using Node = map<char, int>;
using vi = vector<int>;
using Trie = vector<Node>;

```

```

Trie build(const string &s) {

```

```

int n = (int)s.size();
Trie trie(1);
string suffix;

for (int i = n - 1; i >= 0; --i) {
    suffix = s.substr(i) + '#';

    int v = 0; // root
    for (auto c : suffix) {
        if (c == '#') { // makrs the poistion of an occurence
            trie[v][c] = i;
            break;
        }
        if (trie[v][c])
            v = trie[v][c];
        else {
            trie.push_back({});
            trie[v][c] = trie.size() - 1;
            v = trie.size() - 1;
        }
    }
}
return trie;
}

vi search(Trie &trie, string s) {
    int p = 0;
    vi occ;
    for (auto &c : s) {
        p = trie[p][c];
        if (!p) return occ;
    }

    queue<int> q;
    q.push(0);
    while (!q.empty()) {
        auto cur = q.front();
        q.pop();
        for (auto [c, v] : trie[cur]) {
            if (c == '#')
                occ.push_back(v);
            else
                q.push(v);
        }
    }
    return occ;
}

ll distinct_substr(const Trie &trie) {
    ll cnt = 0;
    queue<int> q;
    q.push(0);
    while (!q.empty()) {
        auto u = q.front();
        q.pop();

        for (auto [c, v] : trie[u]) {
            if (c != '#') {

```

```

                cnt++;
                q.push(v);
            }
        }
    }
    return cnt;
}

```

8 Trees

8.1 Binary Lifting

```

/*
 * far[h][i] = the node that 2^h far from node i
 * sometimes is useful invert the order of loops
 * time : O(nlogn)
 * */
const int maxlog = 20;
int far[maxlog + 1][n + 1];
int n;
for (int h = 1; h <= maxlog; h++) {
    for (int i = 1; i <= n; i++) {
        far[h][i] = far[h - 1][far[h - 1][i]];
    }
}

```

8.2 Maximum Distances

```

/*
 * Returns the maximum distance from every node to any other node in the tree.
 * */
ll mostDistantFrom(const vector<vll> &adj, ll n, ll root) {
    // 0 indexed
    ll mostDistantNode = root;
    ll nodeDistance = 0;
    queue<pll> q;
    vector<char> vis(n);
    q.emplace(root, 0);
    vis[root] = true;
    while (!q.empty()) {
        auto [node, dist] = q.front();
        q.pop();
        if (dist > nodeDistance) {
            nodeDistance = dist;
            mostDistantNode = node;
        }
        for (auto u : adj[node]) {
            if (!vis[u]) {
                vis[u] = true;
                q.emplace(u, dist + 1);
            }
        }
    }
    return {mostDistantNode, nodeDistance};
}

ll twoNodesDist(const vector<vll> &adj, ll n, ll a, ll b) {

```

```

queue<pll> q;
vector<char> vis(n);
q.emplace(a, 0);
while (!q.empty()) {
    auto [node, dist] = q.front();
    q.pop();
    if (node == b) return dist;
    for (auto u : adj[node]) {
        if (!vis[u]) {
            vis[u] = true;
            q.emplace(u, dist + 1);
        }
    }
}
return -1;
}

tuple<ll, ll, ll> tree_diameter(const vector<vll> &adj, ll n) {
    // returns two points of the diameter and the diameter itself
    auto [node1, dist1] = mostDistantFrom(adj, n, 0);
    auto [node2, dist2] = mostDistantFrom(adj, n, node1);
    auto diameter = twoNodesDist(adj, n, node1, node2);
    return make_tuple(node1, node2, diameter);
}

vll everyDistanceFromNode(const vector<vll> &adj, ll n, ll root) {
    // Single Source Shortest Path, from a given root
    queue<pair<ll, ll>> q;
    vll ans(n, -1);
    ans[root] = 0;
    q.emplace(root, 0);
    while (!q.empty()) {
        auto [u, d] = q.front();
        q.pop();

        for (auto w : adj[u]) {
            if (ans[w] != -1) continue;
            ans[w] = d + 1;
            q.emplace(w, d + 1);
        }
    }
    return ans;
}

vll maxDistances(const vector<vll> &adj, ll n) {
    auto [node1, node2, diameter] = tree_diameter(adj, n);
    auto distances1 = everyDistanceFromNode(adj, n, node1);
    auto distances2 = everyDistanceFromNode(adj, n, node2);
    vll ans(n);
    for (int i = 0; i < n; ++i) ans[i] = max(distances1[i], distances2[i]);
    return ans;
}

```

8.3 Tree Diameter

```

pll mostDistantFrom(const vector<vll> &adj, ll n, ll root) {
    // 0 indexed
    ll mostDistantNode = root;

```

```

    ll nodeDistance = 0;
    queue<pll> q;
    vector<char> vis(n);
    q.emplace(root, 0);
    vis[root] = true;
    while (!q.empty()) {
        auto [node, dist] = q.front();
        q.pop();
        if (dist > nodeDistance) {
            nodeDistance = dist;
            mostDistantNode = node;
        }
        for (auto u : adj[node]) {
            if (!vis[u]) {
                vis[u] = true;
                q.emplace(u, dist + 1);
            }
        }
    }
    return {mostDistantNode, nodeDistance};
}

ll twoNodesDist(const vector<vll> &adj, ll n, ll a, ll b) {
    // 0 indexed
    queue<pll> q;
    vector<char> vis(n);
    q.emplace(a, 0);
    while (!q.empty()) {
        auto [node, dist] = q.front();
        q.pop();
        if (node == b) {
            return dist;
        }
        for (auto u : adj[node]) {
            if (!vis[u]) {
                vis[u] = true;
                q.emplace(u, dist + 1);
            }
        }
    }
    return -1;
}

ll tree_diameter(const vector<vll> &adj, ll n) {
    // 0 indexed !!!
    auto [node1, dist1] = mostDistantFrom(adj, n, 0);
    auto [node2, dist2] = mostDistantFrom(adj, n, node1);
    auto diameter = twoNodesDist(adj, n, node1, node2);
    return diameter;
}

```

9 Settings and macros

9.1 .vimrc

```

set ts=4 sw=4 sta nu rnu sc cindent
set bg=dark ruler clipboard=unnamed,unnamedplus, timeoutlen=100
colorscheme default

```

```
nnoremap <C-j> :botright belowright term bash <CR>
syntax on
```

9.2 degug.cpp

```
#include <bits/stdc++.h>
using namespace std;
/***** Debug Code *****/
template <typename T>
concept Printable = requires(T t) {
    { std::cout << t } -> std::same_as<std::ostream &>;
};
template <Printable T>
void __print(const T &x) {
    cerr << x;
}
template <size_t T>
void __print(const bitset<T> &x) {
    cerr << x;
}
template <typename A, typename B>
void __print(const pair<A, B> &p);
template <typename... A>
void __print(const tuple<A...> &t);
template <typename T>
void __print(stack<T> s);
template <typename T>
void __print(queue<T> q);
template <typename T, typename... U>
void __print(priority_queue<T, U...> q);
template <typename A>
void __print(const A &x) {
    bool first = true;
    cerr << '{';
    for (const auto &i : x) {
        cerr << (first ? "" : ","), __print(i);
        first = false;
    }
    cerr << '}';
}
template <typename A, typename B>
void __print(const pair<A, B> &p) {
    cerr << '(';
    __print(p.first);
    cerr << ',';
    __print(p.second);
    cerr << ')';
}
template <typename... A>
void __print(const tuple<A...> &t) {
    bool first = true;
    cerr << '(';
    apply(
        [&first](const auto &...args) {
            ((cerr << (first ? "" : ","), __print(args), first = false), ...);
        },
        t);
    cerr << ')';
}
```

```

}
template <typename T>
void __print(stack<T> s) {
    vector<T> debugVector;
    while (!s.empty()) {
        T t = s.top();
        debugVector.push_back(t);
        s.pop();
    }
    reverse(debugVector.begin(), debugVector.end());
    __print(debugVector);
}
template <typename T>
void __print(queue<T> q) {
    vector<T> debugVector;
    while (!q.empty()) {
        T t = q.front();
        debugVector.push_back(t);
        q.pop();
    }
    __print(debugVector);
}
template <typename T, typename... U>
void __print(priority_queue<T, U...> q) {
    vector<T> debugVector;
    while (!q.empty()) {
        T t = q.top();
        debugVector.push_back(t);
        q.pop();
    }
    __print(debugVector);
}
void _print() { cerr << "]\n"; }
template <typename Head, typename... Tail>
void _print(const Head &H, const Tail &...T) {
    __print(H);
    if (sizeof...(T)) cerr << ", ";
    _print(T...);
}

#define dbg(x...) \
    cerr << "[" << #x << "]" = ["; \
    _print(x)
```

9.3 .bashrc

```
cpp() {
    echo ">> COMPILING <<" 1>&2
    g++ -std=c++17 \
        -O2 \
        -g \
        -g3 \
        -Wextra \
        -Wshadow \
        -Wformat=2 \
        -Wconversion \
        -fsanitize=address,undefined \
        -fno-sanitize-recover \
```

```

-Wfatal-errors \
-DDEBUG $1 \

if [ $? -ne 0 ]; then
    echo ">> FAILED <<" 1>&2
    return 1
fi
echo ">> DONE <<" 1>&2
time ./a.out ${@:2}
}

prepare() {
    for i in {a..z}
    do
        cp macro.cpp $i.cpp
        touch $i.py
    done

    for i in {1..10}
    do
        touch in${i}
        touch out${i}
        touch ans${i}
    done
}

```

9.4 macro.cpp

```

#include <bits/stdc++.h>
using namespace std;
#ifdef DEBUG
#include "debug.cpp"
#else
#define dbg(...) 666
#endif

```

```

#define endl '\n'
#define fastio \
    ios_base::sync_with_stdio(false); \
    cin.tie(0); \
    cout.tie(0);
#define len(__x) (ll) __x.size()
using ll = long long;
using vll = vector<ll>;
using pll = pair<ll, ll>;
using vll2d = vector<vll>;
using vi = vector<int>;
using vi2d = vector<vi>;
using pii = pair<int, int>;
using vii = vector<pii>;
using vc = vector<char>;
#define all(a) a.begin(), a.end()
#define snd second
#define fst first
#define pb(__x) push_back(__x)
#define mp(__a, __b) make_pair(__a, __b)
#define eb(__x) emplace_back(__x)

const ll INF = 1e18;

void run() {

}

int32_t main(void) {
    fastio;
    int t;
    t = 1;
    // cin >> t;
    while (t--) run();
}

```