

Contents

1 Data structures	2		
1.1 Bitree 2D	2		
1.2 Bitree	2		
1.3 Convex Hull Trick / Line Container	2		
1.4 Disjoint Sparse Table	3		
1.5 Dsu	3		
1.6 Lichao Tree (dynamic)	4		
1.7 Merge Sort Tree	5		
1.8 Ordered Set	5		
1.9 Prefix Sum 2D	5		
1.10 Sparse Table	6		
2 Dynamic programming	6		
2.1 Binary Knapsack (bottom up)	6		
2.2 Binary Knapsack (top down)	7		
2.3 Edit Distance	7		
2.4 Kadane	7		
2.5 Knapsack with quantity (no recover)	7		
2.6 Longest Increasing Subsequence (LIS)	8		
2.7 Money Sum (Bottom Up)	8		
2.8 Travelling Salesman Problem	9		
3 Extras	9		
3.1 Binary To Gray	9		
3.2 Closest value greater than	9		
3.3 Get Permutation Cycles	10		
3.4 Hanoi Tower	10		
3.5 Meet in the middle	10		
3.6 Mo's Algorithm	11		
3.7 Ternary Search Recursive	11		
3.8 To Any Base	12		
4 Geometry	12		
4.1 Check Point Inside Triangle	12		
4.2 Convex Hull	12		
4.3 Determinant	13		
4.4 Equals	13		
4.5 Line	13		
4.6 Point Struct And Utils (2d)	13		
4.7 Polygon Lattice Points (Pick's Theorem)	14		
4.8 Segment Intersection	14		
4.9 Segment	15		
4.10 Template Line	15		
		4.11 Template Point	16
		4.12 Template Segment	16
5 Graphs	17		
5.1 2 SAT	17		
5.2 Cycle Distances	18		
5.3 SCC (struct)	18		
5.4 Bellman-Ford (find negative cycle)	18		
5.5 Bellman Ford	19		
5.6 BFS 01	19		
5.7 Biconnected Components	20		
5.8 Binary Lifting/Jumping	20		
5.9 Block Cut Tree	20		
5.10 Check Bipartitie	21		
5.11 Dijkstra (k Shortest Paths)	21		
5.12 Dijkstra	22		
5.13 Disjoint Edges Path (Maxflow)	22		
5.14 Euler Path (directed)	23		
5.15 Euler Path (undirected)	24		
5.16 Extra Edges to Make Digraph Fully Strongly Connected	25		
5.17 Find Articulation/Cut Points	26		
5.18 Find Bridge Tree Components	26		
5.19 Find Bridges (online)	27		
5.20 Find Bridges	28		
5.21 Find Centroid	28		
5.22 Floyd Warshall	29		
5.23 Functional/Successor Graph	29		
5.24 Graph Cycle (directed)	29		
5.25 Graph Cycle (undirected)	30		
5.26 Heavy Light Decomposition	30		
5.27 Kruskal	31		
5.28 Lowest Common Ancestor (Binary Lifting)	32		
5.29 Lowest Common Ancestor	33		
5.30 Prim (MST)	34		
5.31 Shortest Path With K-edges	34		
5.32 Small to Large	34		
5.33 Successor Graph-(struct)	35		
5.34 Sum every node distance	37		
5.35 Topological Sorting (Kahn)	37		
5.36 Topological Sorting (Tarjan)	37		
5.37 Tree Diameter (DP)	38		
5.38 Tree Isomorphism (not rooted)	38		
5.39 Tree Isomorphism (rooted)	39		
5.40 Tree Maximum Distance	39		

6	Math	40	7	Primitives	53
6.1	GCD	40	7.1	Bigint	53
6.2	LCM	40	7.2	Integer Mod	57
6.3	Arithmetic Progression Sum	40	7.3	Matrix	58
6.4	Binomial MOD	40			
6.5	Binomial	40	8	Strings	60
6.6	Chinese Remainder Theorem	41	8.1	Count Distinct Anagrams	60
6.7	Derangement / Matching Problem	41	8.2	Double Hash Range Query	61
6.8	Euler phi $\varphi(n)$ (in range)	42	8.3	Hash Interl mod $2^{64} - 1$	61
6.9	Euler phi $\varphi(n)$	42	8.4	Hash Range Query	62
6.10	Factorial Factorization	42	8.5	Hash Ull	62
6.11	Factorization (Pollard Rho)	42	8.6	K-th digit in digit string	63
6.12	Factorization	43	8.7	Longest Palindrome Substring (Manacher)	63
6.13	Fast pow	43	8.8	Longest Palindrome	63
6.14	FFT Convolution	43	8.9	Rabin Karp	64
6.15	Find Multiplicative Inverse	44	8.10	Suffix Automaton (complete)	64
6.16	Linear Diophantine Equation: Find any solution	44	8.11	Trie	66
6.17	Gauss Elimination	45	8.12	Z-function get occurence positions	67
6.18	Integer Partition	46			
6.19	Integer Mod	46	9	Settings and macros	67
6.20	Linear Recurrence	47	9.1	short-macro.cpp	67
6.21	N Choose K (elements)	48	9.2	.bashrc	67
6.22	Matrix Exponentiation	48	9.3	gen.cpp	68
6.23	NTT integer convolution and exponentiation	48	9.4	macro.cpp	69
6.24	NTT Integer Convolution (combine 2 modules)	50	9.5	.vimrc	70
6.25	Power Sum	52	9.6	debug.cpp	70
6.26	Sieve list primes	52			

1 Data structures

1.1 Bitree 2D

Given a 2d array allow you to sum val to the position (x, y) and find the sum of the rectangle with left top corner $(x1, y1)$ and right bottom corner $(x2, y2)$

Update and query 1 indexed!

Time: update $O(\log n^2)$, query $O(\log n^2)$

```
struct Bit2d {
    int n;
    vll2d bit;
    Bit2d(int ni) : n(ni), bit(n + 1, vll(n + 1)) {}
    Bit2d(int ni, vll2d &xs) : n(ni), bit(n + 1, vll(n + 1)) {
        for (int i = 1; i <= n; i++) {
            for (int j = 1; j <= n; j++) {
                update(i, j, xs[i][j]);
            }
        }
    }
    void update(int x, int y, ll val) {
        for (; x <= n; x += (x & (-x))) {
            for (int i = y; i <= n; i += (i & (-i))) {
                bit[x][i] += val;
            }
        }
    }
    ll sum(int x, int y) {
        ll ans = 0;

        for (int i = x; i; i -= (i & (-i))) {
            for (int j = y; j; j -= (j & (-j))) {
                ans += bit[i][j];
            }
        }
        return ans;
    }
    ll query(int x1, int y1, int x2, int y2) {
        return sum(x2, y2) - sum(x2, y1 - 1) - sum(x1 - 1, y2) +
            sum(x1 - 1, y1 - 1);
    }
};
```

1.2 Bitree

```
template <typename T>
```

```
struct BITree {
    int N;
    vector<T> v;

    BITree(int n) : N(n), v(n + 1, 0) {}

    void update(int i, const T& x) {
        if (i == 0) return;
        for (; i <= N; i += i & -i) v[i] += x;
    }

    T range_sum(int i, int j) {
        return range_sum(j) - range_sum(i - 1);
    }

    T range_sum(int i) {
        T sum = 0;
        for (; i > 0; i -= i & -i) sum += v[i];
        return sum;
    }
};
```

1.3 Convex Hull Trick / Line Container

Container where you can add lines of the form $mx + b$, and query maximum value at point x .

$insert_line(m, b)$ inserts the line $m \cdot x + b$ in the container.

$eval(x)$ find the highest value among all lines in the point x .

both in $O(\log N)$

```
const ll LLINF = 1e18;
const ll is_query = -LLINF;
struct Line {
    ll m, b;
    mutable function<const Line*> succ;
    bool operator<(const Line& rhs) const {
        if (rhs.b != is_query) return m < rhs.m;
        const Line* s = succ();
        if (!s) return 0;
        ll x = rhs.m;
        return b - s->b < (s->m - m) * x;
    }
};

struct Cht : public multiset<Line> { // maintain max m*x+b
    bool bad(iterator y) {
        auto z = next(y);
        if (y == begin()) {
            if (z == end()) return 0;

```

```

    return y->m == z->m && y->b <= z->b;
}
auto x = prev(y);
if (z == end()) return y->m == x->m && y->b <= x->b;
return (ld)(x->b - y->b) * (z->m - y->m) >=
        (ld)(y->b - z->b) * (y->m - x->m);
}
void insert_line(
    ll m, ll b) { // min -> insert (-m, -b) -> -eval()
    auto y = insert({m, b});
    y->succ = [=] {
        return next(y) == end() ? 0 : &*next(y);
    };
    if (bad(y)) {
        erase(y);
        return;
    }
    while (next(y) != end() && bad(next(y))) erase(next(y));
    while (y != begin() && bad(prev(y))) erase(prev(y));
}
ll eval(ll x) {
    auto l = *lower_bound((Line){x, is_query});
    return l.m * x + l.b;
}
};

```

1.4 Disjoint Sparse Table

Answers queries of any monoid operation (i.e. has identity element and is associative)
 Build: $O(N \log N)$, Query: $O(1)$

```

#define F(expr) [](auto a, auto b) { return expr; }
template <typename T>
struct DisjointSparseTable {
    using Operation = T (*)(T, T);

    vector<vector<T>> st;
    Operation f;
    T identity;

    static constexpr int log2_floor(
        unsigned long long i) noexcept {
        return i ? __builtin_clzll(1) - __builtin_clzll(i) : -1;
    }

    // Lazy loading constructor. Needs to call build!

```

```

DisjointSparseTable(Operation op, const T neutral = T())
    : st(), f(op), identity(neutral) {}

DisjointSparseTable(vector<T> v)
    : DisjointSparseTable(v, F(min(a, b))) {}

DisjointSparseTable(vector<T> v, Operation op,
                    const T neutral = T())
    : st(), f(op), identity(neutral) {
    build(v);
}

void build(vector<T> v) {
    st.resize(log2_floor(v.size()) + 1,
              vector<T>(1ll << (log2_floor(v.size()) + 1)));
    v.resize(st[0].size(), identity);
    for (int level = 0; level < (int)st.size(); ++level) {
        for (int block = 0; block < (1 << level); ++block) {
            const auto l = block << (st.size() - level);
            const auto r = (block + 1) << (st.size() - level);
            const auto m = l + (r - l) / 2;

            st[level][m] = v[m];
            for (int i = m + 1; i < r; i++)
                st[level][i] = f(st[level][i - 1], v[i]);
            st[level][m - 1] = v[m - 1];
            for (int i = m - 2; i >= l; i--)
                st[level][i] = f(st[level][i + 1], v[i]);
        }
    }
}

T query(int l, int r) const {
    if (l > r) return identity;
    if (l == r) return st.back()[l];

    const auto k = log2_floor(l ^ r);
    const auto level = (int)st.size() - 1 - k;
    return f(st[level][l], st[level][r]);
}
};

```

1.5 Dsu

```

struct DSU {

```

```

vi ps, sz;

// vector<unordered_set<int>> sts;

DSU(int N) : ps(N + 1), sz(N, 1) /*, sts(N) */ {
    iota(all(ps), 0);
    // for (int i = 0; i < N; i++) sts[i].insert(i);
}
int find_set(int x) {
    return ps[x] == x ? x : ps[x] = find_set(ps[x]);
}
int size(int u) { return sz[find_set(u)]; }
bool same_set(int x, int y) {
    return find_set(x) == find_set(y);
}
void union_set(int x, int y) {
    if (same_set(x, y)) return;

    int px = find_set(x);
    int py = find_set(y);

    if (sz[px] < sz[py]) swap(px, py);

    ps[py] = px;
    sz[px] += sz[py];
    // sts[px].merge(sts[py]);
}
};

```

1.6 Lichao Tree (dynamic)

Lichao Tree that creates the nodes dynamically, allowing to query and update from range $[MAXL, MAXR]$

query(x) : find the highest point among all lines in the structure

add(a, b) : add a line of form $y = ax + b$ in the structure

addSegment(a, b, l, r) : add a line segment of form $y = ax + b$ which covers from range $[l, r]$

time: $O(\log N)$

```

template <typename T = ll, T MAXL = 0,
          T MAXR = 1'000'000'001>
struct LiChaoTree {
    static const T inf = -numeric_limits<T>::max() / 2;
    bool first_best(T a, T b) { return a > b; }
    T get_best(T a, T b) { return first_best(a, b) ? a : b; }
    struct line {
        T m, b;
        T operator()(T x) { return m * x + b; }
    };
};

```

```

struct node {
    line li;
    node *left, *right;
    node(line _li = {0, inf})
        : li(_li), left(nullptr), right(nullptr) {}
    ~node() {
        delete left;
        delete right;
    }
};

node *root;
LiChaoTree(line li = {0, inf}) : root(new node(li)) {}
~LiChaoTree() { delete root; }

T query(T x, node *cur, T l, T r) {
    if (cur == nullptr) return inf;
    if (x < l or x > r) return inf;
    T mid = midpoint(l, r);
    T ans = cur->li(x);
    ans = get_best(ans, query(x, cur->left, l, mid));
    ans = get_best(ans, query(x, cur->right, mid + 1, r));
    return ans;
}

T query(T x) { return query(x, root, MAXL, MAXR); }

void add(line li, node *&cur, T l, T r) {
    if (cur == nullptr) {
        cur = new node(li);
        return;
    }
    T mid = midpoint(l, r);
    if (first_best(li(mid), cur->li(mid)))
        swap(li, cur->li);
    if (first_best(li(l), cur->li(l)))
        add(li, cur->left, l, mid);
    if (first_best(li(r), cur->li(r)))
        add(li, cur->right, mid + 1, r);
}

void add(T m, T b) { add({m, b}, root, MAXL, MAXR); }

void addSegment(line li, node *&cur, T l, T r, T lseg,
                T rseg) {
    if (r < lseg || l > rseg) return;
    if (cur == nullptr) cur = new node;
    if (lseg <= l && r <= rseg) {
        add(li, cur, l, r);
        return;
    }
}

```

```

    T mid = midpoint(l, r);
    if (l != r) {
        addSegment(li, cur->left, l, mid, lseg, rseg);
        addSegment(li, cur->right, mid + 1, r, lseg, rseg);
    }
}

void addSegment(T a, T b, T l, T r) {
    addSegment({a, b}, root, MAXL, MAXR, l, r);
}
};

```

1.7 Merge Sort Tree

Like a segment tree but each node st_i stores a sorted subarray

- $\text{inrange}(l, r, a, b)$: counts the number of elements $x \in [l, r]$ such that $a \leq x \leq b$.

Memory: $O(n \log N)$ Time: build $O(N \log N)$, inrange $O(\log N)$

```

template <class T>
struct MergeSortTree {
    int n;
    vector<vector<T>> st;
    MergeSortTree(vector<T> &xs) : n(len(xs)), st(n << 1) {
        for (int i = 0; i < n; i++)
            st[i + n] = vector<T>({xs[i]});

        for (int i = n - 1; i > 0; i--) {
            st[i].resize(len(st[i << 1]) + len(st[i << 1 | 1]));
            merge(all(st[i << 1]), all(st[i << 1 | 1]),
                st[i].begin());
        }
    }
    int count(int i, T a, T b) {
        return upper_bound(all(st[i]), b) -
            lower_bound(all(st[i]), a);
    }
    int inrange(int l, int r, T a, T b) {
        int ans = 0;

        for (l += n, r += n + 1; l < r; l >>= 1, r >>= 1) {
            if (l & 1) ans += count(l++, a, b);
            if (r & 1) ans += count(--r, a, b);
        }

        return ans;
    }
};

```

1.8 Ordered Set

If you need an ordered **multiset** you may add an id to each value. Using `greater_equal`, or `less_equal` is considered undefined behavior.

- `order_of_key(k)` : Number of items strictly smaller/greater than k .
- `find_by_order(k)` : K -th element in a set (counting from zero).

```

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;

template <typename T>
using ordered_set = tree<T, null_type, less<T>, rb_tree_tag,
    tree_order_statistics_node_update>;

```

1.9 Prefix Sum 2D

Given an 2d array with n lines and m columns, find the sum of the subarray that have the left upper corner at $(x1, y1)$ and right bottom corner at $(x2, y2)$.

Time: build $O(n \cdot m)$, query $O(1)$.

```

struct psum2d {
    vll2d s;
    vll2d psum;
    psum2d(vll2d &grid, int n, int m)
        : s(n + 1, vll(m + 1)), psum(n + 1, vll(m + 1)) {
        for (int i = 1; i <= n; i++)
            for (int j = 1; j <= m; j++)
                s[i][j] = s[i][j - 1] + grid[i][j];

        for (int i = 1; i <= n; i++)
            for (int j = 1; j <= m; j++)
                psum[i][j] = psum[i - 1][j] + s[i][j];
    }

    ll query(int x1, int y1, int x2, int y2) {
        ll ans = psum[x2][y2] + psum[x1 - 1][y1 - 1];
        ans -= psum[x2][y1 - 1] + psum[x1 - 1][y2];
        return ans;
    }
};

```

1.10 Sparse Table

Answer the range query defined at the function `op`.

Build: $O(N \log N)$, Query: $O(1)$

```
template <typename T>
struct SparseTable {
    vector<T> v;
    int n;
    static const int b = 30;
    vi mask, t;

    int op(int x, int y) { return v[x] < v[y] ? x : y; }
    int msb(int x) {
        return __builtin_clz(1) - __builtin_clz(x);
    }
    SparseTable() {}
    SparseTable(const vector<T>& v_)
        : v(v_), n(v.size()), mask(n), t(n) {
        for (int i = 0, at = 0; i < n; mask[i++] = at |= 1) {
            at = (at << 1) & ((1 << b) - 1);
            while (at and op(i, i - msb(at & -at)) == i)
                at ^= at & -at;
        }
        for (int i = 0; i < n / b; i++)
            t[i] = b * i + b - 1 - msb(mask[b * i + b - 1]);
        for (int j = 1; (1 << j) <= n / b; j++)
            for (int i = 0; i + (1 << j) <= n / b; i++)
                t[n / b * j + i] =
                    op(t[n / b * (j - 1) + i],
                       t[n / b * (j - 1) + i + (1 << (j - 1))]);
    }
    int small(int r, int sz = b) {
        return r - msb(mask[r] & ((1 << sz) - 1));
    }
    T query(int l, int r) {
        if (r - l + 1 <= b) return small(r, r - l + 1);
        int ans = op(small(l + b - 1), small(r));
        int x = l / b + 1, y = r / b - 1;
        if (x <= y) {
            int j = msb(y - x + 1);
            ans = op(ans, op(t[n / b * j + x],
                             t[n / b * j + y - (1 << j) + 1]));
        }
        return ans;
    }
};
```

```
};
```

2 Dynamic programming

2.1 Binary Knapsack (bottom up)

Given the points each element have, and it respective cost, computes the maximum points we can get if we can ignore/choose an element, in such way that the sum of costs don't exceed the maximum cost allowed
Time and space: $O(N * W)$

the vectors *VS* and *WS* starts at one, so it need an empty value at index 0.

```
const int MAXN(1'000), MAXCOST(1'000 * 20);
ll dp[MAXN + 1][MAXCOST + 1];
bool ps[MAXN + 1][MAXCOST + 1];
pair<ll, vi> knapsack(const vll &points, const vi &costs,
                    int maxCost) {
    int n = len(points) - 1; // ELEMENTS START AT INDEX 1 !

    for (int m = 0; m <= maxCost; m++) {
        dp[0][m] = 0;
    }

    for (int i = 1; i <= n; i++) {
        dp[i][0] = dp[i - 1][0] + (costs[i] == 0) * points[i];
        ps[i][0] = costs[i] == 0;
    }

    for (int i = 1; i <= n; i++) {
        for (int m = 1; m <= maxCost; m++) {
            dp[i][m] = dp[i - 1][m], ps[i][m] = 0;
            int w = costs[i];
            ll v = points[i];

            if (w <= m and dp[i - 1][m - w] + v > dp[i][m]) {
                dp[i][m] = dp[i - 1][m - w] + v, ps[i][m] = 1;
            }
        }
    }

    vi is;
    for (int i = n, m = maxCost; i >= 1; --i) {
        if (ps[i][m]) {
            is.emplace_back(i);
            m -= costs[i];
        }
    }
}
```

```

    return {dp[n][maxCost], is};
}

```

2.2 Binary Knapsack (top down)

Given N items, each with its own value V_i and weight W_i and a maximum knapsack weight W , compute the maximum value of the items that we can carry, if we can either ignore or take a particular item.

Assume that $1 \leq n \leq 1000$, $1 \leq S \leq 10000$.

Time and space: $O(N * W)$

the bottom up version is 5 times faster !

```

const int MAXN(2000), MAXM(2000);
ll memo[MAXN][MAXM + 1];
char choosen[MAXN][MAXM + 1];
ll knapSack(int u, int w, vll &VS, vi &WS) {
    if (u < 0) return 0;
    if (memo[u][w] != -1) return memo[u][w];

    ll a = 0, b = 0;
    a = knapSack(u - 1, w, VS, WS);
    if (WS[u] <= w)
        b = knapSack(u - 1, w - WS[u], VS, WS) + VS[u];
    if (b > a) {
        choosen[u][w] = true;
    }
    return memo[u][w] = max(a, b);
}

pair<ll, vi> knapSack(int W, vll &VS, vi &WS) {
    memset(memo, -1, sizeof(memo));
    memset(choosen, 0, sizeof(choosen));
    int n = len(VS);
    ll v = knapSack(n - 1, W, VS, WS);
    ll cw = W;
    vi choosed;
    for (int i = n - 1; i >= 0; i--) {
        if (choosen[i][cw]) {
            cw -= WS[i];
            choosed.emplace_back(i);
        }
    }
    return {v, choosed};
}

```

2.3 Edit Distance

$O(N * M)$

```

int edit_distance(const string &a, const string &b) {
    int n = a.size();
    int m = b.size();
    vector<vi> dp(n + 1, vi(m + 1, 0));

    int ADD = 1, DEL = 1, CHG = 1;
    for (int i = 0; i <= n; ++i) {
        dp[i][0] = i * DEL;
    }
    for (int i = 1; i <= m; ++i) {
        dp[0][i] = ADD * i;
    }

    for (int i = 1; i <= n; ++i) {
        for (int j = 1; j <= m; ++j) {
            int add = dp[i][j - 1] + ADD;
            int del = dp[i - 1][j] + DEL;
            int chg = dp[i - 1][j - 1] +
                (a[i - 1] == b[j - 1] ? 0 : 1) * CHG;
            dp[i][j] = min({add, del, chg});
        }
    }

    return dp[n][m];
}

```

2.4 Kadane

Find the maximum subarray sum in a given array.

```

int kadane(const vi &as) {
    vi s(len(as));
    s[0] = as[0];

    for (int i = 1; i < len(as); ++i)
        s[i] = max(as[i], s[i - 1] + as[i]);

    return *max_element(all(s));
}

```

2.5 Knapsack with quantity (no recover)

finds the maximum score you can achieve, given that you have n items, each item has a *cost*, a *point* and a *quantity*, you can spent at most *maxcost* and buy each item the maximum quantity it has.

time: $O(n \cdot maxcost \cdot \log maxqtd)$ memory: $O(maxcost)$.


```

11 knapsack(const vi &weight, const vll &value,
           const vi &qtd, int maxCost) {
    vi costs;
    vll values;
    for (int i = 0; i < len(weight); i++) {
        ll q = qtd[i];
        for (ll x = 1; x <= q; q -= x, x <= 1) {
            costs.eb(x * weight[i]);
            values.eb(x * value[i]);
        }
        if (q) {
            costs.eb(q * weight[i]);
            values.eb(q * value[i]);
        }
    }

    vll dp(maxCost + 1);
    for (int i = 0; i < len(values); i++) {
        for (int j = maxCost; j > 0; j--) {
            if (j >= costs[i])
                dp[j] = max(dp[j], values[i] + dp[j - costs[i]]);
        }
    }
    return dp[maxCost];
}

```

2.6 Longest Increasing Subsequence (LIS)

Find the pair (sz, psx) where sz is the size of the longest subsequence and psx is a vector where psx_i tells the size of the longest increase subsequence that ends at position i . get_idx just tells which indices could be in the longest increasing subsequence.

Time: $O(n \log n)$

```

template <typename T>
pair<int, vector<int>> lis(const vector<T> &xs) {
    int n = xs.size();

    vector<T> dp(n + 1, numeric_limits<T>::max());
    dp[0] = numeric_limits<T>::min();

    int sz = 0;
    vector<int> psx(n);

    for (int i = 0; i < n; i++) {
        auto it = lower_bound(dp.begin(), dp.end(), xs[i]);
        auto pos = (int)(it - dp.begin());

```

```

        sz = max(sz, pos);

        dp[pos] = xs[i];

        psx[i] = pos;
    }

    return {sz, psx};
}

template <typename T>
vector<int> get_idx(vector<T> xs) {
    auto [sz1, psx1] = lis(xs);

    reverse(xs.begin(), xs.end());
    for (auto &xi : xs) xi = -xi;

    auto [sz2, psx2] = lis(xs);

    vector<int> ans;
    int _n = xs.size();
    for (int i = 0; i < _n; i++) {
        int l = psx1[i];
        int r = psx2[_n - i - 1];
        if (l + r - 1 == sz1) ans.push_back(i);
    }

    return ans;
}

```

2.7 Money Sum (Bottom Up)

Find every possible sum using the given values only once.

```

set<int> money_sum(const vi &xs) {
    using vc = vector<char>;
    using vvc = vector<vc>;
    int _m = accumulate(all(xs), 0);
    int _n = xs.size();
    vvc _dp(_n + 1, vc(_m + 1, 0));
    set<int> _ans;
    _dp[0][xs[0]] = 1;
    for (int i = 1; i < _n; ++i) {
        for (int j = 0; j <= _m; ++j) {
            if (j == 0 or _dp[i - 1][j]) {

```

```

        _dp[i][j + xs[i]] = 1;
        _dp[i][j] = 1;
    }
}
}

for (int i = 0; i < _n; ++i)
    for (int j = 0; j <= _m; ++j)
        if (_dp[i][j]) _ans.insert(j);
return _ans;
}

```

2.8 Travelling Salesman Problem

```

using vi = vector<int>;
vector<vi> dist;
vector<vi> memo;
/* O ( N^2 * 2^N )*/
int tsp(int i, int mask, int N) {
    if (mask == (1 << N) - 1) return dist[i][0];
    if (memo[i][mask] != -1) return memo[i][mask];
    int ans = INT_MAX << 1;
    for (int j = 0; j < N; ++j) {
        if (mask & (1 << j)) continue;
        auto t = tsp(j, mask | (1 << j), N) + dist[i][j];
        ans = min(ans, t);
    }
    return memo[i][mask] = ans;
}

```

3 Extras

3.1 Binary To Gray

```

string binToGray(string bin) {
    string gray(bin.size(), '0');
    int n = bin.size() - 1;
    gray[0] = bin[0];
    for (int i = 1; i <= n; i++) {
        gray[i] = '0' + (bin[i - 1] == '1') ^ (bin[i] == '1');
    }
    return gray;
}

```

3.2 Closest value greater than

This structure allows you to answer the closest value to the position i that is greater than xs_i , the answer is given as a pair (l, r) is the position of the closest greater value to the the left and right respectively, both can be -1 if there is no such value. Build it with the size of the vector or the vector itself.

Time: $O(\log N^2)$

```

template <typename T>
struct CVGT {
    struct SegTree {
        int n;
        vector<T> st;
        SegTree(int _n)
            : n(_n), st(n << 1, numeric_limits<T>::min()) {}

        void assign(int p, const T &k) {
            for (st[p += n] = k; p >= 1;)
                st[p] = max(st[p << 1], st[p << 1 | 1]);
        }

        T query(int l, int r) {
            T ans1, ansr;
            ans1 = ansr = numeric_limits<T>::min();
            for (l += n, r += n + 1; l < r; l >= 1, r >= 1) {
                if (l & 1) ans1 = max(ans1, st[l++]);
                if (r & 1) ansr = max(st[--r], ansr);
            }

            return max(ans1, ansr);
        }
    };

    int n;
    SegTree st;

    CVGT(int _n) : n(_n), st(n) {}
    CVGT(const vector<T> &xs) : n(xs.size()), st(n) {
        for (int i = 0; i < n; i++) {
            st.assign(i, xs[i]);
        }
    }

    void assign(int p, const T &x) { st.assign(p, x); }

    pair<int, int> query(int i) {
        int L = -1;

```

```

auto vi = st.query(i, i);
for (int l = 0, r = i - 1; l <= r;) {
    int m = midpoint(l, r);
    T vm = st.query(m, i - 1);
    if (vm >= vi) {
        L = max(L, m);
        l = m + 1;
    } else
        r = m - 1;
}

int R = n * 2;
for (int l = i + 1, r = n - 1; l <= r;) {
    int m = midpoint(l, r);

    T vm = st.query(i + 1, m);
    if (vm >= vi) {
        r = m - 1;
        R = min(R, m);
    } else
        l = m + 1;
}

return {L, R == n * 2 ? -1 : R};
}
};

```

3.3 Get Permutation Cycles

```

/*
 * receives a permutation [0, n-1]
 * returns a vector of cycles
 * for example: [ 1, 0, 3, 4, 2] -> [[0, 1], [2, 3, 4]]
 * */
vector<vll> getPermutationCicles(const vll &ps) {
    ll n = len(ps);
    vector<char> visited(n);
    vector<vll> cycles;
    for (int i = 0; i < n; ++i) {
        if (visited[i]) continue;

        vll cicle;
        ll pos = i;
        while (!visited[pos]) {
            cicle.pb(pos);

```

```

            visited[pos] = true;
            pos = ps[pos];
        }

        cycles.push_back(vll(all(cicle)));
    }
    return cycles;
}

```

3.4 Hanoi Tower

Let T_n be the total of moves to solve a hanoi tower, we know that $T_n \geq 2 \cdot T_{n-1} + 1$, for $n > 0$, and $T_0 = 0$. By induction it's easy to see that $T_n = 2^n - 1$, for $n > 0$.

The following algorithm finds the necessary steps to solve the game for 3 stacks and n disks.

```

void move(int a, int b) { cout << a << ' ' << b << endl; }
void solve(int n, int s, int e) {
    if (n == 0) return;
    if (n == 1) {
        move(s, e);
        return;
    }
    solve(n - 1, s, 6 - s - e);
    move(s, e);
    solve(n - 1, 6 - s - e, e);
}

```

3.5 Meet in the middle

Answers the query how many subsets of the vector xs have sum equal x .

Time: $O(N \cdot 2^{\frac{N}{2}})$

```

vll get_subset_sums(int l, int r, vll &a) {
    int len = r - l + 1;
    vll res;

    for (int i = 0; i < (1 << len); i++) {
        ll sum = 0;
        for (int j = 0; j < len; j++) {
            if (i & (1 << j)) {
                sum += a[l + j];
            }
        }
        res.push_back(sum);
    }
    return res;
};

```

```

11 count(vll &xs, ll x) {
    int n = len(xs);
    vll left = get_subset_sums(0, n / 2 - 1, xs);
    vll right = get_subset_sums(n / 2, n - 1, xs);
    sort(all(left));
    sort(all(right));
    ll ans = 0;
    for (ll i : left) {
        auto start_index =
            lower_bound(right.begin(), right.end(), x - i) -
            right.begin();
        auto end_index =
            upper_bound(right.begin(), right.end(), x - i) -
            right.begin();
        ans += end_index - start_index;
    }
    return ans;
}

```

3.6 Mo's Algorithm

```

template <typename T>
struct Mo {
    struct Query {
        int l, r, idx, block;

        Query(int _l, int _r, int _idx, int _block)
            : l(_l), r(_r), idx(_idx), block(_block) {}

        bool operator<(const Query &q) const {
            if (block != q.block) return block < q.block;
            return (block & 1 ? (r < q.r) : (r > q.r));
        }
    };

    vector<T> vs;
    vector<Query> qs;
    const int block_size;

    Mo(const vector<T> &a)
        : vs(a), block_size((int)ceil(sqrt(a.size()))) {}

    void add_query(int l, int r) {
        qs.emplace_back(l, r, qs.size(), l / block_size);
    }
}

```

```

auto solve() {
    // get answer return type
    vector<ll> answers(qs.size());
    sort(all(qs));

    int cur_l = 0, cur_r = -1;
    for (auto q : qs) {
        while (cur_l > q.l) add(--cur_l);
        while (cur_r < q.r) add(++cur_r);
        while (cur_l < q.l) remove(cur_l++);
        while (cur_r > q.r) remove(cur_r--);
        answers[q.idx] = get_answer();
    }

    return answers;
}

private:
    // add value at idx from data structure
    inline void add(int idx) {}

    // remove value at idx from data structure
    inline void remove(int idx) {}

    // extract current answer of the data structure
    inline auto get_answer() {}
};

```

3.7 Ternary Search Recursive

```

const double eps = 1e-6;

// IT MUST BE AN UNIMODAL FUNCTION
double f(int x) { return x * x + 2 * x + 4; }

double ternary_search(double l, double r) {
    if (fabs(f(l) - f(r)) < eps)
        return f((l + (r - l) / 2.0));

    auto third = (r - l) / 3.0;
    auto m1 = l + third;
    auto m2 = r - third;

    // change the signal to find the maximum point.

```

```

    return m1 < m2 ? ternary_search(m1, r)
        : ternary_search(l, m2);
}

```

3.8 To Any Base

```

vll to_otherbase(ll x, ll b) {
    vll result;

    while (x) {
        auto [quot, rem] = std::div(x, b);

        x = rem < 0 ? quot + 1 : quot;
        rem = rem < 0 ? rem + -b : rem;

        result.eb(rem);
    }

    if (!len(result)) return {0ll};

    reverse(all(result));

    // [msb, ..., lsb]
    return result;
}

```

4 Geometry

4.1 Check Point Inside Triangle

Guess what ? it checks if the point e is inside the triangle formed by the points $t1, t2, t3$.

```

struct point {
    int x, y;
    int id;

    point operator-(const point &o) const {
        return {x - o.x, y - o.y};
    }
    int operator^(const point &o) const {
        return x * o.y - y * o.x;
    }
};

/*
    Verify the direction that the point
    _e_ is in relation to the vector

```

```

    formed by the points a->b
    -1 = right
    0 = collinear
    1 = left
*/
int ccw(point a, point b, point e) {
    int tmp = (b - a) ^ (e - a);
    return (tmp > 0) - (tmp < 0);
}

/*
    Verify if the point e
    is inside the triangle formed by
    the points t1, t2, t3
*/
bool inside_triangle(point t1, point t2, point t3,
    point e) {
    int x = ccw(t1, t2, e);
    int y = ccw(t2, t3, e);
    int z = ccw(t3, t1, e);
    return !((x == 1 or y == 1 or z == 1) and
        (x == -1 or y == -1 or z == -1));
}

```

4.2 Convex Hull

Given a set of points find the smallest convex polygon that contains all the given points.

Time: $O(N \log N)$

By default it removes the collinear points, set the boolean to true if you don't want that

```

struct pt {
    double x, y;
    int id;
};

int orientation(pt a, pt b, pt c) {
    double v = a.x * (b.y - c.y) + b.x * (c.y - a.y) +
        c.x * (a.y - b.y);
    if (v < 0) return -1; // clockwise
    if (v > 0) return +1; // counter-clockwise
    return 0;
}

bool cw(pt a, pt b, pt c, bool include_collinear) {
    int o = orientation(a, b, c);
    return o < 0 || (include_collinear && o == 0);
}

```

```

}
bool collinear(pt a, pt b, pt c) {
    return orientation(a, b, c) == 0;
}

void convex_hull(vector<pt>& pts,
                bool include_collinear = false) {
    pt p0 = *min_element(all(pts), [](pt a, pt b) {
        return make_pair(a.y, a.x) < make_pair(b.y, b.x);
    });
    sort(all(pts), [&p0](const pt& a, const pt& b) {
        int o = orientation(p0, a, b);
        if (o == 0)
            return (p0.x - a.x) * (p0.x - a.x) +
                   (p0.y - a.y) * (p0.y - a.y) <
                   (p0.x - b.x) * (p0.x - b.x) +
                   (p0.y - b.y) * (p0.y - b.y);
        return o < 0;
    });
    if (include_collinear) {
        int i = len(pts) - 1;
        while (i >= 0 && collinear(p0, pts[i], pts.back())) i--;
        reverse(pts.begin() + i + 1, pts.end());
    }

    vector<pt> st;
    for (int i = 0; i < len(pts); i++) {
        while (st.size() > 1 && !cw(st[len(st) - 2], st.back(),
                                   pts[i], include_collinear))
            st.pop_back();
        st.push_back(pts[i]);
    }

    pts = st;
}

```

4.3 Determinant

```

#include "Point.cpp"

template <typename T>
T D(const Point<T> &P, const Point<T> &Q,
    const Point<T> &R) {
    return (P.x * Q.y + P.y * R.x + Q.x * R.y) -
           (R.x * Q.y + R.y * P.x + Q.x * P.y);
}

```

```

}

```

4.4 Equals

```

template <typename T>
bool equals(T a, T b) {
    const double EPS{1e-9};
    if (is_floating_point<T>::value)
        return fabs(a - b) < EPS;
    else
        return a == b;
}

```

4.5 Line

```

#include <bits/stdc++.h>

#include "point-struct-and-utils.cpp"
using namespace std;

struct line {
    ld a, b, c;
};

// the answer is stored in the third parameter (pass by
// reference)
void pointsToLine(const point &p1, const point &p2,
                  line &l) {
    if (fabs(p1.x - p2.x) < EPS)
        // vertical line
        l = {1.0, 0.0, -p1.x};
    // default values
    else
        l = {-(ld)(p1.y - p2.y) / (p1.x - p2.x), 1.0,
            -(ld)(l.a * p1.x) - p1.y};
}

```

4.6 Point Struct And Utils (2d)

```

#include <bits/stdc++.h>
using namespace std;
using ld = long double;

struct point {
    ld x, y;
    int id;
}

```

```

point(ld x = 0.0, ld y = 0.0, int id = -1)
: x(x), y(y), id(id) {}

point& operator+=(const point& t) {
    x += t.x;
    y += t.y;
    return *this;
}

point& operator-=(const point& t) {
    x -= t.x;
    y -= t.y;
    return *this;
}

point& operator*=(ld t) {
    x *= t;
    y *= t;
    return *this;
}

point& operator/=(ld t) {
    x /= t;
    y /= t;
    return *this;
}

point operator+(const point& t) const {
    return point(*this) += t;
}

point operator-(const point& t) const {
    return point(*this) -= t;
}

point operator*(ld t) const { return point(*this) *= t; }
point operator/(ld t) const { return point(*this) /= t; }
};

ld dot(point& a, point& b) { return a.x * b.x + a.y * b.y; }

ld norm(point& a) { return dot(a, a); }

ld abs(point a) { return sqrt(norm(a)); }

ld proj(point a, point b) { return dot(a, b) / abs(b); }

ld angle(point a, point b) {
    return acos(dot(a, b) / abs(a) / abs(b));
}

```

```
ld cross(point a, point b) { return a.x * b.y - a.y * b.x; }
```

4.7 Polygon Lattice Points (Pick's Theorem)

Given a polygon with N points finds the number of lattice points inside and on boundaries. Time : $O(N)$

```

ll cross(ll x1, ll y1, ll x2, ll y2) {
    return x1 * y2 - x2 * y1;
}

ll polygonArea(vector<pll>& pts) {
    ll ats = 0;
    for (int i = 2; i < len(pts); i++)
        ats += cross(pts[i].first - pts[0].first,
                     pts[i].second - pts[0].second,
                     pts[i - 1].first - pts[0].first,
                     pts[i - 1].second - pts[0].second);
    return abs(ats / 2ll);
}

ll boundary(vector<pll>& pts) {
    ll ats = pts.size();
    for (int i = 0; i < len(pts); i++) {
        ll deltax =
            (pts[i].first - pts[(i + 1) % pts.size()].first);
        ll deltay =
            (pts[i].second - pts[(i + 1) % pts.size()].second);
        ats += abs(__gcd(deltax, deltay)) - 1;
    }
    return ats;
}

pll latticePoints(vector<pll>& pts) {
    ll bounds = boundary(pts);
    ll area = polygonArea(pts);
    ll inside = area + 1ll - bounds / 2ll;

    return {inside, bounds};
}

```

4.8 Segment Intersection

```

using ld = long double;

template <typename T = ld>

```

```

struct Point {
    T x, y;
    bool is_port;
};

template <typename T = ld>
bool operator==(const Point<T> &a, const Point<T> &b) {
    return a.x == b.x and a.y == b.y;
}

template <typename T = ld>
struct Segment {
    Point<T> p1, p2;
};

template <typename T>
int orientation(Point<T> p, Point<T> q, Point<T> r) {
    int val =
        (q.y - p.y) * (r.x - q.x) - (q.x - p.x) * (r.y - q.y);
    // TODO: if it's a float must use other way to compare
    if (val == 0)
        return 0; // colinear
    else if (val > 0)
        return 1; // clockwise
    else
        return 2; // counterclockwise
}

template <typename T>
bool do_segment_intersect(Segment<T> s1, Segment<T> s2) {
    int o1 = orientation(s1.p1, s1.p2, s2.p1);
    int o2 = orientation(s1.p1, s1.p2, s2.p2);

    int o3 = orientation(s2.p1, s2.p2, s1.p1);
    int o4 = orientation(s2.p1, s2.p2, s1.p2);

    return (o1 != o2 and o3 != o4) or (o1 == 0 and o3 == 0) or
        (o2 == 0 and o4 == 0);
}

```

4.9 Segment

```

#include "Line.cpp"
#include "Point.cpp"
#include "equals.cpp"

```

```

template <typename T>
struct segment {
    Point<T> A, B;

    bool contains(const Point<T> &P) const;

    Point<T> closest(const Point<T> &p) const;
};

template <typename T>
bool segment<T>::contains(const Point<T> &P) const {
    // verifica se P éest contido na reta
    double dAB = Point<T>::dist(A, B),
        dAP = Point<T>::dist(A, P),
        dPB = Point<T>::dist(P, B);

    return equals(dAP + dPB, dAB);
}

template <typename T>
Point<T> segment<T>::closest(const Point<T> &P) const {
    Line<T> R(A, B);
    auto Q = R.closest(P);

    if (this->contains(Q)) return Q;

    auto distA = Point<T>::dist(P, A);
    auto distB = Point<T>::dist(P, B);

    if (distA <= distB)
        return A;
    else
        return B;
}

```

4.10 Template Line

```

#include "template-point.cpp"

template <typename T>
struct Line {
    T a, b, c;

    Line(T av, T bv, T cv) : a(av), b(bv), c(cv) {}
}

```



```

Line(const Point<T> &P, const Point<T> &Q)
: a(P.y - Q.y),
  b(Q.x - P.x),
  c(P.x * Q.y - Q.x * P.y) {}

// verify if a point belongs to the line
bool contains(const Point<T> &P) {
    return equals(a * P.x + b * P.y + c, 0);
}

// shortest distance between P and a point Q that belongs
// to this line
double distance(const Point<T> &P) const {
    return fabs(a * P.x + b * P.y + c) / hypot(a, b);
}

// the closest point in this line to the given point
Point<T> closest(const Point<T> &P) const {
    auto den = (a * a) + (b * b);

    auto x = (b * (b * P.x - a * P.y) - a * c) / den;
    auto y = (a * (-b * P.x + a * P.y) - b * c) / den;

    return Point<T>{x, y};
}
};

```

4.11 Template Point

```

template <typename T>
struct Point {
    T x, y;

    Point(T xv = 0, T yv = 0) : x(xv), y(yv) {}

    double distance(const Point<T> &P) const {
        return hypot(static_cast<double>(P.x - this->x),
                     static_cast<double>(P.y - this->y));
    }
};

```

4.12 Template Segment

```

#include "equals.cpp"
#include "template-line.cpp"

```

```

#include "template-point.cpp"

template <typename T>
struct Segment {
    Point<T> A, B;

    Segment(const Point<T> &a, const Point<T> &b)
        : A(a), B(b) {}

    /*
     * Verify if a given point P belongs to the segment,
     * considering that P belongs to the line defined with A
     * and B
     */
    bool contains(const Point<T> &P) const {
        return equals(A.x, B.x)
            ? min(A.y, B.y) <= P.y and P.y <= max(A.y, B.y)
            : min(A.x, B.x) <= P.x and
              P.x <= max(A.x, B.x);
    }

    /*
     * Verify if P belongs to the segment AB,
     * even if P don't belong to the line defined with A and B
     */
    bool contains2(const Point<T> &P) const {
        double dAB = dist(A, B), dAP = dist(A, P),
              dPB = dist(P, B);
        return equals(dAP + dPB, dAB);
    }

    /*
     * Find the closest point in P that belongs to the segment
     */
    Point<T> closest(const Point<T> &P) {
        Line<T> r(A, B);
        auto Q = r.closest(P);

        if (this->contains(Q)) return Q;

        auto distA = P.distance(A);
        auto distB = P.distance(B);

        return distA <= distB ? A : B;
    }
};

```

```

double distToClosest(const Point<T> &P) {
    return closest(P).distance(P);
}
};

```

5 Graphs

5.1 2 SAT

```

struct SAT {
    int n;
    vi2d g, tg;
    vi vis;
    vi order, comp;
    vc assignment;
    bool solvable;
    int qtdcomp;

    SAT(int _n)
        : n(2 * _n),
          g(n),
          tg(n),
          vis(n),
          comp(n, -1),
          assignment(n / 2) {}

    void dfs1(int u) {
        vis[u] = 1;
        for (auto v : g[u]) {
            if (!vis[v]) {
                dfs1(v);
            }
        }
        order.emplace_back(u);
    }

    void dfs2(int u) {
        comp[u] = qtdcomp;
        for (auto v : tg[u]) {
            if (comp[v] == -1) {
                dfs2(v);
            }
        }
    }
}

```

```

bool solve2sat() {
    for (int i = 0; i < n; i++) {
        if (!vis[i]) dfs1(i);
    }

    reverse(all(order));
    qtdcomp = 0;
    for (auto u : order) {
        if (comp[u] == -1) {
            dfs2(u);
            qtdcomp++;
        }
    }

    assignment.assign(n / 2, false);
    for (int i = 0; i < n; i += 2) {
        if (comp[i] == comp[i + 1]) {
            solvable = false;
            return false;
        }

        assignment[i / 2] = comp[i] < comp[i + 1];
    }

    solvable = 1;
    return solvable;
}

void add_dis(int a, bool va, int b, bool vb) { // a V b
    va = !va, vb = !vb;
    a = (2 * a) ^ va, b = (2 * b) ^ vb;
    int nota = a ^ 1, notb = b ^ 1;
    g[nota].emplace_back(b), g[notb].emplace_back(a),
    tg[b].emplace_back(nota), tg[a].emplace_back(notb);
}

void add_impl(int a, bool va, int b, int vb) { // a -> b
    add_dis(a, !va, b, vb);
}

void add_equiv(int a, bool va, int b,
                bool vb) { // a <-> b
    add_impl(a, 1, b, 1);
    add_impl(b, 1, a, 1);
}

```

```

    add_impl(a, 0, b, 0);
    add_impl(b, 0, a, 0);
}

void add_xor(int a, bool va, int b, bool vb) { // a xor b
    add_impl(a, 1, b, 0);
    add_impl(a, 0, b, 1);
    add_impl(b, 1, a, 0);
    add_impl(b, 0, a, 1);
}
};

```

5.2 Cycle Distances

Given a vertex s finds the longest cycle that end's in s , note that the vector **dist** will contain the distance that each vertex u needs to reach s .

Time: $O(N)$

```

using adj = vector<vector<pair<int, ll>>>;
ll cycleDistances(int u, int n, int s, vc &vis, adj &g,
                  vll &dist) {

    vis[u] = 1;

    for (auto [v, d] : g[u]) {
        if (v == s) {
            dist[u] = max(dist[u], d);
            continue;
        }

        if (vis[v] == 1) {
            continue;
        }

        if (vis[v] == 2) {
            dist[u] = max(dist[u], dist[v] + d);
        } else {
            ll d2 = cycleDistances(v, n, s, vis, g, dist);
            if (d2 != -oo) {
                dist[u] = max(dist[u], d2 + d);
            }
        }
    }
    vis[u] = 2;
    return dist[u];
}

```

5.3 SCC (struct)

Build the condensation graph based in the strongly connected components.

tiem: $O(V + E)$

```

struct SCC {
    int num_sccs = 0;
    vi scc_id;
    vector<set<ll>> gscc;

    SCC(const vi2d& adj)
        : scc_id(len(adj), -1), gscc(len(adj)) {
        int n = len(adj), timer = 1;
        vi tin(n), st;
        st.reserve(n);
        auto dfs = [&](auto&& self, int u) -> int {
            int low = tin[u] = timer++, siz = len(st);
            st.push_back(u);
            for (int v : adj[u])
                if (scc_id[v] < 0)
                    low = min(low, tin[v] ? tin[v] : self(self, v));
            if (tin[u] == low) {
                for (int i = siz; i < len(st); i++)
                    scc_id[st[i]] = num_sccs;
                st.resize(siz);
                num_sccs++;
            }
            return low;
        };
        for (int i = 0; i < n; i++)
            if (!tin[i]) dfs(dfs, i);

        for (int i = 0; i < len(adj); ++i)
            for (auto j : adj[i])
                if (scc_id[i] != scc_id[j])
                    gscc[scc_id[i]].emplace(scc_id[j]);
    }
};

```

5.4 Bellman-Ford (find negative cycle)

Given a directed graph find a negative cycle by running n iterations, and if the last one produces a relaxation than there is a cycle.

Time: $O(V \cdot E)$

```

const ll oo = 2500 * 1e9;

using graph = vector<vector<pair<int, ll>>>;

```

```

vi negative_cycle(graph &g, int n) {
    vll d(n, oo);
    vi p(n, -1);
    int x = -1;
    d[0] = 0;
    for (int i = 0; i < n; i++) {
        x = -1;
        for (int u = 0; u < n; u++) {
            for (auto &[v, l] : g[u]) {
                if (d[u] + l < d[v]) {
                    d[v] = d[u] + l;
                    p[v] = u;
                    x = v;
                }
            }
        }
    }

    if (x == -1)
        return {};
    else {
        for (int i = 0; i < n; i++) x = p[x];
        vi cycle;
        for (int v = x;; v = p[v]) {
            cycle.pb(v);
            if (v == x and len(cycle) > 1) break;
        }
        reverse(all(cycle));
        return cycle;
    }
}

```

5.5 Bellman Ford

Find shortest path from a single source to all other nodes. Can detect negative cycles.
Time: $O(V * E)$

```

bool bellman_ford(const vector<vector<pair<int, ll>>> &g,
                  int s, vector<ll> &dist) {
    int n = (int)g.size();
    dist.assign(n, LLONG_MAX);

    vector<int> count(n);
    vector<char> in_queue(n);
    queue<int> q;

```

```

    dist[s] = 0;
    q.push(s);
    in_queue[s] = true;

    while (not q.empty()) {
        int cur = q.front();
        q.pop();
        in_queue[cur] = false;

        for (auto [to, w] : g[cur]) {
            if (dist[cur] + w < dist[to]) {
                dist[to] = dist[cur] + w;
                if (not in_queue[to]) {
                    q.push(to);
                    in_queue[to] = true;
                    count[to]++;
                    if (count[to] > n) return false;
                }
            }
        }
    }

    return true;
}

```

5.6 BFS 01

Similar to a Dijkstra given a weighted graph finds the distance from source s to every other node (SSSP).
Applicable only when the weight of the edges $\in \{0, x\}$
Time: $O(V + E)$

```

vector<pair<ll, int>> adj[maxn];
ll dists[maxn];
int s, n;
void bfs_01() {
    fill(dists, dists + n, oo);
    dist[s] = 0;

    deque<int> q;
    q.emplace_back(s);

    while (not q.empty()) {
        auto u = q.front();
        q.pop_front();

        for (auto [v, w] : adj[u]) {

```

```

        if (dist[v] <= dist[u] + w) continue;
        dist[v] = dist[u] + w;
        w ? q.emplace_back(v) : q.emplace_front(v);
    }
}
}

```

5.7 Biconnected Components

Build a vector of vectors, where the i -th vector correspond to the nodes of the i -th biconnected component, a biconnected component is a subset of nodes and edges in which there is no cut point, also exist at least two distinct routes in vertex between any two vertex in the same biconnected component.

time: $O(N + M)$

```

const int maxn(5'00'000);
int tin[maxn], stck[maxn], bcc_cnt, n, top = 0, timer = 1;
vector<int> g[maxn], nodes[maxn];

```

```

int tarjan(int u, int p = -1) {
    int lowu = tin[u] = timer++;
    int son_cnt = 0;
    stck[++top] = u;
    for (auto v : g[u]) {
        if (!tin[v]) {
            son_cnt++;
            int lowx = tarjan(v, u);
            lowu = min(lowu, lowx);
            if (lowx >= tin[u]) {
                while (top != -1 && stck[top + 1] != v)
                    nodes[bcc_cnt].emplace_back(stck[top--]);
                nodes[bcc_cnt++].emplace_back(u);
            }
        } else {
            lowu = min(lowu, tin[v]);
        }
    }

    if (p == -1 && son_cnt == 0) {
        nodes[bcc_cnt++].emplace_back(u);
    }

    return lowu;
}

```

```

void build_bccs() {
    timer = 1;

```

```

top = -1;
memset(tin, 0, sizeof(int) * n);
for (int i = 0; i < n; i++) nodes[i] = {};
bcc_cnt = 0;

for (int u = 0; u < n; u++)
    if (!tin[u]) tarjan(u);
}

```

5.8 Binary Lifting/Jumping

Given a function/successor graph answers queries of the form which is the node after k moves starting from u .

Time: build $O(N \cdot \text{MAXLOG2})$, query $O(\text{MAXLOG2})$.

```

const int MAXN(2e5), MAXLOG2(30);
int bl[MAXN][MAXLOG2 + 1];
int N;

int jump(int u, ll k) {
    for (int i = 0; i <= MAXLOG2; i++) {
        if (k & (1ll << i)) u = bl[u][i];
    }
    return u;
}

void build() {
    for (int i = 1; i <= MAXLOG2; i++) {
        for (int j = 0; j < N; j++) {
            bl[j][i] = bl[bl[j][i - 1]][i - 1];
        }
    }
}

```

5.9 Block Cut Tree

```

struct block_cut_tree {
    int n;
    vector<int> id, is_cutpoint, tin, low, stk;
    vector<vector<int>> comps, tree;
    block_cut_tree(vector<vector<int>> &g)
        : n(g.size()), id(n), is_cutpoint(n), tin(n), low(n) {
        // build comps
        for (int i = 0; i < n; i++) {
            if (!tin[i]) {
                int timer = 0;
                dfs(i, -1, timer, g);
            }
        }
    }

```

```

    }
}

int node_id = 0;
for (int u = 0; u < n; u++) {
    if (is_cutpoint[u]) {
        id[u] = node_id++;
        tree.push_back({});
    }
}

for (auto &comp : comps) {
    int node = node_id++;
    tree.push_back({});
    for (int u : comp) {
        if (!is_cutpoint[u]) {
            id[u] = node;
        } else {
            tree[node].emplace_back(id[u]);
            tree[id[u]].emplace_back(node);
        }
    }
}

void dfs(int u, int p, int &timer,
        vector<vector<int>> &g) {
    tin[u] = low[u] = ++timer;
    stk.emplace_back(u);

    for (auto v : g[u]) {
        if (v == p) continue;
        if (!tin[v]) {
            dfs(v, u, timer, g);
            low[u] = min(low[u], low[v]);
            if (low[v] >= tin[u]) {
                is_cutpoint[u] = (tin[u] > 1 or tin[v] > 2);
                comps.push_back({u});
                while (comps.back().back() != v) {
                    comps.back().emplace_back(stk.back());
                    stk.pop_back();
                }
            }
        } else
            low[u] = min(low[u], tin[v]);
    }
}

```

```

    }
};

5.10 Check Bipartite
O(V)

vi2d G;
int N, M;

bool check() {
    vi side(N, -1);
    queue<int> q;
    for (int st = 0; st < N; st++) {
        if (side[st] == -1) {
            q.emplace(st);
            side[st] = 0;
            while (not q.empty()) {
                int u = q.front();
                q.pop();
                for (auto v : G[u]) {
                    if (side[v] == -1) {
                        side[v] = side[u] ^ 1;
                        q.push(v);
                    } else if (side[u] == side[v])
                        return false;
                }
            }
        }
    }
    return true;
}

```

5.11 Dijkstra (k Shortest Paths)

```

const ll oo = 1e9 * 1e5 + 1;
using adj = vector<vector<pll>>;
vector<priority_queue<ll>> dijkstra(
    const vector<vector<pll>> &g, int n, int s, int k) {
    priority_queue<pll, vector<pll>, greater<pll>> pq;

    vector<priority_queue<ll>> dist(n);
    dist[0].emplace(0);
    pq.emplace(0, s);
    while (!pq.empty()) {

```

```

auto [d1, v] = pq.top();
pq.pop();

if (not dist[v].empty() and dist[v].top() < d1)
    continue;

for (auto [d2, u] : g[v]) {
    if (len(dist[u]) < k) {
        pq.emplace(d2 + d1, u);
        dist[u].emplace(d2 + d1);
    } else {
        if (dist[u].top() > d1 + d2) {
            dist[u].pop();
            dist[u].emplace(d1 + d2);
            pq.emplace(d2 + d1, u);
        }
    }
}
return dist;
}

```

5.12 Dijkstra

Finds the shortest path from s to every other node, and keep the 'parent' tracking.
Time: $O(E \cdot \log V)$

```

pair<vll, vi> dijkstra(const vector<vector<p11>> &g, int n,
                    int s) {
    priority_queue<p11, vector<p11>, greater<p11>> pq;
    vll dist(n, oo);
    vi p(n, -1);
    pq.emplace(0, s);
    dist[s] = 0;
    while (!pq.empty()) {
        auto [d1, v] = pq.top();
        pq.pop();
        if (dist[v] < d1) continue;

        for (auto [d2, u] : g[v]) {
            if (dist[u] > d1 + d2) {
                dist[u] = d1 + d2;
                p[u] = v;
                pq.emplace(dist[u], u);
            }
        }
    }
}

```

```

return {dist, p};
}

```

5.13 Disjoint Edges Path (Maxflow)

Given a directed graph find's every path with disjoint edges that starts at s and ends at t
Time: $O(E \cdot V^2)$

```

struct DisjointPaths {
    int n;
    vi2d g, capacity;
    vector<vc> isedge;

    DisjointPaths(int _n)
        : n(_n), g(n), capacity(n, vi(n)), isedge(n, vc(n)) {}

    void add(int u, int v, int w = 1) {
        g[u].emplace_back(v);
        g[v].emplace_back(u);
        capacity[u][v] += w;
        isedge[u][v] = true;
    }

    // finds the new flow to insert
    int bfs(int s, int t, vi &parent) {
        fill(all(parent), -1);
        parent[s] = -2;
        queue<pair<int, int>> q;
        q.push({oo, s});

        while (!q.empty()) {
            auto [flow, cur] = q.front();
            q.pop();

            for (auto next : g[cur]) {
                if (parent[next] == -1 and capacity[cur][next]) {
                    parent[next] = cur;
                    ll new_flow = min(flow, capacity[cur][next]);
                    if (next == t) return new_flow;
                    q.push({new_flow, next});
                }
            }
        }

        return 0;
    }
}

```

```

int maxflow(int s, int t) {
    int flow = 0;
    vi parent(n);
    int new_flow;

    while ((new_flow = bfs(s, t, parent))) {
        flow += new_flow;
        int cur = t;
        while (cur != s) {
            int prev = parent[cur];
            capacity[prev][cur] -= new_flow;
            capacity[cur][prev] += new_flow;
            cur = prev;
        }
    }

    return flow;
}

// build the distinct routes based in the capacity set by
// maxflow
void dfs(int u, int t, vc2d &vis, vi &route,
        vi2d &routes) {
    route.eb(u);
    if (u == t) {
        routes.emplace_back(route);
        route.pop_back();
        return;
    }

    for (auto &v : g[u]) {
        if (capacity[u][v] == 0 and isedge[u][v] and
            not vis[u][v]) {
            vis[u][v] = true;
            dfs(v, t, vis, route, routes);
            route.pop_back();
            return;
        }
    }
}

vi2d disjoint_paths(int s, int t) {
    int mf = maxflow(s, t);
    vi2d routes;

```

```

    vi route;
    vc2d vis(n, vc(n));
    for (int i = 0; i < mf; i++)
        dfs(s, t, vis, route, routes);
    return routes;
}
};

```

5.14 Euler Path (directed)

Given a **directed** graph finds a path that visits every edge exactly once.
Time: $O(E)$

```

vector<int> euler_cycle(vector<vector<int>> &g, int u) {
    vector<int> res;

    stack<int> st;
    st.push(u);
    while (!st.empty()) {
        auto cur = st.top();
        if (g[cur].empty()) {
            res.push_back(cur);
            st.pop();
        } else {
            auto next = g[cur].back();
            st.push(next);

            g[cur].pop_back();
        }
    }

    for (auto &x : g)
        if (!x.empty()) return {};

    return res;
}

vector<int> euler_path(vector<vector<int>> &g, int first) {
    {
        int n = (int)g.size();
        vector<int> in(n), out(n);
        for (int i = 0; i < n; i++)
            for (auto x : g[i]) in[x]++, out[i]++;

        int a = 0, b = 0, c = 0;
    }
}

```



```

for (int i = 0; i < n; i++)
    if (in[i] == out[i])
        c++;
    else if (in[i] - out[i] == 1)
        b++;
    else if (in[i] - out[i] == -1)
        a++;

if (c != n - 2 or a != 1 or b != 1) return {};
}

auto res = euler_cycle(g, first);
if (res.empty()) return res;

reverse(all(res));
return res;
}

```

5.15 Euler Path (undirected)

Given a **undirected** graph finds a path that visits every edge exactly once.

Time: $O(E)$

```

vector<int> euler_cycle(vector<vector<int>> &g, int u) {
    vector<int> res;
    multiset<pair<int, int>> vis;

    stack<int> st;
    st.push(u);
    while (!st.empty()) {
        auto cur = st.top();

        while (!g[cur].empty()) {
            auto it = vis.find(make_pair(cur, g[cur].back()));
            if (it == vis.end()) break;
            g[cur].pop_back();
            vis.erase(it);
        }

        if (g[cur].empty()) {
            res.push_back(cur);
            st.pop();
        } else {
            auto next = g[cur].back();
            st.push(next);
        }
    }
}

```

```

        vis.emplace(next, cur);
        g[cur].pop_back();
    }
}

for (auto &x : g)
    if (!x.empty()) return {};

return res;
}

vector<int> euler_path(vector<vector<int>> &g, int first) {
    int n = (int)g.size();
    int v1 = -1, v2 = -1;
    {
        bool bad = false;
        for (int i = 0; i < n; i++)
            if (g[i].size() & 1) {
                if (v1 == -1)
                    v1 = i;
                else if (v2 == -1)
                    v2 = i;
                else
                    bad = true;
            }

        if (bad or (v1 != -1 and v2 == -1)) return {};
    }

    if (v2 != -1) {
        // insert cycle
        g[v1].push_back(v2);
        g[v2].push_back(v1);
    }

    auto res = euler_cycle(g, first);
    if (res.empty()) return res;

    if (v1 != -1) {
        for (int i = 0; i + 1 < (int)res.size(); i++) {
            if ((res[i] == v1 and res[i + 1] == v2) ||
                (res[i] == v2 and res[i + 1] == v1)) {
                vector<int> res2;
                for (int j = i + 1; j < (int)res.size(); j++)

```

```

        res2.push_back(res[j]);
    for (int j = 1; j <= i; j++) res2.push_back(res[j]);
    res = res2;
    break;
}
}
}

reverse(all(res));
return res;
}

```

5.16 Extra Edges to Make Digraph Fully Strongly Connected

Given a directed graph G find the necessary edges to add to make the graph a single strongly connected component.

time : $O(N + M)$, memory : $O(N)$

```

struct SCC {
    int num_sccs = 0;
    vi scc_id;
    SCC(const vi2d& adj) : scc_id(len(adj), -1) {
        int n = len(adj), timer = 1;
        vi tin(n), st;
        st.reserve(n);
        auto dfs = [&](auto&& self, int u) -> int {
            int low = tin[u] = timer++, siz = len(st);
            st.push_back(u);
            for (int v : adj[u])
                if (scc_id[v] < 0)
                    low = min(low, tin[v] ? tin[v] : self(self, v));
            if (tin[u] == low) {
                for (int i = siz; i < len(st); i++)
                    scc_id[st[i]] = num_sccs;
                st.resize(siz);
                num_sccs++;
            }
            return low;
        };
        for (int i = 0; i < n; i++)
            if (!tin[i]) dfs(dfs, i);
    }
};

vector<array<int, 2>> extra_edges(const vi2d& adj) {
    SCC scc(adj);

```

```

    auto scc_id = scc.scc_id;
    auto num_sccs = scc.num_sccs;

    if (num_sccs == 1) return {};

    int n = len(adj);
    vi2d scc_adj(num_sccs);
    vi zero_in(num_sccs, 1);
    for (int u = 0; u < n; u++)
        for (int v : adj[u]) {
            if (scc_id[u] == scc_id[v]) continue;
            scc_adj[scc_id[u]].eb(scc_id[v]);
            zero_in[scc_id[v]] = 0;
        }

    int random_source =
        max_element(all(zero_in)) - zero_in.begin();

    vi vis(num_sccs);
    auto dfs = [&](auto&& self, int u) {
        if (empty(scc_adj[u])) return u;
        for (int v : scc_adj[u])
            if (!vis[v]) {
                vis[v] = 1;
                int zero_out = self(self, v);
                if (zero_out != -1) return zero_out;
            }
        return -1;
    };

    vector<array<int, 2>> edges;
    vi in_unused;
    for (int i = 0; i < num_sccs; i++)
        if (zero_in[i]) {
            vis[i] = 1;
            int zero_out = dfs(dfs, i);
            if (zero_out != -1)
                edges.push_back({zero_out, i});
            else
                in_unused.push_back(i);
        }

    for (int i = 1; i < len(edges); i++)
        swap(edges[i][0], edges[i - 1][0]);

```

```

for (int i = 0; i < num_sccs; i++) {
    if (scc_adj[i].empty() && !vis[i]) {
        if (!in_unused.empty()) {
            edges.push_back({i, in_unused.back()});
            in_unused.pop_back();
        } else {
            edges.push_back({i, random_source});
        }
    }
}

for (int u : in_unused) edges.push_back({0, u});

vi to_node(num_sccs);
for (int i = 0; i < n; i++) to_node[scc_id[i]] = i;
for (auto& [u, v] : edges) u = to_node[u], v = to_node[v];

return edges;
}

```

5.17 Find Articulation/Cut Points

Given an **undirected** graph find its articulation points.

articulation point (or cut vertex): is defined as a **vertex** which, when removed along with associated edges, increases the number of connected components in the graph.

A vertex u can be an articulation point if and only if has at least 2 adjacent vertex

Time: $O(N + M)$

```

const int MAXN(100);
int N;
vi2d G;
int timer;
int tin[MAXN], low[MAXN];
set<int> cpoints;

int dfs(int u, int p = -1) {
    int cnt = 0;
    low[u] = tin[u] = timer++;
    for (auto v : G[u]) {
        if (not tin[v]) {
            cnt++;
            dfs(v, u);

            if (low[v] >= tin[u]) cpoints.insert(u);
            low[u] = min(low[u], low[v]);
        }
    }
}

```

```

    } else if (v != p)
        low[u] = min(low[u], tin[v]);
}

return cnt;
}

void getCutPoints() {
    memset(low, 0, sizeof(low));
    memset(tin, 0, sizeof(tin));
    cpoints.clear();

    timer = 1;
    for (int i = 0; i < N; i++) {
        if (tin[i]) continue;
        int cnt = dfs(i);
        if (cnt == 1) cpoints.erase(i);
    }
}

```

5.18 Find Bridge Tree Components

$label2CC(u, p)$ finds the 2-edge connected component of every node.

notes: 0 indexed, it also works with not simple graphs.

time: $O(n + m)$

```

const int maxn(3'00'000);
int tin[maxn], compId[maxn], qtdComps;
vi g[maxn], stck;
int n;
int dfs(int u, int p = -1) {
    int low = tin[u] = len(stck);
    stck.emplace_back(u);

    bool multEdge = false;
    for (auto v : g[u]) {
        if (v == p and !multEdge) {
            multEdge = 1;
            continue;
        }
        low = min(low, tin[v] == -1 ? dfs(v, u) : tin[v]);
    }

    if (low == tin[u]) {
        for (int i = tin[u]; i < len(stck); i++)
            compId[stck[i]] = qtdComps;
        stck.resize(tin[u]);
    }
}

```

```

    qtdComps++;
}

return low;
}

void label2CC() {
    memset(compId, -1, sizeof(int) * n);
    memset(tin, -1, sizeof(int) * n);

    stck.reserve(n);
    for (int i = 0; i < n; i++) {
        if (tin[i] == -1) dfs(i);
    }
}

```

5.19 Find Bridges (online)

```

// O((n+m)*log(n))
struct BridgeFinder {
    // 2ecc = 2 edge conected component
    // cc = conected component
    vector<int> parent, dsu_2ecc, dsu_cc, dsu_cc_size;
    int bridges, lca_iteration;
    vector<int> last_visit;

    BridgeFinder(int n)
        : parent(n, -1),
          dsu_2ecc(n),
          dsu_cc(n),
          dsu_cc_size(n, 1),
          bridges(0),
          lca_iteration(0),
          last_visit(n) {
        for (int i = 0; i < n; i++) {
            dsu_2ecc[i] = i;
            dsu_cc[i] = i;
        }
    }

    int find_2ecc(int v) {
        if (v == -1) return -1;
        return dsu_2ecc[v] == v
            ? v
            : dsu_2ecc[v] = find_2ecc(dsu_2ecc[v]);
    }
}

```

```

}

int find_cc(int v) {
    v = find_2ecc(v);
    return dsu_cc[v] == v ? v
        : dsu_cc[v] = find_cc(dsu_cc[v]);
}

void make_root(int v) {
    v = find_2ecc(v);
    int root = v;
    int child = -1;
    while (v != -1) {
        int p = find_2ecc(parent[v]);
        parent[v] = child;
        dsu_cc[v] = root;
        child = v;
        v = p;
    }
    dsu_cc_size[root] = dsu_cc_size[child];
}

void merge_path(int a, int b) {
    ++lca_iteration;
    vector<int> path_a, path_b;
    int lca = -1;
    while (lca == -1) {
        if (a != -1) {
            a = find_2ecc(a);
            path_a.push_back(a);
            if (last_visit[a] == lca_iteration) {
                lca = a;
                break;
            }
            last_visit[a] = lca_iteration;
            a = parent[a];
        }
        if (b != -1) {
            b = find_2ecc(b);
            path_b.push_back(b);
            if (last_visit[b] == lca_iteration) {
                lca = b;
                break;
            }
            last_visit[b] = lca_iteration;
        }
    }
}

```

```

        b = parent[b];
    }
}

for (auto v : path_a) {
    dsu_2ecc[v] = lca;
    if (v == lca) break;
    --bridges;
}
for (auto v : path_b) {
    dsu_2ecc[v] = lca;
    if (v == lca) break;
    --bridges;
}
}

void add_edge(int a, int b) {
    a = find_2ecc(a);
    b = find_2ecc(b);

    if (a == b) return;

    int ca = find_cc(a);
    int cb = find_cc(b);

    if (ca != cb) {
        ++bridges;
        if (dsu_cc_size[ca] > dsu_cc_size[cb]) {
            swap(a, b);
            swap(ca, cb);
        }
        make_root(a);
        parent[a] = dsu_cc[a] = b;
        dsu_cc_size[cb] += dsu_cc_size[a];
    } else {
        merge_path(a, b);
    }
}
};

```

5.20 Find Bridges

Find every bridge in a **undirected** connected graph.

bridge: A bridge is defined as an **edge** which, when removed, increases the number of connected components in the graph.

Remember to read the graph as pair where the second is the id of the edge !

Time: $O(N + M)$

```

const int MAXN(10000), MAXM(100000);
int N, M, clk, tin[MAXN], low[MAXN], isBridge[MAXM];
vector<pii> G[MAXN];

void dfs(int u, int p = -1) {
    tin[u] = low[u] = clk++;

    for (auto [v, i] : G[u]) {
        if (v == p) continue;
        if (tin[v]) {
            low[u] = min(low[u], tin[v]);
        } else {
            dfs(v, u);
            low[u] = min(low[u], low[v]);
            if (low[v] > tin[u]) {
                isBridge[i] = 1;
            }
        }
    }
}

void findBridges() {
    fill(tin, tin + N, 0);
    fill(low, low + N, 0);
    fill(isBridge, isBridge + M, 0);
    clk = 1;
    for (int i = 0; i < N; i++) {
        if (!tin[i]) dfs(i);
    }
}

```

5.21 Find Centroid

Given a tree (don't forget to make it 'undirected'), find it's centroids.

Time: $O(V)$

```

void dfs(int u, int p, int n, vi2d &g, vi &sz,
        vi &centroid) {
    sz[u] = 1;

    bool iscentroid = true;
    for (auto v : g[u])
        if (v != p) {
            dfs(v, u, n, g, sz, centroid);
            if (sz[v] > n / 2) iscentroid = false;
            sz[u] += sz[v];
        }
}

```

```

    }

    if (n - sz[u] > n / 2) iscentroid = false;
    if (iscentroid) centroid.eb(u);
}

vi getCentroid(vi2d &g, int n) {
    vi centroid;
    vi sz(n);
    dfs(0, -1, n, g, sz, centroid);
    return centroid;
}

```

5.22 Floyd Warshall

Simply finds the minimal distance for each node to every other node. $O(V^3)$

```

vector<vll> floyd_warshall(const vector<vll> &adj, ll n) {
    auto dist = adj;

    for (int i = 0; i < n; ++i) {
        for (int j = 0; j < n; ++j) {
            for (int k = 0; k < n; ++k) {
                dist[j][k] =
                    min(dist[j][k], dist[j][i] + dist[i][k]);
            }
        }
    }
    return dist;
}

```

5.23 Functional/Successor Graph

Given a functional graph find the vertex after k moves starting at u and also the distance between u and v , if it's impossible to reach v starting at u returns -1.

Time: build $O(N \cdot \text{MAXLOG2})$, kth $O(\text{MAXLOG2})$, dist $O(\text{MAXLOG2})$

```

const int MAXN(2'000'000), MAXLOG2(24);
int N;
vi2d succ(MAXN, vi(MAXLOG2 + 1));
vi dst(MAXN, 0);

int vis[MAXN];
void dfsbuild(int u) {
    if (vis[u]) return;
    vis[u] = 1;
    int v = succ[u][0];
    dfsbuild(v);
}

```

```

    dst[u] = dst[v] + 1;
}

void build() {
    for (int i = 0; i < N; i++) {
        if (not vis[i]) dfsbuild(i);
    }

    for (int k = 1; k <= MAXLOG2; k++) {
        for (int i = 0; i < N; i++) {
            succ[i][k] = succ[succ[i][k - 1]][k - 1];
        }
    }
}

int kth(int u, ll k) {
    if (k <= 0) return u;
    for (int i = 0; i <= MAXLOG2; i++)
        if ((1ll << i) & k) u = succ[u][i];
    return u;
}

int dist(int u, int v) {
    int cu = kth(u, dst[u]);
    if (kth(u, dst[u] - dst[v]) == v)
        return dst[u] - dst[v];
    else if (kth(cu, dst[cu] - dst[v]) == v)
        return dst[u] + (dst[cu] - dst[v]);
    else
        return -1;
}

```

5.24 Graph Cycle (directed)

Given a directed graph finds a cycle (or not).

Time : $O(E)$

```

bool dfs(int v, vi2d &adj, vc &visited, vi &parent,
         vc &color, int &cycle_start, int &cycle_end) {
    color[v] = 1;
    for (int u : adj[v]) {
        if (color[u] == 0) {
            parent[u] = v;
            if (dfs(u, adj, visited, parent, color, cycle_start,
                    cycle_end))
                return true;
        }
    }
}

```

```

    } else if (color[u] == 1) {
        cycle_end = v;
        cycle_start = u;
        return true;
    }
}
color[v] = 2;
return false;
}

vi find_cycle(vi2d &g, int n) {
    vc visited(n);
    vi parent(n);
    vc color(n);
    int cycle_start, cycle_end;
    color.assign(n, 0);
    parent.assign(n, -1);
    cycle_start = -1;

    for (int v = 0; v < n; v++) {
        if (color[v] == 0 && dfs(v, g, visited, parent, color,
                                cycle_start, cycle_end))
            break;
    }

    if (cycle_start == -1) {
        return {};
    } else {
        vector<int> cycle;
        cycle.push_back(cycle_start);
        for (int v = cycle_end; v != cycle_start; v = parent[v])
            cycle.push_back(v);
        cycle.push_back(cycle_start);
        reverse(cycle.begin(), cycle.end());
        return cycle;
    }
}

```

5.25 Graph Cycle (undirected)

Detects if a graph contains a cycle. If path parameter is not null, it will contain the cycle if one exists.
Time: $O(V + E)$

```

void graph_cycles(const vector<vector<int>> &g, int u,
                 int p, vector<int> &ps,
                 vector<int> &color, int &cn,

```

```

                 vector<vector<int>> &cycles) {
    if (color[u] == 2) {
        return;
    }

    if (color[u] == 1) {
        cn++;
        int cur = p;
        cycles.emplace_back();
        auto &v = cycles.back();
        v.push_back(cur);
        while (cur != u) {
            cur = ps[cur];
            v.push_back(cur);
        }
        reverse(all(v));
        return;
    }

    ps[u] = p;
    color[u] = 1;
    for (auto v : g[u]) {
        if (v != p)
            graph_cycles(g, v, u, ps, color, cn, cycles);
    }

    color[u] = 2;
}

vector<vector<int>> graph_cycles(
    const vector<vector<int>> &g) {
    vector<int> ps(g.size(), -1), color(g.size());
    int cn = 0;
    vector<vector<int>> cycles;
    for (int i = 0; i < (int)g.size(); i++)
        graph_cycles(g, i, -1, ps, color, cn, cycles);
    return cycles;
}

```

5.26 Heavy Light Decomposition

```

struct HeavyLightDecomposition {
    vector<int> parent, depth, size, heavy, head, pos;

    using SegT = int;

```

```

static SegT op(SegT a, SegT b) { return max(a, b); }
SegTree<SegT, op> seg;

HeavyLightDecomposition(const vector<vector<int>> &g,
                        const vector<int> &v,
                        int root = 0)
: parent(g.size()),
  depth(g.size()),
  size(g.size()),
  heavy(g.size(), -1),
  head(g.size()),
  pos(g.size()),
  seg((int)g.size()) {
dfs(g, root);
int cur_pos = 0;
decompose(g, root, root, cur_pos);

for (int i = 0; i < (int)g.size(); i++) {
    seg.set(pos[i], v[i]);
}
}

SegT query_path(int a, int b) const {
    int res = 0;
    for (; head[a] != head[b]; b = parent[head[b]]) {
        if (depth[head[a]] > depth[head[b]]) swap(a, b);
        res = op(res, seg.query(pos[head[b]], pos[b]));
    }
    if (depth[a] > depth[b]) swap(a, b);
    return op(res, seg.query(pos[a], pos[b]));
}

SegT query_subtree(int a) const {
    return seg.query(pos[a], pos[a] + size[a] - 1);
}

void set(int a, int x) { seg.set(pos[a], x); }

private:
void dfs(const vector<vector<int>> &g, int u) {
    size[u] = 1;
    int mx_child_size = 0;
    for (auto x : g[u])
        if (x != parent[u]) {
            parent[x] = u;

```

```

            depth[x] = depth[u] + 1;
            dfs(g, x);
            size[u] += size[x];
            if (size[x] > mx_child_size)
                mx_child_size = size[x], heavy[u] = x;
        }
    }

void decompose(const vector<vector<int>> &g, int u, int h,
              int &cur_pos) {
    head[u] = h;
    pos[u] = cur_pos++;
    if (heavy[u] != -1) decompose(g, heavy[u], h, cur_pos);

    for (auto x : g[u])
        if (x != parent[u] and x != heavy[u]) {
            decompose(g, x, x, cur_pos);
        }
}
};

```

5.27 Kruskal

Find the minimum spanning tree of a graph.

Time: $O(E \log E)$

can be used to find the maximum spanning tree by changing the comparison operator in the sort

```

struct UFDS {
    vector<int> ps, sz;
    int components;

    UFDS(int n) : ps(n + 1), sz(n + 1, 1), components(n) {
        iota(all(ps), 0);
    }

    int find_set(int x) {
        return (x == ps[x] ? x : (ps[x] = find_set(ps[x])));
    }

    bool same_set(int x, int y) {
        return find_set(x) == find_set(y);
    }

    void union_set(int x, int y) {
        x = find_set(x);
        y = find_set(y);

```



```

    if (x == y) return;

    if (sz[x] < sz[y]) swap(x, y);

    ps[y] = x;
    sz[x] += sz[y];

    components--;
}
};

vector<tuple<ll, int, int>> kruskal(
    int n, vector<tuple<ll, int, int>> &edges) {
    UFDS udfs(n);
    vector<tuple<ll, int, int>> ans;

    sort(all(edges));
    for (auto [a, b, c] : edges) {
        if (ufds.same_set(b, c)) continue;

        ans.emplace_back(a, b, c);
        udfs.union_set(b, c);
    }

    return ans;
}

```

5.28 Lowest Common Ancestor (Binary Lifting)

given a directed tree, finds the LCA between two nodes using binary lifting, and answer a few queries with it.

lca: returns the LCA between the two given nodes

on_path: fids if c is in the path from a to b

Time: build $O(N \cdot \text{MAXLOG}2)$ all queries $O(\text{MAXLOG}2)$

```

struct LCA {
    int n;
    const int maxlog;
    vector<vector<int>> up;
    vector<int> depth;

    LCA(const vector<vector<int>> &tree)
        : n(tree.size()),
          maxlog(ceil(log2(n))),
          up(n, vector<int>(maxlog + 1)),
          depth(n, -1) {

```

```

        for (int i = 0; i < n; i++) {
            if (depth[i] == -1) {
                depth[i] = 0;
                dfs(i, -1, tree);
            }
        }
    }

    void dfs(int u, int p, const vector<vector<int>> &tree) {
        if (p != -1) {
            depth[u] = depth[p] + 1;
            up[u][0] = p;
            for (int i = 1; i <= maxlog; i++) {
                up[u][i] = up[up[u][i - 1]][i - 1];
            }
        }
        for (int v : tree[u]) {
            if (v == p) continue;
            dfs(v, u, tree);
        }
    }

    int kth_jump(int u, int k) {
        for (int i = maxlog; i >= 0; i--) {
            if ((1 << i) & k) {
                u = up[u][i];
            }
        }
        return u;
    }

    int lca(int u, int v) {
        if (depth[u] < depth[v]) swap(u, v);
        int diff = depth[u] - depth[v];
        u = kth_jump(u, diff);
        if (u == v) return u;
        for (int i = maxlog; i >= 0; i--) {
            if (up[u][i] != up[v][i]) {
                u = up[u][i];
                v = up[v][i];
            }
        }
        return up[u][0];
    }
}

```

```

bool on_path(int u, int v, int s) {
    int uv = lca(u, v), us = lca(u, s), vs = lca(v, s);
    return (uv == s or (us == uv and vs == s) or
            (vs == uv and us == s));
}

int dist(int u, int v) {
    return depth[u] + depth[v] - 2 * depth[lca(u, v)];
}
};

```

5.29 Lowest Common Ancestor

Given two nodes of a tree find their lowest common ancestor, or their distance
 Build : $O(V)$, Queries: $O(1)$

```

template <typename T>
struct SparseTable {
    vector<T> v;
    int n;
    static const int b = 30;
    vi mask, t;

    int op(int x, int y) { return v[x] < v[y] ? x : y; }
    int msb(int x) {
        return __builtin_clz(1) - __builtin_clz(x);
    }
    SparseTable() {}
    SparseTable(const vector<T>& v_)
        : v(v_), n(v.size()), mask(n), t(n) {
        for (int i = 0, at = 0; i < n; mask[i++] = at |= 1) {
            at = (at << 1) & ((1 << b) - 1);
            while (at and op(i, i - msb(at & -at)) == i)
                at ^= at & -at;
        }
        for (int i = 0; i < n / b; i++)
            t[i] = b * i + b - 1 - msb(mask[b * i + b - 1]);
        for (int j = 1; (1 << j) <= n / b; j++)
            for (int i = 0; i + (1 << j) <= n / b; i++)
                t[n / b * j + i] =
                    op(t[n / b * (j - 1) + i],
                      t[n / b * (j - 1) + i + (1 << (j - 1))]);
    }
    int small(int r, int sz = b) {
        return r - msb(mask[r] & ((1 << sz) - 1));
    }
};

```

```

T query(int l, int r) {
    if (r - l + 1 <= b) return small(r, r - l + 1);
    int ans = op(small(l + b - 1), small(r));
    int x = l / b + 1, y = r / b - 1;
    if (x <= y) {
        int j = msb(y - x + 1);
        ans = op(ans, op(t[n / b * j + x],
                        t[n / b * j + y - (1 << j) + 1]));
    }
    return ans;
}
};

struct LCA {
    SparseTable<int> st;
    int n;
    vi v, pos, dep;

    LCA(const vi2d& g, int root) : n(len(g)), pos(n) {
        dfs(root, 0, -1, g);
        st = SparseTable<int>(vector<int>(all(dep)));
    }

    void dfs(int i, int d, int p, const vi2d& g) {
        v.eb(len(dep)) = i, pos[i] = len(dep), dep.eb(d);
        for (auto j : g[i])
            if (j != p) {
                dfs(j, d + 1, i, g);
                v.eb(len(dep)) = i, dep.eb(d);
            }
    }

    int lca(int a, int b) {
        int l = min(pos[a], pos[b]);
        int r = max(pos[a], pos[b]);
        return v[st.query(l, r)];
    }
    int dist(int a, int b) {
        return dep[pos[a]] + dep[pos[b]] -
            2 * dep[pos[lca(a, b)]];
    }
};

```

5.30 Prim (MST)

Given a graph with N vertex finds the minimum spanning tree, if there is no such tree returns inf, it starts using the edges that connect with each $s_i \in s$, if none is provided than it starts with the edges of node 0.

Time: $O(V \log E)$

```
const int MAXN(1'00'000);
int N;
vector<pair<ll, int>> G[MAXN];
ll prim(vi s = vi(1, 0)) {
    priority_queue<pair<ll, int>, vector<pair<ll, int>>,
        greater<pair<ll, int>>>
        pq;
    vector<char> ingraph(MAXN);
    int ingraphcnt(0);
    for (auto si : s) {
        ingraphcnt++;
        ingraph[si] = true;
        for (auto &[w, v] : G[si]) pq.emplace(w, v);
    }

    ll mstcost = 0;
    while (ingraphcnt < N and !pq.empty()) {
        ll w;
        int v;

        do {
            tie(w, v) = pq.top();
            pq.pop();
        } while (not pq.empty() and ingraph[v]);

        mstcost += w, ingraph[v] = true, ingraphcnt++;

        for (auto &[w2, v2] : G[v]) {
            pq.emplace(w2, v2);
        }
    }

    return ingraphcnt == N ? mstcost : oo;
}
```

5.31 Shortest Path With K-edges

Given an adjacency matrix of a graph, and a number K computes the shortest path between all nodes that uses exactly K edges, so for $0 \leq i, j \leq N - 1$ ans[i][j] = "the shortest path between i and j that uses exactly K edges, remember to initialize the adjacency matrix with ∞ .

time : $O(N^3 \cdot \log K)$

```
template <typename T>
vector<vector<T>> prod(vector<vector<T>> &a,
    vector<vector<T>> &b) {
    const T _oo = numeric_limits<T>::max();
    int n = a.size();
    vector<vector<T>> c(n, vector<T>(n, _oo));

    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            for (int k = 0; k < n; k++)
                if (a[i][k] != _oo and b[k][j] != _oo)
                    c[i][j] = min(c[i][j], a[i][k] + b[k][j]);

    return c;
}

template <typename T>
vector<vector<T>> shortest_with_k_moves(
    vector<vector<T>> adj, long long k) {
    if (k == 1) return adj;

    auto ans = adj;
    k--;

    while (k) {
        if (k & 1) ans = prod(ans, adj);
        k >>= 1;
        adj = prod(adj, adj);
    }

    return ans;
}
```

5.32 Small to Large

Answer queries of the form "How many vertices in the subtree of vertex v have property P ?"

* this implementation answers how many distinct *values*[i] are in the subtree starting at u .

Build: $O(N)$, Query: $O(N \log N)$

```
struct SmallToLarge {
    int n;
    vi2d tree, vis_childs;
    vi sizes, values, ans;
    set<int> cnt;

    SmallToLarge(vi2d &g, vi &v)
```

```

: tree(g),
  vis_chlds(len(g)),
  sizes(len(g)),
  values(v),
  ans(len(g)) {
get_size(0);
dfs(0);
}

inline void add_value(int u) { cnt.insert(values[u]); }

inline void remove_value(int u) { cnt.erase(values[u]); }

inline void update_ans(int u) { ans[u] = len(cnt); }

void dfs(int u, int p = -1, bool keep = true) {
  int mx = -1;
  for (auto x : tree[u]) {
    if (x == p) continue;

    if (mx == -1 or sizes[mx] < sizes[x]) mx = x;
  }

  for (auto x : tree[u]) {
    if (x != p and x != mx) dfs(x, u, false);
  }

  if (mx != -1) {
    dfs(mx, u, true);
    swap(vis_chlds[u], vis_chlds[mx]);
  }

  vis_chlds[u].push_back(u);
  add_value(u);

  for (auto x : tree[u]) {
    if (x != p and x != mx) {
      for (auto y : vis_chlds[x]) {
        add_value(y);
        vis_chlds[u].push_back(y);
      }
    }
  }

  update_ans(u);
}

```

```

if (!keep) {
  for (auto x : vis_chlds[u]) remove_value(x);
}

void get_size(int u, int p = -1) {
  sizes[u] = 1;
  for (auto x : tree[u])
    if (x != p) {
      get_size(x, u);
      sizes[u] += sizes[x];
    }
}
};

```

5.33 Successor Graph-(struct)

```

struct SuccessorGraph {
  vector<vector<int>> paths;
  vector<int> path_num, pos;
  vector<char> is_cycle;

  SuccessorGraph(const vector<int> &v)
    : path_num(v.size()), pos(v.size()) {
    paths.reserve(v.size());
    is_cycle.reserve(v.size());

    vector<char> vis(v.size());
    for (auto i : topological_order(v)) {
      if (vis[i]) continue;

      vector<int> path;
      int cur;
      for (cur = i; not vis[cur]; cur = v[cur]) {
        path.push_back(cur);
        vis[cur] = 1;
      }

      int cycle_start = 0;
      for (; cycle_start < (int)path.size() and
        path[cycle_start] != cur;
        cycle_start++)
        ;
    }
  }
};

```

```

    if (cycle_start > 0) {
        paths.emplace_back();
        for (int j = 0; j < cycle_start; j++) {
            paths.back().push_back(path[j]);
            pos[path[j]] = j;
            path_num[path[j]] = (int)paths.size() - 1;
        }
        paths.back().push_back(cur);
        is_cycle.push_back(false);
    }

    if (cycle_start < (int)path.size()) {
        paths.emplace_back();
        for (int j = cycle_start; j < (int)path.size(); j++) {
            paths.back().push_back(path[j]);
            pos[path[j]] = j - cycle_start;
            path_num[path[j]] = (int)paths.size() - 1;
        }
        is_cycle.push_back(true);
    }
}

const vector<int> &path(int cur) const {
    return paths[path_num[cur]];
}

int kth_pos(int cur, ll k) const {
    while (not is_cycle[path_num[cur]]) {
        auto &p = path(cur);
        int remain = (int)p.size() - pos[cur] - 1;
        if (k <= remain) return p[pos[cur] + k];
        cur = p.back();
        k -= remain;
    }

    auto &p = path(cur);
    return p[(pos[cur] + k) % p.size()];
}

// {element, number_of_moves}
pair<int, int> go_to_cycle(int cur) const {
    int moves = 0;
    while (not is_cycle[path_num[cur]]) {

```

```

        auto &p = path(cur);
        moves += (int)p.size() - pos[cur] - 1;
        cur = p.back();
    }
    return {cur, moves};
}

// min cost to reach dest from cur
int reach(int cur, int dest) const {
    int moves = 0;
    while (not is_cycle[path_num[cur]] and
           path_num[cur] != path_num[dest]) {
        auto &p = path(cur);
        moves += (int)p.size() - pos[cur] - 1;
        cur = p.back();
    }

    if (path_num[cur] != path_num[dest]) return -1;

    if (pos[cur] <= pos[dest])
        return moves + pos[dest] - pos[cur];

    if (not is_cycle[path_num[cur]]) return -1;

    return moves + pos[dest] + (int)path(cur).size() -
           pos[cur];
}

private:
void topological_order(const vector<int> &g,
                      vector<char> &vis,
                      vector<int> &order, int u) {
    vis[u] = true;
    if (not vis[g[u]])
        topological_order(g, vis, order, g[u]);
    order.push_back(u);
}

vector<int> topological_order(const vector<int> &g) {
    vector<char> vis(g.size(), false);
    vector<int> order;
    for (auto i = 0; i < (int)g.size(); i++)
        if (not vis[i]) topological_order(g, vis, order, i);
    reverse(order.begin(), order.end());
    return order;
}

```

```

    }
};

```

5.34 Sum every node distance

Given a **tree**, for each node i find the sum of distance from i to every other node.
don't forget to set the tree as undirected, that's needed to choose an arbitrary root
Time: $O(N)$

```

void getRoot(int u, int p, vi2d &g, vll &d, vll &cnt) {
    for (int i = 0; i < len(g[u]); i++) {
        int v = g[u][i];
        if (v == p) continue;
        getRoot(v, u, g, d, cnt);
        d[u] += d[v] + cnt[v];
        cnt[u] += cnt[v];
    }
}

void dfs(int u, int p, vi2d &g, vll &cnt, vll &ansd,
        int n) {
    for (int i = 0; i < len(g[u]); i++) {
        int v = g[u][i];
        if (v == p) continue;

        ansd[v] = ansd[u] - cnt[v] + (n - cnt[v]);
        dfs(v, u, g, cnt, ansd, n);
    }
}

vll fromToAll(vi2d &g, int n) {
    vll d(n);
    vll cnt(n, 1);
    getRoot(0, -1, g, d, cnt);

    vll ansdist(n);
    ansdist[0] = d[0];

    dfs(0, -1, g, cnt, ansdist, n);
    return ansdist;
}

```

5.35 Topological Sorting (Kahn)

Finds the topological sorting in a **DAG**, if the given graph is not a **DAG** than an empty vector is returned, need to 'initialize' the **INCNT** as you build the graph.
Time: $O(V + E)$

```

const int MAXN(2'00'000);
int INCNT[MAXN];
vi2d GOUT(MAXN);
int N;

vi toposort() {
    vi order;
    queue<int> q;

    for (int i = 0; i < N; i++)
        if (!INCNT[i]) q.emplace(i);

    while (!q.empty()) {
        auto u = q.front();
        q.pop();
        order.emplace_back(u);
        for (auto v : GOUT[u]) {
            INCNT[v]--;
            if (INCNT[v] == 0) q.emplace(v);
        }
    }

    return len(order) == N ? order : vi();
}

```

5.36 Topological Sorting (Tarjan)

Finds a the topological order for the graph, if there is no such order it means the graph is cyclic, then it returns an empty vector
 $O(V + E)$

```

const int maxn(1'00'000);
int n, m;
vi g[maxn];

int not_found = 0, found = 1, processed = 2;
int state[maxn];

bool dfs(int u, vi &order) {
    if (state[u] == processed) return true;
    if (state[u] == found) return false;

    state[u] = found;

    for (auto v : g[u]) {
        if (not dfs(v, order)) return false;
    }
}

```

```

}

state[u] = processed;
order.emplace_back(u);

return true;
}

vi topo_sort() {
    vi order;
    memset(state, 0, sizeof state);

    for (int u = 0; u < n; u++) {
        if (state[u] == not_found and not dfs(u, order))
            return {};
    }

    reverse(all(order));
    return order;
}

```

5.37 Tree Diameter (DP)

```

const int MAXN(1'000'000);
int N;
vi G[MAXN];

int diameter, toLeaf[MAXN];
void calcDiameter(int u = 0, int p = -1) {
    int d1, d2;
    d1 = d2 = -1;

    for (auto v : G[u]) {
        if (v != p) {
            calcDiameter(v, u);
            d1 = max(d1, toLeaf[v]);
            tie(d1, d2) = minmax({d1, d2});
        }
    }
    toLeaf[u] = d2 + 1;
    diameter = max(diameter, d1 + d2 + 2);
}

```

5.38 Tree Isomorphism (not rooted)

Two trees are considered **isomorphic** if the hash given by *thash()* is the same.

Time: $O(V \cdot \log V)$

```

map<vi, int> mphash;

struct Tree {
    int n;
    vi2d g;
    vi sz, cs;

    Tree(int n_) : n(n_), g(n), sz(n) {}

    void add_edge(int u, int v) {
        g[u].emplace_back(v);
        g[v].emplace_back(u);
    }

    void dfs_centroid(int v, int p) {
        sz[v] = 1;
        bool cent = true;
        for (int u : g[v])
            if (u != p) {
                dfs_centroid(u, v);
                sz[v] += sz[u];
                cent &= not(sz[u] > n / 2);
            }
        if (cent and n - sz[v] <= n / 2) cs.push_back(v);
    }

    int fhash(int v, int p) {
        vi h;
        for (int u : g[v])
            if (u != p) h.push_back(fhash(u, v));
        sort(all(h));
        if (!mphash.count(h)) mphash[h] = mphash.size();
        return mphash[h];
    }

    ll thash() {
        cs.clear();
        dfs_centroid(0, -1);
        if (cs.size() == 1) return fhash(cs[0], -1);
        ll h1 = fhash(cs[0], cs[1]), h2 = fhash(cs[1], cs[0]);
        return (min(h1, h2) << 30ll) + max(h1, h2);
    }
};

```

5.39 Tree Isomorphism (rooted)

Given a rooted tree find the hash of each subtree, if two roots of two distinct trees have the same hash they are considered isomorphic
hash first time in $O(\log N_v \cdot N_v)$ where (N_v) is the of the subtree of v

```
map<vi, int> hasher;
int hs = 0;
struct RootedTreeIso {
    int n;
    vi2d adj;
    vi hashes;
    RootedTreeIso(int _n) : n(_n), adj(_n), hashes(_n, -1){};

    void add_edge(int u, int v) {
        adj[u].emplace_back(v);
        adj[v].emplace_back(u);
    }

    int hash(int u, int p = -1) {
        if (hashes[u] != -1) return hashes[u];

        vi children;
        for (auto v : adj[u])
            if (v != p) children.emplace_back(hash(v, u));

        sort(all(children));
        if (!hasher.count(children)) hasher[children] = hs++;

        return hashes[u] = hasher[children];
    }
};
```

5.40 Tree Maximum Distance

Returns the maximum distance from every node to any other node in the tree.
 $O(6V) = O(V)$

```
pll mostDistantFrom(const vector<vll> &adj, ll n, ll root) {
    // O(V)
    // 0 indexed
    ll mostDistantNode = root;
    ll nodeDistance = 0;
    queue<pll> q;
    vector<char> vis(n);
    q.emplace(root, 0);
    vis[root] = true;
    while (!q.empty()) {
```

```
        auto [node, dist] = q.front();
        q.pop();
        if (dist > nodeDistance) {
            nodeDistance = dist;
            mostDistantNode = node;
        }
        for (auto u : adj[node]) {
            if (!vis[u]) {
                vis[u] = true;
                q.emplace(u, dist + 1);
            }
        }
    }
    return {mostDistantNode, nodeDistance};
}

ll twoNodesDist(const vector<vll> &adj, ll n, ll a, ll b) {
    queue<pll> q;
    vector<char> vis(n);
    q.emplace(a, 0);
    while (!q.empty()) {
        auto [node, dist] = q.front();
        q.pop();
        if (node == b) return dist;
        for (auto u : adj[node]) {
            if (!vis[u]) {
                vis[u] = true;
                q.emplace(u, dist + 1);
            }
        }
    }
    return -1;
}

tuple<ll, ll, ll> tree_diameter(const vector<vll> &adj,
                                ll n) {
    // returns two points of the diameter and the diameter
    // itself
    auto [node1, dist1] = mostDistantFrom(adj, n, 0); // O(V)
    auto [node2, dist2] =
        mostDistantFrom(adj, n, node1); // O(V)
    auto diameter =
        twoNodesDist(adj, n, node1, node2); // O(V)
    return make_tuple(node1, node2, diameter);
}
```



```

vll everyDistanceFromNode(const vector<vll> &adj, ll n,
                        ll root) {
    // Single Source Shortest Path, from a given root
    queue<pair<ll, ll>> q;
    vll ans(n, -1);
    ans[root] = 0;
    q.emplace(root, 0);
    while (!q.empty()) {
        auto [u, d] = q.front();
        q.pop();

        for (auto w : adj[u]) {
            if (ans[w] != -1) continue;
            ans[w] = d + 1;
            q.emplace(w, d + 1);
        }
    }
    return ans;
}

vll maxDistances(const vector<vll> &adj, ll n) {
    auto [node1, node2, diameter] =
        tree_diameter(adj, n); // O(3V)
    auto distances1 =
        everyDistanceFromNode(adj, n, node1); // O(V)
    auto distances2 =
        everyDistanceFromNode(adj, n, node2); // O(V)
    vll ans(n);
    for (int i = 0; i < n; ++i)
        ans[i] = max(distances1[i], distances2[i]); // O(V)
    return ans;
}

```

6 Math

6.1 GCD

```

ll gcd(ll a, ll b) { return b ? gcd(b, a % b) : a; }

```

6.2 LCM

```

ll gcd(ll a, ll b) { return b ? gcd(b, a % b) : a; }
ll lcm(ll a, ll b) { return a / gcd(a, b) * b; }

```

6.3 Arithmetic Progression Sum

- s : first term
- d : common difference
- n : number of terms

```

ll arithmeticProgressionSum(ll s, ll d, ll n) {
    return (s + (s + d * (n - 1))) * n / 2ll;
}

```

6.4 Binomial MOD

Precompute every factorial until $maxn$ ($O(maxn)$) allowing to answer the $\binom{n}{k}$ in $O(\log mod)$ time, due to the fastpow. Note that it needs $O(maxn)$ in memory.

```

const ll MOD = 1e9 + 7;
const ll MAXN = 1'000'000;
ll FACT[MAXN + 1];
void precompute() {
    #warning Remember to call precompute before use binommod !
    FACT[0] = 1;
    for (ll i = 1; i <= MAXN; i++) {
        FACT[i] = (FACT[i - 1] * i) % MOD;
    }
}

ll fpow(ll a, ll k) {
    ll ret = 1;
    while (k) {
        if (k & 1) ret = (ret * a) % MOD;
        a = (a * a) % MOD;
        k >>= 1;
    }
    return ret;
}

ll binommod(ll n, ll k) {
    ll upper = FACT[n];
    ll lower = (FACT[k] * FACT[n - k]) % MOD;
    return (upper * fpow(lower, MOD - 2ll)) % MOD;
}

```

6.5 Binomial

$O(nm)$ time, $O(m)$ space
 Equal to n choose k

```

11 binom(11 n, 11 k) {
    if (k > n) return 0;
    v11 dp(k + 1, 0);
    dp[0] = 1;
    for (11 i = 1; i <= n; i++)
        for (11 j = k; j > 0; j--) dp[j] = dp[j] + dp[j - 1];
    return dp[k];
}

```

6.6 Chinese Remainder Theorem

Finds the solution x to the n modular equations.

$$x \equiv a_1 \pmod{m_1}$$

...

$$x \equiv a_n \pmod{m_n}$$

The m_i don't need to be coprime, if there is no solution then it returns -1.

```

tuple<11, 11, 11> ext_gcd(11 a, 11 b) {
    if (!a) return {b, 0, 1};
    auto [g, x, y] = ext_gcd(b % a, a);
    return {g, y - b / a * x, x};
}

template <typename T = 11>
struct crt {
    T a, m;

    crt() : a(0), m(1) {}
    crt(T a_, T m_) : a(a_), m(m_) {}
    crt operator*(crt C) {
        auto [g, x, y] = ext_gcd(m, C.m);
        if ((a - C.a) % g != 0) a = -1;
        if (a == -1 or C.a == -1) return crt(-1, 0);
        T lcm = m / g * C.m;
        T ans = a + (x * (C.a - a) / g % (C.m / g)) * m;
        return crt((ans % lcm + lcm) % lcm, lcm);
    }
};

template <typename T = 11>
struct Congruence {
    T a, m;
};

template <typename T = 11>

```

```

T chinese_remainder_theorem(
    const vector<Congruence<T>> &equations) {
    crt<T> ans;

    for (auto &[a_, m_] : equations) {
        ans = ans * crt<T>(a_, m_);
    }

    return ans.a;
}

```

6.7 Derangement / Matching Problem

Computes the derangement of N , which is given by the formula :

$$D_N = N! \left(1 - \frac{1}{1!} + \frac{1}{2!} - \frac{1}{3!} + \dots + (-1)^N \frac{1}{N!}\right)$$

time: $O(N)$

```

#warning Remember to call precompute !
const 11 MOD = 1e9 + 7;
const int MAXN(1'000'000);
11 fats[MAXN + 1];
void precompute() {
    fats[0] = 1;
    for (11 i = 1; i <= MAXN; i++) {
        fats[i] = (fats[i - 1] * i) % MOD;
    }
}

11 fastpow(11 a, 11 p, 11 m) {
    11 ret = 1;
    while (p) {
        if (p & 1) ret = (ret * a) % MOD;
        p >>= 1;
        a = (a * a) % MOD;
    }
    return ret;
}

11 divmod(11 a, 11 b) {
    return (a * fastpow(b, MOD - 2, MOD)) % MOD;
}

11 derangement(const 11 n) {
    11 ans = fats[n];
    for (11 i = 1; i <= n; i++) {
        11 k = divmod(fats[n], fats[i]);

```

```

    if (i & 1) {
        ans = (ans - k + MOD) % MOD;
    } else {
        ans = (ans + k) % MOD;
    }
}
return ans;
}

```

6.8 Euler phi $\varphi(n)$ (in range)

Computes the number of positive integers less than n that are coprimes with n , in the range $[1, n]$, in $O(N \log N)$.

```

const int MAX = 1e6;
vi range_phi(int n) {
    bitset<MAX> sieve;
    vi phi(n + 1);

    iota(phi.begin(), phi.end(), 0);
    sieve.set();

    for (int p = 2; p <= n; p += 2) phi[p] /= 2;
    for (int p = 3; p <= n; p += 2) {
        if (sieve[p]) {
            for (int j = p; j <= n; j += p) {
                sieve[j] = false;
                phi[j] /= p;
                phi[j] *= (p - 1);
            }
        }
    }

    return phi;
}

```

6.9 Euler phi $\varphi(n)$

Computes the number of positive integers less than n that are coprimes with n , in $O(\sqrt{N})$.

```

int phi(int n) {
    if (n == 1) return 1;

    auto fs = factorization(n); // a vector of pair or a map
    auto res = n;

```

```

    for (auto [p, k] : fs) {
        res /= p;
        res *= (p - 1);
    }

    return res;
}

```

6.10 Factorial Factorization

Computes the factorization of $n!$ in $\pi(N) * \log n$

```

// O(logN)
ll E(ll n, ll p) {
    ll k = 0, b = p;
    while (b <= n) {
        k += n / b;
        b *= p;
    }
    return k;
}

// O(pi(N)*logN)
map<ll, ll> factorial_factorization(ll n,
                                   const vll &primes) {

    map<ll, ll> fs;
    for (const auto &p : primes) {
        if (p > n) break;
        fs[p] = E(n, p);
    }
    return fs;
}

```

6.11 Factorization (Pollard Rho)

Factorizes a number into its prime factors in $O(n^{\frac{1}{4}} * \log(n))$.

```

ll mul(ll a, ll b, ll m) {
    ll ret = a * b - (ll)((ld)1 / m * a * b + 0.5) * m;
    return ret < 0 ? ret + m : ret;
}

ll pow(ll a, ll b, ll m) {
    ll ans = 1;
    for (; b > 0; b /= 2ll, a = mul(a, a, m)) {
        if (b % 2ll == 1) ans = mul(ans, a, m);
    }
}

```

```

}
return ans;
}

bool prime(ll n) {
    if (n < 2) return 0;
    if (n <= 3) return 1;
    if (n % 2 == 0) return 0;

    ll r = __builtin_ctzll(n - 1), d = n >> r;
    for (int a :
        {2, 325, 9375, 28178, 450775, 9780504, 795265022}) {
        ll x = pow(a, d, n);
        if (x == 1 or x == n - 1 or a % n == 0) continue;

        for (int j = 0; j < r - 1; j++) {
            x = mul(x, x, n);
            if (x == n - 1) break;
        }
        if (x != n - 1) return 0;
    }
    return 1;
}

ll rho(ll n) {
    if (n == 1 or prime(n)) return n;
    auto f = [n](ll x) { return mul(x, x, n) + 1; };

    ll x = 0, y = 0, t = 30, prd = 2, x0 = 1, q;
    while (t % 40 != 0 or gcd(prd, n) == 1) {
        if (x == y) x = ++x0, y = f(x);
        q = mul(prd, abs(x - y), n);
        if (q != 0) prd = q;
        x = f(x), y = f(f(y)), t++;
    }
    return gcd(prd, n);
}

vll fact(ll n) {
    if (n == 1) return {};
    if (prime(n)) return {n};
    ll d = rho(n);
    vll l = fact(d), r = fact(n / d);
    l.insert(l.end(), r.begin(), r.end());
    return l;
}

```

```

}

```

6.12 Factorization

Computes the factorization of n in $O(\sqrt{n})$.

```

map<ll, ll> factorization(ll n) {
    map<ll, ll> ans;
    for (ll i = 2; i * i <= n; i++) {
        ll count = 0;
        for (; n % i == 0; count++, n /= i)
            ;
        if (count) ans[i] = count;
    }
    if (n > 1) ans[n]++;
    return ans;
}

```

6.13 Fast pow

Computes $a^b \pmod m$ in $O(\log N)$.

```

ll fpow(ll a, ll b, ll m) {
    ll ret = 1;
    while (b) {
        if (b & 1) ret = (ret * a) % m;
        b >>= 1;
        a = (a * a) % m;
    }
    return ret;
}

ll fpow2(ll a, ll b, ll m) {
    if (!b) return 1;
    ll ans = fpow2((a * a) % m, b / 2, m);
    return b & 1 ? (a * ans) % m : ans;
}

```

6.14 FFT Convolution

Performs convolution in a vector duh !

```

const ld PI = acos(-1);

/* change the ld to double may increase performance =D */
struct num {
    ld a{0.0}, b{0.0};
}

```

```

num() {}
num(ld na) : a{na} {}
num(ld na, ld nb) : a{na}, b{nb} {}

const num operator+(const num& c) const {
    return num(a + c.a, b + c.b);
}
const num operator-(const num& c) const {
    return num(a - c.a, b - c.b);
}
const num operator*(const num& c) const {
    return num(a * c.a - b * c.b, a * c.b + b * c.a);
}
const num operator/(const ll& c) const {
    return num(a / c, b / c);
}
};

void fft(vector<num>& a, bool invert) {
    int n = len(a);
    for (int i = 1, j = 0; i < n; i++) {
        int bit = n >> 1;
        for (; j & bit; bit >>= 1) j ^= bit;
        j ^= bit;
        if (i < j) swap(a[i], a[j]);
    }
    for (int sz = 2; sz <= n; sz <= 1) {
        ld ang = 2 * PI / sz * (invert ? -1 : 1);
        num wsz(cos(ang), sin(ang));
        for (int i = 0; i < n; i += sz) {
            num w(1);
            rep(j, 0, sz / 2) {
                num u = a[i + j], v = a[i + j + sz / 2] * w;
                a[i + j] = u + v;
                a[i + j + sz / 2] = u - v;
                w = w * wsz;
            }
        }
    }
    if (invert)
        for (num& x : a) x = x / n;
}

vi conv(vi const a, vi const b) {
    vector<num> fa(all(a));

```

```

vector<num> fb(all(b));
int n = 1;
while (n < len(a) + len(b)) n <= 1;
fa.resize(n);
fb.resize(n);
fft(fa, false);
fft(fb, false);
rep(i, 0, n) fa[i] = fa[i] * fb[i];
fft(fa, true);
vi result(n);
rep(i, 0, n) result[i] = round(fa[i].a);
while (len(result) and result.back() == 0)
    result.pop_back();

/* Uncomment this line if you want a boolean convolution*/
for (auto& xi : result) xi = min(xi, 1ll);

return result;
}

vll poly_exp(vll& ps, int k) {
    vll ret(len(ps));
    auto base = ps;
    ret[0] = 1;

    while (k) {
        if (k & 1) ret = conv(ret, base);
        k >>= 1;
        base = conv(base, base);
    }

    return ret;
}

```

6.15 Find Multiplicative Inverse

```

ll inv(ll a, ll m) {
    return a > 1ll ? m - inv(m % a, a) * m / a : 1ll;
}

```

6.16 Linear Diophantine Equation: Find any solution

Given a, b, c finds the solution to the equation $ax + by = c$, the result will be stored in the reference variables x_0 and y_0
time: $O(\log \min(a, b))$

```

template <typename T>
tuple<T, T, T> ext_gcd(T a, T b) {

```

```

    if (b == 0) return {a, 1, 0};

    auto [d, x1, y1] = ext_gcd(b, a % b);

    return {d, y1, x1 - y1 * (a / b)};
}

template <typename T>
tuple<bool, T, T> find_any_solution(T a, T b, T c) {
    assert(a != 0 or b != 0);
    #warning Be careful with overflow, use __int128 if needed !

    auto [d, x0, y0] =
        ext_gcd(a < 0 ? -a : a, b < 0 ? -b : b);

    if (c % d) return {false, 0, 0};

    x0 *= c / d;
    y0 *= c / d;
    if (a < 0) x0 = -x0;
    if (b < 0) y0 = -y0;

    return {true, x0, y0};
}

// optional if you want to use __int128
void print(__int128 x) {
    if (x < 0) {
        cout << '-';
        x = -x;
    }
    if (x > 9) print(x / 10);
    cout << (char)((x % 10) + '0');
}

__int128 read() {
    string s;
    cin >> s;
    __int128 x = 0;
    for (auto c : s) {
        if (c != '-') x += c - '0';
        x *= 10;
    }
    x /= 10;
    if (s[0] == '-') x = -x;

```

```

    return x;
}

```

6.17 Gauss Elimination

```

template <size_t Dim>
struct GaussianElimination {
    vector<ll> basis;
    size_t size;

    GaussianElimination() : basis(Dim + 1), size(0) {}

    void insert(ll x) {
        for (ll i = Dim; i >= 0; i--) {
            if ((x & 1ll << i) == 0) continue;

            if (!basis[i]) {
                basis[i] = x;
                size++;
                break;
            }

            x ^= basis[i];
        }
    }

    void normalize() {
        for (ll i = Dim; i >= 0; i--)
            for (ll j = i - 1; j >= 0; j--)
                if (basis[i] & 1ll << j) basis[i] ^= basis[j];
    }

    bool check(ll x) {
        for (ll i = Dim; i >= 0; i--) {
            if ((x & 1ll << i) == 0) continue;

            if (!basis[i]) return false;

            x ^= basis[i];
        }

        return true;
    }

    auto operator[](ll k) { return at(k); }
}

```

```

11 at(11 k) {
    11 ans = 0;
    11 total = 111 << size;
    for (11 i = Dim; ~i; i--) {
        if (!basis[i]) continue;

        11 mid = total >> 111;
        if ((mid < k and (ans & 111 << i) == 0) ||
            (k <= mid and (ans & 111 << i)))
            ans ^= basis[i];

        if (mid < k) k -= mid;

        total >>= 111;
    }
    return ans;
}

11 at_normalized(11 k) {
    11 ans = 0;
    k--;
    for (size_t i = 0; i <= Dim; i++) {
        if (!basis[i]) continue;
        if (k & 1) ans ^= basis[i];
        k >>= 1;
    }
    return ans;
}
};

```

6.18 Integer Partition

Find the total of ways to partition a given number N in such way that none of the parts is greater than K .

Remember to memset everything to -1 before using it

time: $O(N \cdot \min(N, K))$

memory: $O(N)$

```

const 11 MOD = 1000000007;
const int MAXN(100);
11 memo[MAXN + 1];
11 dp(11 n, 11 k = oo) {
    if (n == 0) return 1;
    11 &ans = memo[n];
    if (ans != -1) return ans;

    ans = 0;

```

```

    for (int i = 1; i <= min(n, k); i++) {
        ans = (ans + dp(n - i, k)) % MOD;
    }

    return ans;
}

```

6.19 Integer Mod

```

const 11 INF = 1e18;
const 11 mod = 998244353;
template <11 MOD = mod>
struct Modular {
    11 value;
    static const 11 MOD_value = MOD;

    Modular(11 v = 0) {
        value = v % MOD;
        if (value < 0) value += MOD;
    }

    Modular(11 a, 11 b) : value(0) {
        *this += a;
        *this /= b;
    }

    Modular& operator+=(Modular const& b) {
        value += b.value;
        if (value >= MOD) value -= MOD;
        return *this;
    }

    Modular& operator-=(Modular const& b) {
        value -= b.value;
        if (value < 0) value += MOD;
        return *this;
    }

    Modular& operator*=(Modular const& b) {
        value = (11)value * b.value % MOD;
        return *this;
    }

    friend Modular mexp(Modular a, 11 e) {
        Modular res = 1;
        while (e) {
            if (e & 1) res *= a;
            a *= a;

```

```

    e >>= 1;
}
return res;
}
friend Modular inverse(Modular a) {
    return mexp(a, MOD - 2);
}

Modular& operator/=(Modular const& b) {
    return *this *= inverse(b);
}
friend Modular operator+(Modular a, Modular const b) {
    return a += b;
}
Modular operator++(int) {
    return this->value = (this->value + 1) % MOD;
}
Modular operator++() {
    return this->value = (this->value + 1) % MOD;
}
friend Modular operator-(Modular a, Modular const b) {
    return a -= b;
}
friend Modular operator-(Modular const a) {
    return 0 - a;
}
Modular operator--(int) {
    return this->value = (this->value - 1 + MOD) % MOD;
}
Modular operator--() {
    return this->value = (this->value - 1 + MOD) % MOD;
}
friend Modular operator*(Modular a, Modular const b) {
    return a *= b;
}
friend Modular operator/(Modular a, Modular const b) {
    return a /= b;
}
friend std::ostream& operator<<(std::ostream& os,
                                Modular const& a) {
    return os << a.value;
}
friend bool operator==(Modular const& a,
                        Modular const& b) {

```

```

    return a.value == b.value;
}
friend bool operator!=(Modular const& a,
                        Modular const& b) {
    return a.value != b.value;
}
};

```

6.20 Linear Recurrence

Find the n -th term of a linear recurrence, given the recurrence rec and the first K values of the recurrence, remember that $first_k[i]$ is the value of $f(i)$, considering 0-indexing.
time: $O(K^3 \log N)$

```

using ll = long long;

template <typename T>
vector<vector<T>> prod(vector<vector<T>> &a,
                      vector<vector<T>> &b, const ll mod) {

    int n = a.size();
    vector<vector<T>> c(n, vector<T>(n));

    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            for (int k = 0; k < n; k++) {
                c[i][j] =
                    (c[i][j] + ((a[i][k] * b[k][j]) % mod)) % mod;
            }
        }
    }

    return c;
}

template <typename T>
vector<vector<T>> fpow(vector<vector<T>> &xs, ll p,
                    ll mod) {
    vector<vector<T>> ans(xs.size(), vector<T>(xs.size()));
    for (int i = 0; i < (int)xs.size(); i++) ans[i][i] = 1;

    for (auto b = xs; p; p >>= 1, b = prod(b, b, mod))
        if (p & 1) ans = prod(ans, b, mod);

    return ans;
}

ll linear_req(vector<vector<ll>> rec, vector<ll> first_k,

```



```

        ll n, ll mod) {
int k = first_k.size();
if (n < k) {
    return first_k[n];
}

ll n2 = n - k + 1;
rec = fpow(rec, n2, mod);

ll ret = 0;

for (int i = 0; i < k; i++) {
    ret = (ret + (rec.back()[i] * first_k[i]) % mod) % mod;
}

return ret;
}

```

6.21 N Choose K (elements)

process every possible combination of K elements from N elements, those index marked as 1 in the index vector says which elements are chosen at that moment.

Time : $O(\binom{N}{K} \cdot O(\text{process}))$

```

void process(vi &index) {
    for (int i = 0; i < len(index); i++) {
        if (index[i]) cout << i << " \n"[i == len(index) - 1];
    }
}

```

```

void n_choose_k(int n, in k) {
    vi index(n);
    fill(index.end() - k, index.end(), 1);
}

```

```

do {
    process(index);
} while (next_permutation(all(index)));
}

```

6.22 Matrix Exponentiation

```
const ll MOD = 1'000'000'007;
```

```

template <typename T>
vector<vector<T>> prod(vector<vector<T>> &a,
                    vector<vector<T>> &b) {

```

```

int n = len(a);
vector<vector<T>> c(n, vector<T>(n));

for (int i = 0; i < n; i++) {
    for (int j = 0; j < n; j++) {
        for (int k = 0; k < n; k++) {
            c[i][j] =
                (c[i][j] + ((a[i][k] * b[k][j]) % MOD)) % MOD;
        }
    }
}

return c;
}

```

```

template <typename T>
vector<vector<T>> fpow(vector<vector<T>> &xs, ll p) {
    vector<vector<T>> ans(len(xs), vector<T>(len(xs)));
    for (int i = 0; i < len(xs); i++) ans[i][i] = 1;

    auto b = xs;
    while (p) {
        if (p & 1) ans = prod(ans, b);
        p >>= 1;
        b = prod(b, b);
    }
    return ans;
}

```

6.23 NTT integer convolution and exponentiation

Convolution finds the product a and b , and exp finds a^k

time: convolution $O(N \cdot \log N)$, exponentiation: $O(\log K \cdot N \cdot \log N)$

```

/*
=====
*/

/*===== MINT ===== */
template <int _mod>
struct mint {
    ll expo(ll b, ll e) {
        ll ret = 1;
        while (e) {
            if (e % 2) ret = ret * b % _mod;
            e /= 2, b = b * b % _mod;
        }
        return ret;
    }
}

```

```

}
ll inv(ll b) { return expo(b, _mod - 2); }

using m = mint;
ll v;
mint() : v(0) {}
mint(ll v_) {
    if (v_ >= _mod or v_ <= -_mod) v_ %= _mod;
    if (v_ < 0) v_ += _mod;
    v = v_;
}
m& operator+=(const m& a) {
    v += a.v;
    if (v >= _mod) v -= _mod;
    return *this;
}
m& operator-=(const m& a) {
    v -= a.v;
    if (v < 0) v += _mod;
    return *this;
}
m& operator*=(const m& a) {
    v = v * ll(a.v) % _mod;
    return *this;
}
m& operator/=(const m& a) {
    v = v * inv(a.v) % _mod;
    return *this;
}
m operator-() { return m(-v); }
m& operator^=(ll e) {
    if (e < 0) {
        v = inv(v);
        e = -e;
    }
    v = expo(v, e);
    // possivel otimizacao:
    // cuidado com 0^0
    // v = expo(v, e%(p-1));
    return *this;
}
bool operator==(const m& a) { return v == a.v; }
bool operator!=(const m& a) { return v != a.v; }

friend istream& operator>>(istream& in, m& a) {

```

```

    ll val;
    in >> val;
    a = m(val);
    return in;
}
friend ostream& operator<<(ostream& out, m a) {
    return out << a.v;
}
friend m operator+(m a, m b) { return a += b; }
friend m operator-(m a, m b) { return a -= b; }
friend m operator*(m a, m b) { return a *= b; }
friend m operator/(m a, m b) { return a /= b; }
friend m operator^(m a, ll e) { return a ^= e; }
};
/*===== END MINT ===== */

/*===== ntt int convolution =====*/
const ll MOD1 = 998244353;
const ll MOD2 = 754974721;
const ll MOD3 = 167772161;

template <int _mod>
void ntt(vector<mint<_mod>>& a, bool rev) {
    int n = len(a);
    auto b = a;
    assert(!(n & (n - 1)));
    mint<_mod> g = 1;
    while ((g ^ (_mod / 2)) == 1) g += 1;
    if (rev) g = 1 / g;

    for (int step = n / 2; step; step /= 2) {
        mint<_mod> w = g ^ (_mod / (n / step)), wn = 1;
        for (int i = 0; i < n / 2; i += step) {
            for (int j = 0; j < step; j++) {
                auto u = a[2 * i + j], v = wn * a[2 * i + j + step];
                b[i + j] = u + v;
                b[i + n / 2 + j] = u - v;
            }
            wn = wn * w;
        }
        swap(a, b);
    }
    if (rev) {
        auto n1 = mint<_mod>(1) / n;
        for (auto& x : a) x *= n1;
    }
}

```

```

    }
}

template <ll _mod>
vector<mint<_mod>> convolution(
    const vector<mint<_mod>>& a,
    const vector<mint<_mod>>& b) {
    vector<mint<_mod>> l(all(a)), r(all(b));
    int N = len(l) + len(r) - 1, n = 1;
    while (n <= N) n *= 2;
    l.resize(n), r.resize(n);
    ntt(l, false), ntt(r, false);
    for (int i = 0; i < n; i++) l[i] *= r[i];
    ntt(l, true);
    l.resize(N);

    // Uncommnent for a boolean convolution :)
    /*

    for (auto& li : l) {
        li.v = min(li.v, 1ll);
    }
    */

    return l;
}

template <ll _mod>
vector<mint<_mod>> poly_exp(vector<mint<_mod>>& ps, int k) {
    vector<mint<_mod>> ret(len(ps));
    auto base = ps;
    ret[0] = 1;

    while (k) {
        if (k & 1) ret = convolution(ret, base);
        k >>= 1;
        base = convolution(base, base);
    }

    return ret;
}

```

6.24 NTT Integer Convolution (combine 2 modules)

Computes the convolution between polynomials (vectors) a and b

This is pure magic !
time: $O(N \log N)$

```

/*
=====
*/
*/
/*===== MINT ===== */
template <int _mod>
struct mint {
    ll expo(ll b, ll e) {
        ll ret = 1;
        while (e) {
            if (e % 2) ret = ret * b % _mod;
            e /= 2, b = b * b % _mod;
        }
        return ret;
    }
    ll inv(ll b) { return expo(b, _mod - 2); }

    using m = mint;
    ll v;
    mint() : v(0) {}
    mint(ll v_) {
        if (v_ >= _mod or v_ <= -_mod) v_ %= _mod;
        if (v_ < 0) v_ += _mod;
        v = v_;
    }
    m& operator+=(const m& a) {
        v += a.v;
        if (v >= _mod) v -= _mod;
        return *this;
    }
    m& operator-=(const m& a) {
        v -= a.v;
        if (v < 0) v += _mod;
        return *this;
    }
    m& operator*=(const m& a) {
        v = v * ll(a.v) % _mod;
        return *this;
    }
    m& operator/=(const m& a) {
        v = v * inv(a.v) % _mod;
        return *this;
    }
    m operator-() { return m(-v); }
}

```

```

m& operator^=(ll e) {
    if (e < 0) {
        v = inv(v);
        e = -e;
    }
    v = expo(v, e);
    // possivel otimizacao:
    // cuidado com 0^0
    // v = expo(v, e%(p-1));
    return *this;
}

bool operator==(const m& a) { return v == a.v; }
bool operator!=(const m& a) { return v != a.v; }

friend istream& operator>>(istream& in, m& a) {
    ll val;
    in >> val;
    a = m(val);
    return in;
}

friend ostream& operator<<(ostream& out, m a) {
    return out << a.v;
}

}

friend m operator+(m a, m b) { return a += b; }
friend m operator-(m a, m b) { return a -= b; }
friend m operator*(m a, m b) { return a *= b; }
friend m operator/(m a, m b) { return a /= b; }
friend m operator^(m a, ll e) { return a ^= e; }
};

/*===== END MINT ===== */

/*===== ntt int convolution =====*/
const ll MOD1 = 998244353;
const ll MOD2 = 754974721;
const ll MOD3 = 167772161;

template <int _mod>
void ntt(vector<mint<_mod>>& a, bool rev) {
    int n = len(a);
    auto b = a;
    assert(!(n & (n - 1)));
    mint<_mod> g = 1;
    while ((g ^ (_mod / 2)) == 1) g += 1;
    if (rev) g = 1 / g;

```

```

    for (int step = n / 2; step; step /= 2) {
        mint<_mod> w = g ^ (_mod / (n / step)), wn = 1;
        for (int i = 0; i < n / 2; i += step) {
            for (int j = 0; j < step; j++) {
                auto u = a[2 * i + j], v = wn * a[2 * i + j + step];
                b[i + j] = u + v;
                b[i + n / 2 + j] = u - v;
            }
            wn = wn * w;
        }
        swap(a, b);
    }
    if (rev) {
        auto n1 = mint<_mod>(1) / n;
        for (auto& x : a) x *= n1;
    }
}

tuple<ll, ll, ll> ext_gcd(ll a, ll b) {
    if (!a) return {b, 0, 1};
    auto [g, x, y] = ext_gcd(b % a, a);
    return {g, y - b / a * x, x};
}

template <typename T = ll>
struct crt {
    T a, m;

    crt() : a(0), m(1) {}
    crt(T a_, T m_) : a(a_), m(m_) {}
    crt operator*(crt C) {
        auto [g, x, y] = ext_gcd(m, C.m);
        if ((a - C.a) % g != 0) a = -1;
        if (a == -1 or C.a == -1) return crt(-1, 0);
        T lcm = m / g * C.m;
        T ans = a + (x * (C.a - a) / g % (C.m / g)) * m;
        return crt((ans % lcm + lcm) % lcm, lcm);
    }
};

template <typename T = ll>
struct Congruence {
    T a, m;
};

```

```

template <typename T = ll>
T chinese_remainder_theorem(
    const vector<Congruence<T>>& equations) {
    crt<T> ans;

    for (auto& [a_, m_] : equations) {
        ans = ans * crt<T>(a_, m_);
    }

    return ans.a;
}

#define int long long
template <ll m1, ll m2>
vll merge_two_mods(const vector<mint<m1>>& a,
                   const vector<mint<m2>>& b) {
    int n = len(a);
    vll ans(n);
    for (int i = 0; i < n; i++) {
        auto cur = crt<ll>();
        auto ai = a[i].v;
        auto bi = b[i].v;
        cur = cur * crt<ll>(ai, m1);
        cur = cur * crt<ll>(bi, m2);
        ans[i] = cur.a;
    }

    return ans;
}

vll convolution_2mods(const vll& a, const vll& b) {
    vector<mint<MOD1>> l(all(a)), r(all(b));
    int N = len(l) + len(r) - 1, n = 1;
    while (n <= N) n *= 2;
    l.resize(n), r.resize(n);
    ntt(l, false), ntt(r, false);
    for (int i = 0; i < n; i++) l[i] *= r[i];
    ntt(l, true);
    l.resize(N);

    vector<mint<MOD2>> l2(all(a)), r2(all(b));
    l2.resize(n), r2.resize(n);
    ntt(l2, false), ntt(r2, false);
    rep(i, 0, n) l2[i] *= r2[i];
    ntt(l2, true);

```

```

    l2.resize(N);

    return merge_two_mods(l, l2);
}

vll poly_exp(const vll& xs, ll k) {
    vll ret(len(xs));
    ret[0] = 1;
    auto base = xs;
    while (k) {
        if (k & 1) ret = convolution_2mods(ret, base);
        k >>= 1;
        base = convolution_2mods(base, base);
    }

    return ret;
}

```

6.25 Power Sum

Calculates $K^0 + K^1 + \dots + K^n$

```

ll powersum(ll n, ll k) {
    return (fastpow(n, k + 1) - 1) / (k - 1);
}

```

6.26 Sieve list primes

List every prime until MAXN, $O(N \log N)$ in time and $O(MAXN)$ in memory.

```

const ll MAXN = 2e5;
vll list_primes(ll n = MAXN) {
    vll ps;
    bitset<MAXN + 1> sieve;
    sieve.set();
    sieve.reset(1);
    for (ll i = 2; i <= n; ++i) {
        if (sieve[i]) ps.push_back(i);
        for (ll j = i * 2; j <= n; j += i) {
            sieve.reset(j);
        }
    }
    return ps;
}

```

7 Primitives

7.1 Bigint

```
const int maxn = 1e2 + 14, lg = 15;
const int base = 1000000000;
const int base_digits = 9;
struct bigint {
    vi a;
    int sign;

    int size() {
        if (a.empty()) return 0;
        int ans = (a.size() - 1) * base_digits;
        int ca = a.back();
        while (ca) ans++, ca /= 10;
        return ans;
    }
    bigint operator^(const bigint &v) {
        bigint ans = 1, a = *this, b = v;
        while (!b.isZero()) {
            if (b % 2) ans *= a;
            a *= a, b /= 2;
        }
        return ans;
    }
    string to_string() {
        stringstream ss;
        ss << *this;
        string s;
        ss >> s;
        return s;
    }
    int sumof() {
        string s = to_string();
        int ans = 0;
        for (auto c : s) ans += c - '0';
        return ans;
    }
    /*</arpa>*/
    bigint() : sign(1) {}

    bigint(long long v) { *this = v; }

    bigint(const string &s) { read(s); }
```

```
void operator=(const bigint &v) {
    sign = v.sign;
    a = v.a;
}

void operator=(long long v) {
    sign = 1;
    a.clear();
    if (v < 0) sign = -1, v = -v;
    for (; v > 0; v = v / base) a.push_back(v % base);
}

bigint operator+(const bigint &v) const {
    if (sign == v.sign) {
        bigint res = v;

        for (int i = 0, carry = 0;
             i < (int)max(a.size(), v.a.size()) || carry;
             ++i) {
            if (i == (int)res.a.size()) res.a.push_back(0);
            res.a[i] += carry + (i < (int)a.size() ? a[i] : 0);
            carry = res.a[i] >= base;
            if (carry) res.a[i] -= base;
        }
        return res;
    }
    return *this - (-v);
}

bigint operator-(const bigint &v) const {
    if (sign == v.sign) {
        if (abs() >= v.abs()) {
            bigint res = *this;
            for (int i = 0, carry = 0;
                 i < (int)v.a.size() || carry; ++i) {
                res.a[i] -=
                    carry + (i < (int)v.a.size() ? v.a[i] : 0);
                carry = res.a[i] < 0;
                if (carry) res.a[i] += base;
            }
            res.trim();
            return res;
        }
        return -(v - *this);
    }
}
```

```

    }
    return *this + (-v);
}

void operator*=(int v) {
    if (v < 0) sign = -sign, v = -v;
    for (int i = 0, carry = 0; i < (int)a.size() || carry;
        ++i) {
        if (i == (int)a.size()) a.push_back(0);
        long long cur = a[i] * (long long)v + carry;
        carry = (int)(cur / base);
        a[i] = (int)(cur % base);
        // asm("divl %%ecx" : "=a"(carry), "=d"(a[i]) :
        // "A"(cur), "c"(base));
    }
    trim();
}

bigint operator*(int v) const {
    bigint res = *this;
    res *= v;
    return res;
}

void operator*=(long long v) {
    if (v < 0) sign = -sign, v = -v;
    if (v > base) {
        *this =
            *this * (v / base) * base + *this * (v % base);
        return;
    }
    for (int i = 0, carry = 0; i < (int)a.size() || carry;
        ++i) {
        if (i == (int)a.size()) a.push_back(0);
        long long cur = a[i] * (long long)v + carry;
        carry = (int)(cur / base);
        a[i] = (int)(cur % base);
        // asm("divl %%ecx" : "=a"(carry), "=d"(a[i]) :
        // "A"(cur), "c"(base));
    }
    trim();
}

bigint operator*(long long v) const {
    bigint res = *this;

```

```

    res *= v;
    return res;
}

friend pair<bigint, bigint> divmod(const bigint &a1,
                                   const bigint &b1) {
    int norm = base / (b1.a.back() + 1);
    bigint a = a1.abs() * norm;
    bigint b = b1.abs() * norm;
    bigint q, r;
    q.a.resize(a.a.size());

    for (int i = a.a.size() - 1; i >= 0; i--) {
        r *= base;
        r += a.a[i];
        int s1 =
            r.a.size() <= b.a.size() ? 0 : r.a[b.a.size()];
        int s2 = r.a.size() <= b.a.size() - 1
            ? 0
            : r.a[b.a.size() - 1];
        int d = ((long long)base * s1 + s2) / b.a.back();
        r -= b * d;
        while (r < 0) r += b, --d;
        q.a[i] = d;
    }

    q.sign = a1.sign * b1.sign;
    r.sign = a1.sign;
    q.trim();
    r.trim();
    return make_pair(q, r / norm);
}

bigint operator/(const bigint &v) const {
    return divmod(*this, v).first;
}

bigint operator%(const bigint &v) const {
    return divmod(*this, v).second;
}

void operator/=(int v) {
    if (v < 0) sign = -sign, v = -v;
    for (int i = (int)a.size() - 1, rem = 0; i >= 0; --i) {
        long long cur = a[i] + rem * (long long)base;

```

```

        a[i] = (int)(cur / v);
        rem = (int)(cur % v);
    }
    trim();
}

bigint operator/(int v) const {
    bigint res = *this;
    res /= v;
    return res;
}

int operator%(int v) const {
    if (v < 0) v = -v;
    int m = 0;
    for (int i = a.size() - 1; i >= 0; --i)
        m = (a[i] + m * (long long)base) % v;
    return m * sign;
}

void operator+=(const bigint &v) { *this = *this + v; }
void operator-=(const bigint &v) { *this = *this - v; }
void operator*=(const bigint &v) { *this = *this * v; }
void operator/=(const bigint &v) { *this = *this / v; }

bool operator<(const bigint &v) const {
    if (sign != v.sign) return sign < v.sign;
    if (a.size() != v.a.size())
        return a.size() * sign < v.a.size() * v.sign;
    for (int i = a.size() - 1; i >= 0; i--)
        if (a[i] != v.a[i])
            return a[i] * sign < v.a[i] * sign;
    return false;
}

bool operator>(const bigint &v) const {
    return v < *this;
}

bool operator<=(const bigint &v) const {
    return !(v < *this);
}

bool operator>=(const bigint &v) const {
    return !(*this < v);
}

bool operator==(const bigint &v) const {

```

```

        return !(*this < v) && !(v < *this);
    }

    bool operator!=(const bigint &v) const {
        return *this < v || v < *this;
    }

    void trim() {
        while (!a.empty() && !a.back()) a.pop_back();
        if (a.empty()) sign = 1;
    }

    bool isZero() const {
        return a.empty() || (a.size() == 1 && !a[0]);
    }

    bigint operator-() const {
        bigint res = *this;
        res.sign = -sign;
        return res;
    }

    bigint abs() const {
        bigint res = *this;
        res.sign *= res.sign;
        return res;
    }

    long long longValue() const {
        long long res = 0;
        for (int i = a.size() - 1; i >= 0; i--)
            res = res * base + a[i];
        return res * sign;
    }

    friend bigint gcd(const bigint &a, const bigint &b) {
        return b.isZero() ? a : gcd(b, a % b);
    }

    friend bigint lcm(const bigint &a, const bigint &b) {
        return a / gcd(a, b) * b;
    }

    void read(const string &s) {
        sign = 1;
        a.clear();
        int pos = 0;

```



```

while (pos < (int)s.size() &&
      (s[pos] == '-' || s[pos] == '+')) {
    if (s[pos] == '-') sign = -sign;
    ++pos;
}
for (int i = s.size() - 1; i >= pos; i -= base_digits) {
    int x = 0;
    for (int j = max(pos, i - base_digits + 1); j <= i;
         j++)
        x = x * 10 + s[j] - '0';
    a.push_back(x);
}
trim();
}

friend istream &operator>>(istream &stream, bigint &v) {
    string s;
    stream >> s;
    v.read(s);
    return stream;
}

friend ostream &operator<<(ostream &stream,
                           const bigint &v) {
    if (v.sign == -1) stream << '-';
    stream << (v.a.empty() ? 0 : v.a.back());
    for (int i = (int)v.a.size() - 2; i >= 0; --i)
        stream << setw(base_digits) << setfill('0') << v.a[i];
    return stream;
}

static vector<int> convert_base(const vector<int> &a,
                               int old_digits,
                               int new_digits) {
    vector<long long> p(max(old_digits, new_digits) + 1);
    p[0] = 1;
    for (int i = 1; i < (int)p.size(); i++)
        p[i] = p[i - 1] * 10;
    vector<int> res;
    long long cur = 0;
    int cur_digits = 0;
    for (int i = 0; i < (int)a.size(); i++) {
        cur += a[i] * p[cur_digits];
        cur_digits += old_digits;
        while (cur_digits >= new_digits) {

```

```

            res.push_back(int(cur % p[new_digits]));
            cur /= p[new_digits];
            cur_digits -= new_digits;
        }
    }
    res.push_back((int)cur);
    while (!res.empty() && !res.back()) res.pop_back();
    return res;
}

typedef vector<long long> vll;

static vll karatsubaMultiply(const vll &a, const vll &b) {
    int n = a.size();
    vll res(n + n);
    if (n <= 32) {
        for (int i = 0; i < n; i++)
            for (int j = 0; j < n; j++)
                res[i + j] += a[i] * b[j];
        return res;
    }

    int k = n >> 1;
    vll a1(a.begin(), a.begin() + k);
    vll a2(a.begin() + k, a.end());
    vll b1(b.begin(), b.begin() + k);
    vll b2(b.begin() + k, b.end());

    vll a1b1 = karatsubaMultiply(a1, b1);
    vll a2b2 = karatsubaMultiply(a2, b2);

    for (int i = 0; i < k; i++) a2[i] += a1[i];
    for (int i = 0; i < k; i++) b2[i] += b1[i];

    vll r = karatsubaMultiply(a2, b2);
    for (int i = 0; i < (int)a1b1.size(); i++)
        r[i] -= a1b1[i];
    for (int i = 0; i < (int)a2b2.size(); i++)
        r[i] -= a2b2[i];

    for (int i = 0; i < (int)r.size(); i++)
        res[i + k] += r[i];
    for (int i = 0; i < (int)a1b1.size(); i++)
        res[i] += a1b1[i];
    for (int i = 0; i < (int)a2b2.size(); i++)

```

```

        res[i + n] += a2b2[i];
    return res;
}

bigint operator*(const bigint &v) const {
    vector<int> a6 = convert_base(this->a, base_digits, 6);
    vector<int> b6 = convert_base(v.a, base_digits, 6);
    vll a(a6.begin(), a6.end());
    vll b(b6.begin(), b6.end());
    while (a.size() < b.size()) a.push_back(0);
    while (b.size() < a.size()) b.push_back(0);
    while (a.size() & (a.size() - 1))
        a.push_back(0), b.push_back(0);
    vll c = karatsubaMultiply(a, b);
    bigint res;
    res.sign = sign * v.sign;
    for (int i = 0, carry = 0; i < (int)c.size(); i++) {
        long long cur = c[i] + carry;
        res.a.push_back((int)(cur % 1000000));
        carry = (int)(cur / 1000000);
    }
    res.a = convert_base(res.a, 6, base_digits);
    res.trim();
    return res;
}
};

```

7.2 Integer Mod

```

const ll MOD = 1'000'000'000 + 7;
template <ll _mod = MOD>
struct mint {
    ll value;
    static const ll MOD_value = _mod;

    mint(ll v = 0) {
        value = v % _mod;
        if (value < 0) value += _mod;
    }

    mint(ll a, ll b) : value(0) {
        *this += a;
        *this /= b;
    }

    mint& operator+=(mint const& b) {

```

```

        value += b.value;
        if (value >= _mod) value -= _mod;
        return *this;
    }

    mint& operator-=(mint const& b) {
        value -= b.value;
        if (value < 0) value += _mod;
        return *this;
    }

    mint& operator*=(mint const& b) {
        value = (ll)value * b.value % _mod;
        return *this;
    }

    friend mint mexp(mint a, ll e) {
        mint res = 1;
        while (e) {
            if (e & 1) res *= a;
            a *= a;
            e >>= 1;
        }
        return res;
    }

    friend mint inverse(mint a) { return mexp(a, _mod - 2); }

    mint& operator/=(mint const& b) {
        return *this *= inverse(b);
    }

    friend mint operator+(mint a, mint const b) {
        return a += b;
    }

    mint operator++(int) {
        return this->value = (this->value + 1) % _mod;
    }

    mint operator++() {
        return this->value = (this->value + 1) % _mod;
    }

    friend mint operator-(mint a, mint const b) {
        return a -= b;
    }

    friend mint operator-(mint const a) { return 0 - a; }

    mint operator--(int) {
        return this->value = (this->value - 1 + _mod) % _mod;
    }
}

```

```

mint operator--() {
    return this->value = (this->value - 1 + _mod) % _mod;
}
friend mint operator*(mint a, mint const b) {
    return a *= b;
}
friend mint operator/(mint a, mint const b) {
    return a /= b;
}
friend std::ostream& operator<<(std::ostream& os,
                                mint const& a) {
    return os << a.value;
}
friend bool operator==(mint const& a, mint const& b) {
    return a.value == b.value;
}
friend bool operator!=(mint const& a, mint const& b) {
    return a.value != b.value;
}
};

```

7.3 Matrix

```

template <typename T>
struct Matrix {
    vector<vector<T>> d;

    Matrix() : Matrix(0) {}
    Matrix(int n) : Matrix(n, n) {}
    Matrix(int n, int m)
        : Matrix(vector<vector<T>>(n, vector<T>(m))) {}
    Matrix(const vector<vector<T>> &v) : d(v) {}

    constexpr int n() const { return (int)d.size(); }
    constexpr int m() const {
        return n() ? (int)d[0].size() : 0;
    }

    void rotate() { *this = rotated(); }

    Matrix<T> rotated() const {
        Matrix<T> res(m(), n());
        for (int i = 0; i < m(); i++) {
            for (int j = 0; j < n(); j++) {
                res[i][j] = d[n() - j - 1][i];
            }
        }
    }
};

```

```

    }
}
return res;
}

Matrix<T> pow(int power) const {
    assert(n() == m());

    auto res = Matrix<T>::identity(n());
    auto b = *this;
    while (power) {
        if (power & 1) res *= b;
        b *= b;
        power >>= 1;
    }
    return res;
}

Matrix<T> submatrix(int start_i, int start_j,
                    int rows = INT_MAX,
                    int cols = INT_MAX) const {
    rows = min(rows, n() - start_i);
    cols = min(cols, m() - start_j);
    if (rows <= 0 or cols <= 0) return {};

    Matrix<T> res(rows, cols);
    for (int i = 0; i < rows; i++)
        for (int j = 0; j < cols; j++)
            res[i][j] = d[i + start_i][j + start_j];
    return res;
}

Matrix<T> translated(int x, int y) const {
    Matrix<T> res(n(), m());
    for (int i = 0; i < n(); i++) {
        for (int j = 0; j < m(); j++) {
            if (i + x < 0 or i + x >= n() or j + y < 0 or
                j + y >= m())
                continue;
            res[i + x][j + y] = d[i][j];
        }
    }
    return res;
}

```

```

static Matrix<T> identity(int n) {
    Matrix<T> res(n);
    for (int i = 0; i < n; i++) res[i][i] = 1;
    return res;
}

vector<T> &operator[](int i) { return d[i]; }
const vector<T> &operator[](int i) const { return d[i]; }
Matrix<T> &operator+=(T value) {
    for (auto &row : d) {
        for (auto &x : row) x += value;
    }
    return *this;
}
Matrix<T> operator+(T value) const {
    auto res = *this;
    for (auto &row : res) {
        for (auto &x : row) x = x + value;
    }
    return res;
}
Matrix<T> &operator-=(T value) {
    for (auto &row : d) {
        for (auto &x : row) x -= value;
    }
    return *this;
}
Matrix<T> operator-(T value) const {
    auto res = *this;
    for (auto &row : res) {
        for (auto &x : row) x = x - value;
    }
    return res;
}
Matrix<T> &operator*=(T value) {
    for (auto &row : d) {
        for (auto &x : row) x *= value;
    }
    return *this;
}
Matrix<T> operator*(T value) const {
    auto res = *this;
    for (auto &row : res) {
        for (auto &x : row) x = x * value;
    }
}

```

```

    return res;
}
Matrix<T> &operator/=(T value) {
    for (auto &row : d) {
        for (auto &x : row) x /= value;
    }
    return *this;
}
Matrix<T> operator/(T value) const {
    auto res = *this;
    for (auto &row : res) {
        for (auto &x : row) x = x / value;
    }
    return res;
}
Matrix<T> &operator+=(const Matrix<T> &o) {
    assert(n() == o.n() and m() == o.m());
    for (int i = 0; i < n(); i++) {
        for (int j = 0; j < m(); j++) {
            d[i][j] += o[i][j];
        }
    }
    return *this;
}
Matrix<T> operator+(const Matrix<T> &o) const {
    assert(n() == o.n() and m() == o.m());
    auto res = *this;
    for (int i = 0; i < n(); i++) {
        for (int j = 0; j < m(); j++) {
            res[i][j] = res[i][j] + o[i][j];
        }
    }
    return res;
}
Matrix<T> &operator-=(const Matrix<T> &o) {
    assert(n() == o.n() and m() == o.m());
    for (int i = 0; i < n(); i++) {
        for (int j = 0; j < m(); j++) {
            d[i][j] -= o[i][j];
        }
    }
    return *this;
}
Matrix<T> operator-(const Matrix<T> &o) const {
    assert(n() == o.n() and m() == o.m());
}

```

```

    auto res = *this;
    for (int i = 0; i < n(); i++) {
        for (int j = 0; j < m(); j++) {
            res[i][j] = res[i][j] - o[i][j];
        }
    }
    return res;
}

Matrix<T> &operator*=(const Matrix<T> &o) {
    *this = *this * o;
    return *this;
}

Matrix<T> operator*(const Matrix<T> &o) const {
    assert(m() == o.n());
    Matrix<T> res(n(), o.m());
    for (int i = 0; i < res.n(); i++) {
        for (int j = 0; j < res.m(); j++) {
            auto &x = res[i][j];
            for (int k = 0; k < m(); k++) {
                x += (d[i][k] * o[k][j]);
            }
        }
    }
    return res;
}

friend istream &operator>>(istream &is, Matrix<T> &mat) {
    for (auto &row : mat)
        for (auto &x : row) is >> x;
    return is;
}

friend ostream &operator<<(ostream &os,
                           const Matrix<T> &mat) {
    bool frow = 1;
    for (auto &row : mat) {
        if (not frow) os << '\n';
        bool first = 1;
        for (auto &x : row) {
            if (not first) os << ' ';
            os << x;
            first = 0;
        }

        frow = 0;
    }
}

```

```

    return os;
}

auto begin() { return d.begin(); }
auto end() { return d.end(); }
auto rbegin() { return d.rbegin(); }
auto rend() { return d.rend(); }

auto begin() const { return d.begin(); }
auto end() const { return d.end(); }
auto rbegin() const { return d.rbegin(); }
auto rend() const { return d.rend(); }
};

```

8 Strings

8.1 Count Distinct Anagrams

```

const ll MOD = 1e9 + 7;
const int maxn = 1e6;
vll fs(maxn + 1);
void precompute() {
    fs[0] = 1;
    for (ll i = 1; i <= maxn; i++) {
        fs[i] = (fs[i - 1] * i) % MOD;
    }
}

ll fpow(ll a, int n, ll mod = LLONG_MAX) {
    if (n == 0) return 1;
    if (n == 1) return a;
    ll x = fpow(a, n / 2, mod) % mod;
    return ((x * x) % mod * (n & 1 ? a : 1)) % mod;
}

ll distinctAnagrams(const string &s) {
    precompute();
    vi hist('z' - 'a' + 1, 0);
    for (auto &c : s) hist[c - 'a']++;
    ll ans = fs[len(s)];
    for (auto &q : hist) {
        ans = (ans * fpow(fs[q], MOD - 2, MOD)) % MOD;
    }
    return ans;
}

```

8.2 Double Hash Range Query

```
using ll = long long;
using vll = vector<ll>;
using pll = pair<ll, ll>;

const int MAXN(1'000'000);
const ll MOD = 1000027957;
const ll MOD2 = 1000015187;
const ll P = 31;

ll p[MAXN + 1], p2[MAXN + 1];
void precompute() {
    p[0] = p2[0] = 1;
    for (int i = 1; i <= MAXN; i++)
        p[i] = (P * p[i - 1]) % MOD,
        p2[i] = (P * p2[i - 1]) % MOD2;
}

struct Hash {
    int n;
    vll h, h2, hi, hi2;
    Hash() {}
    Hash(const string& s)
        : n(s.size()), h(n), h2(n), hi(n), hi2(n) {
        h[0] = h2[0] = s[0];
        for (int i = 1; i < n; i++)
            h[i] = (s[i] + h[i - 1] * P) % MOD,
            h2[i] = (s[i] + h2[i - 1] * P) % MOD2;

        hi[n - 1] = hi2[n - 1] = s[n - 1];
        for (int i = n - 2; i >= 0; i--)
            hi[i] = (s[i] + hi[i + 1] * P) % MOD,
            hi2[i] = (s[i] + hi2[i + 1] * P) % MOD2;
    }
    pll query(int l, int r) {
        ll hash =
            (h[r] - (1 ? h[l - 1] * p[r - l + 1] % MOD : 0));
        ll hash2 =
            (h2[r] - (1 ? h2[l - 1] * p2[r - l + 1] % MOD2 : 0));

        return {(hash < 0 ? hash + MOD : hash),
                (hash2 < 0 ? hash2 + MOD2 : hash2)};
    }
    pll query_inv(int l, int r) {
```

```
        ll hash =
            (hi[l] -
             (r + 1 < n ? hi[r + 1] * p[r - l + 1] % MOD : 0));
        ll hash2 =
            (hi2[l] -
             (r + 1 < n ? hi2[r + 1] * p2[r - l + 1] % MOD2 : 0));
        return {(hash < 0 ? hash + MOD : hash),
                (hash2 < 0 ? hash2 + MOD2 : hash2)};
    }
};
```

8.3 Hash Interal mod $2^{64} - 1$

Arithmetic mod $2^{64} - 1$. 2x slower than mod 2^{64} and more code, but works on evil test data (e.g. Thue-Morse, where ABBA... and BAAB... of length 2^{10} hash the same mod 2^{64}).
"typedef ull H;" instead if you think test data is random.

```
typedef uint64_t ull;
struct H {
    ull x;
    H(ull x = 0) : x(x) {}
    H operator+(H o) { return x + o.x + (x + o.x < x); }
    H operator-(H o) { return *this + ~o.x; }
    H operator*(H o) {
        auto m = (__uint128_t)x * o.x;
        return H((ull)m) + (ull)(m >> 64);
    }
    ull get() const { return x + !~x; }
    bool operator==(H o) const { return get() == o.get(); }
    bool operator<(H o) const { return get() < o.get(); }
};

static const H C =
    (long long)1e11 + 3; // (order ~ 3e9; random also ok)

struct Hash {
    int n;
    vector<H> ha, pw;
    Hash(string& str)
        : n(str.size()), ha((int)str.size() + 1), pw(ha) {
        pw[0] = 1;
        for (int i = 0; i < (int)str.size(); i++)
            ha[i + 1] = ha[i] * C + str[i], pw[i + 1] = pw[i] * C;
    }
    H query(int a, int b) { // hash [a, b]
        b++;
        return ha[b] - ha[a] * pw[b - a];
    }
};
```

```
};

vector<H> getHashes(string& str, int length) {
    if ((int)str.size() < length) return {};
    H h = 0, pw = 1;
    for (int i = 0; i < length; i++)
        h = h * C + str[i], pw = pw * C;
    vector<H> ret = {h};
    for (int i = length; i < (int)str.size(); i++)
        ret.push_back(h =
            h * C + str[i] - pw * str[i - length]);

    return ret;
}

H hashString(string& s) {
    H h{};
    for (char c : s) h = h * C + c;
    return h;
}
```

8.4 Hash Range Query

```
const ll P = 31;
const ll MOD = 1e9 + 9;
const int MAXN(1e6);

ll ppow[MAXN + 1];
void pre_calc() {
    ppow[0] = 1;
    for (int i = 1; i <= MAXN; i++)
        ppow[i] = (ppow[i - 1] * P) % MOD;
}

struct Hash {
    int n;
    vll h, hi;
    Hash(const string &s) : n(s.size()), h(n), hi(n) {
        h[0] = s[0];
        hi[n - 1] = s[n - 1];
        for (int i = 1; i < n; i++) {
            h[i] = (s[i] + h[i - 1] * P) % MOD;
            hi[n - i - 1] =
                (s[n - i - 1] + hi[n - i - 1] * P) % MOD;
        }
    }
}
```

```
ll qry(int l, int r) {
    ll hash =
        (h[r] - (l ? h[l - 1] * ppow[r - l + 1] % MOD : 0));
    return hash < 0 ? hash + MOD : hash;
}

ll qry_inv(int l, int r) {
    ll hash =
        (hi[l] -
            (r + 1 < n ? hi[r + 1] * ppow[r - l + 1] % MOD : 0));
    return hash < 0 ? hash + MOD : hash;
}
};
```

8.5 Hash Ull

```
using ull = unsigned long long;

const int MAXN(1'000'000);

const ull P = 31;
ull p[MAXN + 1];
void precompute() {
    p[0] = 1;
    for (int i = 1; i <= MAXN; i++) p[i] = (P * p[i - 1]);
}

struct Hash {
    int n;
    vector<ull> h;
    // vector<ull> hi;
    Hash() {}

    Hash(const string& s) : n(s.size()), h(n) /*, hi(n) */ {
        h[0] = s[0];
        for (int i = 1; i < n; i++)
            h[i] = (s[i] + h[i - 1] * P);

        // hi[n - 1] = s[n - 1];
        // for (int i = n - 2; i >= 0; i--)
        //     hi[i] = (s[i] + hi[i + 1] * P);
    }

    ull query(int l, int r) {
```

```

    ull hash = (h[r] - (l ? h[l - 1] * p[r - 1 + 1] : 0));
    return hash;
}

// ull query_inv(int l, int r) {
//     ull hash = (hi[l] - (r + 1 < n ? hi[r + 1] * p[r - 1 +
//     1] : 0)); return hash;
// }

};

```

8.6 K-th digit in digit string

Find the k-th digit in a *digit string*, only works for $1 \leq k \leq 10^{18}$!

Time: precompute $O(1)$, query $O(1)$

```

using ull = vector<ull>;
ull pow10;
vector<array<ull, 4>> memo;
void precompute(int maxpow = 18) {
    ull qtd = 1;
    ull start = 1;
    ull end = 9;
    ull curlenght = 9;
    ull startstr = 1;
    ull endstr = 9;

    for (ull i = 0, j = 1ll; (int)i < maxpow; i++, j *= 10ll)
        pow10.eb(j);

    for (ull i = 0; i < maxpow - 1ull; i++) {
        memo.push_back({start, end, startstr, endstr});

        start = end + 1ll;
        end = end + (9ll * pow10[qtd]);
        curlenght = end - start + 1ull;

        qtd++;
        startstr = endstr + 1ull;
        endstr = (endstr + 1ull) + (curlenght)*qtd - 1ull;
    }
}

char kthDigit(ull k) {
    int qtd = 1;
    for (auto [s, e, ss, es] : memo) {
        if (k >= ss and k <= es) {
            ull pos = k - ss;
            ull index = pos / qtd;

```

```

            ull nmr = s + index;
            int i = k - ss - qtd * index;

            return ((nmr / pow10[qtd - i - 1]) % 10) + '0';
        }
        qtd++;
    }

    return 'X';
}

```

8.7 Longest Palindrome Substring (Manacher)

Finds the longest palindrome substring, manacher returns a vector where the i-th position is how much is possible to grow the string to the left and the right of i and keep it a palindrome.

Time: $O(N)$

```

vi manacher(const string &s) {
    int n = len(s) - 2;
    vi p(n + 2);
    int l = 1, r = 1;
    for (int i = 1; i <= n; i++) {
        p[i] = max(0, min(r - i, p[l + (r - i)]));
        while (s[i - p[i]] == s[i + p[i]]) p[i]++;
        if (i + p[i] > r) l = i - p[i], r = i + p[i];
        p[i]--;
    }
    return p;
}

string longest_palindrome(const string &s) {
    string t("$#");
    for (auto c : s) t.push_back(c), t.push_back('#');
    t.push_back('^');
    vi xs = manacher(t);
    int mpos = max_element(all(xs)) - xs.begin();
    string p;
    for (int k = xs[mpos], i = mpos - k; i <= mpos + k; i++)
        if (t[i] != '#') p.push_back(t[i]);
    return p;
}

```

8.8 Longest Palindrome

```

string longest_palindrome(const string &s) {
    int n = (int)s.size();
    vector<array<int, 2>> dp(n);

```



```

pii odd(0, -1), even(0, -1);
pii ans;
for (int i = 0; i < n; i++) {
    int k = 0;
    if (i > odd.second)
        k = 1;
    else
        k = min(dp[odd.first + odd.second - i][0],
                odd.second - i + 1);
    while (i - k >= 0 and i + k < n and
           s[i - k] == s[i + k])
        k++;
    dp[i][0] = k--;
    if (i + k > odd.second) odd = {i - k, i + k};
    if (2 * dp[i][0] - 1 > ans.second)
        ans = {i - k, 2 * dp[i][0] - 1};

    k = 0;
    if (i <= even.second)
        k = min(dp[even.first + even.second - i + 1][1],
                even.second - i + 1);
    while (i - k - 1 >= 0 and i + k < n and
           s[i - k - 1] == s[i + k])
        k++;
    dp[i][1] = k--;
    if (i + k > even.second) even = {i - k - 1, i + k};
    if (2 * dp[i][1] > ans.second)
        ans = {i - k - 1, 2 * dp[i][1]};
}
return s.substr(ans.first, ans.second);
}

```

8.9 Rabin Karp

```

size_t rabin_karp(const string &s, const string &p) {
    if (s.size() < p.size()) return 0;

    auto n = s.size(), m = p.size();
    const ll p1 = 31, p2 = 29, q1 = 1e9 + 7, q2 = 1e9 + 9;
    const ll p1_1 = fpow(p1, q1 - 2, q1),
             p1_2 = fpow(p1, m - 1, q1);
    const ll p2_1 = fpow(p2, q2 - 2, q2),
             p2_2 = fpow(p2, m - 1, q2);

```

```

pair<ll, ll> hs, hp;
for (int i = (int)m - 1; ~i; --i) {
    hs.first = (hs.first * p1) % q1;
    hs.first = (hs.first + (s[i] - 'a' + 1)) % q1;
    hs.second = (hs.second * p2) % q2;
    hs.second = (hs.second + (s[i] - 'a' + 1)) % q2;

    hp.first = (hp.first * p1) % q1;
    hp.first = (hp.first + (p[i] - 'a' + 1)) % q1;
    hp.second = (hp.second * p2) % q2;
    hp.second = (hp.second + (p[i] - 'a' + 1)) % q2;
}

size_t occ = 0;
for (size_t i = 0; i < n - m; i++) {
    occ += (hs == hp);

    int fi = s[i] - 'a' + 1;
    int fm = s[i + m] - 'a' + 1;

    hs.first = (hs.first - fi + q1) % q1;
    hs.first = (hs.first * p1_1) % q1;
    hs.first = (hs.first + fm * p1_2) % q1;
    hs.second = (hs.second - fi + q2) % q2;
    hs.second = (hs.second * p2_1) % q2;
    hs.second = (hs.second + fm * p2_2) % q2;
}
occ += hs == hp;

return occ;
}

```

8.10 Suffix Automaton (complete)

```

struct state {
    int len, link, cnt, firstpos;
    // this can be optimized using a vector with the alphabet
    // size
    map<char, int> next;
    vi inv_link;
};

struct SuffixAutomaton {
    vector<state> st;
    int sz = 0;
    int last;

```

```

vc cloned;

SuffixAutomaton(const string &s, int maxlen)
: st(maxlen * 2), cloned(maxlen * 2) {
    st[0].len = 0;
    st[0].link = -1;
    sz++;
    last = 0;
    for (auto &c : s) add_char(c);

    // precompute for count occurrences
    for (int i = 1; i < sz; i++) {
        st[i].cnt = !cloned[i];
    }
    vector<pair<state, int>> aux;
    for (int i = 0; i < sz; i++) {
        aux.push_back({st[i], i});
    }

    sort(all(aux), [](const pair<state, int> &a,
                     const pair<state, int> &b) {
        return a.fst.len > b.fst.len;
    });

    for (auto &[stt, id] : aux) {
        if (stt.link != -1) {
            st[stt.link].cnt += st[id].cnt;
        }
    }

    // for find every occurende position
    for (int v = 1; v < sz; v++) {
        st[st[v].link].inv_link.push_back(v);
    }
}

void add_char(char c) {
    int cur = sz++;
    st[cur].len = st[last].len + 1;
    st[cur].firstpos = st[cur].len - 1;
    int p = last;
    // follow the suffix link until find a transition to c
    while (p != -1 and !st[p].next.count(c)) {
        st[p].next[c] = cur;
        p = st[p].link;
    }
}

```

```

}
// there was no transition to c so create and leave
if (p == -1) {
    st[cur].link = 0;
    last = cur;
    return;
}

int q = st[p].next[c];
if (st[p].len + 1 == st[q].len) {
    st[cur].link = q;
} else {
    int clone = sz++;
    cloned[clone] = true;
    st[clone].len = st[p].len + 1;
    st[clone].next = st[q].next;
    st[clone].link = st[q].link;
    st[clone].firstpos = st[q].firstpos;
    while (p != -1 and st[p].next[c] == q) {
        st[p].next[c] = clone;
        p = st[p].link;
    }
    st[q].link = st[cur].link = clone;
}
last = cur;
}

bool checkOccurrence(const string &t) { // 0(len(t))
    int cur = 0;
    for (auto &c : t) {
        if (!st[cur].next.count(c)) return false;
        cur = st[cur].next[c];
    }
    return true;
}

11 totalSubstrings() { // distinct, 0(len(s))
    11 tot = 0;
    for (int i = 1; i < sz; i++) {
        tot += st[i].len - st[st[i].link].len;
    }
    return tot;
}

// count occurrences of a given string t
int countOccurrences(const string &t) {

```

```

int cur = 0;
for (auto &c : t) {
    if (!st[cur].next.count(c)) return 0;
    cur = st[cur].next[c];
}
return st[cur].cnt;
}

// find the first index where t appears a substring
// O(len(t))
int firstOccurence(const string &t) {
    int cur = 0;
    for (auto c : t) {
        if (!st[cur].next.count(c)) return -1;
        cur = st[cur].next[c];
    }
    return st[cur].firstpos - len(t) + 1;
}

vi everyOccurence(const string &t) {
    int cur = 0;
    for (auto c : t) {
        if (!st[cur].next.count(c)) return {};
        cur = st[cur].next[c];
    }
    vi ans;
    getEveryOccurence(cur, len(t), ans);
    return ans;
}

void getEveryOccurence(int v, int P_length, vi &ans) {
    if (!cloned[v]) ans.pb(st[v].firstpos - P_length + 1);
    for (int u : st[v].inv_link)
        getEveryOccurence(u, P_length, ans);
}
};

```

8.11 Trie

- build with the size of the alphabet (*sigma*) and the first char (*norm*)
- *insert(s)* insert the string in the trie $O(|s| * \text{sigma})$
- *erase(s)* remove the string from the trie $O(|s|)$
- *find(s)* return the last node from the string s, 0 if not found $O(|s|)$

```

struct trie {
    vi2d to;

```

```

    vi end, pref;
    int sigma;
    char norm;

    trie(int sigma_ = 26, char norm_ = 'a')
        : sigma(sigma_), norm(norm_) {
        to = {vector<int>(sigma)};
        end = {0}, pref = {0};
    }

    int next(int node, char key) {
        return to[node][key - norm];
    }

    void insert(const string &s) {
        int x = 0;
        for (auto c : s) {
            int &nxt = to[x][c - norm];
            if (!nxt) {
                nxt = len(to);
                to.push_back(vi(sigma));
                end.emplace_back(0), pref.emplace_back(0);
            }
            x = nxt, pref[x]++;
        }
        end[x]++, pref[0]++;
    }

    void erase(const string &s) {
        int x = 0;
        for (char c : s) {
            int &nxt = to[x][c - norm];
            x = nxt, pref[x]--;
            if (!pref[x]) nxt = 0;
        }
        end[x]--, pref[0]--;
    }

    int find(const string &s) {
        int x = 0;
        for (auto c : s) {
            x = to[x][c - norm];
            if (!x) return 0;
        }
        return x;
    }
};

```

8.12 Z-function get occurrence positions

$O(\text{len}(s) + \text{len}(p))$

```
vi getOccPos(string &s, string &p) {
    // Z-function
    char delim = '#';
    string t{p + delim + s};
    vi zs(len(t));

    int l = 0, r = 0;
    for (int i = 1; i < len(t); i++) {
        if (i <= r) zs[i] = min(zs[i - l], r - i + 1);
        while (zs[i] + i < len(t) and t[zs[i]] == t[i + zs[i]])
            zs[i]++;
        if (r < i + zs[i] - 1) l = i, r = i + zs[i] - 1;
    }

    // Iterate over the results of Z-function to get ranges
    vi ans;
    int start = len(p) + 1 + 1 - 1;
    for (int i = start; i < len(zs); i++) {
        if (zs[i] == len(p)) {
            int l = i - start;
            ans.emplace_back(l);
        }
    }
    return ans;
}
```

9 Settings and macros

9.1 short-macro.cpp

```
#include <bits/stdc++.h>
using namespace std;
#define fastio \
    ios_base::sync_with_stdio(0); \
    cin.tie(0);

void run() {

}

int32_t main(void) {
    fastio;
```

```
int t;
t = 1;
// cin >> t;
while (t--) run();
}
```

9.2 .bashrc

```
#copy first argument to clipborad ! ONLY WORK ON XORG !
alias clip="xclip -sel clip"
```

```
# compile the $1 parameter, if a $2 is provided
# the name will be the the binary output, if
# none is provided the binary name will be
# 'a.out'
```

```
comp() {
    echo ">> COMPILING $1 <<" 1>&2
```

```
if [ $# -gt 1 ]; then
    outfile="${2}"
else
    outfile="a.out"
fi
```

```
time g++ -std=c++20 \
    -O2 \
    -g3 \
    -Wall \
    -fsanitize=address,undefined \
    -fno-sanitize-recover \
    -D LOCAL \
    -o "${outfile}" \
    "$1"
```

```
if [ $? -ne 0 ]; then
    echo ">> FAILED <<" 1>&2
    return 1
```

```
fi
echo ">> DONE << " 1>&2
```

```
}
```

```
# run the binary given in $1, if none is
# given it will try to run the 'a.out'
# binary
run() {
```

```

to_run=./a.out
if [ -n "$1" ]; then
    to_run="$1"
fi
time $to_run
}

# just comp and run your cpp file
# accpets <in1 >out and everything else
comprun() {
    comp "$1" "a"
    run ./a ${@:2}
}

testall() {
    comp "$1" generator
    comp "$2" brute
    comp "$3" main

    input_counter=1

    while true; do
        echo "$input_counter"
        run ./generator > input
        run ./main < input > main_output.txt
        run ./brute < input > brute_output.txt

        diff brute_output.txt main_output.txt
        if [ $? -ne 0 ]; then
            echo "Outputs differ at input $input_counter"
            echo "Brute file output:"
            cat brute_output.txt
            echo "Main file output:"
            cat main_output.txt
        fi
        echo "input used: "
        cat input
        break
    fi

    ((input_counter++))
done
}

```

9.3 gen.cpp

```

#include <bits/stdc++.h>
using namespace std;
#ifdef LOCAL
#include "debug.cpp"
#else
#define dbg(...)
#endif
#define endl '\n'
#define fastio \
    ios_base::sync_with_stdio(0); \
    cin.tie(0);
// #define int long long
#define len(__x) (int)__x.size()
using ll = long long;
using ull = unsigned long long;
using ld = long double;
using vll = vector<ll>;
using pll = pair<ll, ll>;
using vll2d = vector<vll>;
using vi = vector<int>;
using vi2d = vector<vi>;
using pii = pair<int, int>;
using vii = vector<pii>;
using vc = vector<char>;
#define all(a) a.begin(), a.end()
#define rall(a) a.rbegin(), a.rend()
#define pb push_back
#define eb emplace_back
#define ff first
#define ss second
#define rep(i, begin, end) \
    for (__typeof(begin) i = (begin) - ((begin) > (end)); \
         i != (end) - ((begin) > (end)); \
         i += 1 - 2 * ((begin) > (end)))

int lg2(ll x) {
    return __builtin_clzll(1) - __builtin_clzll(x);
}

// vector<string> dir({"LU", "U", "RU", "R", "RD", "D",
// "LD", "L"}); int dx[] = {-1, -1, -1, 0, 1, 1, 1, 0}; int
// dy[] = {-1, 0, 1, 1, 1, 0, -1, -1};
vector<string> dir({"U", "R", "D", "L"});
int dx[] = {-1, 0, 1, 0};
int dy[] = {0, 1, 0, -1};

```

```

const ll oo = 1e18;
int T(1);

ll random() {
    std::random_device
        rd; // Obtain a random number from hardware
    std::mt19937 gen(rd()); // Seed the generator
    //
    std::uniform_int_distribution<> distribution(1, 4);
    return distribution(gen);
}

auto run() {
}

int32_t main(void) {
    srand(time(NULL));
#ifdef LOCAL
    fastio;
#endif

    // cin >> T;

    for (int t = 1; t <= T; t++) {
        run();
    }
}

```

9.4 macro.cpp

```

#include <bits/stdc++.h>
using namespace std;
#ifdef LOCAL
#include "debug.cpp"
#else
#define dbg(...)
#endif
#define endl '\n'
#define fastio \
    ios_base::sync_with_stdio(0); \
    cin.tie(0);
// #define int long long
#define len(__x) (int)__x.size()

```

```

using ll = long long;
using ull = unsigned long long;
using ld = long double;
using vll = vector<ll>;
using pll = pair<ll, ll>;
using vll2d = vector<vll>;
using vi = vector<int>;
using vi2d = vector<vi>;
using pii = pair<int, int>;
using vii = vector<pii>;
using vc = vector<char>;
#define all(a) a.begin(), a.end()
#define rall(a) a.rbegin(), a.rend()
#define pb push_back
#define eb emplace_back
#define ff first
#define ss second
#define rep(i, begin, end) \
    for (__typeof(begin) i = (begin) - ((begin) > (end)); \
        i != (end) - ((begin) > (end)); \
        i += 1 - 2 * ((begin) > (end)))

int lg2(ll x) {
    return __builtin_clzll(1) - __builtin_clzll(x);
}

// vector<string> dir({"LU", "U", "RU", "R", "RD", "D",
// "LD", "L"}); int dx[] = {-1, -1, -1, 0, 1, 1, 1, 0}; int
// dy[] = {-1, 0, 1, 1, 1, 0, -1, -1};
vector<string> dir({"U", "R", "D", "L"});
int dx[] = {-1, 0, 1, 0};
int dy[] = {0, 1, 0, -1};

const ll OO = 1e18;
const int oo = 1e9;

int T(1);

auto run() {
}

int32_t main(void) {
#ifdef LOCAL
    fastio;

```

```

#endif

// cin >> T;

for (int t = 1; t <= T; t++) {
    run();
}
}

```

9.5 .vimrc

```

set sta nu rnu sc cindent
set bg=dark ruler clipboard=unnamed,unnamedplus, timeoutlen=100
colorscheme default
syntax on

```

```

" Takes the hash of the selected text and put
" in the vim clipboard
function! HashSelectedText()
    " Yank the selected text to the unnamed register
    normal! gvy
    " Use the system() function to call sha256sum with the
    yanked text
    let l:hash = system('echo ' . shellescape(@@) . ' |
    sha256sum')
    " Yank the hash into Vim's unnamed register
    let @" = l:hash
endfunction

```

9.6 debug.cpp

```

#include <bits/stdc++.h>
using namespace std;
/***** Debug Code *****/
template <typename T>
concept Printable = requires(T t) {
    { std::cout << t } -> std::same_as<std::ostream &>;
};
template <Printable T>
void __print(const T &x) {
    cerr << x;
}
template <size_t T>
void __print(const bitset<T> &x) {
    cerr << x;
}

```

```

template <typename A, typename B>
void __print(const pair<A, B> &p);
template <typename... A>
void __print(const tuple<A...> &t);
template <typename T>
void __print(stack<T> s);
template <typename T>
void __print(queue<T> q);
template <typename T, typename... U>
void __print(priority_queue<T, U...> q);
template <typename A>
void __print(const A &x) {
    bool first = true;
    cerr << '{';
    for (const auto &i : x) {
        cerr << (first ? "" : ","), __print(i);
        first = false;
    }
    cerr << '}';
}

template <typename A, typename B>
void __print(const pair<A, B> &p) {
    cerr << '(';
    __print(p.first);
    cerr << ',';
    __print(p.second);
    cerr << ')';
}

template <typename... A>
void __print(const tuple<A...> &t) {
    bool first = true;
    cerr << '(';
    apply(
        [&first](const auto &...args) {
            ((cerr << (first ? "" : ","), __print(args), first
= false), ...);
        },
        t);
    cerr << ')';
}

template <typename T>
void __print(stack<T> s) {
    vector<T> debugVector;
    while (!s.empty()) {
        T t = s.top();

```

```

        debugVector.push_back(t);
        s.pop();
    }
    reverse(debugVector.begin(), debugVector.end());
    __print(debugVector);
}
template <typename T>
void __print(queue<T> q) {
    vector<T> debugVector;
    while (!q.empty()) {
        T t = q.front();
        debugVector.push_back(t);
        q.pop();
    }
    __print(debugVector);
}
template <typename T, typename... U>
void __print(priority_queue<T, U...> q) {
    vector<T> debugVector;

```

```

    while (!q.empty()) {
        T t = q.top();
        debugVector.push_back(t);
        q.pop();
    }
    __print(debugVector);
}
void _print() { cerr << "]\n"; }
template <typename Head, typename... Tail>
void _print(const Head &H, const Tail &...T) {
    __print(H);
    if (sizeof...(T)) cerr << ", ";
    _print(T...);
}

#define dbg(x...) \
    cerr << "[" << #x << "]" = ["; \
    _print(x)

```