

ID#:	3773164	User making request:	N/A
Fax:		Phone:	
Email:		Date Created:	11/04/2019
Date Assessment Reviewed	04/01/2021	Next Review Date:	04/01/2022
Material Code:	230846	Tradename:	CEMENTONE CONCRETE MOULD OIL,
Supplier:	BOSTIK LIMITED	IMC:	
Keyword:	Mould (Oil)	Frequency of use:	Daily
Approximately how much of the material is used by one person in one working day:	1 TO 10 LITRES	How many people are directly exposed?:	2-5
Are any other people put at risk from indirect exposure?:	No	How are they exposed?:	
Are there any susceptible workers?:	No	Susceptible Categories:	
Other info:		Is this material being used outside of the normal temperature range?:	No
Additional work practices:			
Existing Control measures:			
Exp Limit			
Notes	Classification is based on the contents stated in the suppliers safety data sheet rather than the suppliers classification		

Files Uploaded

File Name

Activities

Act No.	Method	Area	Exposure
2	Hand applying	Outside	4 to 8 hours per shift
3	Hand applying	Outside	2 to 4 hours per shift

Work Area

Work Area Code	Sub Area Code
TELECOMS	

Safer Substitute Chosen	Reason for leaving/swapping material
-------------------------	--------------------------------------

MATERIAL/PROCESS

CEMENTONE CONCRETE MOULD OIL,

MEDIUM HAZARD

LIQUID

SUPPLIER

BOSTIK LIMITED

KEYWORD

Mould (Oil)

CONTENTS

Kerosine (petroleum), hydrodesulphurised 10 - 30%,

SIGNAL WORD

WARNING

EXP LIMIT

HEALTH HAZARDS

Causes skin irritation
May cause drowsiness or dizziness
Toxic to aquatic life with long lasting effects
May cause ill health if ingested in quantity
May cause eye irritation

CONSIDERATIONS



METHOD

Hand applying

AREA

Outside

EXPOSURE TIME

4 to 8 hours per shift

SPILLAGE

Ventilate area
Wear polythene or nitrile gloves
Wear eye protection if contact likely
Wear respiratory protection if spill is in a poorly ventilated space
Wear respiratory protection if whole container is spilt
Wear protective overalls & chemical proof footwear
Absorb in sand or inert absorbent material
Small spills - wipe up with cloth
Collect into a container, close lid
Dispose or recycle of spillages in a controlled manner - Refer to Hazardous Waste Regulations if appropriate


HIGH ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE


CONTROL MEASURES

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY


MEDIUM CHRONIC RISK - INDIVIDUAL ACTIVITY




KEEP SKIN COVERED




POLYTHENE OR NITRILE




IF CONTACT LIKELY




AND




LEV OR




FILTER TYPE A2




WASH AFTER EXPOSURE



AT END OF SHIFT



CLOSE ALL CONTAINERS



ACUTE HAZARD / ECOTOXIC

FIRST AID

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill
Ingestion - do not induce vomiting, wash out mouth with water
If feeling unwell consult your doctor immediately
Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor
Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

FIRE

Isolated small scale fire:
Carbon dioxide - powder - foam - inert material
Large fire: evacuate area, call fire brigade or follow site procedure
Wear self-contained breathing apparatus and protective clothing

MATERIAL/PROCESS

CEMENTONE CONCRETE MOULD OIL,

MEDIUM HAZARD

LIQUID

SUPPLIER

BOSTIK LIMITED

KEYWORD

Mould (Oil)

CONTENTS

Kerosine (petroleum), hydrodesulphurised 10 - 30%,

SIGNAL WORD

WARNING

EXP LIMIT

HEALTH HAZARDS

Causes skin irritation
May cause drowsiness or dizziness
Toxic to aquatic life with long lasting effects
May cause ill health if ingested in quantity
May cause eye irritation

CONSIDERATIONS



METHOD

Hand applying

AREA

Outside

EXPOSURE TIME

2 to 4 hours per shift

SPILLAGE

Ventilate area
Wear polythene or nitrile gloves
Wear eye protection if contact likely
Wear respiratory protection if spill is in a poorly ventilated space
Wear respiratory protection if whole container is spilt
Wear protective overalls & chemical proof footwear
Absorb in sand or inert absorbent material
Small spills - wipe up with cloth
Collect into a container, close lid
Dispose or recycle of spillages in a controlled manner - Refer to Hazardous Waste Regulations if appropriate


HIGH ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE


CONTROL MEASURES

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY


MEDIUM CHRONIC RISK - INDIVIDUAL ACTIVITY




KEEP SKIN COVERED




POLYTHENE OR NITRILE




IF CONTACT LIKELY




AND




LEV OR




FILTER TYPE A2




WASH AFTER EXPOSURE



IF SOILED



CLOSE ALL CONTAINERS




ACUTE HAZARD / ECOTOXIC

FIRST AID

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill
Ingestion - do not induce vomiting, wash out mouth with water
If feeling unwell consult your doctor immediately
Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor
Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

FIRE

Isolated small scale fire:
Carbon dioxide - powder - foam - inert material
Large fire: evacuate area, call fire brigade or follow site procedure
Wear self-contained breathing apparatus and protective clothing




Alcumus®
Safer, Healthier, Stronger

ACTIVITY COMMENTS

This assessment was compiled by Alcumus Sypol Limited from supplier's safety data sheets where appropriate. Safety in the use of assessments is the responsibility of the subscriber. For advice call the helpdesk on 01296 678464

Printed 16/04/2021



Alcumus®
Safer, Healthier, Stronger

DATE ASSESSMENT REVIEWED04/01/2021

LATEST SAFETY DATA SHEET REFERENCE

02/2014

MATERIAL/PROCESS

CEMENTONE CONCRETE MOULD OIL,

SUPPLIER

BOSTIK LIMITED

KEYWORD



Mould (Oil)

SIGNAL WORD

WARNING

MEDIUM HAZARD

LIQUID



METHOD

Hand applying

AREA

Outside

EXPOSURE TIME

4 to 8 hours per shift

ACTIVITY COMMENTS


HIGH ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE


CONTROL MEASURES

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK - INDIVIDUAL ACTIVITY




KEEP SKIN COVERED




POLYTHENE OR NITRILE




IF CONTACT LIKELY



AND




LEV OR



FILTER TYPE A2




WASH AFTER EXPOSURE



AT END OF SHIFT



CLOSE ALL CONTAINERS



ACUTE HAZARD / ECOTOXIC

HEALTH HAZARDS

Causes skin irritation

May cause drowsiness or dizziness

Toxic to aquatic life with long lasting effects

May cause ill health if ingested in quantity

May cause eye irritation

MATERIAL/PROCESS

CEMENTONE CONCRETE MOULD OIL,

SUPPLIER

BOSTIK LIMITED

KEYWORD



Mould (Oil)

SIGNAL WORD

WARNING

MEDIUM HAZARD

LIQUID



METHOD

Hand applying

AREA

Outside

EXPOSURE TIME

2 to 4 hours per shift

ACTIVITY COMMENTS

HIGH ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

CONTROL MEASURES

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY


MEDIUM CHRONIC RISK - INDIVIDUAL ACTIVITY




KEEP SKIN COVERED




POLYTHENE OR NITRILE




IF CONTACT LIKELY




AND




LEV OR




FILTER TYPE A2



WASH AFTER EXPOSURE



IF SOILED



CLOSE ALL CONTAINERS



ACUTE HAZARD / ECOTOXIC

HEALTH HAZARDS

Causes skin irritation

May cause drowsiness or dizziness

Toxic to aquatic life with long lasting effects

May cause ill health if ingested in quantity

May cause eye irritation

REQUEST DETAILS	#ID:	3773164	User making request:	N/A
MATERIAL DETAILS	Material Code:	230846	<div>HIGH UNCONTROLLED ACUTE RISK</div> <div>MEDIUM UNCONTROLLED CHRONIC RISK</div> <div>LOW CONTROLLED ACUTE/CHRONIC RISK</div>	
Tradename:	CEMENTONE CONCRETE MOULD OIL,			
IMC:	Supplier:	BOSTIK LIMITED		



ACTIVITY DETAILS			
Act No.	Method	Area	Exposure
2	Hand applying	Outside	4 to 8 hours per shift
3	Hand applying	Outside	2 to 4 hours per shift

SCENARIO DETAILS	Additional work practices:			
Approximately how much of the material is used by one person in one working day:	1 TO 10 LITRES	Frequency of use:	Daily	How many people are directly exposed?: 2-5
Are any other people put at risk from indirect exposure?:	No	How are they exposed?:		
Are there any susceptible workers?:	No	Susceptible Categories:		

WORK AREA	Sub Area Code
Work Area Code	
TELECOMS	

OTHER INFORMATION

Classification is based on the contents stated in the suppliers safety data sheet rather than the suppliers classification

CONSIDERATIONS	Answer
 Has the elimination or substitution of this material been considered?	YES
 Are procedures to ensure the maintenance of controls in place?	YES