

MATERIAL/PROCESS

WEBER.TEC BEDDING MORTAR

MEDIUM HAZARD

MULTI PACK

SUPPLIER

SAINT-GOBAIN WEBER LIMITED

KEYWORD

Mortar

CONTENTS

A: Styrene 40.00%, B: Dibenzoyl peroxide 3.00 - 6.00%, A: phthalic anhydride < 1.00%,

SIGNAL WORD

DANGER

EXP LIMIT

Dibenzoyl peroxide 5mg/m3 8hTWA WEL,
phthalic anhydride 4mg/m3 8hTWA

HEALTH HAZARDS

Heating may cause a fire
Flammable liquid and vapour
Harmful if inhaled
Causes serious eye irritation
Causes skin irritation
May cause an allergic skin reaction
May cause allergic reaction in susceptible individuals
May cause ill health if ingested in quantity
When using do not eat, drink or smoke
Causes damage to organs through prolonged or repeated exposure
Suspected of damaging fertility or the unborn child

CONSIDERATIONS






LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE


CONTROL MEASURES

LOW ACUTE RISK - INDIVIDUAL ACTIVITY


LOW CHRONIC RISK - INDIVIDUAL ACTIVITY





KEEP SKIN COVERED




POLYTHENE








WASH AFTER USE



IF SOILED



ONCE CURED

SPILLAGE


Ventilate area and exclude all sources of ignition
Wear polythene gloves
Wear eye protection (bs en166)
Wear RPE with organic filter (a)
Wear protective clothing if whole container is spilt
Absorb in sand or inert absorbent material
Collect into a container, close lid
Dispose or recycle of spillages in a controlled manner

FIRST AID

Inhalation - remove to fresh air and rest
After a significant exposure or if feeling unwell call for medical assistance immediately
Ingestion - do not induce vomiting
Ingestion - give plenty of water in sips
If feeling unwell consult your doctor immediately
Eye - irrigate with water for at least 15 minutes
Skin - remove contaminated clothing
Skin - remove clothing & wash contaminated area with water
If irritation persists then consult a doctor

FIRE

Isolated small scale fire:
Powder - foam - carbon dioxide (CO2)
Do not use water jet
Large fire: evacuate area, call fire brigade or follow site procedure
Wear self-contained breathing apparatus and protective clothing
Toxic fumes are produced when material is involved in a fire



Alcumus®
Safer, Healthier, Stronger

ACTIVITY COMMENTS

This assessment was compiled by Alcumus Sypol Limited from supplier's safety data sheets where appropriate. Safety in the use of assessments is the responsibility of the subscriber. For advice call the helpdesk on 01296 678464

MORRISON
ZERO HARM

YOU CAN MAKE A DIFFERENCE

Printed 14/01/2019

DATE ASSESSMENT REVIEWED06/02/2018

LATEST SAFETY DATA SHEET REFERENCE

08/10/2014