



Plan View (Ducts omitted for clarity)




Isometric


CW2 Cast Iron lids and frame, approved and supplied by Virgin Media



Section B-B



Section A-A



Notes/Key:

1. All dimensions in millimetres.
2. Reinstatement to comply with the requirements of the NRSWA (subject to category).
3. All covers whall have an approved BS standard kite mark to the approval of the Virgin Media Delivery Engineer.
4. All duct ends to be flush with brick work and in line.
5. The maximum number of duct entries into any single wall is 8. no.
6. All materials and workmanship to be in accordance with the specification.
7. All concrete to be in accordance with BS8110 (EN1992). Reinforced concrete to be minimum grade C40 and subject to the minimum requirements of BS8110 (EN1992). Concrete mix to chambers to be C40/20 with S.R.C used only as directed by the Virgin Media Delivery Engineer.
8. Carriageway covers and frames to be class D400 to BSEN124.
9. All end ducts to be built into brick work with class 1 mortar.

Version 6.0 Last Updated 28/06/12	Created by: Stephen Scott
Drawing Title: VMNB0007	Authorised by: Nigel Myers

Carriageway Junction Box CW2

Virgin Media New Build Team
1 Dove Wynd
Strathclyde Business Park
Bellshill
ML4 3AL

newbuild@virginmedia.co.uk
0800 408 0088



© 2012 Virgin Media Ltd
All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted in any form or by any means (Electronic, Mechanical, Photocopying, Recording or otherwise) without the prior written expressed consent of the Company.