

MATERIAL/PROCESS

CEMENTONE CONCRETE MOULD OIL

MEDIUM HAZARD

LIQUID

SUPPLIER

BOSTIK LIMITED

KEYWORD

Mould (Oil)

CONTENTS

Kerosine (petroleum), hydrodesulphurised 10 - 30%,

SIGNAL WORD

WARNING

EXP LIMIT



HEALTH HAZARDS

Causes skin irritation
May cause drowsiness or dizziness
May cause ill health if ingested in quantity
May cause eye irritation
Toxic to aquatic life with long lasting effects

CONSIDERATIONS



METHOD

Hand applying

AREA

Outside

EXPOSURE TIME

4 to 8 hours per shift

SPILLAGE

Ventilate area
Wear polythene or nitrile gloves
Wear eye protection if contact likely
Wear respiratory protection if spill is in a poorly ventilated space
Wear respiratory protection if whole container is spilt
Wear protective overalls & chemical proof footwear
Absorb in sand or inert absorbent material
Small spills - wipe up with cloth
Collect into a container, close lid
Dispose or recycle of spillages in a controlled manner


HIGH ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE


MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK - INDIVIDUAL ACTIVITY


CONTROL MEASURES




KEEP SKIN COVERED




POLYTHENE OR NITRILE




IF CONTACT LIKELY




AND




LEV OR




FILTER TYPE A2




WASH AFTER EXPOSURE



IF SOILED



CLOSE ALL CONTAINERS



ACUTE HAZARD / ECOTOXIC

FIRST AID

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill
Ingestion - do not induce vomiting, wash out mouth with water
If feeling unwell consult your doctor immediately
Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor
Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

FIRE

Isolated small scale fire:
Carbon dioxide - powder - foam - inert material
Large fire: evacuate area, call fire brigade or follow site procedure
Wear self-contained breathing apparatus and protective clothing

MATERIAL/PROCESS

CEMENTONE CONCRETE MOULD OIL

MEDIUM HAZARD

LIQUID

SUPPLIER

BOSTIK LIMITED

KEYWORD

Mould (Oil)

CONTENTS

Kerosine (petroleum), hydrodesulphurised 10 - 30%,

!

HEALTH HAZARDS

Causes skin irritation
May cause drowsiness or dizziness
May cause ill health if ingested in quantity
May cause eye irritation
Toxic to aquatic life with long lasting effects

CONSIDERATIONS

SIGNAL WORD

WARNING

EXP LIMIT

METHOD

Hand applying

AREA

Outside

EXPOSURE TIME

2 to 4 hours per shift

SPILLAGE

Ventilate area
Wear polythene or nitrile gloves
Wear eye protection if contact likely
Wear respiratory protection if spill is in a poorly ventilated space
Wear respiratory protection if whole container is spilt
Wear protective overalls & chemical proof footwear
Absorb in sand or inert absorbent material
Small spills - wipe up with cloth
Collect into a container, close lid
Dispose or recycle of spillages in a controlled manner

HIGH ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

CONTROL MEASURES

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK - INDIVIDUAL ACTIVITY

KEEP SKIN COVERED

POLYTHENE OR NITRILE

IF CONTACT LIKELY

AND

LEV OR

FILTER TYPE A2

WASH AFTER EXPOSURE

IF SOILED

CLOSE ALL CONTAINERS

ACUTE HAZARD / ECOTOXIC

FIRST AID

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill
Ingestion - do not induce vomiting, wash out mouth with water
If feeling unwell consult your doctor immediately
Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor
Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

FIRE

Isolated small scale fire:
Carbon dioxide - powder - foam - inert material
Large fire: evacuate area, call fire brigade or follow site procedure
Wear self-contained breathing apparatus and protective clothing

Alcumus

Safer, Healthier, Stronger

ACTIVITY COMMENTS

This assessment was compiled by Alcumus Sypol Limited from supplier's safety data sheets where appropriate. Safety in the use of assessments is the responsibility of the subscriber. For advice call the helpdesk on 01296 678464

MORRISON

ZERO HARM

YOU CAN MAKE A DIFFERENCE

DATE ASSESSMENT REVIEWED

06/02/2018

LATEST SAFETY DATA SHEET REFERENCE

02/2014