

MATERIAL/PROCESS

BITUMEN PAINT

LOW HAZARD

LIQUID

SUPPLIER

PLAPRODUCTS LTD

KEYWORD

Paint (Bitumen)

CONTENTS

Asphalt (oxidised),

SIGNAL WORD

DANGER

EXP LIMIT

Asphalt (oxidised) 5mg/m3 8hTWA 10mg/m3 15mSTEL OEL

HEALTH HAZARDS

May cause ill health if ingested in quantity
Skin - irritation and dermatitis may result from prolonged contact
May cause eye irritation

CONSIDERATIONS

METHOD

Hand applying

AREA

Outside

EXPOSURE TIME

4 to 8 hours per shift

SPILLAGE

Ventilate area
Wear butyl or nitrile gloves
Wear eye protection if contact likely
Wear respiratory protection for large spills in poorly ventilated areas
Wear protective overalls and footwear for large spillages
Absorb in sand or inert absorbent material
Small spills - wipe up with cloth
Collect into a container, close lid
Dispose or recycle of spillages in a controlled manner

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

CONTROL MEASURES

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK - INDIVIDUAL ACTIVITY

AVOID SKIN CONTACT

BUTYL OR NITRILE

IF CONTACT LIKELY

WASH AFTER EXPOSURE

IF HEAVILY SOILED

CLOSE ALL CONTAINERS

CONTROLLED STORE /WASTE

FIRST AID

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill
Ingestion - do not induce vomiting, wash out mouth with water
If feeling unwell consult your doctor immediately
Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor
Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

FIRE

Isolated small scale fire:
Water fog - carbon dioxide - powder - foam - inert material
Do not use water jet
Large fire: evacuate area, call fire brigade or follow site procedure
Wear self-contained breathing apparatus and protective clothing

MATERIAL/PROCESS

BITUMEN PAINT

LOW HAZARD

LIQUID

SUPPLIER

PLAPRODUCTS LTD

KEYWORD

Paint (Bitumen)

CONTENTS

Asphalt (oxidised),

SIGNAL WORD

DANGER



EXP LIMIT

Asphalt (oxidised) 5mg/m3 8hTWA 10mg/m3 15mSTEL OEL

HEALTH HAZARDS

May cause ill health if ingested in quantity
Skin - irritation and dermatitis may result from prolonged contact
May cause eye irritation

CONSIDERATIONS



METHOD

Hand applying

AREA

Inside Well Ventilated

EXPOSURE TIME

4 to 8 hours per shift

SPILLAGE

Ventilate area
Wear butyl or nitrile gloves
Wear eye protection if contact likely
Wear respiratory protection for large spills in poorly ventilated areas
Wear protective overalls and footwear for large spillages
Absorb in sand or inert absorbent material
Small spills - wipe up with cloth
Collect into a container, close lid
Dispose or recycle of spillages in a controlled manner


LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE


CONTROL MEASURES

LOW ACUTE RISK - INDIVIDUAL ACTIVITY


LOW CHRONIC RISK - INDIVIDUAL ACTIVITY




AVOID SKIN CONTACT




BUTYL OR NITRILE




IF CONTACT LIKELY







WASH AFTER EXPOSURE



IF HEAVILY SOILED



CLOSE ALL CONTAINERS




CONTROLLED STORE /WASTE

FIRST AID

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill
Ingestion - do not induce vomiting, wash out mouth with water
If feeling unwell consult your doctor immediately
Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor
Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

FIRE

Isolated small scale fire:
Water fog - carbon dioxide - powder - foam - inert material
Do not use water jet
Large fire: evacuate area, call fire brigade or follow site procedure
Wear self-contained breathing apparatus and protective clothing



Alcumus®
Safer, Healthier, Stronger

ACTIVITY COMMENTS

This assessment was compiled by Alcumus Sypol Limited from supplier's safety data sheets where appropriate. Safety in the use of assessments is the responsibility of the subscriber. For advice call the helpdesk on 01296 678464

MORRISON
ZERO HARM

YOU CAN MAKE A DIFFERENCE

Printed 09/01/2019

DATE ASSESSMENT REVIEWED06/02/2018

LATEST SAFETY DATA SHEET REFERENCE

Derived

MATERIAL/PROCESS

BITUMEN PAINT

LOW HAZARD

LIQUID

SUPPLIER

PLAPRODUCTS LTD

KEYWORD

Paint (Bitumen)

CONTENTS

Asphalt (oxidised),

SIGNAL WORD

DANGER

EXP LIMIT

Asphalt (oxidised) 5mg/m3 8hTWA 10mg/m3 15mSTEL OEL

HEALTH HAZARDS

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

May cause eye irritation

CONSIDERATIONS





METHOD

Hand applying

AREA

Inside Poorly Ventilated

EXPOSURE TIME

4 to 8 hours per shift

SPILLAGE

Ventilate area

Wear butyl or nitrile gloves

Wear eye protection if contact likely

Wear respiratory protection for large spills in poorly ventilated areas

Wear protective overalls and footwear for large spillages

Absorb in sand or inert absorbent material

Small spills - wipe up with cloth

Collect into a container, close lid

Dispose or recycle of spillages in a controlled manner

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

CONTROL MEASURES

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK - INDIVIDUAL ACTIVITY



AVOID SKIN CONTACT



BUTYL OR NITRILE



IF CONTACT LIKELY





WASH AFTER EXPOSURE



IF HEAVILY SOILED



CLOSE ALL CONTAINERS



CONTROLLED STORE /WASTE

FIRST AID

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill

Ingestion - do not induce vomiting, wash out mouth with water

If feeling unwell consult your doctor immediately

Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor

Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

FIRE

Isolated small scale fire:

Water fog - carbon dioxide - powder - foam - inert material

Do not use water jet

Large fire: evacuate area, call fire brigade or follow site procedure

Wear self-contained breathing apparatus and protective clothing

Safer, Healthier, Stronger

ACTIVITY COMMENTS

This assessment was compiled by Alcumus Sypol Limited from supplier's safety data sheets where appropriate. Safety in the use of assessments is the responsibility of the subscriber. For advice call the helpdesk on 01296 678464

MORRISON ZERO HARM YOU CAN MAKE A DIFFERENCE

Printed 09/01/2019

DATE ASSESSMENT REVIEWED06/02/2018

LATEST SAFETY DATA SHEET REFERENCE

Derived