



FLOOR UPPER LAYERS

- BAR NOTATION**

7 B 12 04 150

No. OF BARS

TYPE OF STEEL

DIA OF BARS

BAR MARK

SPACING

BAR LOCATION

FAR FACE OUTER LAYER — F1

FAR FACE SECOND LAYER — F2

NEAR FACE OUTER LAYER — N1

NEAR FACE SECOND LAYER — N2

BOTTOM FACE OUTER LAYER — B1

BOTTOM FACE SECOND LAYER — B2

TOP FACE OUTER LAYER — T1

TOP FACE SECOND LAYER — T2

| | | | | | | | | | |
|---------------|---|--|---------------|--|-------|--|--|---|--------------|
| A1 A2 | DRN RFG C S CKD M.S. | ANY MODIFICATION TO THE DRAWING OR THE USE OF ALTERNATIVE ITEMS TO THOSE SPECIFIED <u>MUST</u> BE AGREED WITH THE DESIGNER. | MATERIAL - | OMS Drawing Review Drawing number amended to 02 of 08 | E | TOLERANCES TO SPECS BS8666, BS5606, BS EN1992 CN15456. | STANDARD MANHOLE MRX611A,611B,611C FLOOR REINFORCEMENT | REFERENCES SPECS: BS8666, BS EN1992 DRGS: CN15456. | |
| | CERTIFICATION DESIGNER M DA RIOS CLIENT M DA RIOS | | FINISH - | | | BT | | | OMS |
| DATE 04/07/94 | | | | AMENDMENT | ISSUE | Openreach | ALA944 | CN 14947 | SHT 02 OF 08 |