

MATERIAL/PROCESS

PROMAT PROMASEAL INTUMESCENT SEALANT

MEDIUM HAZARD

SEMI-SOLID

SUPPLIER

PROMAT UK LIMITED

KEYWORD

Sealant

CONTENTS

Naphtha (petroleum), hydrodesulfurized heavy 1 - 10%, Contains a plasticised acrylic polymer, fire retardant fillers, blowing agents and minor additives,

SIGNAL WORD

DANGER

EXP LIMIT

1200mg/m3 8hrTWA Hydrocarbon Recommended, Naphtha (petroleum),

HEALTH HAZARDS

Causes damage to organs through prolonged or repeated exposure
Causes skin irritation
Harmful to aquatic life with long lasting effects
May cause ill health if ingested in quantity
May cause eye irritation

CONSIDERATIONS

METHODGun Cleaning

AREAOutside

EXPOSURE TIME1/2 to 2 hours per shift

SPILLAGE

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

CONTROL MEASURES

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK - INDIVIDUAL ACTIVITY

KEEP SKIN COVERED

POLYTHENE OR NITRILE

IF CONTACT LIKELY

AND

LEV OR

FILTER TYPE A2

WASH AFTER EXPOSURE

IF SOILED

ACUTE HAZARD / ECOTOXIC

FIRST AID

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill
Ingestion - do not induce vomiting, wash out mouth with water
If feeling unwell consult your doctor immediately
Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor
Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor
High pressure injection of material into skin - get immediate medical attention

MATERIAL/PROCESS

PROMAT PROMASEAL INTUMESCENT SEALANT

MEDIUM HAZARD

SEMI-SOLID

SUPPLIER

PROMAT UK LIMITED

KEYWORD

Sealant

CONTENTS

Naphtha (petroleum), hydrodesulfurized heavy 1 - 10%, Contains a plasticised acrylic polymer, fire retardant fillers, blowing agents and minor additives,

SIGNAL WORD

DANGER



EXP LIMIT


1200mg/m3 8hrTWA Hydrocarbon Recommended, Naphtha (petroleum),

HEALTH HAZARDS

Causes damage to organs through prolonged or repeated exposure
Causes skin irritation
Harmful to aquatic life with long lasting effects
May cause ill health if ingested in quantity
May cause eye irritation

CONSIDERATIONS





METHODGun Cleaning

AREAINside Well Ventilated

EXPOSURE TIME1/2 to 2 hours per shift

SPILLAGE


MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE


CONTROL MEASURES

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY


MEDIUM CHRONIC RISK - INDIVIDUAL ACTIVITY




KEEP SKIN COVERED




POLYTHENE OR NITRILE




IF CONTACT LIKELY




AND




LEV OR




FILTER TYPE A2



WASH AFTER EXPOSURE



IF SOILED




ACUTE HAZARD / ECOTOXIC

FIRST AID

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill
Ingestion - do not induce vomiting, wash out mouth with water
If feeling unwell consult your doctor immediately
Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor
Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor
High pressure injection of material into skin - get immediate medical attention

FIRE

Isolated small scale fire:
Carbon dioxide - powder - foam - inert material
Large fire: evacuate area, call fire brigade or follow site procedure
Wear self-contained breathing apparatus and protective clothing



Alcumus®
Safer, Healthier, Stronger

ACTIVITY COMMENTS

This assessment was compiled by Alcumus Sypol Limited from supplier's safety data sheets where appropriate. Safety in the use of assessments is the responsibility of the subscriber. For advice call the helpdesk on 01296 678464

MORRISON
ZERO HARM

YOU CAN MAKE A DIFFERENCE

Printed 14/01/2019

DATE ASSESSMENT REVIEWED06/02/2018

LATEST SAFETY DATA SHEET REFERENCE

July 2016