**COSHH SUMMARY SHEET** www.alcumusgroup.com

MAIN **SUB FACILITY** JOB PACK JOB PACK

## MATERIAL/PROCESS

# BITUKOLD.

## MEDIUM HAZARD

**SUPPLIER COLAS LIMITED KEYWORD** Bitumen

**CONTENTS** 

Calcium chloride 1 - < 2.5%, bentonite 1 - < 2.5%, Rosin 1 - < 2.5%, Potassium hydroxide 0 - < 1%, 1,2-benzisothiazol-3(2H)one 0 - < 1%, Bitumen,

**HIGH ACUTE RISK - FULL EXPOSURE** 

SIGNAL WORD WARNING

Potassium hydroxide 2mg/m3 15mSTEL WEL, **EXP LIMIT** 

Rosin 0.05mg/m3 8hTWA 0.15mg/m3

#### **HEALTH HAZARDS**

Causes serious eye irritation

Causes skin irritation

May cause an allergic skin reaction

Skin - possible irreversible effects from prolonged contact if personal cleanliness ignored

May cause ill health if ingested in quantity





51047



**METHOD** Hand applying

AREA Outside

**HIGH CHRONIC RISK - FULL EXPOSURE** 

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY MEDIUM CHRONIC RISK - INDIVIDUAL ACTIVITY Wear respiratory protection for large spills in poorly ventilated areas

Ventilate area

Wear heavy duty impervious gloves

Suitable eye protection must be worn

Wear protective overalls & chemical proof footwear

Absorb in sand or inert absorbent material

Small spills - wipe up with cloth

Collect into a container, close lid

Dispose or recycle of spillages in a controlled manner



**CONTROL MEASURES** 



**IMPERVIOUS OVERALLS** 



**HEAVYDUTY IMPERVIOUS** 



**BS EN166** 





WASH AFTER **EXPOSURE** 



**EXPOSURE TIME** Up to 1/2 hour per shift SPILLAGE

AT END OF SHIFT

#### **FIRST AID**

In case of allergic reaction/anaphylactic shock call for immediate assistance from trained first aiders

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill Ingestion - do not induce vomiting, wash out mouth with water

If feeling unwell consult your doctor immediately

Eye - rinse thoroughly with water for 20 minutes - take care not to affect uncontaminated eye. If irritation persists then consult a doctor

Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Do not try to remove any adhering bitumen.



CONTAINERS



SENSITISER/AC UTE HAZARD

### FIRE

Isolated small scale fire:

Water fog - carbon dioxide - powder - foam - inert material

Do not use water jet

Large fire: evacuate area, call fire brigade or follow site procedure

Wear self-contained breathing apparatus and protective clothing



**ACTIVITY COMMENTS** 

This assessment was compiled by Alcumus Sypol Limited from supplier's safety data sheets where appropriate. Safety in the use of assessments is the responsibility of the subscriber. For advice call the helpdesk on 01296 678464

Printed 15/01/2019



www.alcumusgroup.com **COSHH SUMMARY SHEET** 

**FACILITY** JOB PACK MAIN JOB PACK **SUB** 

## MATERIAL/PROCESS

# BITUKOLD.

## MEDIUM HAZARD

**COLAS LIMITED SUPPLIER KEYWORD** Bitumen **CONTENTS** 

Calcium chloride 1 - < 2.5%, bentonite 1 - < 2.5%, Rosin 1 - < 2.5%, Potassium hydroxide 0 - < 1%, 1,2-benzisothiazol-3(2H)one 0 - < 1%, Bitumen,

SIGNAL WORD WARNING

**EXP LIMIT** 

Potassium hydroxide 2mg/m3 15mSTEL WEL, Rosin 0.05mg/m3 8hTWA 0.15mg/m3

**HEALTH HAZARDS** 

Causes serious eye irritation

Causes skin irritation

May cause an allergic skin reaction

Skin - possible irreversible effects from prolonged contact if personal cleanliness ignored

May cause ill health if ingested in quantity



CONSIDERATIONS

51047



**METHOD** Hand applying

AREA Confined Space **HIGH ACUTE RISK - FULL EXPOSURE** 

**EXPOSURE TIME** Up to 1/2 hour per shift SPILLAGE

**HIGH CHRONIC RISK - FULL EXPOSURE** 

**HIGH ACUTE RISK - INDIVIDUAL ACTIVITY** 

HIGH CHRONIC RISK - INDIVIDUAL ACTIVITY

Ventilate area

Wear heavy duty impervious gloves

Suitable eye protection must be worn

Wear respiratory protection for large spills in poorly ventilated areas

Wear protective overalls & chemical proof footwear

Absorb in sand or inert absorbent material

Small spills - wipe up with cloth

Collect into a container, close lid

Dispose or recycle of spillages in a controlled manner





**CONTROL MEASURES** 







**IMPERVIOUS OVERALLS** 



**HEAVYDUTY IMPERVIOUS** 



**BS EN166** 



AND



In case of allergic reaction/anaphylactic shock call for immediate assistance from trained first aiders Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill Ingestion - do not induce vomiting, wash out mouth with water

If feeling unwell consult your doctor immediately

Eye - rinse thoroughly with water for 20 minutes - take care not to affect uncontaminated eye. If irritation persists then consult a doctor

Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Do not try to remove any adhering bitumen.

LATEST SAFETY DATA SHEET REFERENCE



LEV AND



**EN137 OR** 14593/14594



WASH AFTER **EXPOSURE** 



AT END OF

SHIFT



**CLOSE ALL** CONTAINERS



SENSITISER/AC **UTE HAZARD** 

#### FIRE

Isolated small scale fire:

Water fog - carbon dioxide - powder - foam - inert material

Do not use water jet

Large fire: evacuate area, call fire brigade or follow site procedure Wear self-contained breathing apparatus and protective clothing



#### **ACTIVITY COMMENTS**

Refer to Confined Spaces Regulations 1997 and your specific Confined Spaces Risk Assessment for further requirements.

This assessment was compiled by Alcumus Sypol Limited from supplier's safety data sheets where appropriate. Safety in the use of assessments is the responsibility of the subscriber. For advice call the helpdesk on 01296 678464

Printed 15/01/2019

