
MRX412A

1500 25 400 400 295 295 690

+ SPECIFIED TO THE NEAREST 25mm

REFER TO DRAWING CN14937 SHT. 1 of 5 FOR NOTES

MRX412B



+ SPECIFIED TO THE NEAREST 25mm


* SPECIFIED TO THE NEAREST 5mm

CHAMFER BAR — BAR MARK 28 SHAPE CODE 24

DIMENSIONS IN mm UNLESS OTHERWISE STATED © British Telecommunications plc 1994 MATERIAL OMS Drawing Review Drawing number amended to 05 of 05 Chamfer bars (BM28) shape code amended to 24 **FINISH** 21.08.15

MRX412C

MEMBER	BAR MARK	TYPE & SIZE	NO OF MBRS	NO IN EACH	TOTAL NO	LENGTH OF EACH BAR + MM	SHAPE CODE	A *	B *	C *	D* E/	* 'R •
FLOOR	01	B20	1	46	46	2550	00	2550				
FLOOR	02	B20	1	54	54	2100	00	2100				
SIDE WALLS	03	B20	2	30	60	2925	00	2925				
FLOOR	04	B20	1	48	48	2550	00	2550				
SIDE WALLS	05	B20	2	36	72	2550	00	2550				
FL00R	06	B20	1	56	56	2100	00	2100				
SIDE & END WALLS	07	B20	4	19	76	1600	11	800				
END WALLS	80	B20	2	20	40	2925	00	2925				
FLOOR & SIDE WALLS	09	B20	2	50	100	1900	11	1100	STARTER	BAR (SHO	rt leg in fla	XOR)
END WALLS	10	B20	2	18	36	2100	00	2100				
FLOOR & END WALLS	11	B20	2	42	84	1900	11	1100	STARTER	BAR (SHO	rt leg in fla	XOR)
SIDE WALLS	12	B20	2	25	50	2925	00	2925				
SIDE WALLS	13	B20	2	36	72	2550	00	2550				
END WALLS	14	B20	2	21	42	2925	00	2925				
END WALLS	15	B20	2	36	72	2100	00	2100				
ROOF	16	B20	1	54	54	2100	00	2100				
ROOF	17	B20			24	2220	00	2220			Ming Bar G CN1391	_
R00F	18	B20			2	1850	11	1000			MING BAR G CN1391	_
ROOF & SIDE WALLS	19	B20	2	58	116	1600	11	800				
ROOF	20	B20	1	46	46	2550	00	2550				
ROOF	21	B20	1	46	46	2550	00	2550				
ROOF	22	B20	1	54	54	2100	00	2100				
ROOF & END WALLS	23	B20	2	42	84	1600	11	800				
		B10			20	750	98	250	165	120	SEE NOT	E #
(FLOOR)	24B	B10			20	900	98	250	150	200	SEE NOT	E #
SIDE & END WALLS	25	B10			64	525	21	200	165		U BARS	3
SPARE	26											
WHERE NEEDED		B20		•				2200			MING BAR	S
CHAMFER BARS	28	B16	2	100	200	1475	24	400	665	400	470	
CHAMFER 28 B16 2 100 200 1475 24 400 665 400 470 ALL BENDING DIMENSIONS ARE IN ACCORDANCE WITH B.S.8666 * SPECIFIED TO THE NEAREST 5mm + SPECIFIED TO THE NEAREST 25mm												



BAR MARK 24A-B10 & 24B-B10 SHAPE CODE 99

FOR BAR DETAILS SEE ABOVE

NOTE: CHAIRS CAN BE REPLACED WITH PROPRIETARY SPACERS AT THE CONTRACTOR'S DISCRETION.

DO NOT SCALE ORIGINAL SCALE 1:20 REFERENCES STANDARD SPECS: BS8666, BS5606 & MANHOLE MRX412A,412B,412C BS EN1992 BAR SCHEDULE

CN

14937

DRN RFG C S M DA RIOS M DA RIOS

DATE 04/07/94

ANY MODIFICATION TO THE DRAWING OR THE USE OF ALTERNATIVE ITEMS TO THOSE SPECIFIED MUST BE AGREED WITH THE DESIGNER.

* SPECIFIED TO THE NEAREST 5mm

AMENDMENT

ISSUE Openreach

VARIOUS LOCATIONS

TOLERANCES TO SPECS

CN15456.

BS8666, BS5606, BS EN1992

ALA944

DRGS: CN15456.

SHT 05 OF 05