

ID#:	4015080	User making request:	Dorrett Bryan
Fax:		Phone:	01438 903752
Email:	dorrett.bryan@morrisonus.com	Date Created:	19/03/2020
Date Assessment Reviewed	19/03/2020	Next Review Date:	19/03/2025
Material Code:	246377	Tradename:	4 TRADE ADMIXTURE MORTAR PLASTICISER
Supplier:	BOSTIK LIMITED	IMC:	
Keyword:	Plasticiser	Frequency of use:	Weekly
Approximately how much of the material is used by one person in one working day:	5 litres	How many people are directly exposed?:	1
Are any other people put at risk from indirect exposure?:	No	How are they exposed?:	
Are there any susceptible workers?:	No	Susceptible Categories:	
Other info:		Is this material being used outside of the normal temperature range?:	No

Additional work practices:

Existing Control measures:

Exp Limit

Notes

Files Uploaded

File Name

S4ziL9rZ.pdf

Activities

Act No.	Method	Area	Exposure
1	Decanting	Outside	Up to 1/2 hour per shift

Work Area

Work Area Code	Sub Area Code
----------------	---------------

TELECOMS

Safer Substitute Chosen	Reason for leaving/swapping material
-------------------------	--------------------------------------

4 TRADE ADMIXTURE MORTAR PLASTICISER



LOW HAZARD

LIQUID

SUPPLIER BOSTIK LIMITED
KEYWORD Plasticiser

CONTENTS
Full details of constituents not provided by supplier, This product has been classified as per the supplier's safety data sheet,

SIGNAL WORD NONE
EXP LIMIT

HEALTH HAZARDS
May cause ill health if ingested in quantity
Skin - irritation and dermatitis may result from prolonged contact
May cause eye irritation

METHOD Decanting AREA Outside EXPOSURE TIME Up to 1/2 hour per shift

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK - INDIVIDUAL ACTIVITY

AVOID SKIN CONTACT

IF OVEREXPOSURE LIKELY

IF CONTACT LIKELY

WASH AFTER EXPOSURE

IF HEAVILY SOILED

CLOSE ALL CONTAINERS

CONTROLLED STORE /WASTE

SPILLAGE
Ventilate area
Wear polythene or nitrile gloves
Wear eye protection if contact likely
Wear respiratory protection for large spills in poorly ventilated areas
Wear protective overalls and footwear for large spillages
Absorb in sand or inert absorbent material
Small spills - wipe up with cloth
Collect into a container, close lid
Dispose or recycle of spillages in a controlled manner - Refer to Hazardous Waste Regulations if appropriate

FIRST AID
Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill
Ingestion - do not induce vomiting, wash out mouth with water
If feeling unwell consult your doctor immediately
Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor
Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor
High pressure injection of material into skin - get immediate medical attention

FIRE
Isolated small scale fire:
Water fog - carbon dioxide - powder - foam - inert material
Do not use water jet
Large fire: evacuate area, call fire brigade or follow site procedure
Wear self-contained breathing apparatus and protective clothing

ACTIVITY COMMENTS

MATERIAL/PROCESS

4 TRADE ADMIXTURE MORTAR PLASTICISER


SUPPLIERBOSTIK LIMITED

KEYWORDPlasticiser

SIGNAL WORDNONE

LOW HAZARD

LIQUID



METHODDecanting

AREAA Outside

EXPOSURE TIMEUp to 1/2 hour per shift

ACTIVITY COMMENTS

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

CONTROL MEASURES

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK - INDIVIDUAL ACTIVITY



AVOID SKIN CONTACT



IF OVEREXPOSURE LIKELY



IF CONTACT LIKELY





WASH AFTER EXPOSURE



IF HEAVILY SOILED



CLOSE ALL CONTAINERS



CONTROLLED STORE /WASTE

HEALTH HAZARDS

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

May cause eye irritation


REQUEST DETAILS	#ID:	4015080	User making request:	Dorrett Bryan
MATERIAL DETAILS	Material Code:	246377	LOW UNCONTROLLED ACUTE RISK LOW UNCONTROLLED CHRONIC RISK LOW CONTROLLED ACUTE/CHRONIC RISK	
Tradename:	4 TRADE ADMIXTURE MORTAR PLASTICISER			
IMC:	Supplier:	BOSTIK LIMITED		

ACTIVITY DETAILS			
Act No.	Method	Area	Exposure
1	Decanting	Outside	Up to 1/2 hour per shift

SCENARIO DETAILS		Additional work practices:	
Approximately how much of the material is used by one person in one working day:	5 litres	Frequency of use:	Weekly
Are any other people put at risk from indirect exposure?:	No	How many people are directly exposed?:	1
Are there any susceptible workers?:	No	How are they exposed?:	
		Susceptible Categories:	

WORK AREA	
Work Area Code	Sub Area Code
TELECOMS	

OTHER INFORMATION

CONSIDERATIONS	Answer
 Are procedures to ensure the maintenance of controls in place?	YES