

ID#:	4015016	User making request:	Sypol Super User
Fax:		Phone:	01296415715
Email:	user@sypol.com	Date Created:	19/03/2020
Date Assessment Reviewed	19/03/2020	Next Review Date:	19/03/2025
Material Code:	2396	Tradename:	WD-40 MULTI-USE PRODUCT [AEROSOL]
Supplier:	WD-40 COMPANY LIMITED	IMC:	
Keyword:	Lubricant (Aerosol)	Frequency of use:	Daily
Approximately how much of the material is used by one person in one working day:	up to 100 ml	How many people are directly exposed?:	1
Are any other people put at risk from indirect exposure?:	No	How are they exposed?:	
Are there any susceptible workers?:	No	Susceptible Categories:	
Other info:		Is this material being used outside of the normal temperature range?:	No
Additional work practices:			
Existing Control measures:			
Exp Limit	Oil mist(min*) 5mg/m3TWA 10mg/m3STEL OEL, Carbon dioxide 9150mg/m3 8hTWA 5000ppm 8hTWA 27400mg/m3 15mSTEL 15000ppm 15mSTEL WEL, Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics 800mg/m3 8hTWA OEL		
Notes	Classification is based upon the contents stated in the supplier's safety data sheet rather than upon the supplier's classification.		

Files Uploaded

File Name

Activities

Act No.	Method	Area	Exposure
20	Spraying (Aerosol)	Inside Well Ventilated	Up to 1/2 hour per shift

Work Area

Work Area Code	Sub Area Code
TELECOMS	

Safer Substitute Chosen No Reason for leaving/swapping material

MATERIAL/PROCESS

CONSIDERATIONS

WD-40 MULTI-USE PRODUCT [AEROSOL]

MEDIUM HAZARD

AEROSOL

SUPPLIER

WD-40 COMPANY LIMITED

KEYWORD

Lubricant (Aerosol)

CONTENTS

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics 60 - 80%, Carbon dioxide 1 - < 3%,

SIGNAL WORD

DANGER

EXP LIMIT

Oil mist(min\*) 5mg/m3TWA 10mg/m3STEL  
OEL, Carbon dioxide 9150mg/m3 8hTWA



HEALTH HAZARDS

Extremely flammable aerosol  
Pressurised container: May burst if heated.  
May cause drowsiness or dizziness  
Repeated exposure may cause skin dryness or cracking  
May cause ill health if ingested in quantity  
May cause eye irritation



METHOD

Spraying (Aerosol)

AREA

Inside Well Ventilated

EXPOSURE TIME

Up to 1/2 hour per shift

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK - INDIVIDUAL ACTIVITY

CONTROL MEASURES



KEEP SKIN COVERED



POLYTHENE OR NITRILE



IF CONTACT LIKELY



WASH AFTER EXPOSURE



IF HEAVILY SOILED



PRESSURISED

SPILLAGE

Not applicable when intact  
In case of leakage or loss of containment:  
Ventilate area and exclude all sources of ignition  
Wear protective clothing if whole container is spilt  
Allow to dissipate  
Wear polythene or nitrile gloves  
Ensure area is safe before re-entry

FIRST AID

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill  
Ingestion - do not induce vomiting, wash out mouth with water  
If feeling unwell consult your doctor immediately  
Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor  
Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

FIRE

Keep aerosol cans cool, do not burn for disposal  
Isolated small scale fire:  
Vapour may spread - distant ignition is possible  
Water fog - carbon dioxide - powder - foam  
Do not use water jet  
Large fire: evacuate area, call fire brigade or follow site procedure  
Wear self-contained breathing apparatus and protective clothing  
Keep containers cool with water spray  
Risk of explosion if involved in a fire

ACTIVITY COMMENTS

Intermittent use of aerosol spray.

This assessment was compiled by Alcumus Sypol Limited from supplier's safety data sheets where appropriate. Safety in the use of assessments is the responsibility of the subscriber. For advice call the helpdesk on 01296 678464

Printed 15/04/2021



MATERIAL/PROCESS

WD-40 MULTI-USE PRODUCT [AEROSOL]



SUPPLIERWD-40 COMPANY LIMITED

KEYWORDLubricant (Aerosol)

SIGNAL WORDDANGER

MEDIUM HAZARD

AEROSOL



METHODSpraying (Aerosol)

AREAINside Well Ventilated

EXPOSURE TIMEUp to 1/2 hour per shift

ACTIVITY COMMENTSI

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Intermittent use of aerosol spray.

CONTROL MEASURES

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK - INDIVIDUAL ACTIVITY



KEEP SKIN COVERED



POLYTHENE OR NITRILE



IF CONTACT LIKELY





WASH AFTER EXPOSURE



IF HEAVILY SOILED



PRESSURISED

HEALTH HAZARDS

Extremely flammable aerosol

Pressurised container: May burst if heated.

May cause drowsiness or dizziness

Repeated exposure may cause skin dryness or cracking

May cause ill health if ingested in quantity

May cause eye irritation

REQUEST DETAILS	#ID:	4015016	User making request:	Sypol Super User
MATERIAL DETAILS	Material Code:	2396	<div>LOW UNCONTROLLED ACUTE RISK</div> <div>LOW UNCONTROLLED CHRONIC RISK</div> <div>LOW CONTROLLED ACUTE/CHRONIC RISK</div>	
Tradename:	WD-40 MULTI-USE PRODUCT [AEROSOL]			
IMC:	Supplier:	WD-40 COMPANY LIMITED		




ACTIVITY DETAILS			
Act No.	Method	Area	Exposure
20	Spraying (Aerosol)	Inside Well Ventilated	Up to 1/2 hour per shift

SCENARIO DETAILS		Additional work practices:	
Approximately how much of the material is used by one person in one working day:	up to 100 ml	Frequency of use:	Daily
Are any other people put at risk from indirect exposure?:	No	How many people are directly exposed?:	1
Are there any susceptible workers?:	No	How are they exposed?:	
		Susceptible Categories:	

WORK AREA	
Work Area Code	Sub Area Code
TELECOMS	

OTHER INFORMATION

Classification is based upon the contents stated in the supplier's safety data sheet rather than upon the supplier's classification.

CONSIDERATIONS		Answer
	Has the elimination or substitution of this material been considered?	YES
	Are procedures to ensure the maintenance of controls in place?	YES
	Are procedures to undertake skin checks in place?	YES