



NOTES:

- 1. THE BASE OF THE EXCAVATION TO BE WELL CONSOLIDATED, FLAT AND FREE FROM STONES, THEN COVERED WITH A 50mm LAYER OF SAND.
- 2. A BACKFILL OF SOIL, FREE FROM STONES, TO BE WELL COMPACTED ALL AROUND THE BOX. IF COMPACTION IS DIFFICULT, THEN A LEAN MIX CONCRETE SHOULD BE USED AS THE BACKFILL MATERIAL.
- 3. THE UPPERMOST SURFACE OF FRAME AND COVER TO BE LEVEL WITH FOOTWAY SURFACE.
- 4. THE KNOCKOUT MATERIAL TO BE CAREFULLY REMOVED USING A 1Kg. CLUB HAMMER.

© British Telecommunications plc 1986					DO NOT SCALE		ORIGINAL SCALE	
		NOTE 5 REMOVED.		C	REFERENCES			
		D.CUSSELLE S.A.D 29/09/05						
		AMENDMENT		ISSUE				
A3 A4	DRN	MATERIAL	FINISH					
	CKD							
	CERTIFICATION		BOX JOINT 26 INSTALLATION					
DATE 9-2-87								
R699	BRITISH TELECOMMUNICATIONS HEADQUARTERS IC/LLS3.1.1				CN14113			