

ID#:	3772919	User making request:	N/A
Fax:		Phone:	
Email:		Date Created:	11/04/2019
Date Assessment Reviewed	11/04/2019	Next Review Date:	11/04/2024
Material Code:	257986	Tradename:	TECH LUBE CABLE LUBRICANT
Supplier:	SOCOMORE	IMC:	
Keyword:	Lubricant	Frequency of use:	Monthly
Approximately how much of the material is used by one person in one working day:	1 LITRE	How many people are directly exposed?:	1
Are any other people put at risk from indirect exposure?:	Yes	How are they exposed?:	POURING LUBRICANT FROM A CONTAINER OVER THE CABLE
Are there any susceptible workers?:	No	Susceptible Categories:	
Other info:		Is this material being used outside of the normal temperature range?:	No
Additional work practices:	AS ABOVE		
Existing Control measures:	OUTSIDE		
Exp Limit			
Notes			

Files Uploaded

File Name

Activities

Act No.	Method	Area	Exposure
2	Pouring	Outside	1/2 to 2 hours per shift

Work Area

Work Area Code	Sub Area Code
TELECOMS	

Safer Substitute Chosen	Reason for leaving/swapping material
-------------------------	--------------------------------------

SUMMARY SHEET

FACILITY	TELECOMS	MAIN	TELECOMS	SUB	257986
----------	----------	------	----------	-----	--------

MATERIAL/PROCESS

TECH LUBE CABLE LUBRICANT

LOW HAZARD

LIQUID

SUPPLIER SOCOMORE
KEYWORD Lubricant

CONTENTS
Not classified as hazardous under the CLP regulations, This product has been classified as per the supplier's safety data sheet, Full details of constituents not provided by supplier,

SIGNAL WORD NONE
EXP LIMIT



HEALTH HAZARDS

May cause ill health if ingested in quantity
May cause eye irritation
Skin - irritation and dermatitis may result from prolonged contact



CONSIDERATIONS

METHOD	Pouring	AREA	Outside	EXPOSURE TIME	1/2 to 2 hours per shift
--------	---------	------	---------	---------------	--------------------------

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK - INDIVIDUAL ACTIVITY

AVOID SKIN CONTACT

POLYTHENE OR NITRILE

IF CONTACT LIKELY

WASH AFTER EXPOSURE

IF HEAVILY SOILED

CLOSE ALL CONTAINERS

CONTROLLED STORE /WASTE

SPILLAGE

Ventilate area
Wear polythene or nitrile gloves
Wear eye protection if contact likely
Wear respiratory protection for large spills in poorly ventilated areas
Wear protective overalls and footwear for large spillages
Absorb in sand or inert absorbent material
Small spills - wipe up with cloth
Collect into a container, close lid
Dispose or recycle of spillages in a controlled manner - Refer to Hazardous Waste Regulations if appropriate

FIRST AID

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill
Ingestion - do not induce vomiting, wash out mouth with water
If feeling unwell consult your doctor immediately
Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor
Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

FIRE

Isolated small scale fire:
Powder - foam - carbon dioxide (CO2)
Large fire: evacuate area, call fire brigade or follow site procedure
Wear self-contained breathing apparatus and protective clothing

ACTIVITY COMMENTS



This assessment was compiled by Alcumus Sypol Limited from supplier's safety data sheets where appropriate. Safety in the use of assessments is the responsibility of the subscriber. For advice call the helpdesk on 01296 678464

Printed 16/04/2021




MATERIAL/PROCESS

TECH LUBE CABLE LUBRICANT

LOW HAZARD

LIQUID



SUPPLIER

SOCOMORE

KEYWORD

Lubricant

SIGNAL WORD

NONE

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

CONTROL MEASURES

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK - INDIVIDUAL ACTIVITY



AVOID SKIN CONTACT



POLYTHENE OR NITRILE



IF CONTACT LIKELY



WASH AFTER EXPOSURE



IF HEAVILY SOILED



CLOSE ALL CONTAINERS



CONTROLLED STORE /WASTE

HEALTH HAZARDS

May cause ill health if ingested in quantity

May cause eye irritation

Skin - irritation and dermatitis may result from prolonged contact

REQUEST DETAILS	#ID:	3772919	User making request:	N/A
MATERIAL DETAILS	Material Code:	257986	LOW UNCONTROLLED ACUTE RISK LOW UNCONTROLLED CHRONIC RISK LOW CONTROLLED ACUTE/CHRONIC RISK	
Tradename:	TECH LUBE CABLE LUBRICANT			
IMC:	Supplier:	SOCOMORE		

ACTIVITY DETAILS			
Act No.	Method	Area	Exposure
2	Pouring	Outside	1/2 to 2 hours per shift

SCENARIO DETAILS	Additional work practices:		AS ABOVE	
Approximately how much of the material is used by one person in one working day:	1 LITRE	Frequency of use:	Monthly	How many people are directly exposed?: 1
Are any other people put at risk from indirect exposure?:	Yes	How are they exposed?:		POURING LUBRICANT FROM A CONTAINER OVER THE CABLE
Are there any susceptible workers?:	No	Susceptible Categories:		

WORK AREA	
Work Area Code	Sub Area Code
TELECOMS	

OTHER INFORMATION

CONSIDERATIONS	Answer
 Are procedures to ensure the maintenance of controls in place?	YES