

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)



Properties of Regular Languages

Reading: Chapter 4



Topics

1) How to prove whether a given language is regular or not?

2) Closure properties of regular languages

3) Minimization of DFAs

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Some languages are *not* regular

When is a language is regular?


if we are able to construct one of the following: DFA *or* NFA *or* ε -NFA *or* regular expression

When is it not?

If we can show that no FA can be built for a language

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

How to prove languages are ***not*** regular?



What if we cannot come up with any FA?

A) Can it be language that is not regular?

B) Or is it that we tried wrong approaches?

How do we *decisively* prove that a language is not regular?

"The hardest thing of all is to find a black cat in a dark room, especially if there is no cat!" *-Confucius*

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Example of a non-regular language

Let L = {w | w is of the form 0^n1^n , for all n≥0}

- *Hypothesis: L is not regular*
- Intuitive rationale: How do you keep track of a running count in an FA?
- A more formal rationale:
  - By contradition, if L is regular then there should exist a DFA for L.
  - Let k = number of states in that DFA.
  - Consider the special word w= 0^k1^k => w ∈ L
  - DFA is in some state p_i, after consuming the first i symbols in w

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Rationale…

- Let $\{p_0, p_1, \ldots p_k\}$ be the sequence of states that the DFA should have visited after consuming the first k symbols in w which is 0^k
- But there are only k states in the DFA!
- ==> at least one state should repeat somewhere along the path (by  Principle)
- ==> Let the repeating state be $p_i = p_J$ for $i < j$
- ==> We can fool the DFA by inputing $0^{(k-(j-i))}1^k$ and still get it to accept (note: k-(j-i) is at most k-1).
- ==> DFA accepts strings w/ unequal number of 0s and 1s, implying that the DFA is wrong!



AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

The Pumping Lemma for Regular Languages

What it is?

The Pumping Lemma is a property of all regular languages.

How is it used?

A technique that is used to show that a given language is not regular

Pumping Lemma for Regular Languages

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Let L be a regular language

Then *there exists* some constant ***N*** such that *for every* string $w \in L$ s.t. $|w| \geq N$, *there exists* a way to break w into three parts, $w=xyz$, such that:

1. $y \neq \varepsilon$
2. $|xy| \leq N$
3. For all $k \geq 0$, all strings of the form $xy^kz \in L$

This property should hold for all regular languages.

Definition: *N* is called the "Pumping Lemma Constant"

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)


Pumping Lemma: Proof

- L is regular => it should have a DFA.
  - Set N := number of states in the DFA
- Any string $w \in L$, s.t. $|w| \geq N$, should have the form: $w=a_1a_2\ldots a_m$, where $m \geq N$
- Let the states traversed after reading the first N symbols be: $\{p_0, p_1, \ldots p_N\}$
  - ==> There are N+1 p-states, while there are only N DFA states
  - ==> at least one state has to repeat
    i.e, $p_i = p_J$ where $0 \leq i < j \leq N$ (by PHP)

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)


Pumping Lemma: Proof…

- => We should be able to break w=xyz as follows:
  - $x=a_1a_2..a_i$; $y=a_{i+1}a_{i+2}..a_J$; $z=a_{J+1}a_{J+2}..a_m$
  - x's path will be $p_0..p_i$
  - y's path will be $p_i\ p_{i+1}..p_J$ (but $p_i=p_J$ implying a loop)
  - z's path will be $p_Jp_{J+1}..p_m$
- Now consider another string $w_k=xy^kz$, where k≥0
- Case k=0
  - DFA will reach the accept state p_m
- Case k>0
  - DFA will loop for y^k, and finally reach the accept state p_m for z
- In either case, $w_k \in L$ This proves part (3) of the lemma



Pumping Lemma: Proof…

- For part (1):
  - Since i<j, y ≠ ε




- For part (2):
  - By PHP, the repetition of states has to occur within the first N symbols in w
  - ==> |xy|≤N

□

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)


The Purpose of the Pumping Lemma for RL



- To prove that some languages *cannot be* regular.

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

How to use the pumping lemma?



Think of playing a 2 person game

- Role 1: ***We*** claim that the language cannot be regular
- Role 2: An ***adversary*** who claims the language is regular
- We show that the adversary's statement will lead to a contradiction that implyies pumping lemma *cannot* hold for the language.
- We win!!

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

How to use the pumping lemma? (The Steps)

1. (we) L is not regular.
2. (adv.) Claims that L is regular and gives you a value for N as its P/L constant
3. (we) Using N, choose a string w $\in$ L s.t.,
   1. $|w| \geq N$,
   2. Using w as the template, construct other words w_k of the form xy^kz and show that at least one such $w_k \notin L$

      => this implies we have successfully broken the pumping lemma for the language, and hence that the adversary is wrong.

(Note: In this process, we may have to try many values of k, starting with k=0, and then 2, 3, .. so on, until $w_k \notin L$)

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Note: We don't have any control over N, except that it is positive.
We also don't have any control over how to split w=xyz,
but xyz should respect the P/L conditions (1) and (2).

Using the Pumping Lemma

- What WE do?

3. Using *N*, we construct our template string *w*
4. Demonstrate to the adversary, either through pumping up or down on *w*, that some string $w_k \notin L$ (this should happen regardless of w=xyz)

- What the Adversary does?

1. Claims L is regular
2. Provides *N*

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Note: This N can be anything (need not necessarily be the #states in the DFA. It's the adversary's choice.)

Example of using the Pumping Lemma to prove that a language is not regular

Let L_{eq} = {w | w is a binary string with equal number of 1s and 0s}

- Your Claim: L_{eq} is not regular
- Proof:
  - By contradiction, let L_{eq} be regular → adv.
  - P/L constant should exist → adv.
    - Let *N* = that P/L constant
  - Consider input $w = 0^N1^N$ → you
    (your choice for the template string)
  - By pumping lemma, we should be able to break w=xyz, such that: →you
    1) $y \neq \varepsilon$
    2) $|xy| \leq N$
    3) For all $k \geq 0$, the string xy^kz is also in L

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Template string $w = 0^N1^N = \underbrace{00\ldots}_{N}\underbrace{011\ldots}_{N}1$

Proof…

- Because $|xy| \leq N$, xy should contain only 0s
  - (This and because $y \neq \varepsilon$, implies $y=0^+$)
- Therefore x can contain *at most* N-1 0s
- Also, all the N 1s must be inside z
- By (3), any string of the form $xy^kz \in L_{eq}$ for all $k \geq 0$
- Case k=0: xz has at most N-1 0s but has N 1s
- Therefore, $xy^0z \notin L_{eq}$
- This violates the P/L (a contradiction)


➔ you

Setting k=0 is referred to as **"pumping down"**

Setting k>1 is referred to as **"pumping up"**

Another way of proving this will be to show that if the #0s is arbitrarily pumped up (e.g., k=2), then the #0s will become exceed the #1s

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)



Exercise 2

Prove L = {$0^n 1 0^n$ | $n \geq 1$} is not regular

Note: This n is not to be confused with the pumping lemma constant N. That *can* be different.

In other words, the above question is same as proving:

- L = {$0^m 1 0^m$ | $m \geq 1$} is not regular

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Example 3: Pumping Lemma

Claim: L = { 0^i | i is a perfect square} is not regular

- Proof:
  - By contradiction, let L be regular.
  - P/L should apply
  - Let *N* = P/L constant
  - Choose w=0^{N^2}
  - By pumping lemma, w=xyz satisfying all three rules
  - By rules (1) & (2), y has between 1 and N 0s
  - By rule (3), any string of the form xy^kz is also in L for all k≥0
  - Case k=0:
    - #zeros (xy^0z) = #zeros (xyz) - #zeros (y)
    - $N^2 - N \leq$ #zeros (xy^0z) $\leq N^2 - 1$
    - $(N-1)^2 < N^2 - N \leq$ #zeros (xy^0z) $\leq N^2 - 1 < N^2$
    - $xy^0z \notin L$
    - But the above will complete the proof ONLY IF N>1.
    - … (proof contd.. Next slide)

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Example 3: Pumping Lemma

- (proof contd…)
  - If the adversary pick N=1, then $\mathbf{(N-1)^2} \leq N^2 - N$, and therefore the #zeros(xy^0z) could end up being a perfect square!
  - This means that pumping down (i.e., setting k=0) is not giving us the proof!
  - So lets try pumping up next…
- Case k=2:
  - #zeros (xy^2z) = #zeros (xyz) + #zeros (y)
  - $N^2 + 1 \leq$ #zeros (xy^2z) $\leq N^2 + N$
  - $\mathbf{N^2} < N^2 + 1 \leq$ #zeros (xy^2z) $\leq N^2 + N < \mathbf{(N+1)^2}$
  - $xy^2z \notin L$ 
  - (Notice that the above should hold for all possible N values of N>0. Therefore, this completes the proof.)



Closure properties of Regular Languages

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Closure properties for Regular Languages (RL)


This is different from Kleene closure

- *Closure property:*
  - If a set of regular languages are combined using an operator, then the resulting language is also regular
- Regular languages are *closed* under:
  - Union, intersection, complement, difference
  - Reversal
  - Kleene closure
  - Concatenation
  - Homomorphism
  - Inverse homomorphism

Now, lets prove all of this!

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)



RLs are closed under union

- IF L and M are two RLs THEN:
  - they both have two corresponding regular expressions, R and S respectively
  - (L U M) can be represented using the regular expression R+S
  - Therefore, (L U M) is also regular


□

How can this be proved using FAs?

RLs are closed under complementation

- If L is an RL over ∑, then $\overline{L}$=∑*-L
  - To show $\overline{L}$ is also regular, make the following construction

Convert every final state into non-final, and every non-final state into a final state



Assumes q0 is a non-final state. If not, do the opposite.

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

RLs are closed under intersection

- A quick, indirect way to prove:
  - By DeMorgan's law:
  - $L \cap M = (\overline{\bar{L} \cup \bar{M}})$
  - Since we know RLs are closed under union and complementation, they are also closed under intersection
- A more direct way would be construct a finite automaton for $L \cap M$


AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

DFA construction for L ∩ M

- A_L = DFA for L = $\{Q_L, \sum, q_L, F_L, \delta_L\}$
- A_M = DFA for M = $\{Q_M, \sum, q_M, F_M, \delta_M\}$
- Build $A_{L \cap M} = \{Q_L \times Q_M, \sum, (q_L, q_M), F_L \times F_M, \delta\}$ such that:
  - $\delta((p,q),a) = (\delta_L(p,a), \delta_M(q,a))$, where p in Q_L, and q in Q_M
- This construction ensures that a string w will be accepted if and only if w reaches an accepting state in <u>both</u> input DFAs.

DFA construction for L ∩ M



AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)


RLs are closed under set difference

- We observe:
  - $L - M = L \cap \overline{M}$
- Therefore, L - M is also regular

Closed under intersection

Closed under complementation

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)



RLs are closed under reversal

Reversal of a string w is denoted by w^R

- E.g., w=00111, w^R=11100


Reversal of a language:

- L^R = The language generated by reversing all strings in L

Theorem: If L is regular then L^R is also regular

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

ε -NFA Construction for L^R



What to do if q_0 was one of the final states in the input DFA?

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

If L is regular, L^R is regular (proof using regular expressions)

- Let E be a regular expression for L
- Given E, how to build E^R?
- Basis: If E= ε, Ø, or a, then E^R=E
- Induction: Every part of E (refer to the part as "F") can be in only *one* of the three following forms:
  1. $F = F_1+F_2$
     - $F^R = F_1^R+F_2^R$
  2. $F = F_1F_2$
     - $F^R = F_2^RF_1^R$
  3. $F = (F_1)^*$
     - $(F^R)^* = (F_1^R)^*$

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Homomorphisms

- Substitute each symbol in ∑ (main alphabet) by a corresponding string in T (another alphabet)
  - h: ∑--->T*
- Example:
  - Let ∑={0,1} and T={a,b}
  - Let a homomorphic function h on ∑ be:
    - h(0)=ab, h(1)=ε
  - If w=10110, then h(w) = εabεεab = abab
- In general,
  - $h(w) = h(a_1)\, h(a_2) \ldots h(a_n)$

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

RLs are closed under homomorphisms


- Theorem: If L is regular, then so is h(L)
- Proof: If E is a RE for L, then show L(h(E)) = h(L(E))
- Basis: If E= ε, Ø, or a, then the claim holds.
- Induction: There are three forms of E:
  1. $E = E_1+E_2$
     - $L(h(E)) = L(h(E_1) + h(E_2)) = L(h(E_1)) \cup L(h(E_2))$ ----- (1)
     - $h(L(E)) = h(L(E_1) + L(E_2)) = h(L(E_1)) \cup h(L(E_2))$ ----- (2)
     - By inductive hypothesis, $L(h(E_1))= h(L(E_1))$ and $L(h(E_2))= h(L(E_2))$
     - Therefore, L(h(E)= h(L(E)
  2. $E = E_1E_2$
  3. $E = (E_1)^*$

  } Similar argument

Think of a DFA based construction

Given a DFA for L, how to convert it into an FA for h(L)?

FA Construction for h(L)



Replace every edge "a" by a path labeled h(a) in the new DFA

- Build a new FA that simulates h(a) for every symbol a transition in the above DFA
- The resulting FA may or may not be a DFA, but will be a FA for h(L)

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Given a DFA for M, how to convert it into an FA for $h^{-1}(M)$?

The set of strings in $\sum^*$ whose homomorphic translation results in the strings of M

Inverse homomorphism

- Let h: $\sum$--->T*
- Let M be a language over alphabet T
- $h^{-1}(M) = \{w \mid w \in \sum^* \text{ s.t., } h(w) \in M\}$

Claim: If M is regular, then so is $h^{-1}(M)$


- Proof:
  - Let A be a DFA for M
  - Construct another DFA A' which encodes $h^{-1}(M)$
  - A' is an exact replica of A, except that its transition functions are s.t. for any input symbol *a* in $\sum$, A' will simulate *h(a)* in A.
    - $\delta(p,a) = \hat{\delta}(p,h(a))$


AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Decision properties of regular languages

Any “decision problem” looks like this:






Membership question

- Decision Problem: Given L, is w in L?
- Possible answers: Yes or No
- Approach:
  1. Build a DFA for L
  2. Input w to the DFA
  3. If the DFA ends in an accepting state, then yes; otherwise no.

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)



Emptiness test


- Decision Problem: Is L=Ø ?
- Approach:

  On a DFA for L:

  1. From the start state, run a *reachability* test, which returns:
     1. success: if there is at least one final state that is reachable from the start state
     2. failure: otherwise
  2. L=Ø if and only if the reachability test fails

How to implement the reachability test?

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)



Finiteness

- Decision Problem: Is L finite or infinite?
- Approach:

  On a DFA for L:

  1. Remove all states unreachable from the start state
  2. Remove all states that cannot lead to any accepting state.
  3. After removal, check for cycles in the resulting FA
  4. L is finite if there are no cycles; otherwise it is infinite
- Another approach
  - Build a regular expression and look for Kleene closure


How to implement steps 2 and 3?

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)


Finiteness test - examples

Ex 1) Is the language of this DFA finite or infinite?




FINITE

Ex 2) Is the language of this DFA finite or infinite?




INFINITE



Equivalence & Minimization of DFAs

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)



Applications of interest

- Comparing two DFAs:
  - $L(DFA_1) == L(DFA_2)$?

- How to minimize a DFA?
  1. Remove unreachable states
  2. Identify & condense equivalent states into one


AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

When to call two states in a DFA "equivalent"?

Past doesn't matter - only future does!


Two states p and q are said to be *equivalent* iff:

i) Any string w accepted by starting at p is also accepted by starting at q;



AND

i) Any string w rejected by starting at p is also rejected by starting at q.




➔ p≡q

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Computing equivalent states in a DFA

Table Filling Algorithm



A	=							
B	=	=						
C	x	x	=					
D	x	x	x	=				
E	x	x	x	x	=			
F	x	x	x	x	x	=		
G	x	x	x	=	x	x	=	
H	x	x	=	x	x	x	x	=
	A	B	C	D	E	F	G	H

Pass #0

1. Mark accepting states ≠ non-accepting states

Pass #1

1. Compare every pair of states
2. Distinguish by one symbol transition
3. Mark = or ≠ or blank(tbd)

Pass #2


1. Compare every pair of states
2. Distinguish by up to two symbol transitions (until different or same or tbd)

….

(keep repeating until table complete)

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)


Table Filling Algorithm - step by step



A	=							
B		=						
C			=					
D				=				
E					=			
F						=		
G							=	
H								=
	A	B	C	D	E	F	G	H

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Table Filling Algorithm - step by step




	A	B	C	D	E	F	G	H
A	=							
B		=						
C			=					
D				=				
E	X	X	X	X	=			
F					X	=		
G					X		=	
H					X			=

1. Mark X between accepting vs. non-accepting state

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Table Filling Algorithm - step by step




A	=							
B		=						
C	X		=					
D	X			=				
E	X	X	X	X	=			
F					X	=		
G	X				X		=	
H	X				X			=
	A	B	C	D	E	F	G	H

1. Mark X between accepting vs. non-accepting state
2. Look 1- hop away for distinguishing states or strings

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Table Filling Algorithm - step by step




	A	B	C	D	E	F	G	H
A	=							
B		=						
C	X	X	=					
D	X	X		=				
E	X	X	X	X	=			
F					X	=		
G	X	X			X		=	
H	X	X			X			=

1. Mark X between accepting vs. non-accepting state
2. Look 1- hop away for distinguishing states or strings

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Table Filling Algorithm - step by step




A	=							
B		=						
C	X	X	=					
D	X	X	X	=				
E	X	X	X	X	=			
F			X		X	=		
G	X	X	X		X		=	
H	X	X	=		X			=
	A	B	C	D	E	F	G	H

1. Mark X between accepting vs. non-accepting state
2. Look 1- hop away for distinguishing states or strings

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Table Filling Algorithm - step by step




A	=							
B		=						
C	X	X	=					
D	X	X	X	=				
E	X	X	X	X	=			
F			X	X	X	=		
G	X	X	X	=	X		=	
H	X	X	=	X	X			=
	A	B	C	D	E	F	G	H

1. Mark X between accepting vs. non-accepting state
2. Look 1- hop away for distinguishing states or strings

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Table Filling Algorithm - step by step




A	=							
B		=						
C	X	X	=					
D	X	X	X	=				
E	X	X	X	X	=			
F			X	X	X	=		
G	X	X	X	=	X	X	=	
H	X	X	=	X	X	X		=
	A	B	C	D	E	F	G	H

1. Mark X between accepting vs. non-accepting state
2. Look 1- hop away for distinguishing states or strings

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Table Filling Algorithm - step by step




A	=							
B		=						
C	X	X	=					
D	X	X	X	=				
E	X	X	X	X	=			
F			X	X	X	=		
G	X	X	X	=	X	X	=	
H	X	X	=	X	X	X	X	=
	A	B	C	D	E	F	G	H

1. Mark X between accepting vs. non-accepting state
2. Look 1- hop away for distinguishing states or strings

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Table Filling Algorithm - step by step




A	=							
B	=	=						
C	X	X	=					
D	X	X	X	=				
E	X	X	X	X	=			
F	X	X	X	X	X	=		
G	X	X	X	=	X	X	=	
H	X	X	=	X	X	X	X	=
	A	B	C	D	E	F	G	H

1. Mark X between accepting vs. non-accepting state
2. Pass 1:
   Look 1- hop away for distinguishing states or strings
3. Pass 2:
   Look 1-hop away again for distinguishing states or strings
   continue….

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Table Filling Algorithm - step by step




	A	B	C	D	E	F	G	H
A	=							
B	=	=						
C	X	X	=					
D	X	X	X	=				
E	X	X	X	X	=			
F	X	X	X	X	X	=		
G	X	X	X	=	X	X	=	
H	X	X	=	X	X	X	X	=

1. Mark X between accepting vs. non-accepting state
2. Pass 1:
   Look 1- hop away for distinguishing states or strings
3. Pass 2:
   Look 1-hop away again for distinguishing states or strings
   continue….

Equivalences:
- A=B
- C=H
- D=G

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Table Filling Algorithm - step by step




Retrain only one copy for each equivalence set of states

Equivalences:
- A=B
- C=H
- D=G

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Table Filling Algorithm – special case




	A	B	C	D	E	F	G	H
A	=							
B		=						
C			=					
D				=				
E				?	=			
F						=		
G							=	
H								=

Q) What happens if the input DFA has more than one final state?
Can all final states initially be treated as equivalent to one another?

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Putting it all together …



How to minimize a DFA?

- Goal: Minimize the number of states in a DFA
- Algorithm:

Depth-first traversal from the start state


1. Eliminate states unreachable from the start state

Table filling algorithm

2. Identify and remove equivalent states
3. Output the resultant DFA

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)

Are Two DFAs Equivalent?




1. Make a new dummy DFA by just putting together both DFAs
2. Run table-filling algorithm on the unified DFA
3. *IF* the start states of both DFAs are found to be equivalent,

   THEN: $DFA_1 \equiv DFA_2$

   ELSE: different

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)



Summary

- How to prove languages are not regular?
  - Pumping lemma & its applications
- Closure properties of regular languages
- Simplification of DFAs
  - How to remove unreachable states?
  - How to identify and collapse equivalent states?
  - How to minimize a DFA?
  - How to tell whether two DFAs are equivalent?

AVAILABLE AT:
Onebyzero Edu - Organized Learning, Smooth Career
The Comprehensive Academic Study Platform for University Students in Bangladesh (www.onebyzeroedu.com)