

Total Members	1
Members	

Name	Role	Email
Harrie	Founder / Solo Builder	iamharrie01@gmail.com

Overview

Project	Hanko
Track	Track 1 (Autonomous Agents) + Track 2 (Dashboards & Interfaces) + Track 3 (New Skills: exit_liquidity)
Problem	Trading agents act on social chatter with no audit trail: no record of what they read, whether five voices were really one voice repeated, what would prove them wrong, or how they behave when a source fails.
Solution	A model reads posts from X, Telegram and Bluesky; code checks every reading (token named in the post, verbatim quote, prompt injection dropped). A pure decide() counts only independent voices, sizes to evidence quality and commits falsifiers before the outcome. Every run is sealed, anchored on Bitcoin and replayable from a bare clone.
Key Features	Echo detection (reposts, forwards, quotes, padded copies are one voice); readings frozen so replay never calls a model; sealed run manifests + OpenTimestamps + replay bundles (hanko verify-run); exit_liquidity from an executable Jupiter quote with the model's error shown, in RYO's envelope, as REST route and MCP server; failure drill (9 held); Echo Index study on 2,094 real posts; workbench; 355 offline tests.
Target Users	Traders and builders who want to audit an agent's reasoning, and RYO, which can adopt exit_liquidity by registering one route. Judges: start at tryhanko.xyz/judges. Live record as of 5 Nov: 66 sealed runs, 204 graded decisions, 103 of them proved wrong and published.
Scope	Full evidence-to-decision-to-review pipeline (X, Telegram, Bluesky, RSS, RYO's six tools, DexScreener, Jupiter), a sealing pipeline, a review/calibration loop, exit_liquidity 2.0, and three screens (workbench, failure drill, Echo Index). First live ENTER sealed 2026-10-23 (BTC, run_836b976720f63dc0).
Limitations	RYO's market data failed from 28 Sep to early Nov; those decisions used DexScreener facts without RYO's safety and ATR fields. On 5-7 Nov, 44 decisions ran on RYO's facts. Then the key's monthly call allowance ran out; later runs record RYO's refusal as a gap. The live record began 24 Oct and is short. Quotes cover Solana only. The first two sealed runs predate replay bundles. See LIMITATIONS.md.

Tech Stack

Frontend Stack	Static HTML/CSS/vanilla JS on Vercel at tryhanko.xyz: /ledger, /try, /workbench, /drill, /echo, /judges. Keyboard and screen-reader accessible.
Backend Stack	Python 3.11: the hanko CLI and library. Vercel Python functions: /api/exit_liquidity, /api/tools/exit_liquidity/call (RYO REST shape), /api/mcp, /api/workbench, /api/drill.
AI Model(s)	grok-4.3 (xAI) for x_search collection and the optional model interpreter (--interpreter llm), whose readings are validated in code and frozen into each decision. decide() itself calls no model. Claude (Anthropic) was used as the coding assistant throughout the build.
Other Technologies	httpx, pytest (355 tests), opentimestamps, DexScreener and Jupiter public APIs (keyless), Telegram and Bluesky public endpoints, Vercel.

Repository / Demo

Github Repository	https://github.com/IamHarrie-Labs/hanko
Demo Video	https://youtu.be/fm0B4hZQCwQ
Documentation	Start at tryhanko.xyz/judges (every rubric line mapped). README.md, DECISIONS.md, LIMITATIONS.md, SEALING.md, study/echo-index/REPORT.md. X post (Social Media Award): https://x.com/IamHarrie/status/2096908693967179844

Testing Information

How to run the Project	CLI (hanko) and pytest suite. Live demos need no install: tryhanko.xyz
Prerequisites	Python 3.11+; pip
Installation Steps	1) Clone the repo 2) pip install -e ".[dev,sealing]" 3) Copy .env.example to .env and fill in credentials (only needed for live runs; tests and verify-run need none)
Environment Variables	XAI_API_KEY (X evidence, model interpreter); RYO_MCP_URL, RYO_MCP_KEY (RYO, MCP transport); RYO_API_BASE, RYO_API_KEY (optional REST fallback)
Build Command	None for the package. Site: python scripts/vendor_for_site.py && python site/build.py
Run Command	hanko verify-run runs/run_836b976720f63dc0.json; hanko seal --watchlist watchlist.json --interpreter llm --ots; hanko exit-liquidity BONK --size 50000; hanko echo-index publish; hanko audit

Test Command	pytest (355 tests, offline, no keys needed)
Test Account(s)	None required. RYO's tools are read-only research APIs, authenticated by an environment variable.