

Group B : Assignment 4**1) Create a Database:**

```
CREATE DATABASE
MySQL > CREATE DATABASE COLLEGE;
Query OK, 1 row affected (0.003 sec)
```

2) Show Database:

```
MySQL > CREATE DATABASE COLLEGE;
Query OK, 1 row affected (0.003 sec)

SHOW DATABASES
MySQL > SHOW DATABASES;
+-----+
| Database          |
+-----+
| college           |
| information_schema |
| mysql             |
| performance_schema |
| phpmyadmin        |
| test              |
+-----+
6 rows in set (0.002 sec)
```

3) Use Database:

```
MySQL > USE COLLEGE
Database changed
```

4) Drop Database:

```
MySQL > DROP DATABASE TP
Query OK, 0 rows affected (0.004 sec)
```

5) Create table and describe:

```
MySQL> CREATE TABLE CUSTOMER (ID INT PRIMARY KEY,
NAME VARCHAR(15) NOT NULL,
CITY VARCHAR(10)
);
Query OK, 0 rows affected (0.534 sec)

MySQL> DESC CUSTOMER;
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| ID    | int(11)       | NO   | PRI | NULL    |       |
| NAME  | varchar(15)   | NO   |     | NULL    |       |
| CITY  | varchar(10)   | YES  |     | NULL    |       |
```

```

+-----+-----+-----+-----+-----+-----+
rows in set (0.017 sec)

MySQL> CREATE TABLE BRANCH (ID INT PRIMARY KEY, BNAME
VARCHAR(15), CITY VARCHAR(10));
Query OK, 0 rows affected (0.247 sec)
MySQL> DESC BRANCH;
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| ID    | int(11)       | NO   | PRI | NULL    |       |
| BNAME | varchar(15)   | YES  |     | NULL    |       |
| CITY  | varchar(10)   | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.009 sec)

MySQL> CREATE TABLE DEPOSIT (ACC_NUMBER VARCHAR(5) PRIMARY
KEY, CUST_ID VARCHAR(10) NOT NULL, AMOUNT INT, BRANCH_ID
VARCHAR(5), OPEN_DATE DATE);
Query OK, 0 rows affected (0.535 sec)

MySQL> DESC DEPOSIT;
+-----+-----+-----+-----+-----+-----+
| Field          | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| ACC_NUMBER    | varchar(5)    | NO   | PRI | NULL    |       |
| CUST_ID       | varchar(10)   | NO   |     | NULL    |       |
| AMOUNT        | int(11)       | YES  |     | NULL    |       |
| BRANCH_ID     | varchar(5)    | YES  |     | NULL    |       |
| OPEN_DATE     | date          | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.017 sec)

MySQL> CREATE TABLE BORROW (LOAD_NO VARCHAR(5) PRIMARY KEY,
CUST_ID VARCHAR(10), BRANCH_ID VARCHAR(5), AMOUNT INT);
Query OK, 0 rows affected (0.282 sec)
MySQL> DESC BORROW;
+-----+-----+-----+-----+-----+-----+
| Field          | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| LOAD_NO       | varchar(5)    | NO   | PRI | NULL    |       |
| CUST_ID       | varchar(10)   | YES  |     | NULL    |       |
| BRANCH_ID     | varchar(5)    | YES  |     | NULL    |       |
| AMOUNT        | int(11)       | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.017 sec)

```

6) Alter Command:**Add address column in customer:**

```
MySQL> ALTER TABLE CUSTOMER ADD ADDRESS VARCHAR(30);
Query OK, 0 rows affected (0.088 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
MySQL> DESC CUSTOMER;
```

Field	Type	Null	Key	Default	Extra
ID	int(11)	NO	PRI	NULL	
NAME	varchar(15)	NO		NULL	
CITY	varchar(10)	YES		NULL	
ADDRESS	varchar(30)	YES		NULL	

4 rows in set (0.009 sec)

Modify column:

```
MySQL> ALTER TABLE BRANCH CHANGE BNAME BRANCH_NAME
VARCHAR(10);
Query OK, 0 rows affected (0.902 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

Modify column name:

```
MySQL> ALTER TABLE CUSTOMER CHANGE ADDRESS NEW_ADDRESS
VARCHAR(30);
Query OK, 0 rows affected (0.111 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

Drop column ADDRESS:

```
MySQL> ALTER TABLE CUSTOMER DROP NEW_ADDRESS;
Query OK, 0 rows affected (0.571 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
MySQL> DESC CUSTOMER;
```

Field	Type	Null	Key	Default	Extra
ID	int(11)	NO	PRI	NULL	
NAME	varchar(15)	NO		NULL	
CITY	varchar(10)	YES		NULL	

3 rows in set (0.010 sec)

RENAME BRANCH:

```
MySQL> ALTER TABLE BRANCH RENAME TO BRANCH1;  
Query OK, 0 rows affected (0.294 sec)
```

7) DCL Commands:**GRANT**

```
MySQL> GRANT SELECT ON CUSTOMER TO SHREYAS;  
Query OK, 0 rows affected (0.013 sec)
```

REVOKE

```
MySQL> REVOKE SELECT ON CUSTOMER FROM SHREYAS;
```

8) Truncate:

```
MySQL> TRUNCATE CUSTOMER;  
Query OK, 0 rows affected (0.509 sec)
```

9) Drop:

```
MySQL> DROP TABLE CUSTOMER;  
Query OK, 0 rows affected (0.229 sec)
```