

# Bill Of Materials for SCR v1

**Design Title** SCR v1  
**Author**  
**Document Number**  
**Revision**  
**Design Created** 04 June 2019  
**Design Last Modified** 04 June 2019  
**Total Parts In Design** 19

## 5 Capacitors

<u>Quantity</u>	<u>References</u>	<u>Value</u>	<u>PCB Package</u>	<u>Description</u>	<u>Category</u>	<u>Unit Cost</u>
2	C1, C2	22pF	CAPC2012X100	CAP 22pF 100V MICA CHIP 0805	Capacitors	\$1.31
1	C3	0.1u	CAPC1005X55	CAP .10uF 16V CERAMIC Y5V 0402	Capacitors	
1	C4	1.0u	CAPC1608X87	CAP 1uF 6.3V CER Y5V SMD 0603	Capacitors	
1	C5	1.0u	CAPC1608X87	CAP CERM 1uF 10V Y5V 0603	Capacitors	

Sub-totals: \$2.62

## 5 Resistors

<u>Quantity</u>	<u>References</u>	<u>Value</u>	<u>PCB Package</u>	<u>Description</u>	<u>Category</u>	<u>Unit Cost</u>
2	R1, R2	22R	0805_RES	0.1W, 1%, 100ppm, SMT Thick film chip resistor (RL5000)	Resistors	
1	R3	1K	RESC2012X50	RES 11K OHM 1/8W 5% 0805 (2012 metric) SMD	Resistors	
1	R4	47K	RESC2012X50	RES 47K OHM 1/8W 5% 0805 (2012 metric) SMD	Resistors	
1	R5	1K	RESC1608X50A	RES 1.0KOHM 1/16W 3300PPM 5% 0603 (1608 metric) SMD	Resistors	

Sub-totals: \$0.00

## 3 Integrated Circuits

<u>Quantity</u>	<u>References</u>	<u>Value</u>	<u>PCB Package</u>	<u>Description</u>	<u>Category</u>	<u>Unit Cost</u>
1	U1	NCN6001DTBR2G	TSSOP20_4P50X6P60	Smart Card interface chip	Modelling Primitives	
1	U2	AT90USB646	QFP80P1600X1600X120-64A	64 KBytes Flash, 4320 Bytes SRAM, 2 KBytes EEPROM, USB Host, USB Device, ADC, Analog Comparator, TWI, SPI, 6 Ports, 4 Timers, 1 USART	Microprocessor ICs	
1	U3	CRYSTAL ABM8G-16	CRYSTAL_ABM8G	A Ceramic 16MHZ Crystal Resonator	Miscellaneous	

Sub-totals:

\$0.00

1 Diodes

Quantity	References	Value	PCB Package	Description	Category	Unit Cost
1	D1	DL4933	DIOMELF3414	1 AMP 50V FAST-RECOVER DIOD S/MT	Diodes	

Sub-totals:

\$0.00

5 Miscellaneous

Quantity	References	Value	PCB Package	Description	Category	Unit Cost
1	J1	21745072 USB MICRO B	J_SMD_217450725_78_5_271	USB_-_micro_B_USB_2.0_Receptacle_Connector_5_Position_Surface_Mount,_Right_Angle	Connectors	
1	J2	26630601RP2	CON6_1X6_HDR_2663	Single Row, Straight, .079in spacing , 6 pins, Gold Flashed.	Connectors	
1	J3	25630401RP2	CON4_1X4_U_2563	Single Row, Receptacle, .079in spacing , 4 pins, Gold Flashed.	Connectors	
1	L1	22u	INDC2520X220	INDUCTOR 22uH 5% FIXED SMD	Inductors	
1	USBCON4	26630201RP2	CON2_1X2_HDR_2663	Single Row, Straight, .079in spacing , 2 pins, Gold Flashed.	Connectors	

Sub-totals:

\$0.00

Totals:

\$2.62