

Name:

Roll:

Department:

CSL1010: Introduction to Computer Science

Quiz 2, IIT Jodhpur, Instructor: Palash Das, Date: 16.10.2025

Time: 20 Minutes

Full Marks: 10 * 1

Attempt all questions. Use the back of the answer sheet for rough work and write your final answers neatly and clearly in the space provided on the question paper. Read each question carefully before attempting. **Good Luck!**

Write down the output of the following questions.

10 * 1

1. #include <stdio.h>

```
int main() {  
    int a[5] = {1, 2, 3};  
    printf("%d", a[3]);  
    return 0;  
}
```

Ans: _____0_____

2. #include <stdio.h>

```
int val = 100;  
int main() {  
    int val = 10;  
    {  
        int val = 1;  
        printf("%d ", val);  
    }  
    printf("%d", val);  
    return 0;  
}
```

Ans: _____1 10_____

3. #include <stdio.h>

```
int x = 5;  
void func() {  
    extern int x;  
    x = 10;  
}
```

```
int main() {  
    func();  
    printf("%d", x);  
    return 0;  
}
```

Ans: _____10_____

4. #include <stdio.h>

```
int sum(int a, int b) {  
    return a + b;  
}
```

```
int main() {  
    int x = 2;  
    printf("%d", sum(x, x++));  
    return 0;  
}
```

Ans: ____Undefined_____

5. #include <stdio.h>

```
int fun(int n) {  
    if (n > 100)  
        return n - 10;  
    return fun(fun(n + 11));  
}
```

Ans: _____91_____

Name:

Roll:

Department:

```
int main() {  
    printf("%d", fun(95));  
    return 0;  
}
```

6. #include <stdio.h>

```
int mystery(int n) {  
    if (n <= 1)  
        return 1;  
    return mystery(n - 1) + mystery(n - 2);  
}
```

Ans: _____8_____

```
int main() {  
    printf("%d", mystery(5));  
}
```

7. #include <stdio.h>

```
int main() {  
    int x = 4;  
    switch (x) {  
        case 1 ... 3: printf("Small");  
            break;  
        case 4 ... 6: printf("Medium");  
            break;  
        default: printf("Large");  
    }  
}
```

Ans: _____Medium/error_____

8. #include <stdio.h>

```
static int x = 5;  
int main() {  
    x = 10;  
    switch (x) {  
        case 5: x += 5;  
        case 10: x += 10;  
        case 15: x += 15;  
        default: x += 20;  
    }  
    printf("%d", x);  
}
```

Ans: _____55_____

9. #include <stdio.h>

```
#define AX(a, b) ((a) > (b) ? (a) : (b))
```

```
int main() {  
    int x = 5;  
    printf("%d", AX(x++, 5));  
}
```

Ans: _____5_____

10. #include <stdio.h>

```
int main() {  
    printf("%zu", sizeof("hello"));  
    return 0;  
}
```

Ans: _____6_____