Evasion Is a Relation

A confidence-routed cascade for political question evasion, and what it measures

SemEval-2026 Task 6 (CLARITY)

Vidvathama R Siddarth Gottumukkula Sanjana Reddy Vonteri Shashikanta Sahoo

Team Nier_ANLP

International Institute of Information Technology, Hyderabad

Advanced NLP ▪ October 2026

The task: how clearly does a politician answer each sub-question?

Each item pairs one **sub-question** from a journalist's turn, the **full question** and the politician's **answer**. We predict the 9-way label and map it to the 3-way one.

Subtask 1	Subtask 2	train
Clear Reply	Explicit	30.5%
Ambivalent	Implicit, Dodging, General, Deflection, Partial/half-answer	59.2%
Clear Non-Reply	Declining to answer, Claims ignorance, Clarification	10.3%

Data and metric

- Train 3,448 rows. Dev 308 items (3 annotators). Test 237 (2 annotators, labels unreleased)
- Macro-F1 over 9 classes. A prediction counts if *any* annotator gave it
- Every score in this talk is on dev

Why it is hard

- 69% of rows share their answer with another sub-question
- Humans disagree: one annotator vs. the other two scores **0.684**

What are we classifying? Three real dev items

Clear Reply → Explicit

Sub-question: "Do you stand by your figure, 30,000?"

Answer: *"You know, I stand by the figure. A lot of innocent people have lost their life—600,000, or whatever they guessed at, is just—it's not credible. . . . "*

Why this label: he states the requested position outright.

Ambivalent → Dodging

Sub-question: "Do you see a risk of triggering a wider war?"

Answer: *"I thought you were going to ask me about the pig."*

Why this label: he ignores the question and changes the subject.

Clear Non-Reply → Declining

Sub-question: "Is it a fair assumption that the CIA operatives are in Pakistan, cooperating with the Pakistanis, and that they're sharing everything with you and vice versa?"

Answer: *"John, what's fair is, I'm not—what you must assume is that I'm not going to talk about ongoing intelligence matters. . . . "*

Why this label: he openly refuses to give the information.

- All three annotators agree on each of these. The "pig" answer is attached to all three sub-questions of its turn, so the model must work out *which part* of an answer responds to *which* sub-question.
- We predict the 9-way evasion type (Subtask 2). The 3-way clarity level (Subtask 1) follows from it.

Shared-task results: LLM pipelines won, encoders stalled near 0.50

Rank	Team	Approach (S2 ranking)	S2 test
1	**TeleAI**	DeepSeek-V3, 3 confidence-routed CoT stages	**0.68**
2	ChulaNLP	fine-tuned DeBERTa-large top-5 labels → few-shot Kimi-K2	0.61
3	CLaC	prompted LLMs, ahead of their fine-tuned encoders	0.59
12	PFW	50 DeBERTa models averaged (5 folds × 10 seeds)	0.50
Organiser baseline		fine-tuned Llama-70B	0.57

- 33 teams entered S2, with a median of about 0.52. Encoders level off near **0.50**.
- TeleAI on dev: 0.617 S2 / 0.812 S1, with 1.94 LLM calls and ∼7.3k input tokens per item.


Test scores (237 items) are from Table 3 of the task overview paper. TeleAI's dev numbers are from its system paper. Our numbers are on dev.

Our two questions

A. Why do fine-tuned classifiers stop where they do?

B. Once we have a good classifier of evasion, what can it tell us about evasion itself?

Overview: five stages, each asking one question




- From E8 on, each experiment's plan, prediction and decision rule was written down *before* the run. Results we did not register are marked **exploratory**.
- Each result slide shows what we **predicted** next to what we **found**, including the many predictions that failed.
- Claims rest on 10 paired seeds. Parameters fitted on dev are scored by nested cross-validation, and the one choice made on dev after a failure ($\delta = 0.5$ for the distilled point) is flagged.
- From Stage 4 on, one frozen system labels everything, so no parameter changes between experiments.

Structural changes failed, while the decision rule, training length and full question helped


Four explanations for the plateau (DeBERTa-v3-large)

- **Noisy labels?** No: 53 errors were on items all annotators agreed on.
- **The decision rule?** A little: logit adjustment +0.073.
- **Label meaning?** No: a re-ranker given label definitions −0.011, though gold was in the top 3 for 90%.
- **Missing knowledge?** → next slide.



Takeaway: nothing trained on the same 3,448 rows moved the system, so we changed the model itself.

Where the DeBERTa ensemble fails



Majority gold label \ Predicted	Explicit	Implicit	Dodging	General	Deflection	Partial	Declining	Claims ign.	Clarif.
Explicit	**56**	14	5		2				
Implicit	20	**20**	7	6	4				
Dodging	2	8	**26**	8	3		1	1	1
General	14	7	11	**8**	7		1		
Deflection	4	5	2	2	**4**				
Partial	1				2				
Declining	1		4	1	1		**3**	1	
Claims ign.		1	3	1			2	**1**	
Clarif.			1						**3**
(no majority)	13	11	4		2		2	1	

How to read it


- Rows are the majority gold label (at least 2 of 3 annotators), plus a "no majority" row (33 items).
- Columns are the argmax of the 10-seed ensemble. The diagonal is right for 121 of 275 majority items.
- Scoring never uses the majority. A prediction counts if *any* annotator gave it.

What it tells us

- Errors sit inside *Ambivalent*. Implicit is predicted as Explicit 20 times, and General is spread over five other labels.
- Partial/half-answer is never predicted.
- The encoder fails on **how committed** an answer is, the same pairs annotators disagree on.

Takeaway: a model with more knowledge should improve these boundaries. We test this by changing only the backbone.

A stronger pretrained backbone gained more per model than all encoder changes combined



One change: DeBERTa-v3-large → Qwen3-8B-Base + LoRA, with the same rows, input, loss and selection, on 10 paired seeds.

Expected: gains on the Explicit–Implicit–General boundaries of the confusion matrix


Found: +0.092 per model, 10 of 10 seeds up (all encoder changes together: +0.069)

Found: the gain is broad, largest on the Non-Reply types (Claims ignorance +0.40), so the expected location did not hold ✗ failed

"Stronger backbone", not "knowledge" alone: size, pretraining, LoRA and the head all changed together.


What it raised: the 8B model ranks the right label far better than it picks it.

The classifier ranks the right label better than it picks it




Takeaway: errors are mostly a choice among a few top candidates, made where the model is unsure. So let a larger model choose among them, *only* for the least confident items.

System design: a classifier, a router and an LLM adjudicator



- Registered checks that set the design: choosing at random inside M1's top 3 *lowers* S2 (0.587 vs 0.598), so the LLM is **fused** with M1, not substituted. Candidate sets by probability mass did not transfer to new rows, but sets by rank did (**top 4**).
- Retrieved examples *hurt* the 27B (0.330 vs 0.353 without), and a 304B model did worse than the local 27B (0.317): short prompt, local model, one output token.

Deferral rate against cost on dev



- **Defer 30%**: **0.669**, +0.067 over M1 [+0.009, +0.124], with 33 items fixed and 9 broken (after we fixed a bug in our own fusion code).
- **Defer everything**: worse (0.636). Where M1 is confident, the LLM is the weaker reader.
- **Distil**: one student plus the 27B reaches 0.608 at a quarter of the ten seeds' GPU time. Ten students add only +0.005 (ten M1 seeds: +0.065).

What it raised: was 0.669 luck? One ensemble, parameters fitted on 308 items.

One answer, two sub-questions, two labels

One journalist's turn at a President's news conference, and one answer

"Is that a make-or-break issue for you, in terms of domestic politics? There's a Republican in Pennsylvania who says he doesn't think the troops should ... would you campaign for Mike Fitzpatrick?"

"I already have."

Explicit (3 of 3 annotators)

Sub-question: Would you campaign for Mike Fitzpatrick?

Answer: *I already have.*

Why this label: the answer states what was asked.

Dodging (3 of 3 annotators)


Sub-question: Is that a make-or-break issue for you, in terms of domestic politics?

Answer: *I already have.*

Why this label: the answer says nothing about whether the issue is make-or-break.


Takeaway: 69% of training rows share their answer with another sub-question, so one answer can receive two labels. Whether an answer evades then depends on the question it is paired with. Stage 4 tests this, and the last slides return to this answer.

Gain over M1 when every parameter is refitted



- Refitting every parameter in each bootstrap draw, the interval includes zero. On 3,448 held-out train rows the gain is small but clear (+0.014 [+0.002, +0.026]).
- No random routing of the same size matches confidence routing. The 27B alone over all nine labels scores 0.591, below M1 (0.598), so fusion is needed.

Option order and server copy change the 27B's answers



- **Order**: in taxonomy order slot A is usually Explicit, so position and label are confounded. Two orders of the same four candidates give the same pick on only 72% of dev items, so we average four orders: four calls, and $+0.011$ at split 0 but only $+0.002$ over ten splits.
- **Server**: a second copy of the identical weights flips 7.5% of decisions, almost all near-ties. It moved the accuracy point $0.669 \rightarrow 0.639$ (0.650 with four orders), and the bootstrap holds the 27B's outputs fixed, so this swing is not in its interval.

Takeaway: everything after this slide uses one 27B copy and four averaged orders.

The frozen system compared with the winning system

System (dev)	S2	S1	LLM calls	GPU-s
DeBERTa-v3-large, 10 seeds	0.405	0.648	0	–
M1: Qwen3-8B, 10 seeds	0.598	0.743	0	0.40
Accuracy point, M1 + 27B	**0.650**	**0.788**	1.43	0.54
Distilled point, 4 orders	**0.608**	**0.785**	2.30	0.27
one option order	0.599	0.784	0.57	0.10
TeleAI, 1st place	0.617	0.812	1.94	n/a

Nested-CV split 0 (0.639 over ten splits for the accuracy point). LLM calls are 27B calls per item, four per deferred item with four orders. GPU-s is inference time per item, all on one GPU. TeleAI's row is its own dev result, with ∼7.3k LLM input tokens against our ∼1.6k. Its GPU time is not published.


What it raised: if a label is not a property of the answer alone, what is it a property of?

Relation to the task's system papers

In the task's 30 system papers, these parts were already in use: candidate sets, LLM choosers, routing, distillation. **None tested whether such systems read the question.**

So we froze every setting and used the cascade as an **instrument**.


Labels of one answer across its sub-questions



- 61.5% of 3,079 train sibling pairs (one answer, two sub-questions) carry different labels, almost as often as two random items.
- Partial, Implicit, Deflection and General answers fit their question as well as Explicit ones, so relevance is not answerhood (Clear Reply vs rest: AUROC 0.55).

Takeaway: evasion is a relation between a question and an answer. "I already have" was the rule, not the exception.

Validity check: removing or swapping the question



A validity check before using it on new speakers: pair each answer with an unrelated question, or with none.


Predicted: the Clear-Reply share at least halves
Found: 25% → 1% ✓held

Surprise: with *no* question, Clear Replies *rise* to 64%. Nothing asked, nothing evaded.

Our answer again, under an unrelated question

"Why did you keep saying there was a relationship between Saddam Hussein, Zarqawi, and Al Qaida . . . ?"
"I already have." → instrument: **Dodging**
With its own two questions it gives Explicit and Dodging, as all six annotations say.


Does the question or the speaker drive evasion? Design



Registered predictions

- If the **question** drives evasion, a speaker with no stake (N) evades where the Presidents did: odds ratio ≥ 1.5.
- If the **stake** drives it, playing the President (P) raises the evasion rate by ≥ 0.10.
- **Pursuit** (F) turns $\geq 50\%$ of evasions into replies.
- **Notes** (B) help more on questions answered indirectly than on non-answers ($\geq +0.15$).

Evasion rates by role



No stake (N): odds ratio 1.18 [0.80, 1.73] ✗ failed

Stake raises the rate: −0.031 ✗ failed

President's role (P): odds ratio **2.74** [1.87, 4.17] exploratory

Pursuit (F): 66% of evasions become replies ✓ held

Notes (B): +0.113 [−0.006, +0.225], below the bar ✗ failed

Reading (b): the move is in the open dots: where the President answered, a neutral analyst still evades 52%, but in the President's role the models evade only 34%.

What the role result shows and does not show

What it shows


- The role changes *where* models evade, not *how often* (52% vs 55%).
- In the President's role they answer directly what the Presidents answered directly. A neutral analyst addressed as "Mr. President" evades about half of everything, because it is not the addressee.
- So a question's answerability shows only for a speaker who can answer it.
- It holds for each model separately (Mistral 3.0, Qwen 2.5).

What it does not show

- It is exploratory, with two model families, one of them the judge's own (Qwen). Our data cannot separate answerability from strategic evasion.
- The P prompt adds identity, date and context, not only a stake, and the role odds ratio was not adjusted for answer length.
- The instrument was not human-validated on LLM text, though it is *more* confident there (seed agreement 0.81 vs 0.73).
- Anything about real politicians' intent.

What it raised: measuring this needs the whole answer and the fine-tuned ten-seed ensemble, with no shortcut (backup). Can it run cheaper?

Lower precision: FP8 and NF4 against 16-bit



- Frozen M1 in FP8 or NF4, each against 16-bit on the same GPU type. FP8: agreement 96.1% (bar 98%) ✗ failed speed 0.83× (bar 1.3×) ✗ failed flips fall where the 27B re-decides, 71% vs 36% by chance ✓ held
- All 10 of M1's membership-changing flips lose it, while the system's go both ways (5 lose, 7 gain), so with the same frozen parameters it loses 0.003 against M1's 0.045. That is below the 0.02–0.03 that changing the 27B's server alone moves the score.
- *NF4: 27B records are missing for 60 of 136 deferred items and the system flips more decisions than M1 (57 vs 45): no conclusion.

Registered predictions that steered the work

1	Classifier	gain on the expected boundaries; gain larger on agreed items
2	Cascade	top-3 headroom; dev gain at 30%; 5 seeds ≈ 10; examples help; student at 30%; student ranks errors better
3	What survives	test text matters; learned router; LLM-knowledge distillation; cached prompt; escalation ladder; two copies agree
4	What it measures	reads the question; pursuit; probe less question-bound; question-driven (N); stake raises rate; notes; half answer suffices; frozen probe suffices
5	Precision	FP8 flips land where the 27B re-decides; FP8 fidelity; FP8 speed

held registered prediction held failed failed, and changed the next step

A selection of the registered predictions that steered the work. Every one, held or not, is in the experiment log.

Limitations, each with what we did and what comes next

Limitation	What we did	Next step
308 dev items; test labels unreleased	10 paired seeds, nested CV and a bootstrap that refits	Score the frozen test predictions once labels are out, and test a second corpus
Not human-checked on LLM text	Label-free check: more confident on LLM text	Two annotators, 100 answers, the registered agreement bar
Two LLM families; role effect exploratory	Per-model results	Add Llama and OLMo, register the role effect and adjust it for answer length
LLM decisions depend on server copy and option order	One copy, four orders averaged	Repeat runs on each copy (none yet) and pin software and hardware
Quantization not faster as implemented	Same-GPU, same-batch comparisons	Fused FP8 kernels, QLoRA for NF4, and every NF4-deferred item scored

Conclusions

What we learned

1. **A stronger pretrained backbone, not more structure,** broke the classifier plateau, with $+0.092$ per model on 10 of 10 seeds.
2. **Rank, then adjudicate only where unsure.** The cascade reaches 0.65 dev S2, on par with the winner, with $\frac{3}{4}$ of its LLM calls. A distilled variant needs a quarter of the classifier's GPU time.
3. **Evasion is a relation.** Labels follow the question. In two LLMs, in the President's role, models answer directly what the Presidents answered directly (exploratory).

The example from the start

"I already have."

campaign for him? $\rightarrow$ Explicit
make-or-break? $\rightarrow$ Dodging
an unrelated question? $\rightarrow$ Dodging

The instrument gets all three, because it reads the pair.

Thank you. Questions?

Code, pre-registered log and every raw output

github.com/IamSid44/CLARITY-Unmasking-Political-Question-Evasions

Runs and adapters huggingface.co/siddarthg44/clarity-semeval26

Training curves wandb.ai/iamsid44-iiit-hyderabad/clarity-semeval26

Is the comparison with the winning system fair?

- **Both are dev numbers.** TeleAI's 0.617 (S2) and 0.812 (S1) are its own dev results. Test labels were never released and the server closed, so no one can be compared on test now.
- **Our dev score uses dev labels for three fitted parameters** (M1's τ and the fusion's λ, τ), chosen by 5-fold nested cross-validation, so the reported predictions are held out. Over ten CV splits it is 0.639. In the two-annotator regime of the test set, the first-copy version (0.669) scores 0.589.
- **Different protocols.** TeleAI calls DeepSeek-V3 through an API (1.94 calls, $\sim$7.3k input and $\sim$380 output tokens per item), while we call a local 27B (1.43 calls, $\sim$1.6k input tokens, 1 output token each). GPU time is therefore not comparable, but calls and tokens are.
- **Test predictions** of both operating points are written (from normalised test text) and in the repository, ready to score when labels appear.

Takeaway: on par on dev with the winner on S2 (lower on S1), at fewer calls and far fewer tokens. Not "better than the winner".

If the refitted interval spans zero, why adopt the cascade?

The refit bootstrap: each of 2,000 draws resamples dev items, reassigns the 5 CV folds and refits M1's τ and the fusion's (λ, τ) inside every fold. Gain $+0.037$ $[-0.044, +0.120]$, $P(\leq 0) = 0.20$. Holding the parameters fixed gives $+0.067$ $[+0.009, +0.124]$.

Why we keep it (none of this is chosen on dev):

- $\delta = 0.3$ was the registered operating point, fixed before the dev run.
- On 3,448 cross-fitted training rows the same cascade gains $+0.014$ $[+0.002, +0.026]$: small, but its interval excludes zero.
- Confidence routing beats all 200 random routings of the same size (0.669 vs 0.604 $\pm$ 0.015).
- Items moved into vs out of the reference set: 33 vs 9 (exact McNemar $p = 0.0003$).

Takeaway: we report $+0.037$ as the gain, with its interval. The direction is supported three ways, but 308 items do not pin down the size.

Option order and server copy: what we measured

Option order

- The four candidates are lettered A–D. In taxonomy order, slot A is usually Explicit, so "prefers A" and "prefers Explicit" cannot be told apart.
- Fix: show the same four candidates in four cyclic orders, average the 27B's letter probabilities after mapping them back to labels.
- Two orders of the same candidates give the same pick on **72%** of dev items (all four on 50%).
- Averaged four orders vs one: $+0.011$ at split 0, $\mathbf{+0.002}$ over ten splits. We keep four because it was adopted on training rows, not because the dev gain is large.

Two copies of the same weights

- Same checkpoint, same prompts, different server: **7.5%** of decisions differ (agreement 92.5%), against a registered gate of 98%.
- By decisiveness: agreement **0.786** on the least decisive third of items, 0.990 and 1.000 on the other two thirds. Batch shape and floating-point order matter only at near-ties.
- The accuracy point is 0.669 on the first copy and 0.639 on the second (0.650 with four orders). We re-scored everything on one copy and kept the lab numbers as what they were.
- A repeat run on one copy would separate server from run-to-run noise. We did not run it.

What else changed with the backbone?

	DeBERTa-v3-large	Qwen3-8B-Base
Parameters	0.4B, all trained	8B, LoRA rank 16 on all linear layers
Pretraining	encoder, ELECTRA-style	decoder LM, far larger corpus
Head	[CLS] $\rightarrow$ pooler $\rightarrow$ 9-way	last token $\rightarrow$ 9-way
Learning rate, epochs	10^{-5}, 16	10^{-4}, 3 (then 12, adopted on the slice)

Held fixed: training rows, train slice, input text and budgets, loss, selection rule, seeds 0–9

- So the claim is "a stronger pretrained backbone beats structural changes", not that "knowledge" alone is the cause.
- Evidence it is not just capacity for the same signal: the gain was largest on the Non-Reply types (recognising *what kind of statement* an answer is), not on the boundary we predicted.
- We cannot rule out that pretraining data include these public transcripts.

E25b: confounds, controls and per-model results

Odds ratio	pooled	Mistral	Qwen
N, neutral analyst	1.18	0.98	1.40
P, the President	**2.74**	3.01	2.46
F, after a follow-up	2.19	1.88	2.45
B, briefed with the answer	4.13	8.13	2.30

Evasion rates: N 0.55, P 0.52, F 0.20, B 0.55. Presidents (gold) 0.74.

- **All four conditions are reported**, as the registered analysis specified. P was not picked from many.
- **Judge family**: Qwen3-8B shares a family with the 27B judge, and Mistral alone shows the effect (3.01).
- **Question-only control** was degenerate: a contentless answer is labelled Dodging for 98% of questions, so it cannot separate the instrument's question prior. N vs P does: same instrument, same questions.
- **Length**: N adjusted is 1.16, and condition effects survive it (follow-up $-1.58 \rightarrow -1.52$ log-odds). The role odds ratio was *not* length-adjusted.

Is the instrument valid on LLM-written answers?

The registered check (two annotators, 100 answers, agreement within 0.10 of their own) was dropped for lack of time. In its place, a label-free check:

Answers	mean uncertainty	seed agreement	deferred to the 27B
Presidents (dev)	0.540	0.730	36%
LLM answers (all conditions)	0.462	0.806	29%

- The instrument is *more* confident on LLM text, so it is not out of its depth there.
- That does not rule out confident, systematic errors on LLM style, which is why the role effect stays exploratory and the human check is the first next step.
- Markdown was stripped from every LLM answer, and the condition effects survive an answer-length covariate.

Is the cascade's tolerance of FP8 true by construction?

- **Partly, yes.** Quantization moves probabilities a little, so it flips decisions near M1's margin, and the router defers low-margin items. We registered this mechanism as the prediction (H26-4) rather than as a discovery.
- **What the measurement adds**: how much, and in which direction. 71% of FP8's 17 flips fall on deferred items (36% would by chance). All 10 of M1's membership-changing flips lose reference-set membership, while the system's go both ways (5 lose, 7 gain).
- **Same frozen parameters**: M1 loses 0.045 S2 under FP8, the system 0.003. The 0.020 sometimes quoted is the nested-CV M1 figure, where τ is refitted: a different estimator.
- **Not automatic**: NF4 flips are larger and less concentrated (49% of 45 on deferred items, close to chance), and its cascade comparison is incomplete (27B records missing for 60 of 136 deferred items).
- 17 flips on 308 items is a small sample, so we report counts, not an interval.


Takeaway: a cheaper first stage can be made safer by deferring where it is unsure, as long as its errors stay near its margin. It is not a cost lever with these kernels: FP8 ran at 0.83$\times$ the 16-bit throughput.

Choices made after seeing results, and how we logged them

Choice	How it is handled
12 epochs for M1	Adopted on the train slice by the registered rule (3 seeds), then confirmed on 10 seeds before use
$\delta = 0.5$ for the distilled point	Chosen after the registered $\delta = 0.3$ failed, and reported as such with the $\delta = 0.3$ number
Fusion bug fix (E15)	Found while explaining a flat result, then corrected and logged. $\delta = 1$ (unaffected) reproduced exactly as the check
Second 27B copy disagreed (E23)	Registered gate (98%) failed, so everything was re-scored on one copy and the lab numbers kept as what they were
E25 on a different GPU; two LLMs failed to load	Amendments written before any E25 result, and reported as a two-family pilot
Human check of LLM text dropped	Replaced by a label-free check, with the role effect kept exploratory

Every amendment is time-stamped in `docs/experiment_log.md`. The fusion-bug fix came after its results and is recorded as a correction.

The other Stage-3 tests



- **Where the 27B helps**: only where M1 is unsure, so a learned fix/break router lost to confidence at 4 of 4 budgets.
- **Teachers** (27B / M1 itself / uniform, same candidates): 0.575 / 0.563 / 0.516. M1-taught came within the registered 0.015: no "LLM knowledge" claim.
- **Test transcripts**: speaker tags and footnotes in 97% of test answers flip 15.6% of M1's dev labels when injected: test uses normalised text.
- **Cost ideas that failed**: a cache-aligned prompt halved the 27B's time per call but changed 9.4% of its decisions, and an escalation ladder reached 0.600, not the registered 0.625.


Cost on one GPU, and why the frozen system makes 1.43 calls per item

All times from one session on one GPU, over the same 308 dev items, batched. An M1 seed takes 0.040 GPU-s per item and a 27B call 0.098–0.101.

System	S2	10 splits	27B calls	GPU-s	vs M1
M1, 10 seeds	0.598	0.601	0	0.397	1.00×
Accuracy point, 4 orders (frozen)	0.650	0.639	1.43	0.538	1.36×
Accuracy point, 1 order	0.639	0.637	0.36	0.433	1.09×
Distilled point, 4 orders	0.608	0.606	2.30	0.266	0.67×
Distilled point, 1 order	0.599	0.606	0.57	0.098	0.25×

Averaging four option orders (adopted on training rows to remove position bias) costs four calls per deferred item, so the 36% deferral rate becomes 1.43 calls per item. Earlier tables counted one call, and the report and these slides count four.

Shortcuts: answer prefixes and frozen-model probes



Predicted: half an answer agrees $\geq$70% with the full-answer label **Found:** 66% ✗ failed refusals show early, and General and Dodging only at the end.

Predicted: a frozen-base probe reaches S2 $\geq$ 0.45 **Found:** 0.397 ✗ failed

Predicted: the probe is less question-bound than M1 **Found:** same label on 45% of disjoint siblings vs 19% ✓ held

E25: the register of hypotheses

	Registered prediction	Result	Verdict
a-1	unrelated question: Clear-Reply share at least halves, $\leq$50% keep their label	0.253 $\rightarrow$ 0.013, 19%	✓ held
b-1	no stake (N): odds ratio $\geq$ 1.5	1.18	✗ failed
b-2	stake: P $-$ N $\geq +0.10$	-0.031	✗ failed
b-3	pursuit: $\geq$50% of evasions become replies	66%	✓ held
b-4	notes: indirect $-$ non-answer $\geq +0.15$	$+0.113$	✗ failed
c	half the answer: $\geq$70% agree with the full label	66%	✗ failed
d-1	frozen-base probe: S2 $\geq$ 0.45	0.397	✗ failed
d-2	probe repeats labels on $\geq$30% of disjoint siblings	45%	✓ held

The metric and the 0.684 reference

- A prediction is a true positive if *any* annotator gave it. If every prediction is acceptable, macro-F1 = (classes predicted at least once) / 9: the score rewards landing in the reference set *and* covering rare classes.
- Floors: always Explicit 0.060, uniform random 0.129, and TF-IDF + logistic regression 0.257.
- One annotator scored against the other two reaches 0.684. That is a **two-annotator** score, and our dev numbers use three annotators per item, which is easier. In the two-annotator regime, the first-copy accuracy point (0.669) scores 0.589.
- The test set has two annotators per item, shorter answers (median 59 vs 292 words) and transcript artifacts.

Implementation details

M1 and students: Qwen3-8B-Base, bf16; LoRA $r = 16$, $\alpha = 32$, dropout 0.05 on all attention and MLP projections, and a new 9-way head on the last token. Training uses AdamW at 10^{-4}, a cosine schedule, 5% warm-up, batch 16 and 12 epochs, keeping the epoch with the best slice macro-F1. The input is "Sub-question / Full question" ($\leq$256 tokens) plus the answer, $\leq$1,024 in all. Students use the same recipe with a soft-target loss on $\frac{1}{2}$ gold $+\frac{1}{2}q$.

M3: Qwen3.8-27B-FP8 with vLLM, thinking off, one output token and top-20 log-probabilities. The prompt holds the task, 9 definitions, a confusion guide, the item and 4 lettered candidates, and q is averaged over 4 cyclic orders.

Frozen instrument (`frozen_system.json`): 10 seeds, slice calibration $\tau_C = 0.20$ and $T = 2.15$, top-4 candidates, and deferral iff $u \geq 0.638$ (slice 70% quantile). Kept items use $\tau_1 = 1.15$, deferred items $\lambda = 0.5$ and $\tau = -0.55$. It reproduces the E23 predictions exactly.

Protocol: epochs, calibration and thresholds are set on a fixed 345-row train slice, dev-fitted parameters by 5-fold nested CV, with 10 paired seeds per claim. Registered hypotheses and time-stamped amendments are in `docs/experiment_log.md`.