Other Liability Insurance (Mercury Insurance Group)

Jenny Liang (Wen Liang) Email: wliang88@berkeley.edu

```
##### function to read data
OthLiab=read.csv("/Users/JennyLiang/Desktop/OthLiab pos.csv",header=TRUE)
grp.code=unique(OthLiab$GRCODE)
ins.line.data=function(g.code){
b=subset(OthLiab,OthLiab$GRCODE==g.code)
name=b$GRNAME
grpcode=b$GRCODE
ay=b$AccidentYear
dev=b$DevelopmentLag
cum pdloss=b[,7]
cum incloss=b[,6]
data.out=data.frame(name,grpcode,av,dev,cum pdloss,cum incloss)
return(data.out)
}
##### my data
which(ins.line.data(grp.code)[,1]=="First Mercury Ins Co") ##[1] 64
data=ins.line.data(grp.code[64])
##### upper triangle
u triangle=subset(data,av+dev<=1998)
##### install necessary packages
 ##install.packages("lme4")
##install.packages("geepack")
##install.packages("ChainLadder")
##install.packages("MuMIn")
##install.packages("MESS")
library(lme4)
library(geepack)
library(ChainLadder)
library(MuMIn)
library(MESS)
##################data in triangles
triangle=as.triangle(u triangle,origin="ay", dev="dev",
          value="cum pdloss")
##### plot the data
triangle
plot(triangle, xlab="Development Year",
  ylab="Cumulative Claims", lwd="5", font.axis = 4, cex.axis = 1.2,
```

```
cex.lab = 1.5, col.lab = "dark red")
plot(triangle,lattice=T)
#####################################ChainLadder Model
###incremental data, function was written before knowing the cum2incr function
inc=u triangle[5]
inc
for (k in (2:91)){
if (is.na(u_triangle[k,3])!=TRUE & u_triangle[k,3]==u_triangle[k-1,3])
 inc[k,1]=u_triangle[k,5]-u_triangle[k-1,5]
 else if (is.na(u triangle[k,3])!=TRUE) inc[k,1]=u triangle[k,5]
u_triangle[5]=inc
inc\_data = cbind(u\_triangle[3], u\_triangle[4], u\_triangle[5])
colnames(inc_data)[3]="inc_loss"
##### incremental data
inc triangle=cum2incr(triangle)
inc triangle[1,] ##Show first origin period and its incremental developement
inc triangle
plot(inc triangle, xlab="Development Year",
  ylab="Cumulative Claims",lwd="5",font.axis = 4, cex.axis = 1.2,
  cex.lab = 1.5, col.lab = "dark red")
plot(inc_triangle,lattice=T)
##### Basic Idea
## Link ratios are calculated as the volumne weighted average developement
## rations of a cumulative loss developement triangle from one development period
## to the next
year=10
f=sapply(1:(year-1),
    function(i){
     sum(triangle[c(1:(year-i)),i+1])/sum(triangle[c(1:(year-i)),i])
f ##[1] 5.592638 2.858319 1.624835 1.322425 1.174066 1.076317 1.020656
1.011057 1.049548
## The oldest origin year is not fully developed, approach to extrapolate
## the developement raions, assuming a log-linear model
dev.lag=1:(year-1)
plot(log(f-1)~dev.lag, main="Log-linear extrapolation of age-to-age factors")
NewModel=lm(log(f-1)~dev.lag)
abline(NewModel)
```

```
co=coef(NewModel)
##### extrapolate another 100 development period
tail=exp(co[1]+c((year+1):(year+100))*co[2])+1
f.tail=prod(tail)
f.tail##[1] 1.005696
##### plot the expected claims development patterns
plot(100*(rev(1/cumprod(rev(c(f,tail[tail>0.999]))))),t="b",
  main="Expected claims development pattern",
  xlim=c(0,15),
  xlab="Development Period", ylab="Development % of ultimate loss")
##### to forecast the next developemtn period
f=c(f,f.tail)
full_triangle=cbind(triangle,Ult=rep(0,10))
for (k in 1:year){
full_triangle[(year-k+1):year,k+1]=full_triangle[(year-k+1):year,k]*f[k]
full triangle=round(full triangle)
full_triangle
sum(full_triangle[,11]-getLatestCumulative(triangle)) ##[1] 29259
##### Mack chain-ladder
mack=MackChainLadder(triangle, est.sigma="Mack")
mack$f
round(mack$FullTriangle)
plot(mack)
plot(mack,lattice=T)
```