

COMP-4745-project-2

Table of Contents

- catkin_ws
 - The main workspace for the project
- frontier-exploration
 - The primary package including nodes and launch files for the project
- frames.pdf
 - A pdf displaying the transform view frame connections
- waffle_tf_listener.py
 - Python transformation listener file to display the current position of the robots base_footprint in reference to the map.
- moveActionClient.py
 - Python action client to move the robot with respect to its base_footprint reference frame.
 - Translation parameters (goals) are entered in the terminal, see setup files tutorial.
- RvizProjectTwoConfig.rviz
 - setup config file for Rviz, includes robot camera and global/local path markers.
- Video of setup files at [Watch the video]

Running setup files

In their own terminal run the following

```
$ roslaunch turtlebot3_gazebo turtlebot3_stage_4.launch
$ roslaunch turtlebot3_slam turtlebot3_slam.launch slam_methods:=gmapping
```

This should open a Gazebo and Rviz window.

The Rviz window config should include a pre-saved camera display and global/local path markers.

If the Rviz config does not load, it can be added by opening the config.

RvizProjectTwoConfig.rviz

Next, in a new terminal run,

```
$ roslaunch frontier-exploration turtlebot3_navigation.launch
```

If this command errors you may need to resource the terminal

```
$ cd catkin_ws
$ source devel/setup.bash
$ roslaunch frontier-exploration turtlebot3_navigation.launch
```

The pdf file frames.pdf displays a tf tree of the objects on the module.

To generate a new pdf, run,

```
$ cd catkin_ws
```

```
$ sudo apt install ros-noetic-tf2-tools
$ rosrun tf2_tools view_frames.py
```

Next, we can see the position of the robot with,

```
$ rosrun tf tf_echo /map /base_footprint
```

Another way to display the position of the robot is with a listener script in terminal

```
$ rosrun frontier-exploration waffle_tf_listener.py
```

This will display the current position of the base of the robot with respect to the map.

Next, we want to issue a command to the robot to move.

This can be done with the moveActionClient.

Running

```
$ rosrun frontier-exploration moveActionClient.py -x <goal in x> -y <goal in y>
```

will translate the position of the robots base frame by (x,y) units.

Note: this translation is with respect to the robots frame not the map so for example translating (x=1,y=1) will move the robot right and up one unit. (instead of moving the coordinate (1,1) on the map.)

Here are a few examples to run.

```
$ rosrun frontier-exploration moveActionClient.py -x -1 -y 1
$ rosrun frontier-exploration moveActionClient.py -x -1 -y -1
```

You can also issue commands without specifying the argument, in the order (x,y)

```
$ rosrun frontier-exploration moveActionClient.py -1 1
$ rosrun frontier-exploration moveActionClient.py -1 -1
```

This concludes the setup for the project.

Troubleshooting

- Cannot find package error
 - This is a problem that is likely caused by the terminal not being sourced correctly. Which can be resourced by
- Problems with tf package for view_frames.py
 - many of the original tf functions are depreciated and so tf2 has been used in exchange.

```
$ sudo apt install ros-noetic-tf2-tools
$ rosrun tf2_tools view_frames.py
```

- If the application is having trouble connecting to the robot try running the following to change the environment to use the waffle_pi robot. `console`
`$ export TURTLEBOT3_MODEL=waffle_pi`
- If anything is added to the package, re-make the workspace
`console $ catkin_make $ cd project/catkin_ws $ source`
`devel/setup.bash`