

UEFI & EDK II Training

Open Source UEFI Platforms

tianocore.org




LESSON OBJECTIVE

- Chart the organization of the Tianocore.org repositories
- Recognize the various Open Source UEFI Platforms




Tianocore.org



Platforms Emulator, OVMF, ArmVirt, MdePkgHardware platforms: MinnowBoard Max/Turbot, Up Squared, and Intel® Galileo Gen 2.



Tianocore.org



Platforms Emulator, OVMF, ArmVirt, MdePkgHardware platforms: MinnowBoard Max/Turbot, Up Squared, and Intel® Galileo Gen 2.







Github/tianocore

Concept of Repositories

- Main development edk2
- Online Info & Help (Wiki pages) tianocore.github.io
- Other platforms edk2-platforms
- "C" library for Apps edk2-libc


To download use "git clone" then "git checkout"






edk2 – Platforms on edk2- "CORE"EmulatorPkgOvmfPkg

See Readme.md files





Emulation Directory Structure




EmulatorPkg files

- ✓ EmulatorPkg.dsc
- ✓ EmulatorPkg.dec
- ✓ EmulatorPkg.fdf




Running Emulator with # Windows






Open Virtual Machine Firmware (OVMF)

- Uses EDK II to support firmware in the OvmfPkg platform package
- Supports UEFI: Helps develop/debug drivers & applications
- QEMU VM; emulates IA32 (x86)/X64 (x86-64) based system
- Exit condition → UEFI Shell
- Tool Chain/OS Support
- Information Ovmf wiki, Tianocore.org





OVMF BIOS w/ QEMU Boots to UEFI Shell






EDK II EADK

EDK II Application
Development Kit includes the
Standard "C" Libraries in UEFI
Shell Applications

Link: wiki EADK

Github: edk2-libc





EDK II EADK COMPONENTS

EDK II Application Development Kit includes the Standard C Libraries in UEFI Shell Applications

- Components
 - Utilities (Python 2.7.2, & 2.7.10 etc.)
 - C Library
 - BSD Socket Library
 - Network Socket Library Ipv4 / Ipv6
 - Packages /AppPkg /StdLib



EDK II EADK - STANDARD ANSI C LIBRARY

FreeBSD Port

ANSI/POSIX compliant

System I/O	- open(), read(), write(), close(), stat()
Standard I/O	- fopen(), printf(), gets(), getchar(),
String/Char	- strcmp(), isascii(), atoi(),
Memory	- malloc(), free(), realloc(),
Time/Date	- time(), asctime(), ctime(),
Math	- sqrt(), pow(), sin(), log(),




Platforms Tianocore.org

edk2-platforms - Platforms

- devel-IntelAtomProcessorE3900
 - Leaf Hill, Up Squared (Apollo Lake)

www.tianocore.org

- VIv2TbltDevicePkg
 - BayTrail-I
- MinPlatformPkg (w/ FSP)
 - KabylakeOpenBoardPkg
 - WhiskeyLakeOpenBoardPkg
- How to buildSee Readme.md files





Slim BootLoader (SBL) Project



Fast & Secure Open source boot solution for IoT

Use Cases

Github: https://github.com/slimbootloader

Supported Hardware:

QEMU

UP2 Board

Apollo Lake CRB

Whisky Lake CRB

Coffee Lake Refresh CRB


UP Xtreme Board

Documentation: Slim Bootloader Project



IoT Use

Cases





Intel® FSP Repository




Intel Developer Zone Overview

Repository of Intel FSP binaries posted by Intel on github:

Includes documentation on how to integrate with various platforms: https://github.com/intel/FSP

Wiki: https://github.com/intel/FSP/wiki

- current specifications






STAGING TIANOCORE.ORG

Implementations not yet Ready for EDK II Main edk2-staging

Projects on branches

- Host-based FW analysis (HBFA)
- edk2-host-test
- FceFmmt (FW Utils)
- UEFI_PCI_ENHANCE-2
- EdkRepo
- Cpu/6-level
- HTTPS-TLS
- RICS-V
- See Readme.md files





SUMMARY

- Chart the organization of the Tianocore.org repositories
- Recognize the various Open Source UEFI Platforms







Return to Main Training Page



Return to Training Table of contents for next presentation link





Redistribution and use in source (original document form) and 'compiled' forms (converted to PDF, epub, HTML and other formats) with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code (original document form) must retain the above copyright notice, this list of conditions and the following disclaimer as the first lines of this file unmodified.

Redistributions in compiled form (transformed to other DTDs, converted to PDF, epub, HTML and other formats) must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS DOCUMENTATION IS PROVIDED BY TIANOCORE PROJECT "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL TIANOCORE PROJECT BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS DOCUMENTATION, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright (c) 2019, Intel Corporation. All rights reserved.



Intel® Quark SoC X1000 Platform

Project EDK II


- Uses EDK II to support firmware
- QuarkPlatformPkg
 -Intel[®] Galileo Gen2
- How to Build: Quark Readme.md



edk2/QuarkPlatformPkg at master · tianocore/edk2 - Mozilla Firefox

Features

- UEFI firmware image with ability to enable/disable major features such a
 - Logging
 - Source level debug using Intel(R) UEFI Development Kit Debugger
 - o Boot Performance Measurements
 - o UEFI Secure Boot with Physical Presence
 - o TCG Measured Boot using TPM 1.2 hardware devices on I2C bus
- Minimal firmware image for initial power-on and debug
- UEFI Shell built into FLASH image
- UEFI Linux operating system boot support from Micro SD FLASH
- Hardware Support
 - Intel(R) Quark SoC X1000 CPU
 - o Intel(R) Galileo Development Board
 - o Intel(R) Galileo Gen 2 Development Board
 - o HPET Timer
 - Real Time Clock



23

Readme.md