

employee (ID, person_name, street, city)

works (ID, company_name, salary)

Figure 1

1. (20%) Consider the employee database with two relations in Figure 1.


(1) Write a function **avg_salary** that takes a company name as an argument and finds the average salary of employees at that company.

```
create function avg_salary(company_name varchar(30))
return integer
begin
    declare avg integer;
    select avg(salary) into avg
    from works
    where works.company_name = company_name;
    return avg;
end
```


(2) Write an SQL statement, using the **avg_salary** function, to find companies whose employees earn a higher average salary than the average salary at "FirstBank".

```
select dept_name
from works
where avg_salary(dept_name) > avg_salary('Firstbank')
```

2. (20%) Design a database using the ER-diagram for an airline. The database must represent the information of each **flight** (航班), including its flight number and schedules (起飛降落的日期時間). The database also needs to keep track of **customers** and their **reservations** on individual flights, including the status and seat assignments. (Design the proper entity sets and relationship sets. For each entity set, represent the proper primary key and attributes.)



3. (20%) Construct appropriate relational schemas for the E-R diagram in Figure 2. For each relational schema, represent the proper attributes and primary key.



customer(customer_id(PK), name, address)

packet(packet_id(PK), place_id(FK), customer_id(FK), city, country, address)

place (place_id(PK), city, country, address)

Figure 2

4. (20%) List two nontrivial functional dependencies satisfied by the relation in Figure 3. Explain your answer.

$A \rightarrow B$

$C \rightarrow B$

A	B	C
a1	b1	c1
a1	b1	c2
a2	b1	c1
a2	b1	c3

Figure 3

Functional dependency 的定義是一組屬性可以唯一地對應到另一個，簡單來說就是可以多對一或是一對一，但不可以一對多(無法唯一的確定)。

Nontrivial 的話就是 $X \rightarrow Y$ ，Y 要被包含在 X 裡。

從圖表來看 $a1 \rightarrow b1$ ， $a2 \rightarrow b1$ ，B 不被包含在 A 裡，所以 $A \rightarrow B$ 。

$c1 \rightarrow b1$ ， $c2 \rightarrow b1$ ， $c3 \rightarrow b1$ ，B 不被包含在 C 裡，所以 $C \rightarrow B$ 。

5. (20%) Consider the schema $R = (A, B, C, D, E, G)$ and the set F of functional dependencies as follows:

$\{AB \rightarrow CD, B \rightarrow D, DE \rightarrow B, DEG \rightarrow AB, AC \rightarrow DE\}$.

- (1) Prove that AB is not a superkey.

Result1: ABCD($AB \rightarrow CD, B \rightarrow D$)

Result2: ABCDE ($AC \rightarrow DE$, AC 包含於 ABCD)

Result 不包含 G，沒辦法組成完整的 R，所以 AB 不是 superkey。

(2) Prove that DEG is a superkey.

Result1: ABDEG

包含 AB，呈上題，最終結果會有 ABCDE，起點 DEG 剛好彌補了上一題沒有 G 的問題，因此 DEG 是 superkey。

Note: Please submit your homework in a single PDF file to TronClass by 12/20/2023 11:59pm.