

employee (ID, person_name, street, city)

works (ID, company_name, salary)

Figure 1

1. (20%) Consider the employee database with two relations in Figure 1.


(1) Write a function **avg_salary** that takes a company name as an argument and finds the average salary of employees at that company.

```
dbFunctionCreate.sql
1 DELIMITER $$
2
3 CREATE FUNCTION avg_salary(companyName VARCHAR(30)) RETURNS DECIMAL(10,2)
4 DETERMINISTIC
5 BEGIN
6     DECLARE ans DECIMAL(10,2);
7     SELECT AVG(salary) INTO ans FROM works
8     WHERE company_name = companyName;
9     RETURN ans;
10 END $$
11
12 DELIMITER ; 7ms
13
```

(2) Write an SQL statement, using the **avg_salary** function, to find companies whose employees earn a higher average salary than the average salary at "FirstBank".

```
98 select distinct w.company_name as name from works as w
99 where avg_salary(w.company_name) > avg_salary('FirstBank'); 2ms
```

2. (20%) Design a database using the ER-diagram for an airline. The database must represent the information of each **flight** (航班), including its flight number and schedules (起飛降落的日期時間). The database also needs to keep track of **customers** and their **reservations** on individual flights, including the status and seat assignments. (Design the proper entity sets and relationship sets. For each entity set, represent the proper primary key and attributes.)



首先解釋entity，考慮即使單一航班也可能發生單人訂多張票的情況，reservation應該為entity，而非relation。

而customers與flight間存在可互相查詢對應的search關係，每個顧客都應該透過flight-number找到自己搭乘的flight，故search右方為total participation，flight上的座位不一定要對應到顧客（座位未售出），可能因時段或重大變故，出現某航空公司發出乘客數為0的航班。

對於reservation左方的seat distribute來說，所有預定應對應到flight上，不可開出沒售出的座位票，相對於flight來說，可以有座位是未售出的，因此非total participation。

對於reservation右方的order來說，所有的預定應找到對應的顧客（total participation），所有顧客也應可以對應到自己的預訂紀錄，因此也為total participation。

3. (20%) Construct appropriate relational schemas for the E-R diagram in Figure 2. For each relational schema, represent the proper attributes and primary key.




Figure 2

Sends_packet	Sends_packet(customer id, packet id)
Receiver_packet	Receiver_packet(customer id, packet id, time_received)
Has_gone_through	Has_gone_through(packet id, place id)
Customer	Customer(customer id, name, address)
Packet	Packet(packet id, weight)
Place	Place(place id, city, country, address)

4. (20%) List two nontrivial functional dependencies satisfied by the relation in Figure 3. Explain your answer.

A	B	C
a1	b1	c1
a1	b1	c2
a2	b1	c1
a2	b1	c3

Figure 3

<u>A -> B</u>	<u>B 不被包含在 A 裡，但可以透過 A 推出唯一的 B (a1->b1, a2 ->b1)</u>
<u>C -> B</u>	<u>B 不包含於 A，但 C 唯一對應到 B (c1 -> b1, c2 -> b1, c3 -> b1)</u>

5. (20%) Consider the schema $R = (A, B, C, D, E, G)$ and the set F of functional dependencies as follows:
 $\{AB \rightarrow CD, B \rightarrow D, DE \rightarrow B, DEG \rightarrow AB, AC \rightarrow DE\}$.

- (1) Prove that AB is not a superkey.

1. AB 藉 $AB \rightarrow CD$ 獲得 CD
 2. AB 已經有 B ，不須藉 $B \rightarrow D$ 獲取 D
 3. $ABCD$ 藉 $AC \rightarrow DE$ 獲得 DE
 4. $ABCD$ 已經有 B ，不須藉 $DE \rightarrow B$ 獲取 B
 5. $ABCDE$ 無法獲得 G
- 以上推斷，可知無法 cover 所有的 attribute，非 superkey

(2) Prove that DEG is a superkey.

1. DEG 藉 $DEG \rightarrow AB$ 獲取 AB

2. ABDEG 藉 $AB \rightarrow CD$ 獲取 C

以上推斷，可知 DEG 可以 cover 所有 attribute，為 superkey