

employee (ID, person_name, street, city)

works (ID, company_name, salary)

Figure 1

1. (20%) Consider the employee database with two relations in Figure 1.

(1) Write a function **avg_salary** that takes a company name as an argument and finds the average salary of employees at that company.

```
create function avg_salary(company_name varchar(127))
return num
begin
    declare avg_salary num;
    select avg(salary) into avg_salary
    from works
    where works.company_name = company_name;
    return avg_salary;
end
```


(2) Write an SQL statement, using the **avg_salary** function, to find companies whose employees earn a higher average salary than the average salary at "FirstBank".

Select company_name


Form works

Where avg_salary(company_name) > avg_salary('FirstBank');

2. (20%) Design a database using the ER-diagram for an airline. The database must represent the information of each **flight** (航班), including its flight number and schedules (起飛降落的日期時間). The database also needs to keep track of **customers** and their **reservations** on individual flights, including the status and seat assignments. (Design the proper entity sets and relationship sets. For each entity set, represent the proper primary key and attributes.



3. (20%) Construct appropriate relational schemas for the E-R diagram in Figure 2. For each relational schema, represent the proper attributes and primary key.



sends_packet(packet_id, customer_id)

receiver_packet(packet_id, customer_id, time_received)

has_gone_through(place_id, packet_id)

Figure 2

4. (20%) List two nontrivial functional dependencies satisfied by the relation in Figure 3. Explain your answer.

*可以多對一或是一對一，但不可以一對多

所以:

C->B

B不被包含在C裡,但可以透過C推出唯一的B (c1->b1, c2->b1, c3->b1)

A->B

B不被包含在A裡, 但可以透過A推出唯一的B (a1->b1, a2 ->b1)

A	B	C
a1	b1	c1
a1	b1	c2
a2	b1	c1
a2	b1	c3

Figure 3

5. (20%) Consider the schema $R = (A, B, C, D, E, G)$ and the set F of functional dependencies as follows:

$\{AB \rightarrow CD, B \rightarrow D, DE \rightarrow B, DEG \rightarrow AB, AC \rightarrow DE\}$.

- (1) Prove that AB is not a superkey.

$\{AB\}$:

$DEG \rightarrow AB \rightarrow CD$, 因為 AB 具transitively dependent,所以 AB 不是superkey

- (2) Prove that DEG is a superkey.

$\{DEG\}$:

$DEG \rightarrow AB, DEG \rightarrow CD$

且 DEG 不被包含在 AB 裡, DEG 不被包含 CD 在裡, 所以 DEG 是superkey

Note: Please submit your homework in a single PDF file to TronClass by 12/20/2023 11:59pm.