Why the irrigation jet makes a ring vortex in the blocked sheath

Analytical model and check against the flow simulation

USZ sheath without internal tube, irrigation outlet in the tip

13 November 2026

Summary

The irrigation leaves a 1 mm outlet about 120 times faster than the sheath lumen needs to carry the same flow. A fast thin jet drags the surrounding fluid along. With every side hole blocked, only the irrigation flow itself can leave through the suction tube, so the dragged fluid has to return along the walls. That return is the ring vortex seen in the animation. The model below gives, with no fitted constant,

- the rate at which the return flow builds up near the outlet, $8\pi\nu$ per unit length (simulation: the same to within 3 %);
- the jet centre speed and width over the first 15 mm (simulation: within 15 %);
- the length of the loop, about 32 mm (simulation: 38 mm);
- the scaling of the loop length, proportional to flow rate and roughly to $1/d$.

It does not give the strength of the loop from first principles: the return flow peaks at 10 mL/min in the simulation, 2.4 times the irrigation, because the walls cut the entrainment short. An earlier estimate of 57 mL/min from the unconfined formula was too high and is withdrawn.

1 Set-up and numbers




Figure 1: Blocked sheath. The jet from the tip outlet (blue) entrains fluid, which returns along the walls (red) up to x_{end}. Beyond that the flow is a slow duct flow towards the suction tube.

Single-phase saline, $\rho = 1000\,\mathrm{kg/m^3}$, $\nu = 1 \times 10^{-6}\,\mathrm{m^2/s}$, steady flow, rigid walls.

Irrigation flow	Q	$250\,\mathrm{mL/h} = 4.17\,\mathrm{mL/min} = 6.94 \times 10^{-8}\,\mathrm{m^3/s}$
Outlet diameter	d	1.0 mm
Outlet mean speed	$U_j = 4Q/\pi d^2$	88.4 mm/s (peak $2U_j = 177$ mm/s)
Jet Reynolds number	$Re = U_j d/\nu$	88
Lumen area, equivalent radius	A, $R_{eq} = \sqrt{A/\pi}$	$93.3\,\mathrm{mm^2}$, 5.45 mm
Lumen mean speed	$U_m = Q/A$	0.744 mm/s
Area ratio	$A/(\pi d^2/4)$	119

2 Momentum of the jet

The fluid leaves the outlet tube with a parabolic profile $u = 2U_j(1 - 4r^2/d^2)$. Its momentum flux divided by density is

$$K = \int_0^{d/2} u^2\, 2\pi r\, dr = \frac{4}{3} U_j^2\, \frac{\pi d^2}{4} = \frac{16}{3\pi} \frac{Q^2}{d^2} = 8.19 \times 10^{-9}\,\mathrm{m}^4/\mathrm{s}^2. \tag{1}$$

Away from walls no force acts on the jet (the pressure is uniform, section 7), so K is the same at every distance x. This single conserved number fixes the whole jet.

3 The laminar round jet (Schlichting)

For a slender steady axisymmetric jet the boundary-layer equations are

$$\frac{\partial u}{\partial x} + \frac{1}{r}\frac{\partial (rv)}{\partial r} = 0, \qquad u\frac{\partial u}{\partial x} + v\frac{\partial u}{\partial r} = \frac{\nu}{r}\frac{\partial}{\partial r}\left(r\frac{\partial u}{\partial r}\right), \qquad 2\pi\int_0^\infty u^2 r\, dr = K. \tag{2}$$

With the stream function $\psi = \nu x\, F(\xi)$ and the similarity variable $\xi = a\, r/x$ they reduce to an ordinary differential equation whose solution is $F = \xi^2/(1 + \xi^2/4)$. Hence

$$u(x, r) = \frac{u_c(x)}{\left(1 + \xi^2/4\right)^2}, \qquad \xi = \sqrt{\frac{3K}{16\pi}}\, \frac{r}{\nu x}, \qquad u_c(x) = \frac{3K}{8\pi\nu x}. \tag{3}$$

Two integrals of this profile matter. Using $\int_0^\infty \xi\, d\xi/(1 + \xi^2/4)^4 = 2/3$ the momentum flux comes out as K for every x, as it must. Using $\int_0^\infty \xi\, d\xi/(1 + \xi^2/4)^2 = 2$ the volume flow carried by the jet is

$$Q_{\mathrm{jet}}(x) = 2\pi\int_0^\infty u\, r\, dr = 8\pi\nu x. \tag{4}$$

The jet therefore takes in surrounding fluid at the constant rate $dQ_{\mathrm{jet}}/dx = 8\pi\nu = 1.51\,\mathrm{mL/min}$ per mm, whatever its momentum.

A real jet starts with finite width, so the point-source solution is shifted by a virtual origin x_0. Choosing it so that the centre speed at the outlet equals the true peak $2U_j$ gives

$$u_c(x) = \frac{3K}{8\pi\nu\,(x + x_0)}, \qquad x_0 = \frac{Re\, d}{16} = 5.5\,\mathrm{mm}. \tag{5}$$

The half-width, where $u = u_c/2$, follows from $(1 + \xi^2/4)^2 = 2$, i.e. $\xi = 1.287$:

$$r_{1/2}(x) = 5.27\, \frac{\nu\,(x + x_0)}{\sqrt{K}} = 0.0582\,(x + x_0). \tag{6}$$

4 Why the flow must turn back

With all holes blocked the net flow through every cross-section of the lumen equals Q. Split it into the part moving towards suction and the part moving back:

$$Q_{\mathrm{forward}}(x) - Q_{\mathrm{back}}(x) = Q \quad \text{for every } x. \tag{7}$$

The jet wants to carry $Q + 8\pi\nu x$. The only source for the extra fluid is the lumen itself, so close to the outlet

$$Q_{\mathrm{back}}(x) \simeq 8\pi\nu x. \tag{8}$$

Fluid moves forward in the core and backward in the surrounding ring: a ring (toroidal) vortex. The return flow already equals the whole irrigation flow at $x = Q/8\pi\nu = 2.8\,\mathrm{mm}$.

Whether a confined jet recirculates at all is measured by the Craya–Curtet number, the ratio of the mean duct speed to the speed scale of the jet momentum spread over the duct:

$$C_t \simeq \frac{U_m}{\sqrt{K/A}} = \frac{0.744}{9.37} = 0.08. \tag{9}$$

Recirculation appears below $C_t \approx 0.75$. This case is a factor ten inside that regime: the jet has about 160 times more momentum than the duct flow could carry ($1/C_t^2$).

5 Where the loop ends

The loop ends where the jet has widened to the walls, since nothing is left to entrain. Take the edge of the jet at $2.5\,r_{1/2}$ (speed down to 8 % of the centre value) and the wall at the equivalent radius:

$$2.5 \times 0.0582\,(x_{\text{end}} + x_0) = R_{\text{eq}} \quad \Longrightarrow \quad x_{\text{end}} = \frac{R_{\text{eq}}\sqrt{K}}{13.2\,\nu} - x_0 = 37.4 - 5.5 = 32\,\text{mm}. \tag{10}$$

The simulation gives 38 mm (return flow below 1 % of Q). The choice of 2.5 half-widths and of a round equivalent for the oval ribbed lumen are the two approximations here.

Substituting K gives a design formula in the Reynolds number of the outlet:

$$\boxed{x_{\text{end}} \simeq Re\left(0.078\,R_{\text{eq}} - \frac{d}{16}\right), \qquad Re = \frac{4Q}{\pi d\,\nu}} \tag{11}$$

The loop length is proportional to the flow rate Q and falls a little faster than $1/d$.

6 Check against the simulation




Figure 2: Blocked-sheath simulation (dots, 117 000 nodes) against the free-jet formulas (red). Left: centre-line speed. Middle: half-width. Right: return flow through each cross-section. The dashed vertical line marks the end of the loop in the simulation.

Quantity	Model	Simulation
Build-up of return flow near the outlet (mL/min per mm)	1.51	1.47
Centre speed at $x = 10$ mm (mm/s)	63	56
Half-width at $x = 10$ mm (mm)	0.90	0.92
Half-width at $x = 20$ mm (mm)	1.49	1.39
Loop length x_{end} (mm)	32	38
Peak return flow (mL/min)	not predicted	10.1 at $x = 14$ mm

The entrainment rate $8\pi\nu$ is reproduced almost exactly. Beyond about 12 mm the walls take over: the return flow occupies a ring of limited area, it opposes the jet, and the jet slows down faster than a free jet would. Equation (8) therefore over-predicts further out. A simple closure that follows the simulation (fitted exponent, not derived) is

$$Q_{\text{back}}(x) \approx 8\pi\nu\,x\left(1 - \frac{x}{x_{\text{end}}}\right)^{3/2}, \qquad \max Q_{\text{back}} \approx 0.19 \times 8\pi\nu\,x_{\text{end}} \text{ at } x = 0.4\,x_{\text{end}}. \tag{12}$$

With $x_{\text{end}} = 38$ mm it gives a peak of 10.7 mL/min at 15 mm; the simulation has 10.1 mL/min at 14 mm.

7 Pressure

When the jet has spread over the lumen its momentum has become a pressure rise

$$\Delta p_{\mathrm{jet}} \simeq \frac{\rho K}{A} = 0.09\,\mathrm{Pa}. \tag{13}$$

The viscous loss of the duct flow is of the same small order: for a round tube of radius R_{eq} and length 80 mm, $\Delta p = 8\mu LQ/\pi R_{\mathrm{eq}}^4 = 0.02\,\mathrm{Pa}$ (the ribs raise it; the simulation has 0.2 Pa). Both are negligible against the suction of 933 Pa (−7 mmHg). The whole interior sits at the suction pressure, and the flow pattern does not depend on the suction level: stronger suction changes the pressure, not the flow, as long as the holes stay blocked.

8 What it means for flushing




Figure 3: Left: fraction of old fluid left, tip zone and duct section taken separately. Right: loop length from eq. (11) against outlet diameter for three irrigation rates; the star is the simulated case.

Tip zone (the loop). Volume $V = A\,x_{\mathrm{end}} = 3.5\,\mathrm{mL}$. The loop turns over in $V/\max Q_{\mathrm{back}} \approx 21\,\mathrm{s}$, faster than the through-flow time $\tau = V/Q = 51\,\mathrm{s}$, so the zone is roughly a stirred tank and old fluid leaves as

$$\phi_{\mathrm{tip}}(t) = e^{-t/\tau}, \qquad \tau = \frac{A\,x_{\mathrm{end}}}{Q} = 51\,\mathrm{s}. \tag{14}$$

5 % is left after $3\tau \approx 2.5\,\mathrm{min}$. Mixing is good, displacement is not: fresh irrigation is diluted into the zone and part of it is carried round again.

Duct section. Length $L = 82\,\mathrm{mm}$, mean residence $t_r = L/U_m = 110\,\mathrm{s}$. Diffusion across the lumen takes $R_{\mathrm{eq}}^2/D \approx 3\times10^4\,\mathrm{s}$ for $D = 1\times10^{-9}\,\mathrm{m^2/s}$, far longer, so each streamline keeps its own speed. For a parabolic profile $u = 2U_m(1 - r^2/R^2)$ the fresh front has reached $z = \min(L, ut)$, and integrating the remaining old fluid over the cross-section gives

$$\phi_{\mathrm{duct}}(t) = 1 - \frac{t}{t_r} \quad \left(t \le \tfrac{1}{2}t_r\right), \qquad \phi_{\mathrm{duct}}(t) = \frac{t_r}{4t} \quad \left(t \ge \tfrac{1}{2}t_r\right). \tag{15}$$

The centre is renewed after $t_r/2$, but the tail falls only as $1/t$: 8 % is still old after three residence times (5.5 min). In the simulation the centre speed is 2.2 mm/s, three times the mean rather than two, because the ribs hold back the fluid near the wall. The first fresh fluid therefore arrives sooner (simulated fastest transit 42 s) and the tail is longer than this formula.

Rib grooves. The flow in the grooves is almost zero (23 % of the lumen volume moves at less than a tenth of U_m). They are renewed mainly by diffusion: a groove 1 mm deep needs of the order of $w^2/D \approx 1000\,\mathrm{s}$, about a quarter of an hour.

9 Design consequences

Outlet d (mm)	Outlet speed (mm/s)	Re	Loop length, eq. (11) (mm)
1.0	88	88	32 (simulation 38)
1.5	39	59	19
2.0	22	44	13
2.5	14	35	9

- A small outlet gives a long stirred zone at the tip, a large outlet gives a short one and more of the sheath in plain displacement flow. Only the 1.0 mm row has been simulated.
- Doubling the irrigation rate doubles the loop length and halves every flushing time.
- Moving the outlet away from the tip leaves the fluid between the tip and the outlet with no through-flow at all; it would be renewed only by whatever the loop stirs backwards. This is the question for the planned position study.

10 With some holes open: orifice estimate

A side hole of area $A_h = \pi(0.5\,\mathrm{mm})^2$ under a pressure difference Δp passes

$$Q_h = C_d\, A_h \sqrt{\frac{2\,\Delta p}{\rho}}. \tag{16}$$

With the lumen about 880 Pa below the outside this is $C_d \times 62$ mL/min. The first open-hole simulation (four holes near the tip, coarse mesh, first 0.43 s only) gives 38 mL/min per hole, i.e. $C_d = 0.61$, the usual value for a sharp orifice. Four open holes bring in about 152 mL/min, 36 times the irrigation.

Irrigation fluid can leave through a hole only if the lumen pressure exceeds the outside pressure. Carrying the irrigation alone to the suction tube costs less than 1 Pa, so the lumen stays close to the suction pressure and the flow through every open hole is inward. Outflow through the holes requires the suction path to be closed or the suction switched off. This part is preliminary until the open-hole runs are complete.

11 Limits of this analysis

Laminar, steady, single fluid; no tissue, air or clogging. The free-jet solution ignores the walls and is used only where the jet is thin. The loop length carries the choice of "edge" of the jet and of the equivalent radius. The simulated jet wobbles slightly (changes of 0.2 % per step remained), and the mesh near the outlet resolves the 1 mm jet with a limited number of cells, so simulation values near the outlet are good to roughly 10 %.