

Steps used to get server email for Ibrahim@yahoo.co.uk 1 Asking DNS for MX record for "yohoo.co.uk" domain name. to get the mail server where my emails are hostedo B test if 75 port on the domain name is open?, if you test if emall exists

configuration file for postfix

```
SMTP Server "Postfix Server"
```

vim /etc/hosts 10.0.0.100 mail1.abc.com

vim /etc/hostname

mail1.abc.com # hostname mail1.abc.com

yum install postfix

vim /etc/postfix/main.cf

95 myhostname = mail1.abc.com

102 mydomain = abc.com

118 myorigin = \$mydomain 4 @abc.com

132 inet_interfaces = all > declare from which interface to recieve SMTP fractic (Instead of all)
184 mydestination = & myhostana declare from which interface to recieve SMTP fractic (Instead of all) 184 mydestination = \$myhostname, localhost.\$mydomain, localhost, \$mydomain

283 mynetworks = 10.0.0.0/8, 127.0.0.0/8 -> declare server hetwork 438 home_mailbox = Maildir/ > which folder to make users receive their enails.

systemctl enable postfix.service --now # systemctl status postfix.service

firewall-cmd --add-service=smtp --permanent # firewall-cmd --reload

firewall-cmd --list-services

telnet to smtp port:-To test the SMIP man server # yum install telnet [root@Server100 ~]# telnet localhost 25 connect to port 25 Trying ::1... Connected to localhost. Escape character is '^]'. 220 mail1.abc.com ESMTP Postfix mail from:<root> sender 250 2.1.0 Ok rcpt to: <hany> recipient 250 2.1.5 Ok 354 End data with <CR><LF>.<CR><LF> welcome hany it is a test mail from my messeage body text root system admin hiiiiiiiiiiiiiiiiii . send messeage 250 2.0.0 Ok: queued as 68189409E18C 221 2.0.0 Bye Connection closed by foreign host. The email Sent From root user to hang user! , So hany eneil's will be found und hany directory maildir/new