

XSS Checklist

- ☐ Automation Script
- ☐ Automation Script for Blind XSS
- ☐ Use Arjun for hidden parameters
- ☐ Gxss for testing reflected parameters
- ☐ Kxss for testing unsafe characters
- ☐ Tools Xsstrike for specific parameter
- ☐ Burpsuite plugins (Reflection + sentinal)
- ☐ <https://xssor.io/> for encoding/decoding
 - []

Encoding

- ☐ url encoding for unsafe character
- ☐ url encoding for the whole payload
- ☐ double url encoding for unsafe character
- ☐ double url encoding for the whole payload
- ☐ Use combination of Lower + UpperCase
- ☐ Insert **%00** at any point
- ☐ use invalid tag `<any onload=alert></any>`
- ☐ use `<base href="url/payload.js">`
- ☐ insert %00 in the attribute name ``
- ☐ use attribute delimiters ``
- ☐ HTML encoding for unsafe character
- ☐ HTML for a character of `alert()`
- ☐ HTML for anything you want
- ☐ Unicode
- ☐ use extra brackets `<<script>alert();//<</script>`
- ☐ Payload strange works by firefox `<script<{alert(1)}/></script>`
- ☐ UTF-7 encoding `+ADw-script+AD4-alert()+ADw-/script+AD4-`
- ☐ US-ASCII encoding `1/4script3/4`
- ☐ UTF-16 encoding