Introduction to AI

How machines learn, and how to build useful, safe systems with today's generative AI

Part A · Foundations

how machines learn


Part B · Generative AI in practice

LLMs, prompts, RAG, agents, MCP, fine-tuning, risks

Ibrahim Sobh, PhD · ibrahimsobh.github.io/introduction-to-ai

AI is a family of nested ideas

- **Artificial intelligence**: machines doing tasks we link to human intelligence (including hand-written rules)
- **Machine learning**: learns patterns from data instead of following hand-written rules
- **Deep learning**: neural networks with many layers
- **Generative AI**: creates new text, images, code



KEY INSIGHT

Generative AI is the innermost circle: today's chatbots are still machine learning, learning patterns from data.

PART A

Foundations: how machines learn


1 What is AI?

2 Learning from data

3 Neural networks

Machines learn in three ways

Type	Learns from	Example
Supervised	examples **with** the right answers (labels)	emails marked spam / not spam → classify new emails
Unsupervised	examples **without** answers	customer data → discover groups of similar customers
Reinforcement	trial and error, with rewards and penalties	a game player learns which moves lead to a win



Supervised
labels → a boundary

Unsupervised
no labels → groups


Reinforcement
rewards → better moves

KEY INSIGHT

The data decides the method: labels → supervised, no labels → unsupervised, rewards → reinforcement.

Supervised learning answers "Which one?" or "How much?"

	Classification	Regression
Predicts	a category from a fixed list	a number that can take any value (continuous)
Asks	"Which one?"	"How much?" or "Where?"
Example	spam or not spam	a house price



Classification: what?
"person", 94% sure


Regression: where?
4 numbers: x, y, width, height

KEY INSIGHT

Real systems often do both at once. A car camera says *what* each object is (classification) and *where* it is (regression).

A model is a formula, and training finds its parameters

- The simplest model is a straight line: **`y = a·x + b`** (x = house size, y = price)
- **Model**: the shape we assume (here, a line)
- **Parameters**: the numbers that set its exact shape (a = slope, b = starting height)
- **Training**: find the a and b that make the line fit the data best
- **Prediction**: put a new size into the trained formula to get a price



KEY INSIGHT


Training is iterative: many small steps, each nudging the parameters to reduce the error.

A good model works on data it hasn't seen

Keep a **test set** aside that the model never sees during training, so it can be checked honestly.

	Training error	Test error	What's happening
Underfitting	high	high	too simple to capture the pattern
Good fit	low	low	learned the real pattern, generalises
Overfitting	very low	**high**	memorised the training data, noise included

Remedies: more and better data, simpler models, test on held-out data. Garbage in, garbage out: bad or unrepresentative data teaches the wrong pattern.




KEY INSIGHT


Low training error alone proves nothing. Only performance on unseen data counts.

A neural network learns by nudging its weights

- Neurons in layers: **input** → **hidden** → **output**
- Each connection has a **weight**: how much one neuron's output matters to the next
- An **activation function** bends each result, so the network can learn curves
- Repeat many times: **forward pass** → **measure the error** → **backpropagation** (who caused it) → **update** every weight a little (gradient descent)



blue = positive weight · orange = negative
thicker = bigger weight



gradient descent:
small steps downhill

KEY INSIGHT

Same idea as the line, just bigger: a line has 2 parameters, the small network 13, an LLM billions, which is why training needs many GPUs.

PART B

Generative AI in practice

4 Generative AI & LLMs

5 Prompt engineering

6 RAG

7 AI agents


8 MCP & Skills

9 Fine-tuning

10 Limitations & risks

An LLM is a very well-read autocomplete

- **Generative AI** creates new content: text, code, images, audio, video
- A **large language model (LLM)** is a very large neural network trained on huge amounts of text to **predict what comes next**
- Same idea as the line: a model with learned parameters, only billions of them
- Many models are **multimodal**: they also read images, audio and documents




KEY INSIGHT

An LLM's core skill is predicting the next piece of text. Answering, writing and coding all emerge from doing that at huge scale.

LLMs read tokens, and the context window is their working memory

- **Token**: a common chunk of text, such as `learn` + `ing`. In English, 1 token ≈ 4 characters ≈ ¾ of a word
- **Context window**: the most tokens the model can handle at once: prompt, conversation, documents and the answer
- 128K tokens ≈ a 300-page book
- When it fills up, the earliest messages are dropped or summarised, so the model "forgets"
- Tokens are how AI use is measured and billed




```
1 token ≈ 4 characters ≈ ¾ of a word
```


KEY INSIGHT

The model only works with what fits in its context window.

Pre-training gives knowledge, tuning makes it an assistant

1. **Pre-training**: predict the next token across a huge amount of text → a *base model* that just continues text
2. **Instruction tuning**: learn from instructions paired with good answers → acts as an assistant
3. **Preference tuning** (e.g. RLHF): people rate answers → more helpful, honest and safe

You type: "What is the capital of France?"	
Base model	"What is the capital of Germany? What is the capital of Italy?..."
Instruction-tuned	"The capital of France is Paris."




KEY INSIGHT


Pre-training gives the model its knowledge. Tuning shapes how it behaves.

Attention lets every word look at every other word

- Most LLMs use the **Transformer** design (2017). Its key idea is **attention**
- For each token, the model scores how relevant every other token is, then mixes in meaning from the most relevant ones
- This happens in every layer, with many attention heads
- text → tokens → embeddings → Transformer layers (× many) → next-token probabilities



"it" = the animal (it was tired)



"it" = the street (it was wide)

Bars: how much "it" attends to each word (set by hand for the picture)


KEY INSIGHT

Attention lets each token use information from anywhere in the context, all in parallel. That parallel work suits GPUs and made today's very large models possible.

An LLM writes one likely token at a time

- At each step: give every possible next token a probability → pick one → add it → repeat
- The pick is random but weighted, so **the same prompt can give different answers**

Temperature	Behaviour	Use it for
Low (0–0.3)	consistent, most likely	facts, code, extraction
Medium (0.5–0.8)	balanced	chat, explanations, emails
High (≥ 1)	varied, can drift	brainstorming, stories




KEY INSIGHT

Fluent is not the same as true. The model picks *likely-sounding* tokens, and that's the root of hallucinations.

Ask clearly and get reliable results

Six things to add to a prompt:

Technique	What you add
Clear instruction	exactly what to do, the options, length, audience
Role	"You are a…" (often in the system prompt)
Context	background, goal, constraints
Examples (few-shot)	a few input → output pairs
Step by step	"think step by step", or list the steps
Structured output	table / list / JSON with keys




KEY INSIGHT

Treat prompts like code: test them on real inputs, change one thing at a time, and keep the versions that work.

The model only knows what's in its context

Context engineering means deciding everything that goes into the context window for each request: instructions, the right documents, tool definitions and results, memories, chat history, and what to leave out or summarise.

	Prompt engineering	Context engineering
Focus	how you write the request	what the model sees when it answers
Done by	a person, once per task	the app or agent harness, at every step




KEY INSIGHT

A great prompt with the wrong documents still gives a wrong answer, and too much irrelevant text buries the important part.

Embeddings turn meaning into numbers

- An **embedding** is a list of numbers (a vector) that captures a text's meaning
- Similar meaning → vectors that point the same way, even with no shared words: "cheap flights" ≈ "low-cost airfares"
- **Cosine similarity** measures this: 1 = same meaning, 0 = unrelated
- Documents are split into **chunks**; each is embedded and stored in a **vector database**. Too big wastes context; too small loses meaning




KEY INSIGHT

Search by meaning, not by keywords: this is how RAG finds the right passages (next slide).

RAG: retrieve, augment, generate

Why LLMs need outside knowledge:

- **Old**: they only know their training data, up to a cut-off date
- **Private**: they have never seen your policies, contracts or databases
- **Trust**: answers from retrieved sources can cite them, which reduces hallucinations



No retraining: update the documents and re-index


KEY INSIGHT

RAG keeps knowledge outside the model. To update it, change the documents and re-index them. No retraining needed.

Agent = LLM + harness

The **LLM** is the brain: it reads, reasons and decides, but on its own it only turns text into text. The **harness** is the program around it:

Harness job	What it means
Tools	offers tools and runs the ones the model asks for
The loop	sends the conversation back until done or a limit is hit
Context and memory	decides what goes in the window; saves and recalls memories
Safety	permissions and limits; a person approves risky actions




KEY INSIGHT

The model never runs anything itself, it only asks. That's why safety checks belong in the harness. Same LLM, different harness = a different agent.

Agents loop: think, act, observe

- The agent plans, then repeats **think → act → observe**, adjusting the plan, until done or a limit is hit (the ReAct pattern)
- Memory: **short-term** = the context window; **long-term** = stored outside the model, fetched when relevant

You need	Use
an answer from general knowledge	plain chat
answers from your own documents	RAG
several steps or real actions	an agent




KEY INSIGHT

Agents are slower and cost more, so use the simplest option that does the job.

MCP gives access, Skills give know-how

- **MCP (Model Context Protocol)**: an open standard for connecting AI apps to tools and data. Build a connector once, use it in any app that supports MCP
- An app (the *host*) talks through *clients* to *servers*, each in front of one system. Servers offer tools, resources (data) and prompts
- **Skills**: folders with a `SKILL.md` of instructions, plus optional scripts and templates
- The agent sees only each skill's short description, and loads the full instructions when a task matches




KEY INSIGHT

Together: the skill says *what to gather and how to present it*, and MCP tools *fetch the data*.

Start with prompts, add RAG, fine-tune last

Fine-tuning trains a pre-trained model further on your own examples. It changes the model's **weights**; prompting and RAG only change its **input**.

	Prompting	RAG	Fine-tuning
Changes	the instructions	the information in the prompt	the model's weights
Best for	most tasks: start here	up-to-date or private knowledge	consistent style, format, narrow tasks
Effort	low	medium	higher
Updating	edit the prompt	update the documents	train again



KEY INSIGHT

Start with prompts. Add RAG for missing knowledge. Fine-tune for behaviour prompts can't reliably produce. The approaches also combine.

Four risks every AI user must know

Risk	What it is	How to reduce it
Hallucinations	confident, fluent answers that are false (fake facts, quotes, sources)	ground with RAG, ask for citations, verify important facts
Bias	repeats unfair patterns from human data	check results across groups, balanced data, a person checks decisions about people
Privacy	sensitive data in prompts may be stored, seen or leaked	follow your organisation's rules, use approved tools, remove personal and secret data
Prompt injection	hidden instructions in content the AI reads try to take control	treat outside content as data, minimal tool permissions, approval for risky actions

KEY INSIGHT


AI is a very fast, very confident trainee: great for drafts, but someone checks before anything important goes out.

Prompt injection needs layered defences, and a human in the loop

An agent can't always tell your instructions from instructions hidden in a web page, email or file. No single fix exists, so **layer the defences**:

1. Treat outside content as data, not instructions
2. Least privilege: only the tools the task needs
3. Human approval before sending or acting

Keep a human in the loop when stakes are high, actions are hard to undo, or facts are hard to check.



The last layer is a person.

KEY INSIGHT

There is no perfect fix for prompt injection yet. Defence comes in layers, and the last layer is a person.

Key takeaways

1. ML learns patterns from data instead of rules written by hand.
2. A model is a formula, and training tunes its parameters. Judge it on data it hasn't seen.
3. Neural networks are the same idea with billions of parameters.
4. An LLM predicts the next token. Fluent is not the same as true.
5. Clear prompts and the right context make results reliable.
6. RAG answers from your documents, with sources.
7. Agent = LLM + harness. The model asks; the harness acts.
8. MCP gives access; Skills give know-how.
9. Prompt first, then RAG, then fine-tune.
10. Know the risks, and keep a human in the loop for anything that matters.

Try it yourself: free course, free certificate

Introduction to AI: a free, self-paced interactive course

`ibrahimsobh.github.io/introduction-to-ai`

- Every idea in this talk has a live demo you can drive: train a line, watch a network learn, sample tokens, run RAG, step through an agent
- No sign-up, runs in your browser. Pass the final quiz (10 of 12) for a free certificate

Source on GitHub · ⭐ Star the repo if you found it useful.



KEY INSIGHT

You remember what you try. Pick one demo tonight.