

Usage of MATLAB Report Generator

Eniz Museljc

7. Juli 2018

Inhaltsverzeichnis

1	Introduction	2
1.1	About this toolset	2
1.2	Setup	2
1.3	How it works	2
2	LATEXGenerator	4
2.1	New report	4
2.2	Set and Get	4
2.3	Title page and TOC	5
2.4	Paragraphs	5
2.5	Headings	5
2.6	Lists	6
2.7	Tabular and table	6

Kapitel 1

Introduction

1.1 About this toolset

This toolset is to be used while programming in MATLAB to create a report or paper of any kind with the data from MATLAB, so it bridges the way and saves you the time to copy values and make pretty tables and plots through an additional LaTeX editor. Please follow the upcoming instructions to get it up and running.

1.2 Setup

To set the LaTeX Generator up, you will need the following installed on your pc :

- L^AT_EX distribution for your system
- Latexmk package
- Ruby framework (on windows)

After installing these components, copy the reportGenerator main folder to a secure location on your machine and be sure to add it to your MATLABs search path so you can work from a different directory and use all the functions without restriction. To be sure that everything is set up correctly, we have provided a very simple "hello world"programme that you can run and check if it generates a pdf document with "hello world"on one page, in your current working directory.

1.3 How it works

In this section we will talk about all the different files that you can use and manipulate to get the best out of this toolset. The main files that you are gonna be changing are :

setting.dat Specifies a variety of settings for the program which can be adjusted to your specific needs.

`myTextBlocks.tex` A file which contains blocks of Latex code separated by lines with `%% TAG` where `TAG` is a unique identifier.

`myCodeBlocks.m` A file which contains blocks of MATLAB code separated by lines with `%% TAG` where `TAG` is a unique identifier. It can be used to evaluate code specified in a section of this file.

`myMatlabInit.m` This is a init-File for MATLAB which is executed at the beginning. One can specify all necessary settings there.

You can also specify files with different names for organisation purposes, if that's the case you will have to change the file names in the `setting.dat` file. Additionally you will need to edit the provided MATLAB `startup.m` file and set the `LATEX` install path to the path on your computer.

Kapitel 2

L^AT_EX Generator

Now we will go through the functions available and show you what you can do with them, you can use this documentation and the MATLAB file `reportingDocu.m` with which it was created, to help you write your own reports. All of the functions that will be mentioned also have descriptions which can be accessed through MATLAB by using the *help* command for the function in question.

2.1 New report

To use the following functions you will need to create a *latexGenerator* object which will be used to access the methods provided and explained in the following sections. This can be easily done with:

```
report = latexGenerator;
```

Note that the constructor function also takes in parameters with which we could like in the following example change the name of the settings file we are using, this can be very useful if we have a settings file with settings that fit our current needs but we might use a different settings file usually.

```
report = latexGenerator('settingFile', 'personalSettings.dat');
```

2.2 Set and Get

Using the *set* and *get* methods from the `reportGenerator` super class, we can access and change the settings provided by the `setting.dat` file from within our MATLAB code. For example, if we wanted to change the name the program gives to the graphics it saves, we could use the following code :

```
report.set('mediaPrefix', 'plot_')
```

With this piece of code we set the name prefix of the plots that are being saved to `'plot_'`. It

can be utilized to set and get, with the get function, all of the parameters in `setting.dat`.

2.3 Title page and TOC

Like in the most cases we would want to add a title page to our document, we will do this in the following lines of code. The title, author and date will be displayed with the corresponding settings from the setting file. We can also add a table of contents.

```
report.addTitlePage
report.addTableOfContents
```

2.4 Paragraphs

All of these paragraphs in this documentation were added using the paragraph function, you can choose if you want to add the paragraph by writing it whole as a string in MATLAB and passing it to the function or using the `myTextBlocks.tex` file from which we can import any latex code or text and use it in our documents just by passing the TAG to the paragraph function. An example for adding a short sentence would be :

```
report.addParagraph('This is an example sentence')
```

This is an example sentence

2.5 Headings

There are several types of headings which can be added :

- part
- chapter
- section
- subsection
- subsubsection

Using one of these heading types we can structure our document much better and provide a better overview, since without them, the table of contents would be useless. The following code was used to create the heading for this current section in this document :

```
report.addHeading('section', 'Headings')
```

2.6 Lists

There are two types of lists you can generate through MATLAB :

- itemize
- enumerate
- description

This list was created with the following code :

```
report.addList('itemize', {'itemize','enumerate','description'});
```

We can see that it is fairly easy and quick to add a MATLAB cell array of strings and make a pretty list in your document. The following examples show that nested lists are also possible, the code that was used to make these can be found in the `reportDocu.m` file under LISTS.

- Item 1
 - 1. Enum 1
 - 2. Enum2
 - 3. Enum3

- Item 2
 - Item 2.1
 - Item 2.2

- Item 3

Definition 1 : Text 1

Definition 2 : Text2 Some more text

2.7 Tabular and table

Tables can be created directly from MATLAB arrays, following example shows a simple table containing the values from an array with random values. The following code was executed.

```
arr = randi(10,[2,3]);  
report.addTabular(arr);
```

5	5	6
5	4	6

All of the settings for the tables can be adjusted in the `setting.dat` file or through the `set` function as we will see in this section. Now we will demonstrate how to lable the rows and columns. We will do that by specifying the row and/or column labels as strings with collon separated labels as we can se in the following code.

```
row_labels = 'row1,row2';
col_labels = 'col1,col2,col3';

report.set('tableRowLabels', row_labels);
report.set('tableColLabels', col_labels);
report.set('tableColumnAlignment','lccc');
%report.set('dataFormat','%.1f')

report.addTabular(arr);
```

	col1	col2	col3
row1	5	5	6
row2	5	4	6

The following example shows that we can also pass data with Not a Number fields, the corresponding parameter in the `setting.dat` file has to be set appropriate, by default it is set to `nan`. We will also demonstrate how `booktabs` and `formatting` for a new table.