SYNCOTEK
Hardware Solution Provider

Room 716, Yiben E-Commerce
and Industrial Park, Chaguang Road
Nanshan District, Shenzhen, China
Post Code: 518055

Tel: +86-755-82706901
Fax: +86-755-82706900
Email: sales@syncotek.com
Http://www.syncotek.com

Card Issuing Machine

Model: SK-AD3



Overview:

SK-AD3 card issuing machine supports IC/RF card R/W and issuing/collecting functions, which is primarily applicable to self-service terminal equipments such as parking lot management system, expressway toll gate, self-service charging system, self-service card vending terminal, and electricity bill payment system.

Features:

* Supports ISO7816-2 contact type IC card reading/writing
* Supports ISO14443-A contactless Type A/B card reading/writing
* Unique dispensing wheel design: is capable of issuing various embossing cards accurately
* Automatic internal adjustment: ensures accurate issuing cards of different thicknesses
* Multi functions in one device: provide IC/RF card reading/writing, issuing/collecting functions and effectively saves space for the complete machine
* Rear card capture box: provides convenience for card management
* Simple collection channel design: satisfies user requirement for large collection amount
* Multiple sensors: are able to judge the card position and indicate the card status
* Scientific card transfer wheel design: automatically avoids dust accumulation which will lead to slippage
*High-strength wearable plastic channel: is adopted to reduce the risk of metal shielding and increase the success rate of RF card reading/writing

Room 716, Yiben E-Commerce
and Industrial Park, Chaguang Road
Nanshan District, Shenzhen, China
Post Code: 518055

Tel: +86-755-82706901
Fax: +86-755-82706900
Email: sales@syncotek.com
Http://www.syncotek.com

* Multiple levels of sensor circuit protection: prevents optical interference
* PCSC protocol: is available

Specification:

Communication Method	USB (PC/SC)/ RS232 (optional)	
Operating Conditions	Power Supply	DC24V±5%, 2.5A
	Quiescent Current	200mA
	Default Baud Rate	9600BPS/sec.
Card Stacker Capacity	175 pcs (0.76mm standard card)	
	130 pcs (0.76mm embossing card)	
	350 pcs (0.4mm thickness)	
Capture Box Capacity	25 pcs (0.76mm standard card)	
Capture Box Capacity	25 pcs (0.76mm standard card)	
Service Life	Issuing Life	1,000,000 passes min.
	IC Contact	500,000 passes min.
Operation Temperature / Humidity	0°C to 50°C, 0 to 90% RH without condensation	
Storage Temperature / Humidity	-25°C to 80°C, 0 to 90% RH without condensation	
Net Weight	Approx. 1.6KG (excluding accessories and package)	
Dimension	233L x 69W x 200H mm	