From Black Box to Transparent Diagnosis: The Role of Explainable AI for Predictive Diagnostics in Healthcare

Ibtasam Ur Rehman* Jibran K. Yousafzai† Abdulraqeb Alhammadi‡
*The Millennium Universal College TMUC, Islamabad, Pakistan
†Faculty of Artificial Intelligence, University of Technology Malaysia
‡College of Engineering and Applied Sciences, American University of Kuwait

***Abstract*—This paper explains systematic review of evolution and integration of Artificial Intelligence in healthcare with focused analysis on explainable models, personalized treatment and its challenges of clinical implementation. We also explore range of machine learning and deep learning technologies including Convolutional Neural Networks, Transformers and ensemble methods that are applied across diverse medical domains such as cardiology, neurology, oncology and medical imaging. The review synthesizes findings from numerous studies highlighting models that achieve diagnostic accuracies often exceeding 95-99% for tasks like brain tumor classification, skin disease detection and cardiovascular risk prediction. A critical emphasis is placed on Explainable AI techniques such as SHAP and LIME which are essential for building clinical trust by providing transparency in AI driven decisions. The paper further examines pivotal role of AI in enabling early disease detection and personalized medicine while also addressing significant challenges related to data privacy algorithmic bias, ethical frameworks and the practical hurdles of deploying these technologies in real world clinical settings including underserved regions.**

***Index Terms*—Artificial Intelligence, Explainable AI (XAI), Medical Diagnostics, Personalized Treatment, Machine Learning, Deep Learning, Clinical Implementation, Medical Imaging Analysis**

I. Introduction

A. Motivation and Challenges for AI in Healthcare

The integration of Artificial Intelligence in healthcare represents paradigm shift with the potential to address challenges that plague current systems. Traditional healthcare relies on the symptomatic presentation at advanced stages and "one-size-fits-all" treatment models that fail to account for individual patient variations. AI offers solutions by enabling early detection through sophisticated pattern recognition, facilitating personalized treatment plans and expanding healthcare access via automated tools. The COVID-19 pandemic further accelerated AI's adoption demonstrating its critical utility in rapid diagnosis and remote patient monitoring during global crises [1, 2].

AI has lot of potential to change healthcare but there are still a lot of big problems that need to be solved. A significant problem is late diagnosis; diseases that can kill you like Alzheimer's and heart disease are often found only when they are very advanced which makes it hard to treat and manage them well [3, 4]. The one-size-fits-all approach to treatment is another problem that keeps coming up. Standardized medical protocols frequently neglect individual variations in genetics, lifestyle, and pre-existing health conditions, potentially resulting in inconsistent or suboptimal treatment outcomes. Healthcare disparities also keep making access to and quality of care very unequal across different regions and socioeconomic groups. Another big problem is that diagnostic tests don't always work. Human factors, including fatigue, cognitive bias, and subjective judgment, can cause differences in how medical tests and images are read, which can sometimes lead to mistakes in diagnosis. The main reason why people are interested in AI is because it could help solve these big problems, making it possible to find problems earlier, get more personalized care, and make the healthcare system fairer and more accurate for everyone.

B. Scope of the Survey and Contributions

This review looks at how Artificial Intelligence in healthcare has changed over time and where it is now, with a focus on how it is changing clinical practice. It focuses on three main areas: (1) using Explainable AI (XAI) to make clinical decision-making more open and trustworthy, (2) using machine learning to make personalized treatment plans, and (3) the problems that come up when AI systems are used in real-world healthcare settings. The survey includes views from cardiology, neurology, oncology, and medical imaging, and it looks at the ethical, regulatory, and technical problems that need to be solved to make AI safe and successful. The principal contributions of this study include a systematic assessment of AI architectures, a performance comparison, and a compilation of evidence-based recommendations to bridge the gap between algorithm development and clinical implementation.

The rest of this paper is set up like this. Section II gives a general idea of some basic AI ideas in healthcare, such as machine learning, deep learning, and explainable AI. Section III provides an extensive examination of AI technologies and their methodologies within diverse medical fields. Section IV looks at personalized treatment plans and clinical decision support systems that are powered by AI. In Section V, we talk about

the new field of mobile health (mHealth) and where research should go in the future. Lastly, Section VI sums up the main points and gives some final thoughts.

II. Background

A. Overview of AI in Healthcare

Alhejaily et al.[5] assert that Artificial Intelligence is transforming the healthcare sector by enhancing the quality of medical services. This is especially true in diagnostics, where AI systems are getting more and more accurate, just like human experts. The authors emphasize that despite the remarkable advancements facilitated by digitized health data, significant challenges remain in the realms of data privacy, ethics, and regulatory compliance. Shaheen et al. [6] also talk about how AI could help with big problems in modern healthcare, like rising costs and not enough workers. AI helps with drug discovery, clinical trials, and patient management, which makes healthcare systems work better and last longer. Figure 1 shows that AI is having a bigger and more varied effect on important parts of healthcare. These include better access to medical care, a better chance of getting better, and more accurate diagnostic tools. Other uses include safe identity verification, automated image-based diagnostics, help with robot-assisted operations, personalized treatments for rare diseases, and chatbots that let patients talk to their doctors and get better service. Each spoke in the picture shows a basic area where AI algorithms and technologies are making medical care more efficient, accurate, and easy to get.



Fig. 1: AI systems in healthcare.

B. Machine Learning, Deep Learning and Explainable AI in Healthcare

Machine learning and deep learning are changing healthcare by speeding up the discovery of new drugs, making clinical trials better, and improving diagnoses, especially when it comes to looking at medical images. But doctors and nurses can't use complicated models like DL in their work because they don't know how decisions are made. To build trust and make things clear, explainable AI is now necessary. There are many ways that XAI methods make things easier to understand: SHAP (SHapley Additive exPlanations) uses cooperative game theory to find out how much each feature adds to each prediction. LIME (Local Interpretable Model-agnostic Explanations) makes explanations that are accurate in a small area by changing input samples and watching how the output changes. Grad-CAM makes heatmaps that show the parts of medical images that had an effect on a model's diagnosis. These methods work together to make sure that AI systems don't look for false correlations and instead look for data and patterns that are important to medicine. Combining ML, DL, and XAI is necessary to make AI tools for patient care that are reliable, efficient, and clinically valid. [7, 8]. Figure 1 shows in great detail how AI systems are being put into healthcare and how they are being improved. The first steps in this process are to get healthcare data, prepare it, and clean it. After that, feature extraction and engineering are done well. Once the data is ready, an AI/ML model, such as a CNN, RNN, or Transformer, is trained and then carefully tested and checked. The training loop keeps going until the performance is good enough. Then, the verified model is used in the clinical workflow as an AI decision support system. The procedure ends with keeping an eye on clinical results, getting feedback, and retraining the model to make sure it stays accurate and useful in a healthcare setting that is always changing.

III. AI Technologies in Healthcare

A. Fundamental AI Algorithms and Architectures

1) Machine Learning Algorithms for Healthcare: Traditional ML algorithms continue to have important role in healthcare applications particularly when dealing with structured clinical data, electronic health records and predictive modeling tasks where interpretability is crucial. These algorithms offer computational efficiency, transparency and efficient performance across different medical domains.

Logistic Regression & Support Vector Machines: These models are valued in medicine for their distinct strengths as logistic Regression is used for clinical risk prediction and diagnostic models such as predicting heart disease risk from clinical parameters due to its transparency and the interpretable odds ratios it provides. The logistic function is:

$$P = \frac{1}{1 + e^{-(\beta_0 + \beta_1 X_1 + \cdots + \beta_n X_n)}} \tag{1}$$

Support Vector Machines are effective for high dimensional data utilizing kernel trick to handle complex boundaries which

make them strong performers in tasks which include cancer subtype classification or medical image analysis. The SVM decision function is:

$$f(x) = \text{sign}\left(\sum_{i=1}^{n} \alpha_i y_i K(x_i, x) + b\right) \tag{2}$$

where $K(x_i, x)$ is the kernel function that enables nonlinear classification.

Random Forests and ensemble methods like **Gradient Boosting Machines e.g. XGBoost, LightGBM)** has shown strong performance in various healthcare prediction tasks. These algorithms handle high dimensional data effectively and they can capture complex non linear relationship while providing feature importance rankings furthermore Random Forest prediction is the average of individual decision trees:

$$\hat{y} = \frac{1}{B}\sum_{b=1}^{B} T_b(x) \tag{3}$$

where B is number of trees and $T_b(x)$ is prediction of b-th tree. Gradient Boosting builds models sequentially:

$$F_m(x) = F_{m-1}(x) + \gamma_m h_m(x) \tag{4}$$

where $h_m(x)$ is weak learner and γ_m is step size. Studies has applied these methods for disease classification or patient outcome forecasting with accuracies often exceeding 85%. Their robustness to missing data and ability to handle mixed data types make them suitable for real world clinical datasets.

k-Nearest Neighbors (k-NN) & Decision Trees: Both algorithms are preffered in healthcare for their interpretability especially with in limited data. k-NN serves as simple intuitive algorithm for pattern recognition tasks like patient similarity analysis and disease subtype classification though it can be intensive for large datasets. The classification is based on majority voting:

$$\hat{y} = \text{mode}\{y_i : i \in \mathcal{N}_k(x)\} \tag{5}$$

where $\mathcal{N}_k(x)$ are k nearest training samples to x. Decision Trees gives transparent decision making processes making them valuable for clinical guideline implementation and treatment pathway analysis. The tree splits data using feature thresholds to maximize information gain:

$$\text{IG} = H(S) - \sum_{i \in \{L,R\}} \frac{|S_i|}{|S|} H(S_i) \tag{6}$$

where $H(S)$ is the entropy of set S.

2) Deep Learning Algorithms for Medical Applications: Deep learning algorithms has transformed medical data analysis by enabling automated feature extraction and hierarchical representation learning from complex datasets. Traditional machine learning methods that rely on custom features however DL models learn directly from raw medical data such as images, signals and electronic health records. The following architectures are among the most widely used in healthcare research and applications.

Convolutional and Recurrent Neural Networks (CNNs & RNNs): CNNs and RNNs shows two neural network architectures for processing different types of medical data as CNNs are used for tasks such as disease detection, segmentation or classification in medical imaging. The convolution operation is defined as:

$$(F * K)(i, j) = \sum_m \sum_n F(i - m, j - n) K(m, n) \tag{7}$$

where F is input image and K is filter kernel. RNNs are designed to process sequential or temporal data by maintaining their hidden states:

$$h_t = \sigma(W_{xh} x_t + W_{hh} h_{t-1} + b_h) \tag{8}$$

where h_t is hidden state at time t, x_t is input and σ is activation function. CNNs capture spatial hierarchies in 2D and 3D data making them suitable for analyzing X-rays, MRI and CT scans however RNNs handles dependencies across time steps enabling effective modeling of physiological signals such as ECG and EEG for patient monitoring and disease progression analysis.

LSTM & Autoencoders: Long Short Term Memory networks and Autoencoders are neural architectures which are used for handling complex patterns in medical data. LSTMs extend RNNs with gating mechanisms:

$$\begin{aligned} f_t &= \sigma(W_f \cdot [h_{t-1}, x_t] + b_f) \\ C_t &= f_t * C_{t-1} + i_t * \tanh(W_C \cdot [h_{t-1}, x_t] + b_C) \\ h_t &= o_t * \tanh(C_t) \end{aligned} \tag{9}$$

where f_t, i_t, o_t are gates and C_t is cell state and Autoencoders learn compressed representations:

$$z = \sigma(W_e x + b_e), \quad \hat{x} = \sigma(W_d z + b_d) \tag{10}$$

where z is latent representation. LSTMs excel learning long term dependencies for clinical time series while Autoencoders are used for medical image denoising and anomaly detection.

U-Net & ResNet: U-Net and ResNet are convolutional neural network architectures with distinct strengths in medical imaging and U-Net uses symmetric encoder decoder structure with skip connections:

$$x_{\text{decoder}}^{(l)} = \text{Conv}(\text{Concat}[x_{\text{encoder}}^{(L-l)}, \text{Up}(x_{\text{decoder}}^{(l-1)})]) \tag{11}$$

where skip connections concatenate encoder features $x_{\text{encoder}}^{(L-l)}$ with upsampled decoder features. ResNet introduces residual connections that enable training of deep architectures:

$$y = \mathcal{F}(x, \{W_i\}) + x \tag{12}$$

where $\mathcal{F}$ shows residual mapping and x is identity shortcut. U-Net design enables precise localization through skip connections making it effective for segmenting organs, tissues and tumors. ResNet residual connections prevent vanishing gradients allowing feature reuse across layers to enhance stability and accuracy in disease classification and lesion detection tasks.

Vision Transformers (ViTs): Vision Transformers utilize self-attention mechanisms to model long range dependencies within image data by treating images as the sequences of patches and the core self attention mechanism is as follows:

$$\text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right)V \tag{13}$$

where Q, K and V are queries, keys and values derived from image patches and d_k is dimension of the keys. This enables ViTs to capture global contextual relationships effectively and in healthcare domain ViTs have shown strong performance in medical image classification or segmentation tasks which is offering enhanced interpretability and comparative overview of these key algorithms.

3) Hybrid and Ensemble Approaches: Hybrid and ensemble approaches combine multiple algorithms to enhance accuracy and generalization in healthcare applications and they are especially effective for heterogeneous medical datasets where single model may miss key patterns, leveraging complementary features and decision strategies from traditional and deep learning methods.

Graph Neural Networks with Transformers combines relational reasoning capabilities of GNNs with powerful attention mechanisms of transformers. The core attention mechanism is defined as:

$$\text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right)V \tag{14}$$

where queries Q, keys K and values V are derived from node features in graph as these hybrids excel in analyzing complex medical relationships such as drug-drug interactions, protein-protein networks by capturing both local neighborhood information through graph connectivity and global dependencies through self attention enabling more accurate predictions in biomedical network analysis and healthcare knowledge graphs.

Autoencoder Random Forest ensembles use feature learning capabilities of autoencoders with interpretability and robustness of random forests as these autoencoder learns compressed representations through:

$$z = f_e(x) = \sigma(W_e x + b_e) \tag{15}$$

where z is latent representation of input x and the compressed representation is then fed into random forests for classification:

$$\hat{y} = \frac{1}{B}\sum_{b=1}^{B} T_b(z) \tag{16}$$

where B is number of trees and $T_b(z)$ is prediction of b-th tree. This approach has shown success in medical image classification or electronic health record processing where both feature reduction and interpretable decision making are crucial.

Multi-modal Fusion Networks integrate information from multiple data sources such as medical images, clinical notes or lab results and these architectures use separate encoders for each modality:

$$\begin{aligned} z_{\text{img}} &= f_{\text{img}}(x_{\text{image}}) \\ z_{\text{text}} &= f_{\text{text}}(x_{\text{clinical}}) \\ z_{\text{lab}} &= f_{\text{lab}}(x_{\text{lab}}) \end{aligned} \tag{17}$$

followed by fusion mechanisms to combine complementary information:

$$z_{\text{fused}} = \begin{cases} f_{\text{early}}(x_{\text{img}}, x_{\text{text}}, x_{\text{lab}}) & \text{(early fusion)} \\ f_{\text{intermediate}}(z_{\text{img}}, z_{\text{text}}, z_{\text{lab}}) & \text{(intermediate fusion)} \\ f_{\text{late}}(y_{\text{img}}, y_{\text{text}}, y_{\text{lab}}) & \text{(late fusion)} \end{cases} \tag{18}$$

This include comprehensive patient profiling, multi parameter diagnostic systems and personalized treatment recommendation engines that consider all available patient data.

Ensemble of Deep Learning Models combine predictions from multiple deep learning architectures e.g. CNN, ViT or ResNet through voting averaging approaches and the ensemble prediction is typically computed as:

$$\hat{y} = \frac{1}{N}\sum_{i=1}^{N} f_i(x) \tag{19}$$

where f_i represent different deep learning models and N is number of models. For weighted averaging:

$$\hat{y} = \sum_{i=1}^{N} w_i f_i(x), \quad \sum_{i=1}^{N} w_i = 1 \tag{20}$$

These ensembles mitigate individual model biases and variances which is leading to more reliable and robust predictions and in medical imaging diagnostics these methods have demonstrated strong performance compared to the single models particularly for rare diseases where diagnostic

TABLE I: Comparison of Traditional and Deep Learning Algorithms in Healthcare

Algorithm	Key Strengths	Common Healthcare Applications
Machine Learning Algorithms		
LR	Interpretable, strong statistical basis	Clinical risk prediction, diagnostic models
RF	Handles high dimensional data, robust, feature importance	Disease classification, outcome forecasting
GB	High accuracy, models complex patterns	Patient outcome prediction
SVM	Effective for high dimensional data, complex boundaries	Medical image analysis, cancer subtype classification
k-NN	Simple, intuitive, good for pattern recognition	Patient similarity analysis, disease subtype classification
DT	Transparent, easily interpretable, simple validation	Clinical guidelines, patient stratification
Deep Learning Algorithm		
CNN	Captures spatial hierarchies, strong in image feature extraction	Medical image classification, disease detection
RNN	Models sequential dependencies in temporal data	ECG/EEG analysis, patient monitoring
LSTM	Learns long-term dependencies, handles vanishing gradients	Outcome prediction, clinical time series forecasting
U-Net	Encoder–decoder with skip connections, precise localization	Tumor boundary detection
ResNet	Skip connections enable deeper networks and stability	Disease classification, lesion detection
Autoencoder	Unsupervised feature learning, data reconstruction	Anomaly detection, image denoising
ViT	Uses self attention for global feature learning	Histopathology, radiology, medical image classification
Hybrid and Esemble Algorithm		
CNN-RNN	Combines spatial and temporal analysis capabilities	Cardiac MRI analysis, video based surgical analytics
GNN-Transformer	Integrates relational reasoning with attention mechanisms	Drug interaction prediction, biomedical network analysis
Autoencoder-RF	Feature learning with interpretable decision making	Genomic data analysis, EHR processing
Multi modal Fusion	Integrates diverse data sources comprehensively	Personalized treatment, multi parameter diagnostics
DL Ensemble	Mitigates individual model biases, improves robustness	Medical imaging diagnostics, rare disease detection
Neuro-Symbolic AI	Combines pattern recognition with logical reasoning	Clinical decision support

Note: LR = Logistic Regression; RF = Random Forests; GB = Gradient Boosting; SVM = Support Vector Machines; k-NN = k-Nearest Neighbors; DT = Decision Trees; CNN = Convolutional Neural Network; RNN = Recurrent Neural Network; LSTM = Long Short-Term Memory; U-Net = U-shaped Network; ResNet = Residual Network; ViT = Vision Transformer; GNN = Graph Neural Network; EHR = Electronic Health Record; DL = Deep Learning.

certainty is critical.

Overall deep learning and hybrid architectures enable intelligent healthcare systems for early detection and personalized treatment. Table I compares these key algorithms.

B. AI Applications in Healthcare Domains

1) Cardiovascular Diseases: Many studies have explored the use of machine learning for predicting cardiovascular diseases. Thenmozhi and Deepika [9] proposed a heart disease prediction system leveraging various decision tree classifiers, including ID3, C4.5, C5.0, and J48, applied to clinical data. They analyzed multiple attribute selection metrics such as Information Gain, Gain Ratio, and Gini Index, and used pruning techniques to improve model efficiency. Their results showed that the J48 decision tree achieved 99.62% accuracy with 15 features, while the Maximal Frequent Itemset Algorithm combined with C4.5 obtained 0.82% precision, 0.92% recall, and 92% accuracy.Sanchula et al. [10] evaluated different models for cardiac disease prediction and found that the Support Vector Machine (SVM) achieved an accuracy of 95.34%, with age, cholesterol, and maximum heart rate identified as key predictors. In a large-scale study, Bilal et al. [11] developed an explainable AI (XAI) system using clinical and lifestyle data from over 300,000 patients, achieving 91.94% accuracy with LightGBM and XGBoost models. Similarly, Yaseen and Rashid [12] reported that XGBoost outperformed other models with 92% accuracy and an AUC-ROC of 0.93, highlighting chest pain type and ST depression as significant predictors.Olawade et al. [13] introduced a coronary artery disease prediction pipeline that employed Bald Eagle Search Optimization for feature selection. Their Random Forest model achieved 92% accuracy, identifying variables such as typical chest discomfort, ST elevation, and ejection fraction as crucial features. Kiran et al. [14] proposed a cardiovascular disease prediction system that combined a highly accurate Random Forest model (98% accuracy) with both global SHAP and local LIME interpretability, allowing clinicians to understand overall patterns as well as individual patient predictions.Adhaileh et al. [15] compared multiple machine learning techniques, including K-Nearest Neighbors (KNN), Random Forest, and

SVM, for predicting and classifying heart attacks. KNN achieved the highest accuracy of 92%, outperforming RF (84%) and SVM. Garg et al. (2025) developed a smart healthcare system for early heart attack prediction using classifiers such as Naive Bayes, Decision Table, J48, and Random Forest, with Random Forest achieving the highest accuracy of 99.89%. Finally, Mishra et al. [16] developed a heart failure prediction model using CatBoost, Logistic Regression, and KNN, evaluating performance through F1-score and ROC curve analysis.

Aashish et al. developed a machine learning model to forecast heart disease utilizing clinical and demographic data [17]. They employed algorithms such as Decision Tree, KNN, Naive Bayes, XGBoost, and Random Forest on a Kaggle dataset, determining that XGBoost exhibited the highest accuracy at 93%. Alsabhan and Alfadhly [18] evaluated 12 machine learning models for forecasting heart disease. The Gradient Boosting Machine has the best accuracy at 90.20%. CatBoost is next at 89.71% and LightGBM is last at 88.73%. It was suggested to use a preprocessed Cleveland dataset to predict heart disease using a method based on machine learning. The process included normalizing the data and finding 11 important clinical parameters. Age and sex were left out on purpose so that the focus could be on more relevant medical indicators. Five classifiers—Support Vector Machine, Gaussian Naïve Bayes, Decision Trees, Artificial Neural Network, and Logistic Regression—were employed to assess their predictive efficacy. Sondos Jameel [19] conducted this evaluation, providing insights into the comparative efficacy of these classification techniques. The Author [20] investigated the relative impacts of WEKA and Google Colab (Scikit-Learn) on the precision of heart disease prediction classifiers. The hyperparameters for Logistic Regression, KNN, SVM, Naïve Bayes, and Decision Tree were all the same. They discovered that WEKA consistently exhibited significantly superior accuracies (e.g., SVM and Logistic Regression at 90.67%) compared to Scikit-Learn (e.g., SVM at 76.58%). This shows how important it is to pick the right computer platform for the performance of machine learning models.

2) Neurological Disorders and Brain Analysis: Saimon et al. [21] discovered that Gradient Boosting was the most Several studies have investigated machine learning methods for early detection and prediction of neurological disorders. An effective approach for early Parkinson's disease detection achieved an accuracy of 89%, while K-Nearest Neighbors (KNN) attained 85% accuracy in identifying epilepsy using EEG data. Adebimpe O. Esan [22] developed a Random Forest model that predicted Parkinson's disease with 93% accuracy using clinical and demographic data and applied XAI techniques like SHAP to provide clinicians with interpretable insights into the model's predictions.In the domain of meningitis, Li et al. [23] developed a clinical prediction model to determine which septic neonates were at risk of developing purulent meningitis. Using logistic regression on data from 535 septic neonates, the model identified significant risk factors and achieved an AUC of 0.765, offering a valuable tool for early risk assessment. Similarly, Lin et al. [24] employed LASSO regression to differentiate cryptococcal meningitis from tuberculous meningitis. Their model, based on six critical features including CSF pressure and India ink staining, achieved AUCs of 0.919–0.921 in both training and validation cohorts.Chen et al. [25] created a model to predict short-term adverse outcomes in newborns with bacterial meningitis using data from 433 full-term neonates and 32 clinical variables. Among nine algorithms tested, logistic regression performed best, achieving 89.0% accuracy and an AUC of 0.908. The model highlighted muscle tone abnormalities, seizures, and elevated CSF protein levels as the most important predictors. Additionally, Sun et al. developed a logistic regression-based nomogram for predicting purulent meningitis in 201 very preterm infants (gestational age < 32 weeks), identifying low birth weight, elevated procalcitonin, cesarean delivery, and premature membrane rupture as significant factors, with a C-index of 0.849.Deep learning has also shown promise in neuroimaging tasks. Dorfner et al. (2025) discussed the use of Convolutional Neural Network (CNN) architectures, including U-Net and ResNet, for tumor classification and segmentation using multi-parametric MRI sequences (T1, T2, FLAIR). Their models extracted features directly from the images to predict genetic biomarkers such as IDH mutation status, achieving 78.8% accuracy on an internal test set and 93.8% on an external test set. However, prediction of MGMT promoter methylation proved more challenging, with a recent top-performing model achieving a suboptimal AUROC of 0.62, highlighting limitations for reliable clinical use.Mohamed S. Elhadidy et al. [26] conducted a comparative study of deep learning models for multiclass brain tumor classification using MRI data, evaluating CNN, Swin Transformer, and EfficientNet on four categories: glioma, meningioma, pituitary tumors, and healthy brains. EfficientNet achieved the highest test accuracy of 98.72%, followed closely by Swin Transformer at 98.08%, both outperforming standard CNNs. Muhammad Naufal Erza Farandi et al. [27] similarly evaluated CNN architectures, including VGG16, ResNet50, and U-Net, on a public MRI dataset. ResNet50 demonstrated the best performance with an average accuracy of 95.35%, VGG16 achieved 93.93%, and U-Net, designed for segmentation rather than classification, showed lower performance at 79%, emphasizing the importance of selecting an appropriate architecture for the task.

Several studies have developed advanced deep learning and hybrid models for brain tumor classification and segmentation using MRI datasets. Md. Nahiduzzaman et al. [28] proposed a hybrid explainable framework that combined a lightweight Parallel Depthwise Separable CNN (PDSCNN) for feature extraction with a Hybrid Ridge Regression Extreme Learning Machine (RRELM) for classification. Using a dataset of 7,023 MRI images across four categories (glioma, meningioma, pituitary, and no tumor), their model achieved an impressive average accuracy of 99.22%, precision of 99.35%, and recall of 99.30%, outperforming other state-of-the-art methods while requiring fewer parameters and employing five fold cross validation.Khalid M. Hosny et al. [29] developed an explainable ensemble deep learning

model for brain tumor detection using the Figshare MRI dataset (3,064 images, three tumor types). Their ensemble of pretrained models (DenseNet121 and InceptionV3) with transfer learning achieved 99.02% accuracy, 98.75% precision, 98.98% recall, and an F1-score of 98.86%, outperforming both single pretrained models and other recent approaches. Similarly, Mohsen Asghari Ilani et al. [30] evaluated multiple architectures including U-Net, a 3-layer CNN, and transfer learning models (InceptionV3, EfficientNetB4, VGG19) on the Figshare dataset. Their U-Net-based model achieved the highest performance with 98.56% accuracy, perfect F1-score, precision, recall (all 99%), and an AUC of 99.8%, demonstrating superior brain tumor classification capability.Ercument Guvenç et al. [31] developed a deep learning system for tumor segmentation using the BRaTS2018 dataset. They employed a Deep Convolutional GAN (DCGAN) to generate synthetic FLAIR MRI images and used K-means clustering for automated labeling, producing an augmented dataset of 782 images. Testing five deep learning models (U-Net, ResUNet, ResNet50, VGG16, VGG19) on the augmented dataset, ResNet50 achieved the best performance, with accuracy increasing from 98.99% to 99.26%, Dice coefficient from 57.33% to 81.32%, and IoU from 40.89% to 66.86%.Syed Sajid Hussain et al. [32] proposed a multitask learning framework for automated segmentation and classification of brain tumors. They developed and tested three advanced architectures: U-Net, Attention U-Net, and Residual Attention U-Net. Their framework achieved 93.35% accuracy for segmentation and 99.40% for binary classification, with precision and recall of 98.60% and 98.06%, respectively. Key innovations included residual connections to facilitate training and attention gates to focus on tumor morphology by leveraging multi-scale features from the encoder, bridge, and decoder. The models were trained and validated on both a real-time clinical dataset and the public Figshare repository.

3) Oncology and Cancer Diagnosis: Numerous studies have employed machine learning techniques for breast cancer diagnosis and prognosis. La Moglia et al. [33] evaluated eight classifiers, including Logistic Regression, Random Forest, Extra Trees, XGBoost, LightGBM, CatBoost, SVC, and Gaussian Naïve Bayes, on a breast cancer dataset with 11 clinical features. Logistic Regression achieved the highest testing accuracy of 91.67% without feature selection. After feature selection identified Tumor Size, Age, Metastasis, and Inv-Nodes as key predictors, LightGBM improved to 90.74% accuracy. Almarri et al. [34] analyzed multiple classifiers on the Wisconsin Diagnostic Breast Cancer dataset with 30 nuclear features. Random Forest achieved the highest accuracy of 92.56%, which was further improved to 92.64% through feature selection and hyperparameter tuning. Montazeri et al. [35] predicted breast cancer survival using Random Forest, SVM, and Multilayer Perceptron on a dataset of 900 patients, with Random Forest achieving 96% accuracy, 96% sensitivity, and an AUC of 93%. Qian et al. [36] developed a multimodal AI system for breast cancer risk stratification, integrating clinical data with mammography and ultrasound images from over 5,000 patients. Their model performed comparably to radiologists, achieving 90.1% accuracy in prospective testing. Cakmak and Pacal [37] compared seven classifiers on the Wisconsin dataset, finding that SVM achieved the highest accuracy of 97.66%. Other studies also highlight the effectiveness of feature optimization and ensemble methods. Moglia et al. [38] showed that feature selection improved LightGBM performance, while Naji et al. [39] found SVM to be most effective in distinguishing benign from malignant tumors. Tarawneh et al. [40] and Sumbaly et al. [41] used decision tree algorithms, achieving accuracies up to 93.56% with proper preprocessing and feature selection. Garba and Hamza [42] reported 97% accuracy using Logistic Regression while maintaining computational efficiency. Duan et al. [43] leveraged transcriptomic data and Random Forest to predict distant metastasis with 93.6% accuracy and 91.3% AUC. Asaye et al. [44] found KNN to perform best (98.4% accuracy, recall 1.0) among four classifiers, followed by Random Forest. Rawal and Ramik [45] concluded that Random Forest and SVM were the most reliable classifiers with feature selection and cross-validation, while k-NN offered the fastest training times.

4) Dermatology and Skin Diseases: Machine learning has also been widely applied to skin disease diagnosis. Zhen Yu et al. [46] proposed a Hierarchical Prototypical Decision Tree (HPDT) that combines deep learning-derived image embeddings with prototypical networks and a decision tree structure. Tested on 235,268 dermoscopic images, HPDT achieved 60.87% accuracy and an 81.56 hierarchical F1 score, while reducing the clinical severity of misclassifications. Fatima Maan et al. developed ensemble models to classify five pediatric skin conditions using 4,141 images. Their best Stacking ensemble, combining ResNet50 and Logistic Regression, achieved 96% accuracy, leveraging transfer learning to address the limited dataset. Almustafa et al. [47] evaluated six classifiers for multi-class skin disease classification, with Logistic Regression and SGD achieving over 98% accuracy after feature selection highlighted clinically relevant attributes like erythema and pruritus. Yang and Luo et al. [48] reviewed conventional ML (KNN, SVM, decision trees) and deep learning approaches (CNNs, transformers, ensembles), noting deep learning models can reach dermatologist-level performance with accuracies exceeding 98%. Verma and Kumar [49] developed a hybrid ensemble machine learning (HEML) model that combined image preprocessing techniques (morphological filtering, DWT, GLCM) with 15 weak learners from Decision Tree, KNN, and SVM classifiers. HEML achieved 95.50% accuracy, outperforming individual classifiers. Mohammed et al. [50] conducted a comprehensive survey showing image-based skin disease methods vary widely in accuracy (50–100%), while tissue-based feature methods consistently reached 94%. Ahammed et al. [51] classified eight skin disorders using

KNN, SVM, and Decision Tree, with SVM achieving 95% accuracy on ISIC 2019 and 97% on HAM10000 datasets. Bordoloi [52] reported that SVM was the most accurate classifier (98.8%), while KNN showed the highest sensitivity (91%) and specificity (99%).

5) Ophthalmology and Vision Disorders: Gao et al. [53] aimed to improve the diagnosis and categorization of cataracts by the application of artificial intelligence utilizing Fundus Images. They got 1340 fundus images, however they created a dual stream cataract evaluation network (DCEN) to sort and rate cataracts. They used deep learning methods, especially ResNet models, to train and test the DCEN model. The DCEN was very good at both classifying cataracts and grading their severity. It had high accuracy, sensitivity, F1 score, and kappa coefficient. The model works with an accuracy of 97.62% in general. Junayed et al. [54] have utilized deep learning to observe cataracts through fundus imaging. For training and testing, they use a number of datasets, including HRF, FIRE, ACHIKO-I, and IDRiD. The algorithm for finding cataracts is called Convolution Neural Networks (CNN), although they suggested the moniker Cataract-Net for the model. We evaluate the performance of the suggested CataractNet with five pre-trained CNN models under different dataset splitting conditions. CataractNet is better than the other models in terms of accuracy and other evaluation measures, and it also takes less time to run. Khalaf et al. [55] investigated and conducted an experiment to categorize ophthalmic illnesses with YOLOv8. They also used fundus photographs from different sources, such as Robotflow, Kaggle, and medical clinics, and they made all of those images the same size, 224 by 224 pixels. There are 5887 images in total, and the dataset was split into two parts: training and testing. We chose YOLOv8n-cls (nano) because it is efficient, small, fast, and performs well. The model was trained on data that used certain settings, such as the ADAM optimizer, learning rate, batch size, weight decay, and 30 epochs. To get to the model, you need to employ a lot of different metrics, like accuracy, precision recall, and F1 score.

Rajhan et al. [56] created a smartphone app for detecting cataracts using a CNN, which was 98.79% accurate. The technology looks at pictures of the eyes taken with a mobile camera and tells users if they have cataracts and how bad they are. Vasan et al. [57] also made a mobile app that uses a CNN with 16 layers to find lens opacity and sort features. Yang et al. [58] utilized a back-propagation neural network on 504 ophthalmologist-labeled images, extracting luminance and texture features (Gray Co-Occurrence Matrix, Gray-Gradient Co-occurrence Matrix) for cataract classification, with performance assessed through ROC curves and confusion matrices. Ibtasam et al. [2] created the smartphone app Cortex Vision, which employs an SVM model with 95% accuracy to find cataracts in eye scans. This shows that AI-driven diagnostics might be available to everyone. Agarwal et al. [59] introduced a smartphone-based Android application for cataract detection, aimed at reducing time and expenses in comparison to conventional clinical approaches. The program employs machine learning (KNN, SVM, Nave Bayes) and image processing with the OpenCV package. The KNN model did better than SVM and Naïve Bayes, getting 83.07% accuracy. Behera et al. [60] show a structured model for finding nuclear cataracts using fundus retinal images. The model processes photos to create binary representations that focus on blood vessels. These blood vessels are used as the feature matrix for a Support Vector Machine (SVM) classifier. We tried out different SVM kernels, and the Radial Basis Function (RBF) had the best accuracy at 95.2%. The research determined that RBF-based SVM is proficient for real-time detection. Setiawan [61] created a mobile app that uses statistical texture analysis and K-Nearest-Neighbor (k-NN) classification to find cataracts. It solves the problem in rural Indonesia, where it is hard to go to an ophthalmologist and diagnostic tools. The study examined 160 ocular pictures employing pre-processing methods, including cropping and grayscale conversion, in conjunction with feature extraction utilizing the gray level co-occurrence matrix (GLCM). The results showed a precision of 97.5%, finding the best attributes, including differentiation, contrast, and uniformity. The best k value for k-NN was found to be 1.

6) Hepatology and Liver Diseases: Mutlu et al. [62] created a deep learning model for automatically predicting liver illness, which is an important use of medical data mining and predictive healthcare. The main goal was to compare how well Convolutional Neural Network works with classic machine learning methods like Naive Bayes, Support Vector Machine, K Nearest Neighbors (KNN), and Logistic Regression. The study included two distinct medical datasets for assessment: the BUPA liver diseases dataset and the ILPD (Indian Liver Patient Dataset). The authors stated that their suggested CNN model got 75.55% correct on the BUPA dataset and 72.00% correct on the ILPD dataset, showing that it worked well for this clinical prediction job. Hassan et al. [63] created a method that uses computers to help doctors figure out what kind of focused liver illness a patient has based on medical ultrasound scans. This system is in the field of medical computer vision. Their method used a deep learning architecture called Stacked Sparse Auto-Encoder to build high-level feature representations directly from picture pixels. The suggested system included preprocessing, liver lesion segmentation using level set and Fuzzy C-Means clustering, the SSAE for unsupervised feature learning, and finally the softmax layer for classification. When they tested it, their deep learning system had a very high overall classification accuracy of 97.2%. Manjunath et al. [64] introduced an innovative deep learning model for the detection and classification of liver tumors from CT scans, specifically differentiating between metastasis and cholangiocarcinoma. Their model exhibited great performance, attaining a high dice similarity coefficient of 98.59%, which signifies exceptional segmentation and classification accuracy in comparison to

previous techniques. Yang et al. (2023) created a two-section deep learning system (2S-NNet) to find nonalcoholic fatty liver disease in a Chinese community-based population using ultrasound pictures. Their model had great performance, with AUROCs of 0.90 for finding NAFLD and 0.93 for finding severe NAFLD. This was better than both one-section neural network models and standard fatty liver indices. Gupta et al. [65] created a model to predict liver disease using the Indian Liver Patient Dataset. They tested algorithms including Logistic Regression, Decision Trees, Random Forest, KNN, and boosting approaches. LightGBM was shown to be the best model, while Random Forest and LightGBM both had the best accuracy of 63%. Khaled [66] evaluated KNN, Gaussian Naive Bayes, and Random Forest using 32,000 patient records, with Random Forest attaining an accuracy of 97.3%. Zhu et al. [67] utilized ten algorithms to screen for Metabolic Dysfunction Associated Steatotic Liver Disease in 10,007 outpatients, determining that Logistic Regression was the most successful method (72.8% accuracy, AUC 0.806). Dash et al. [68] built an ensemble model using the best algorithms (SVM, Random Forest, Decision Tree, and XGBoost). It got 95.24% accuracy and a ROC value of 99.08%. Bwanya et al. [69] created a machine learning framework to forecast Drug-Induced Hepatic Steatosis, a form of fatty liver disease. They utilized transcriptome data from the Open TG-GATEs database [70] as their principal features. They looked at five machine learning algorithms: Support Vector Machine, Random Forest, k-Nearest Neighbors, eXtreme Gradient Boosting, and Elastic Net Logistic Regression. The SVM algorithm was the best, with ROC-AUC values of 0.820 in primary human hepatocytes, 0.975 in a rat in vitro model, and 0.966 in a rat in vivo model. Chowdhury et al. [71] created a hybrid ensemble model to identify liver disease that was 98.38% accurate and used XAI techniques LIME and SHAP to make it easier for doctors to understand. In the same way, Mamun et al. [72] created a Tree Selection and Stacking Ensemble based Random Forest model that got an amazing 99.92% accuracy for diagnosing liver illness. They also used SHAP and LIME to confirm important biomarkers that fit with what doctors know.

7) Nephrology and Kidney Diseases: Kumar et al [73] propose a hybrid deep learning model combining Convolutional Neural Networks (CNN) and Residual Networks (ResNet) for kidney stone detection using medical imaging (ultrasound and CT scans). The model leverages CNN's feature extraction and ResNet's deep learning capabilities to improve accuracy. Preprocessing steps include image compression and noise filtering (e.g., Gaussian filter with PSNR 38.76). The hybrid model achieves 90.9% accuracy, outperforming standalone CNN/ResNet models, with additional metrics like precision (0.90–0.92) and recall (0.90–0.92). Özlem Sabuncu et al [74] developed a deep learning system for kidney stone classification using a hospital-recorded dataset of 8,209 abdominal CT images. The authors employed several pre-trained CNN architectures, with the Inception-V3 model achieving the best performance. The model utilized deep learning features automatically extracted from the CT images and achieved a high test accuracy of 98.52% in detecting kidney stones.Ege Gungor Onal and Hakan Tekgul [75] developed point of care system for kidney stone composition classification. They utilized smartphone microscope to acquire 222 microscopic images from 37 human kidney stones of four types: calcium oxalate, cystine, uric acid and struvite. For classification the authors designed a novel Convolutional Neural Network architecture from scratch. Their model achieved an overall accuracy of 88% and a weighted accuracy of 87% with an average F1 score of 0.84 demonstrating the system's potential for rapid and accurate diagnostic support. Varsha Rathva and Sheshang Degadwala [76] developed ensemble deep learning model to classify kidney CT-scans into four categories: cyst, normal, stone, and tumor. They utilized a fine tuned VGG-16 architecture, optimizing its final 20 layers to extract high-level features, and employed ensemble techniques to enhance robustness. Their model achieved a high classification accuracy of 96% along with precision, recall and F1-scores of 96%. The model was trained and tested on a Kaggle sourced dataset of 2,000 CT scan images (500 per class).

Amit Pimpalkar et al [77] developed system for classifying kidney conditions from CT scans into four categories: cyst, normal, stone and tumor. They utilized hyperparameter-tuned transfer learning models including VGG16, ResNet50, CNNAlexnet and InceptionV3 and enhanced feature extraction using Watershed segmentation and Otsu's binarization. Their best-performing model a fine tuned InceptionV3 achieved a remarkable accuracy of 99.96% and perfect ROC AUC score of 1.0. The models were trained and tested on a Kaggle sourced dataset of 12,446 kidney CT images. Iparraguirre et al [78] evaluated six ML algorithms Logistic Regression, KNN, Decision Tree, SVM, Gaussian Naive Bayes and Random Forest for kidney stone prediction. Their findings revealed that Logistic Regression achieved the best performance with an accuracy of 78%, outperforming other models that ranged between 61% and 76%. The study emphasizes the promise of relatively simple ML approaches for kidney stone prediction, particularly in resource limited healthcare settings. Khan et al [79] developed an automated kidney stone detection system using ultrasound image processing to overcome challenges like speckle noise and low contrast. Their approach employs median filtering for noise reduction, adaptive thresholding for segmentation and morphological analysis for precise stone localization, achieving 96.82% accuracy and 92.16% sensitivity in tests. The method outperforms existing techniques (DIPT, AKSD, IDKS) with a peak signal-to-noise ratio of 1.82 demonstrating superior performance. The study by Panda et al [80] evaluates machine learning models for kidney stone prediction using urine analysis data. The researchers analyzed 79 samples with six physical features including pH and calcium concentration, testing ten different ML algorithms. Their results showed

Logistic Regression achieved the highest performance with 93% accuracy and 87% precision. This work demonstrates the potential of ML-based approaches as cost-effective alternatives to traditional diagnostic methods for kidney stones.

8) Endocrinology and Metabolic Disorders: Febrian et al. [81] compared KNN and Naïve Bayes for diabetes prediction using the Pima Indians dataset. Their study used 10-fold cross-validation across different data splits preprocessed implausible zero values in health metrics, and evaluated performance through confusion matrices while avoiding accuracy metrics. Ashisha at al. [82] focuses on the early detection of diabetes using machine learning specifically employing the Random Forest algorithm. They report that their model achieved an accuracy of 87% in predicting diabetes. Researchers in [83] compared decision tree models (LAD Tree, NB Tree, Genetic J48 Tree) for diabetes prediction using the UCI PIMA Indian dataset. Their novel Genetic J48 model achieved superior results, with 95.8% accuracy and 97.2% efficiency, by enhancing J48 and reducing irrelevant features. This indicates that optimized decision trees offer significant potential for clinical decision support in diabetes. Soni and Varma [84] explored early diabetes prediction using various machine learning algorithms on the Pima Indian Diabetes Dataset. They applied classification and ensemble methods such as KNN, Logistic Regression, Decision Tree, SVM, Gradient Boosting, and Random Forest, with preprocessing steps including missing value handling and data splitting. Alam et al. [85] developed a machine learning model for early diabetes prediction using the Pima Indian Diabetes Dataset. They applied data preprocessing, association rule mining, and classification techniques including ANN, Random Forest, and K-means. Sonar et al develops a machine learning system for early diabetes prediction using classification algorithms like Decision Trees, ANN, Naive Bayes, and SVM [86]. The model analyzes patient data to detect diabetes risk without requiring repeated clinical tests. This study [87] focuses on predicting diabetes in Indian pregnant women using the Decision Tree J48 algorithm. Applied to 768 patient records with 8 clinical features, the model was implemented in Weka and showed efficient performance with low computational cost. Dudkina et al. [88] proposed a decision tree-based approach for diabetes prediction using the Pima Indians Diabetes Dataset. After preprocessing to remove invalid values, they built a binary tree model in Python, optimizing splits with Gini impurity. The model highlighted glucose, BMI and age as key predictors, offering clear and interpretable decision rules.

9) Other Medical Specialties: Rishi et al [89] authored a comprehensive review on deep learning's role in healthcare. The paper analyzes how algorithms like CNNs and Transformers are used for medical image analysis, personalized treatment, and clinical decision support. It broadly focuses on the healthcare domain, utilizing diverse data from medical images, genomics, and electronic records. As a review article, it synthesizes existing research and discusses the high diagnostic accuracy of these models in general, rather than reporting specific new metrics. The work highlights AI's potential to transform diagnostics and treatment across various medical fields. Syed Saad Azhar Ali et al [90] analyzed deep learning frameworks for MRI based diagnosis of neurological disorders. They reviewed 441 studies and found that the most commonly used algorithms were Support Vector Machines and Convolutional Neural Networks including architectures like ResNet and VGG which extracted features from structural and functional MRI data. This review synthesized performance from numerous models noting that specific accuracies varied widely but could reach up to 99% in some studies. The analysis was based on wide range of publicly available datasets with the Alzheimer Disease Neuroimaging Initiative being the most frequently used. Patel et al [91] developed advanced CAD system for pneumonia screening using chest X rays, focusing on radiology domain. Their novel approach integrated Homomorphic Transformation Filter based FAWT for image decomposition with a customized VGG-16 architecture for feature extraction. The system employed SVM classification with multiple kernel functions, achieving exceptional performance with 97.51% accuracy 97.77% specificity and 96.5% sensitivity through ten-fold cross validation. The incorporation of Grad CAM visualization provided critical interpretability by highlighting pathological regions enabling faster pneumonia screening while reducing dependence on manual radiological assessment.

Chia-Tien Hsu [92] developed machine learning models to predict osteoporosis in patients with chronic kidney disease. They used dataset of 6,614 patients and tested nine different algorithms including an Artificial Neural Network, XGBoost and Random Forest. The ANN model performed best achieving high Area Under the Curve of 0.930 on the test dataset. The model used eight key clinical features such as age, weight, and parathyroid hormone levels to identify high-risk patients for bone mineral density scanning. Abdullah et al [93] developed disease prediction mobile application using a Kaggle dataset. They applied Principal Component Analysis for feature reduction and tested three ML models: Support Vector Machine, Logistic Regression and Classification and Regression Trees. The SVM classifier achieved the best performance with 97.62% testing accuracy and was deployed in the final application. Gokalp Cinarer et al [94] classified brain tumor types from MRI images using machine learning. They employed KNN, Random Forest, SVM and LDA algorithms utilizing statistical features extracted from the medical images. Their work focused on the neuro oncology domain specifically categorizing tumors as normal, multifocal, multicentric or gliomatosis. The SVM algorithm achieved the highest performance with a 90% accuracy rate. Chen et al [95] focused on maximizing malignant case detection using the same dataset. By prioritizing recall and employing feature

selection, their study showed that XGBoost achieved perfect recall (1.00), significantly outperforming other models and highlighting the importance of evaluation metrics aligned with clinical needs. [96, 97, 98, 99, 100, 101, 102, 103].

C. Performance Metrics and Evaluation Frameworks

The evaluation of AI models in healthcare requires comprehensive frameworks assessing statistical performance, clinical reliability, and real-world utility. This section outlines essential metrics and validation methodologies for benchmarking AI systems across medical applications, including classification, segmentation, regression, and survival analysis tasks as detailed in Table V. These metrics span multiple dimensions from fundamental statistical measures to advanced clinical impact assessments, ensuring robust evaluation across diverse healthcare scenarios.

1) Standard Classification Metrics: Classification performance extends beyond accuracy to include precision-recall trade-offs tailored to clinical contexts. Screening applications prioritize high sensitivity to minimize false negatives, while diagnostic confirmation requires high specificity to reduce false positives as shown in Table V. The F1-score balances these competing needs, and AUC metrics provide comprehensive threshold-agnostic performance assessment across diverse clinical scenarios. Additional metrics like Matthews Correlation Coefficient offer robust evaluation for imbalanced datasets commonly encountered in rare disease detection and medical diagnostics.

2) Medical Imaging and Segmentation Metrics: Medical image analysis employs spatial accuracy metrics quantifying anatomical alignment and boundary precision. Dice and IoU scores evaluate volumetric overlap for treatment planning, while Hausdorff Distance ensures surgical safety margins as summarized in Table V. Additional metrics like Average Surface Distance and Volumetric Similarity provide comprehensive spatial evaluation for precise anatomical modeling. These metrics are particularly crucial for radiotherapy planning, surgical navigation, and quantitative disease progression monitoring in longitudinal studies.

3) Diagnostic Performance Assessment: Clinical validation requires metrics translating algorithmic performance into diagnostic confidence. Predictive values (PPV, NPV) offer patient-specific probability estimates, while likelihood ratios quantify diagnostic impact as detailed in Table V. Calibration metrics ensure probability outputs match observed event rates, crucial for reliable risk prediction models in clinical practice.

4) Statistical Validation and Clinical Utility: Robust validation ensures model reliability through cross-validation, bootstrapping, and external validation techniques outlined in Table V. Clinical utility metrics assess tangible benefits in healthcare workflows, including time efficiency, inter-rater reliability, and net benefit analysis for informed clinical decision-making and resource allocation.

D. Explainable AI and Interpretability Methods

The **black-box** nature of advanced AI models like CNNs and Transformers hinders clinical adoption despite their high diagnostic accuracy. Explainable AI (XAI) addresses this by providing transparency and interpretability essential for clinical trust and regulatory compliance [7]. As conceptually illustrated in the flowchart (Figure 2), **Input Data** is processed by the **ML Model**, where XAI tools like **SHAP Analysis** and **LIME Analysis** are explicitly integrated. These tools generate **Feature Influence Explanations** that, alongside the **Model Output**, contribute directly to two critical outcomes: **Increased Trustworthiness** and **Improved Interpretability**. XAI techniques operate at *global* (overall model behavior) and *local* (individual prediction) interpretability levels, with model-agnostic methods being particularly valuable for healthcare applications.



Fig. 2: Explainable AI (XAI) workflow. SHAP and LIME provide feature explanations to improve model trustworthiness and interpretability.

TABLE II: Machine Learning and Deep Learning Applications in Healthcare (Part 1: Cardiovascular, Neurological, Oncology, Brain Tumor Applications)

Ref.	Focus Area	Model	Features	Dataset	Acc. (%)
Cardiovascular Applications					
[9]	Heart Disease	J48 Decision Tree	Clinical attributes	Clinical data	99.62
[10]	Heart Disease	SVM	Clinical features	Medical dataset	95.34
[11]	Heart Disease	LightGBM/XGBoost	Clinical + lifestyle	300,000 patients	91.94
[12]	Heart Disease	XGBoost	Clinical predictors	Medical dataset	92.00
[13]	Coronary Artery	Random Forest	Optimized features	Clinical data	92.00
[14]	Cardiovascular	Random Forest	Clinical features	Medical dataset	98.00
[15]	Heart Disease	KNN	Clinical parameters	Medical dataset	92.00
[104]	Heart Attack	Random Forest	Clinical indicators	Medical dataset	99.89
[16]	Heart Failure	CatBoost	Clinical features	Medical dataset	High
[17]	Heart Disease	XGBoost	Clinical + demographic	Kaggle dataset	93.00
[18]	Heart Disease	Gradient Boosting	Clinical features	Medical dataset	90.20
[19]	Heart Disease	Multiple classifiers	Clinical features	Cleveland dataset	Varies
[20]	Heart Disease	SVM/LR	Clinical features	Medical dataset	90.67
Neurological Applications					
[21]	Parkinson's	Gradient Boosting	Clinical data	Medical dataset	89.00
[22]	Parkinson's	Random Forest	Clinical + demographic	Medical dataset	93.00
[23]	Meningitis	Logistic Regression	Clinical risk factors	535 neonates	76.50
[24]	Meningitis	LASSO	Clinical features	Medical dataset	91.90
[25]	Meningitis	Logistic Regression	32 clinical variables	433 neonates	89.00
[105]	Meningitis	Logistic Regression	Clinical predictors	201 preterm infants	84.90
Oncology Applications					
[33]	Breast Cancer	Logistic Regression	Clinical features	Medical dataset	91.67
[34]	Breast Cancer	Random Forest	Cell nuclei features	WDBC dataset	92.56
[35]	Breast Cancer	Random Forest	Clinical data	900 patients	96.00
[36]	Breast Cancer	Multimodal AI	Clinical + imaging	5,000 patients	90.10
[37]	Breast Cancer	SVM	Clinical features	Wisconsin dataset	97.66
[38]	Breast Cancer	LightGBM	Clinical features	Biopsy data	90.74
[39]	Breast Cancer	SVM	Clinical features	Wisconsin dataset	High
[40]	Breast Cancer	Decision Tree	Clinical features	Medical dataset	High
[41]	Breast Cancer	J48	Selected features	Wisconsin dataset	93.56
[42]	Breast Cancer	Logistic Regression	Clinical features	Medical dataset	97.00
[43]	Breast Cancer	Random Forest	Transcriptomic	Gene data	93.60
[44]	Breast Cancer	KNN	Clinical features	Medical dataset	98.40
[45]	Breast Cancer	Random Forest/SVM	Selected features	Wisconsin dataset	High
Brain Tumor Applications					
[106]	Brain Tumor	U-Net/ResNet	Multi-parametric MRI	Various	78.80–93.80
[26]	Brain Tumor	EfficientNet	DL features	MRI multi-class	98.72
[27]	Brain Tumor	ResNet50	DL features	Public MRI	95.35
[28]	Brain Tumor	PDSCNN-RRELM	Hybrid features	MRI (7,023)	99.22
[29]	Brain Tumor	Ensemble DL	Transfer learning	MRI (3,064)	99.02
[30]	Brain Tumor	U-Net	DL features	MRI (3,064)	98.56
[31]	Brain Tumor	ResNet50	Augmented DL features	BRaTS2018	99.26
[32]	Brain Tumor	Attention-UNet	Multi-scale features	Combined datasets	99.40

TABLE III: Machine Learning and Deep Learning Applications in Healthcare (Part 2: Ophthalmology, Nephrology, Dermatology and Hepatology Applications)

Ref.	Focus Area	Model	Features	Dataset	Acc. (%)
Ophthalmology Applications					
[53]	Cataract	DCEN	Dual-stream features	Fundus (1,340)	97.62
[54]	Cataract	CataractNet	CNN features	Multi-dataset	High
[55]	Eye Disease	YOLOv8n-cls	DL features	Multi-dataset	94.00
[56]	Cataract	Mobile CNN	DL features	Mobile images	98.79
[57]	Cataract	Custom CNN	Multi-layer features	Clinical images	High
[58]	Cataract	BPNN	Handcrafted + DL	Custom dataset	–
[2]	Cataract	SVM	Image features	Ocular images	95.00
[59]	Cataract	KNN	Processed features	Mobile images	83.07
[60]	Cataract	SVM-RBF	Blood vessel features	Fundus images	95.20
[61]	Cataract	k-NN	GLCM texture	Eye images (160)	97.50
Nephrology Applications					
[73]	Kidney Stone	Hybrid CNN-ResNet	DL features + preprocessing	Ultrasound	90.90
[74]	Kidney Stone	Inception-V3	DL features	Hospital CT (8,209)	98.52
[75]	Kidney Stone	Custom CNN	DL features	Custom Data	88.00
[76]	Kidney Disease	Ensemble VGG-16	Fine-tuned DL features	Kaggle CT (2,000)	96.00
[77]	Kidney Disease	InceptionV3	Segmented DL features	Kaggle CT (12,446)	99.96
[78]	Kidney Stone	Logistic Regression	Clinical features	Medical dataset	78.00
[79]	Kidney Stone	Image processing	Morphological features	Ultrasound	96.82
[80]	Kidney Stone	Logistic Regression	Urine analysis	79 samples	93.00
Dermatology Applications					
[46]	Skin Lesion	HPDT	Prototypical embeddings	Clinical data	60.87
[107]	Skin Disease	Stacking ensemble	ResNet50 + LR	Clinical data	96.00
[47]	Skin Disease	Logistic Regression/SGD	Dermatological features	Medical dataset	98.00
[48]	Skin Cancer	Multiple DL	Dermoscopic features	Various datasets	>98.00
[49]	Skin Disease	Hybrid ensemble	Texture features	Medical images	95.50
[50]	Skin Disease	Various ML	Multiple features	Survey data	50–100
[51]	Skin Disease	SVM	Dermoscopic features	ISIC/HAM10000	95–97
[52]	Skin Disease	SVM	Image features	Medical images	98.80
Hepatology Applications					
[62]	Liver Disease	CNN	DL features	BUPA/ILPD	75.55
[63]	Liver Disease	SSAE	Auto-encoder features	Ultrasound	97.20
[64]	Liver Tumor	Custom DL	DL features	CT images	98.59
[108]	Liver Disease	2S-NNet	DL features	Community US	0.93
[65]	Liver Disease	LightGBM	Clinical features	ILPD dataset	63.00
[66]	Liver Disease	Random Forest	Clinical parameters	32,000 records	97.30
[67]	Liver Disease	Logistic Regression	Basic clinical	10,007 patients	72.80
[68]	Liver Disease	Ensemble ML	Clinical features	Medical dataset	95.24
[69]	Liver Disease	SVM	Transcriptomic	TG-GATEs DB	82.00
[71]	Liver Disease	Hybrid ensemble	Clinical features	Medical dataset	98.38
[72]	Liver Disease	Ensemble RF	Clinical biomarkers	Medical dataset	99.92

TABLE IV: Machine Learning and Deep Learning Applications in Healthcare (Part 3: Other Specialties)

Ref.	Focus Area	Model	Features	Dataset	Acc. (%)
Other Specialties					
[81]	Diabetes	KNN/NB	Clinical features	Pima Indians	Varies
[82]	Diabetes	Random Forest	Clinical indicators	Medical dataset	87.00
[83]	Diabetes	Genetic J48	Optimized features	Pima Indian	95.80
[84]	Diabetes	Multiple ML	Clinical features	Pima Indian	Varies
[85]	Diabetes	ANN/RF	Clinical data	Pima Indian	Varies
[86]	Diabetes	Multiple classifiers	Clinical features	Medical dataset	Varies
[87]	Diabetes	J48	Clinical features	768 patients	High
[88]	Diabetes	Decision Tree	Clinical predictors	Pima Indian	High
[91]	Pneumonia	VGG-16 + SVM	Custom DL features	Chest X-ray	97.51

Note: Abbreviations: SVM = Support Vector Machine, LightGBM = Light Gradient Boosting Machine, XGBoost = Extreme Gradient Boosting, KNN = K-Nearest Neighbors, LR = Logistic Regression, LASSO = Least Absolute Shrinkage and Selection Operator, DL = Deep Learning, MRI = Magnetic Resonance Imaging, PDSCNN = Parallel Depthwise Separable Convolutional Neural Network, RRELM = Ridge Regression Extreme Learning Machine, BRaTS = Brain Tumor Segmentation, U-Net = U-shaped Network, ResNet = Residual Network, DCEN = Dual-stream Cataract Evaluation Network, CNN = Convolutional Neural Network, YOLO = You Only Look Once, BPNN = Backpropagation Neural Network, SVM-RBF = Support Vector Machine with Radial Basis Function, GLCM = Gray Level Co-occurrence Matrix, VGG = Visual Geometry Group, SSAE = Stacked Sparse Auto-Encoder, 2S-NNet = Two Section Neural Network, ILPD = Indian Liver Patient Dataset, TG-GATEs = Toxicogenomics Project-Genomics Assisted Toxicity Evaluation System, RF = Random Forest, HPDT = Hierarchical Prototypical Decision Tree, SGD = Stochastic Gradient Descent, NB = Naïve Bayes, J48 = Decision Tree Algorithm (C4.5 implementation), ANN = Artificial Neural Network, ML = Machine Learning.

LIME (Local Interpretable Model-agnostic Explanations): LIME explains individual predictions by approximating the complex black-box model with simple, interpretable model in the local vicinity of the instance being explained [109]. The method works by generating perturbed samples around the instance and training a local surrogate model that approximates the black-box model's behavior locally. The core optimization objective of LIME is formalized as:

$$\xi(x) =_{g \in G} \mathcal{L}(f, g, \pi_x) + \Omega(g) \tag{21}$$

where:

1) $\xi(x)$: Explanation for instance x.
2) f: Original complex model (black-box)
3) g: Interpretable surrogate model (e.g., linear model)
4) $\mathcal{L}$: Loss function measuring how well g approximates f in the locality defined by π_x
5) π_x: Proximity measure defining the local neighborhood around x
6) $\Omega(g)$: Complexity penalty for the explanation model g.

In our breast cancer diagnosis application using the Wisconsin Breast Cancer Dataset, LIME provides instance level explanations that identify which clinical features most influenced each individual prediction. For example, as shown in Figure 3, features such as worst area, worst concave points, and worst perimeter consistently emerge as the most influential factors across multiple patient cases. The model achieved 95.6% accuracy in classifying malignant vs. benign tumors, with LIME revealing that larger tumor area (> 500 mm^2) and higher concavity typically pushed predictions toward malignancy, while smaller, smoother tumors supported benign classifications. The distribution of feature impacts (Figure 4) demonstrates that certain features, such as *worst area*, consistently correlate with malignancy (positive impact scores). This local interpretability allows clinicians to verify that the model relies on medically relevant features, building trust in the diagnostic system. While LIME is intuitive and computationally efficient, its explanations can be sensitive to the perturbation process. Furthermore, it only provides local insights without offering a global perspective on model behavior. Nevertheless, in clinical applications like cancer diagnosis, LIME's case specific, human understandable explanations are invaluable for validation and decision support [110].

SHAP (SHapley Additive exPlanations): SHAP is a unified framework based on cooperative game theory that assigns each feature an importance value for a particular prediction [111]. The Shapley value ϕ_i for feature i is calculated as:

$$\phi_i = \sum_{S \subseteq F \setminus \{i\}} \frac{|S|!(|F| - |S| - 1)!}{|F|!} [f(S \cup \{i\}) - f(S)] \tag{22}$$

where F is the set of all features, S is a subset of features excluding i, and $f(S)$ is the model prediction using only feature subset S. The SHAP values satisfy the efficiency property:

$$\sum_{i=1}^{M} \phi_i = f(x) - E[f(X)] \tag{23}$$

where M is the number of features, $f(x)$ is the model prediction for instance x, and $E[f(X)]$ is the expected model prediction. In clinical applications, SHAP provides both local explanations (for individual patients) and global insights (by aggregating many local explanations). For breast cancer

TABLE V: Comprehensive Framework for Healthcare AI Performance Evaluation

Category	Metric	Formula	Clinical Interpretation	Primary Use Case
Classification	Accuracy	$\frac{TP+TN}{TP+TN+FP+FN}$	Overall diagnostic correctness	General screening
	Precision	$\frac{TP}{TP+FP}$	Reliability of positive diagnosis (>90%)	Confirmatory testing
	Recall	$\frac{TP}{TP+FN}$	Ability to detect true cases (>95%)	Disease screening
	F1-Score	$2 \times \frac{P \times R}{P+R}$	Balance of precision/recall trade-off	Imbalanced data
	AUC-ROC	Area under curve	Overall discrimination ability (>0.90)	Model comparison
Segmentation	Dice Score	$\frac{2\lvert P \cap G \rvert}{\lvert P \rvert + \lvert G \rvert}$	Volumetric overlap accuracy (>0.90)	Tumor segmentation
	IoU	$\frac{\lvert P \cap G \rvert}{\lvert P \cup G \rvert}$	Spatial overlap measure (>0.85)	Organ delineation
	Hausdorff Dist.	$\max(d(\partial P, \partial G))$	Worst-case boundary error (<5mm)	Surgical planning
Regression	MAE	$\frac{1}{n} \sum \lvert y_i - \hat{y}_i \rvert$	Average prediction error	Continuous outcomes
	RMSE	$\sqrt{\frac{1}{n} \sum (y_i - \hat{y}_i)^2}$	Penalized large errors	Risk scores
	R²	$1 - \frac{\sum (y_i - \hat{y}_i)^2}{\sum (y_i - \bar{y})^2}$	Variance explained (>0.80)	Predictive models
	MAPE	$\frac{100\%}{n} \sum \left\lvert \frac{y_i - \hat{y}_i}{y_i} \right\rvert$	Percentage error	Clinical measurements
Diagnostic	PPV/NPV	$\frac{TP}{TP+FP}, \frac{TN}{TN+FN}$	Post-test probability (prevalence-dependent)	Clinical decision making
	Likelihood Ratio	$\frac{\text{Sen}}{1-\text{Spec}}$	Diagnostic impact strength (>10 strong)	Evidence-based medicine
	Cohen's κ	Agreement correction	Expert concordance (>0.80)	Validation studies
Validation	K-Fold CV	$\frac{1}{K} \sum_{i=1}^{K} \text{Perf}_i$	Generalizability estimate (stable folds)	Model development
	Bootstrapping CI	$\hat{\theta} \pm z \cdot SE$	Performance uncertainty (narrow CI)	Clinical adoption
	Stratified Sampling	Class balance preservation	Population representation	Medical datasets
Clinical Impact	Net Benefit	$TPR - \frac{FP \times \theta}{1-\theta}$	Risk-benefit trade-off (positive value)	Decision curve analysis
	Time Efficiency	$T_{\text{std}} - T_{\text{AI}}$	Workflow improvement (>30% reduction)	Clinical integration
	Inter-rater Rel.	Fleiss' κ/ICC	Multi-expert consensus (>0.75)	Multi-center trials
Survival Ana	C-index	Concordance probability	Predictive accuracy for time-to-event	Cancer prognosis
	Brier Score	$\frac{1}{N} \sum (p_i - o_i)^2$	Probability calibration (<0.25 good)	Risk prediction models
	Integrated Brier	$\frac{1}{\max(t)} \int_0^{\max(t)} BS(t)dt$	Time-dependent calibration	Survival models
	Calibration Slope	Slope of calibration plot	Calibration quality (1.0 ideal)	Risk models
Fairness & Bias	Equalized Odds	$P(\hat{Y} = 1 \mid Y = y, A = a) = P(\hat{Y} = 1 \mid Y = y, A = b)$	Fairness across subgroups	Equity assessment
	Demographic Parity	$P(\hat{Y} = 1 \mid A = a) = P(\hat{Y} = 1 \mid A = b)$	Equal positive rate	Bias detection
	Disparate Impact	$\frac{P(\hat{Y}=1 \mid A=\text{minority})}{P(\hat{Y}=1 \mid A=\text{majority})}$	Ratio of positive rates (>0.8)	Regulatory compliance
	AUC Difference	$\lvert \text{AUC}_a - \text{AUC}_b \rvert$	Performance gap (<0.05)	Subgroup analysis

Note: Category abbreviations: Class. = Classification, Seg. = Segmentation, Diag. = Diagnostic Assessment, Val. = Statistical Validation, Clin. = Clinical Impact. Metric abbreviations: TP/FP/TN/FN = True/False Positive/Negative, P/R = Precision/Recall, AUC-ROC = Area Under ROC Curve, IoU = Intersection over Union, PPV/NPV = Positive/Negative Predictive Value, CI = Confidence Interval, CV = Cross-Validation, TPR = True Positive Rate, θ = risk threshold, ICC = Intraclass Correlation Coefficient, Sen = Sensitivity, Spec = Specificity.



Fig. 3: Aggregate feature importance across 50 LIME explanations. The chart displays the Mean Absolute Impact Score (Mean |LIME Feature Importance|) for each clinical parameter, with the features ordered by their importance, from the most influential (top bar) to the least influential (bottom bars) in breast cancer diagnosis.



Fig. 4: Distribution of feature impact scores derived from LIME. Scores to the right (positive) support Malignant scores to the left (negative) support Benign.

diagnosis using the Wisconsin Breast Cancer Dataset SHAP can identify the most critical biomarkers driving malignant vs. benign classifications. As shown in Figure 5, features like worst radius, worst perimeter, and mean concave points emerge as the most important predictors. In breast cancer diagnosis, SHAP reveals that tumor morphological characteristics such as radius, texture, and perimeter measurements are key determinants of malignancy. The summary plot demonstrates how each feature affects the model output, with feature values color-coded to show their impact on prediction outcomes. This method offers theoretical guarantees from cooperative game theory and handles feature interactions effectively, though it can be computationally expensive for large datasets.

Grad-CAM (Gradient-weighted Class Activation Mapping) is a technique for CNNs, especially useful in medical image analysis [112]. It generates visual explanations as heatmaps that highlight image regions contributing most to



Fig. 5: SHAP summary plot showing feature importance and impact direction for breast cancer classification. Red features push predictions toward malignancy, while blue indicates benign influence.

the model's decision, based on gradients flowing into the final convolutional layer. As shown in brain tumor MRI studies [29, 113] and your synthetic breast cancer simulation, Grad-CAM effectively pinpoints tumor or lesion areas, confirming the model's focus on clinically relevant regions. The method computes a weighted sum of the final convolutional feature maps ($\mathbf{A}^k$), where the weights (α_k^c) are obtained from the spatial average of the gradients ($\frac{\partial y^c}{\partial \mathbf{A}_{ij}^k}$) for the target class ($c$). The two defining equations are the Neuron Importance Weight (α_k^c) and the Grad-CAM Heatmap ($\mathbf{L}_{\text{Grad-CAM}}^c$):

1) Neuron Importance Weight:

$$\alpha_k^c = \frac{1}{Z} \sum_i \sum_j \frac{\partial y^c}{\partial \mathbf{A}_{ij}^k}$$

2) Grad-CAM Heatmap:

$$\mathbf{L}_{\text{Grad-CAM}}^c = \text{ReLU}\left(\sum_k \alpha_k^c \mathbf{A}^k\right)$$

The Grad-CAM process begins by calculating the Neuron Importance Weight (α_k^c), derived from the gradient $\left(\frac{\partial y^c}{\partial \mathbf{A}_{ij}^k}\right)$ using Global Average Pooling (GAP) to quantify each feature map's relevance to the classification score y^c. These weights are linearly combined with the corresponding feature maps $\mathbf{A}^k$ to generate the final Grad-CAM Heatmap ($\mathbf{L}_{\text{Grad-CAM}}^c$),

followed by Rectified Linear Unit (ReLU) to retain only positive activations. The resulting visualizations, shown in Fig. 6 and Fig. 7, highlight tumor-representative regions that influenced the malignant prediction, while Table VI provides corresponding model interpretation details.



Fig. 6: Raw Grad-CAM Heatmap: The raw output of $\mathbf{L}^c_{\text{Grad-CAM}}$, resized to the original image dimensions, showing relative activation intensity across the image.



Fig. 7: Interpretable Result (Overlay): The heatmap superimposed on the original image, visually confirming that the model focused on the irregular pattern (tumor surrogate) to predict malignant.

1) Comparative Analysis of XAI Techniques: Each XAI method offers distinct advantages and limitations in healthcare applications, as summarized in Table VII. SHAP provides the most mathematically rigorous explanations but requires significant computational resources. LIME offers intuitive local explanations but may lack consistency across similar cases. Grad-CAM delivers excellent visual interpretability for imaging data but is limited to CNN architectures. The choice of XAI technique often depends on the specific clinical context, with SHAP being preferred for tabular clinical data, LIME for mixed data types, and Grad-CAM for medical imaging applications.

TABLE VI: Model prediction details for the Grad-CAM visualization of a malignant case.

Attribute	Description
True Label	Malignant
Predicted Class	Malignant
Confidence	1.000
Target Layer	`conv3`
Focus	Pinpoints the irregular features (tumor surrogate)

TABLE VII: Comparison of XAI Techniques in Healthcare

Technique	Key Characteristics
SHAP	**Level:** Global & Local **Advantages:** Theoretical guarantees, consistent explanations, handles feature interactions **Limitations:** Computationally expensive, complex for non-technical staff
LIME	**Level:** Local **Advantages:** Intuitive, fast computation, model-agnostic, immediate insights **Limitations:** Explanation instability, sensitive to parameters, no global view
Grad-CAM	**Level:** Local (Visual) **Advantages:** Visual heatmaps, no retraining, aligns with radiological practice **Limitations:** Limited to images/CNNs, may miss fine details

2) Model-Specific Interpretability Methods: Model-specific interpretability techniques leverage internal model architectures to generate faithful explanations. **Attention mechanisms** in Transformers provide natural interpretability through attention weights that highlight relevant input regions [90]. For CNNs, **saliency maps** and **guided backpropagation** visualize influential pixels by computing output gradients with respect to inputs:

$$M(x) = \left\| \frac{\partial f_c(x)}{\partial x} \right\| \tag{24}$$

Tree-based models offer inherent interpretability through **rule extraction**, converting decision paths into human-readable "if-then" rules that align with clinical guidelines [18]. **Inherently interpretable models** like Generalized Additive Models (GAMs) provide transparency by design:

$$g(E[y]) = \beta_0 + f_1(x_1) + f_2(x_2) + \cdots + f_p(x_p) \tag{25}$$

These methods deliver architecture-specific insights crucial for clinical validation of AI reasoning processes.

E. Clinical Data Analysis and EHR Processing

1) Structured Data Analysis: Structured EHR data encompasses laboratory results, vital signs, diagnostic codes (ICD-10), and medication records. Machine learning models excel at identifying complex patterns within this multidimensional data. **Random Forests** and **Gradient Boosting Machines** (XGBoost, LightGBM) demonstrate strong performance for tasks like hospital readmission prediction and disease onset forecasting [11, 14]. These models handle mixed data types and missing values common in clinical settings. **Logistic Regression** remains valuable for its interpretability in clinical risk scores, while **Survival Analysis** models (Cox Proportional Hazards) with ML extensions predict time-to-event outcomes like disease progression or mortality [35]. A key challenge is **feature engineering** to represent temporal interactions and medical hierarchies effectively.

2) Unstructured Text Processing: Clinical notes, physician narratives, and radiology reports contain crucial information not captured in structured fields. Natural Language Processing (NLP) techniques extract clinical insights from this unstructured text. **BERT-based models** fine-tuned on clinical corpora (ClinicalBERT, BioBERT) enable tasks such as symptom extraction, disease mention identification, and relation extraction [6]. **Named Entity Recognition** (NER) systems identify medical concepts, medications, and procedures, while **text classification** models categorize clinical documents or detect adverse events. Transformer architectures with attention mechanisms provide both high accuracy and interpretability by highlighting relevant text segments that influence predictions. Recent large language models (LLMs) are now being explored for complex tasks like clinical reasoning and report summarization.

3) Time-Series Medical Data: Temporal medical data including vital sign monitoring, continuous glucose monitoring, and longitudinal laboratory values require specialized sequence modeling approaches. **Recurrent Neural Networks** (RNNs), particularly **LSTM** and **GRU** architectures, capture temporal dependencies in patient trajectories [21]. More recently, **Transformer-based models** with self-attention mechanisms have shown superior performance for long-range dependencies in irregularly sampled clinical time series. These models enable early warning systems for sepsis detection, hemodynamic instability prediction, and chronic disease progression monitoring. Multivariate time-series analysis integrates multiple physiological signals to provide comprehensive patient state assessment, with applications in ICU monitoring and remote patient management. Handling **irregular sampling rates** and **informative missingness** remains an active research area.

IV. Personalized Treatment and Clinical Applications

A. AI-Driven Personalized Medicine

Artificial Intelligence (AI) is reshaping personalized medicine by enabling tailored treatment strategies based on individual patient characteristics, genetic profiles, and clinical history. Traditional "one-size-fits-all" medical approaches are gradually being replaced by precision medicine frameworks that leverage machine learning to analyze complex, multi-modal data—including genomics, proteomics, metabolomics, and clinical parameters—as summarized in Table VIII.

Genomic-Based Personalization: AI algorithms play a pivotal role in identifying biomarkers and genetic signatures that predict how patients will respond to specific treatments. Deep learning models can process large-scale genomic data to detect rare variants that influence drug metabolism and therapeutic efficacy. In oncology, convolutional neural networks (CNNs) analyze genomic and transcriptomic profiles to predict chemotherapy sensitivity and guide the selection of targeted therapies based on tumor-specific mutations. Reinforcement learning approaches further enhance personalization by optimizing dosing regimens—continuously adapting to a patient's treatment response and side effect patterns, as detailed in Table VIII.

Multi Omics Integration: The integration of diverse biological datasets through AI enables a more holistic understanding of disease mechanisms and patient subtypes. Graph neural networks (GNNs) model intricate relationships between genomic variations, gene expression, and protein interactions to uncover new therapeutic targets. Autoencoder-based architectures learn compact, informative representations of high-dimensional omics data, helping to identify patient subgroups with distinct molecular signatures and treatment needs. These integrative approaches have demonstrated improved predictive accuracy for drug response compared to models relying on single data types, highlighting the advantages summarized in Table VIII.

B. Clinical Decision Support Systems

AI-powered **Clinical Decision Support Systems (CDSS)** are transforming the way clinicians make decisions by providing data-driven, evidence-based insights directly at the point of care. These systems combine patient-specific data with vast medical knowledge to assist in diagnosis, treatment planning, and risk assessment, as outlined in Table VIII.

Diagnostic Decision Support: Advanced CDSS employ deep learning models to analyze a combination of medical images, laboratory results, and clinical notes for comprehensive diagnostic support. Transformer-based models are capable of processing multimodal patient data to produce ranked differential diagnoses with associated confidence scores. Furthermore, knowledge graphs integrate structured medical ontologies with real-world clinical

evidence, generating contextualized recommendations that account for comorbidities, drug interactions, and established medical guidelines. In several domains—such as radiology, pathology, and emergency medicine—these systems have demonstrated diagnostic performance on par with human specialists, reinforcing the clinical potential identified in Table VIII.

Risk Stratification and Early Warning: Machine learning-based risk prediction models help identify patients who are most likely to experience adverse clinical events, allowing for timely intervention. Gradient boosting algorithms analyze EHR data to predict outcomes such as hospital readmissions, sepsis onset, and patient deterioration. Real-time monitoring systems interpret streaming physiological data from bedside sensors to detect subtle changes preceding critical events. In parallel, natural language processing (NLP) techniques extract valuable clinical insights from unstructured physician notes, identifying patients who may benefit from additional testing or specialist referrals—addressing the real-world implementation challenges discussed in Table VIII.

Treatment Pathway Optimization: Reinforcement learning frameworks are increasingly used to optimize complex treatment pathways by learning from historical patient outcomes. These systems model treatment selection as a sequential decision-making problem—balancing short-term improvements against long-term health outcomes. Multi-armed bandit algorithms support adaptive clinical trial designs by dynamically allocating treatment arms, expediting the discovery of effective therapies while maintaining ethical integrity. Additionally, Markov decision processes (MDPs) encode clinical guidelines into actionable policies that can be personalized for each patient based on their unique characteristics and preferences, as reflected in the AI technologies column of Table VIII.

C. Ethical Considerations in Healthcare AI

The integration of Artificial Intelligence (AI) into healthcare introduces profound ethical challenges that must be carefully managed to ensure responsible deployment and maintain public trust. These concerns span several dimensions—including fairness, transparency, accountability, and patient autonomy—as summarized in Table IX.

Algorithmic Bias and Health Equity: AI systems are only as fair as the data they are trained on. When trained on datasets that underrepresent certain demographic groups, AI models risk reinforcing or amplifying existing healthcare disparities. Research has shown that diagnostic algorithms may underperform for minority populations, women, and older adults, leading to unequal quality of care. To counter this, developers must employ diverse and representative datasets, implement fairness-aware algorithms, and continuously monitor models for biases that could affect specific patient subgroups. Upholding the principle of health equity means ensuring that AI systems benefit all individuals equally—regardless of race, gender, socioeconomic status, or geographic location.

Informed Consent and Data Governance: The traditional concept of informed consent faces new challenges in the age of AI, where data may be reused for purposes not originally anticipated by patients. Emerging frameworks such as *dynamic consent* allow individuals to make ongoing, informed choices about how their data is used, offering greater transparency and control. Robust data governance practices are equally essential—they must balance the drive for innovation with the need for privacy protection. Transparent policies on data collection, storage, and use can empower patients while ensuring that AI applications operate within ethical and legal boundaries.

D. Regulatory Frameworks and Compliance

The regulatory landscape for AI in healthcare is evolving rapidly as authorities adapt to the distinct challenges posed by adaptive algorithms and software-based medical systems. Global regulatory agencies are developing tailored frameworks that promote safety and efficacy while accommodating the iterative and data-driven nature of AI development, as outlined in Table IX.

Medical Device Regulation and Classification: Many AI systems in healthcare are categorized as medical devices, with regulatory requirements determined by their intended use and associated risk level. Frameworks such as the U.S. Food and Drug Administration's (FDA) *Software as a Medical Device (SaMD)* policy and the European Union's *Medical Device Regulation (MDR)* establish structured pathways for both pre-market evaluation and post-market monitoring. These pathways must account for AI-specific characteristics—such as algorithm transparency, stability across diverse populations, and the capacity for continuous learning and model updates ensuring that safety and performance remain consistent over time.

Quality Management and Lifecycle Regulation: Traditional quality management systems are being redefined to suit the dynamic nature of AI development. The concept of *Good Machine Learning Practice (GMLP)* emphasizes rigorous data quality assurance, thorough validation processes, and version control for iterative model updates. By defining modification protocols and establishing clear performance thresholds in advance, developers can facilitate regulatory review of model updates while maintaining high standards of safety and effectiveness. Such lifecycle regulation ensures that AI systems evolve responsibly, without compromising patient well-being or clinical reliability.

TABLE VIII: Comprehensive Overview of AI Applications in Personalized Treatment and Clinical Decision Support

Application Area	AI Technology	Key Capabilities	Clinical Benefits	Implementation Challenges
Personalized Medicine	Graph Neural Networks Autoencoders Reinforcement Learning	Multi-omics data integration Biomarker discovery Individualized dosing optimization	Improved treatment efficacy Reduced adverse events Targeted therapy selection	Data heterogeneity Interpretability requirements Regulatory validation
Clinical Decision Support	Transformer Architectures Knowledge Graphs Gradient Boosting Machines	Multimodal data analysis Evidence-based recommendations Real-time risk stratification	Enhanced diagnostic accuracy Proactive intervention Reduced medical errors	Workflow integration Alert fatigue management Clinical acceptance
Treatment Recommendation	Multi-objective Reinforcement Learning Bayesian Neural Networks Federated Learning	Balanced treatment optimization Uncertainty quantification Continuous learning from real-world data	Personalized therapy sequences Informed decision making Adaptive treatment strategies	Causal inference limitations Data privacy concerns Validation complexity
Drug Discovery & Development	Generative AI Molecular Dynamics Simulation Predictive Toxicology Models	De novo drug design Binding affinity prediction Toxicity and efficacy forecasting	Accelerated discovery timeline Reduced development costs Improved success rates	Experimental validation Regulatory acceptance Computational complexity
Chronic Disease Management	Temporal Convolutional Networks LSTM/GRU Architectures Digital Twin Modeling	Disease progression prediction Treatment response monitoring Personalized intervention timing	Preventive care optimization Reduced complications Improved quality of life	Long-term data requirements Model drift over time Patient engagement

TABLE IX: Ethical, Regulatory, and Implementation Challenges in Healthcare AI

Category	Key Challenges and Considerations
Ethical Considerations	Algorithmic bias; Informed consent for data use; Accountability and liability; Patient autonomy; Data privacy and secondary use.
Regulatory Frameworks	AI device classification; Pre- and post-market approval; Quality management for adaptive models; Global regulatory alignment; Cybersecurity compliance.
Implementation Challenges	Workflow integration; Infrastructure and interoperability; Change management readiness; Staff training and AI literacy; Cost-benefit evaluation.

E. Clinical Implementation Challenges

Successful integration of AI into clinical workflows faces numerous practical challenges that extend beyond technical performance to encompass human factors, infrastructure requirements, and organizational change management as detailed in Table IX.

Workflow Integration and Human-AI Collaboration: Effective AI implementation requires seamless integration into existing clinical workflows without creating additional burdens for healthcare professionals. Systems must provide timely, context-aware recommendations through intuitive interfaces that complement rather than disrupt clinical reasoning. Training programs for clinicians to develop "AI literacy" – understanding AI capabilities, limitations, and appropriate use cases – are essential for building trust and ensuring effective human-AI collaboration.

Infrastructure and Interoperability Requirements: Healthcare organizations often lack the technical infrastructure needed to support AI systems, including sufficient computing resources, data storage capacity, and network bandwidth. Interoperability challenges arise from fragmented health information systems, non-standardized data formats, and proprietary interfaces. Successful implementation requires significant investment in IT infrastructure, data standardization initiatives, and middleware solutions to bridge compatibility gaps between AI systems and existing clinical software.

V. Mobile Health and Future Directions

The combination of artificial intelligence with mobile health technologies is a game-changer in healthcare delivery, especially for making medical services more available in areas that don't have enough of them. Mobile health apps use the fact that smartphones and wearable devices are everywhere to allow for constant health monitoring, remote diagnosis, and personalized interventions. These deployable solutions show how AI algorithms may be used in real-world healthcare settings, filling the gap between research and clinical use.

Mobile Diagnostic Applications: Numerous studies have shown that it is possible to use AI models on mobile devices to treat a wide range of medical ailments. Rehman et al. [2] created the Cortex Vision app, which is a good example of this trend. It uses an SVM model with 95% accuracy to find cataracts in ocular photos taken with smartphone cameras. In the same way, Rajhan et al. [56] made a mobile

app for detecting cataracts using CNN architecture that was 98.79% accurate. Agarwal et al. [59] made an Android-based system for detecting cataracts using KNN algorithms that was 83.07% accurate. These mobile solutions help people in resource-limited areas get the healthcare they need when specialists aren't available.

Wearable Health Monitoring: AI-powered wearable gadgets can do more than just diagnostics; they can also monitor your body constantly and provide you alerts when something is wrong. Smartwatches and fitness trackers that use machine learning can find arrhythmias, keep an eye on blood sugar levels, and keep track of how well people are taking their medications. These systems use lightweight deep learning models that are tailored for edge computing. They process sensor data locally to protect privacy and give real-time health information. Federated learning and IoT devices coming together make it possible to create tailored health models without having to collect data in one place. This solves privacy issues while keeping the models accurate.

Telemedicine Integration: AI features are being added to mobile health platforms more and more to improve telemedicine services. Natural language processing makes it possible to check symptoms and sort patients automatically, while computer vision algorithms make it possible to check wounds and skin conditions from a distance. These integrated solutions help healthcare providers do remote consultations, which lets specialists help those who live far away. The COVID-19 pandemic sped up the use of these technologies, showing how useful they are for keeping healthcare going amid public health emergencies.

A. Emerging Technologies and Trends

The healthcare AI landscape continues to evolve rapidly, with several emerging technologies showing significant promise for transforming medical diagnosis, treatment, and patient care. These trends represent the cutting edge of research and development in medical artificial intelligence.

Federated Learning and Privacy-Preserving AI: Federated learning enables model training across decentralized data sources without transferring sensitive patient information, addressing critical privacy concerns in healthcare AI. This approach allows institutions to collaboratively develop robust models while maintaining data sovereignty. Combined with differential privacy and homomorphic encryption techniques, federated learning facilitates multi-institutional research while complying with stringent data protection regulations like HIPAA and GDPR. Recent advancements in split learning and swarm learning further enhance the scalability and efficiency of privacy-preserving AI in healthcare.

Generative AI in Healthcare: Generative models particularly large language models and diffusion models, are emerging as powerful tools for medical image synthesis, drug discovery, and clinical decision support. GPT-based systems assist in medical documentation, patient education, and clinical reasoning, while generative adversarial networks create synthetic medical images for data augmentation and training. In drug discovery, generative models design novel molecular structures with desired therapeutic properties, significantly accelerating the early stages of pharmaceutical development. These technologies also enable realistic simulation environments for medical training and procedural planning.[114, 115, 116]

Quantum Machine Learning: Although still in early stages, quantum computing shows potential for solving complex healthcare optimization problems that are intractable for classical computers. Quantum machine learning algorithms may revolutionize drug discovery by simulating molecular interactions at quantum levels, optimizing treatment protocols through quantum annealing, and enhancing medical image analysis through quantum-inspired algorithms. While practical quantum advantage in healthcare remains years away, research in this area is advancing rapidly, with promising applications in genomics, proteomics, and personalized treatment optimization. [117, 118, 119, 120]

Neuromorphic Computing and Brain-Inspired AI: Neuromorphic computing architectures, designed to mimic the brain's neural structure, offer energy-efficient solutions for real-time medical AI applications. These systems enable continuous learning from streaming medical data while consuming significantly less power than traditional computing platforms. Brain-inspired algorithms show particular promise for processing heterogeneous medical data, adapting to individual patient patterns, and providing explainable decisions through biologically plausible reasoning mechanisms. This approach aligns well with the need for sustainable, adaptive healthcare AI systems that can operate in resource-constrained environments.[121, 122]

VI. Conclusion

A. Key Findings and Insights

This extensive analysis has analyzed the revolutionary influence of artificial intelligence within healthcare sectors, uncovering various essential findings regarding the present condition and future direction of medical AI. The evidence shows that AI systems consistently perform diagnostics at a level that is equal to or better than that of human experts in certain fields. For example, many studies have shown that AI systems can classify brain tumors, predict cardiovascular risk, and analyze medical images with accuracies of 95% to 99% or higher, as shown in Tables II, III, and IV. These technological advancements underscore the capacity of AI to substantially improve diagnostic precision and efficiency across several medical professions, as comprehensively delineated in Table X. The incorporation of Explainable AI methodologies has become an essential element in fostering

clinical trust and promoting adoption. Techniques like SHAP, LIME, and Grad-CAM make AI judgments clear enough for healthcare workers to comprehend and check them. This solves the "black box" problem that has kept AI from being widely used in clinical settings. The comparative analysis in Table VII shows how multiple XAI methods can be used together to improve diverse healthcare applications, from tabular clinical data to medical imaging. The information in Table X shows that explainability and trust are essential for successful clinical implementation. This means that different sets of stakeholders and clinical settings need different approaches.

Personalized treatment is one of the most important improvements in modern medicine. AI makes precision medicine possible by taking into account a person's genetic profile, lifestyle, and medical history. The frameworks in Table VIII show how multi-omics integration, longitudinal data analysis, and adaptive learning systems can make treatment plans unique to each patient, instead of using the old "one-size-fits-all" method. Table X shows that these personalized strategies have a lot of potential for treating chronic illnesses and making complex therapies work better. But they also need a strong data infrastructure and a lot of computing power to work well. Even with these technological improvements, there are still a lot of problems with ethics, laws, and putting things into practice in the real world. Algorithmic bias, data privacy issues, and problems with interoperability are still making it hard for AI to be widely used. At the same time, regulatory systems often have a hard time keeping up with how quickly AI technologies are changing. The obstacles to adoption listed in Table IX show how difficult it is to use AI in healthcare settings. As shown again in Table X, these problems are technological, organizational, and social in nature. To make sure that implementation is safe and fair, researchers, clinicians, policymakers, and technology developers need to work together.

B. Recommendations for Clinical Implementation

Based on the comprehensive analysis presented in this review, we propose several evidence-based recommendations to facilitate the successful integration of AI technologies in healthcare settings. These recommendations address technical, ethical, and operational dimensions of AI implementation, providing a roadmap for stakeholders including healthcare providers, technology developers, regulatory bodies, and policymakers. The strategic recommendations outlined in Table X provide a structured approach to addressing the identified challenges while maximizing the benefits of healthcare AI.

Develop Standardized Evaluation Frameworks: Set up thorough validation protocols that look at AI systems from many angles, such as how well they work technically, how useful they are in the clinic, and how well they work in the real world. These frameworks should include the different metrics listed in Table V to make sure that studies are evaluated in the same way and that different AI approaches can be compared in a meaningful way. Implementation must encompass stringent external validation utilizing independent datasets that reflect varied patient populations and clinical environments. As shown in Table X, ongoing performance monitoring is necessary to keep the model accurate and useful as clinical practices and patient populations change.

Prioritize Explainability and Interpretability: Require that all clinical AI systems use XAI techniques, with explanations that meet the needs of all stakeholders. Clinicians need easy-to-understand reasons for AI recommendations that are specific to each case. Patients need clear explanations of how their data is used and what conclusions are drawn. Regulatory approvals ought to encompass mandates for transparency and interpretability, accompanied by validation ensuring that explanations are congruent with clinical knowledge and reasoning processes, as illustrated in Table VII. The suggestions in Table X show how important it is to customize explanations for different user roles and make sure they are clinically relevant so that they help rather than make clinical decision-making harder.

Address Algorithmic Bias Proactively: Use full bias detection and mitigation strategies at every stage of AI development. This entails the curation of diverse datasets, ongoing surveillance for performance discrepancies among demographic groups, and the creation of fairness-aware algorithms. Healthcare organizations ought to implement bias auditing protocols and equity impact assessments for all deployed AI systems, guaranteeing that these technologies mitigate rather than aggravate existing healthcare disparities. Bias mitigation necessitates proactive strategies across the entire AI lifecycle, encompassing data collection, deployment, and monitoring, as indicated in Table X.

Following the suggestions in Table X, healthcare will be able to responsibly and effectively use AI technologies. By proactively addressing technical, ethical, and operational challenges, stakeholders can leverage the transformative potential of AI to enhance patient outcomes, improve clinical efficiency, and broaden access to high-quality healthcare services worldwide. To get from black-box algorithms to clear, reliable clinical tools, people from different fields and sectors need to work together for a long time, with a shared goal of putting patient welfare at the heart of technological progress. The framework in Table X gives a complete guide to how to get through this complicated landscape, balancing innovation with responsibility to make sure that AI technologies help patients and healthcare systems around the world.

REFERENCES

[1] E. J. Topol, "High-performance medicine: the convergence of human and artificial intelligence," *Nature medicine*, vol. 25, no. 1, pp. 44–56, 2019.

TABLE X: Comprehensive Summary of Key Findings, Insights, and Recommendations for Healthcare AI Implementation

Category	Key Findings	Critical Insights	Strategic Recommendations
Technical Performance	AI models achieve 95–99% accuracy in diagnostics; deep learning excels in imaging; ensemble methods enhance robustness.	Performance varies across populations and settings; real-world accuracy often lower; computational costs remain high.	Adopt standardized evaluation frameworks, ensure external validation, and maintain continuous performance monitoring.
Explainability and Trust	XAI improves interpretability using SHAP, LIME, and Grad-CAM; interpretability increases clinician confidence.	Different XAI methods suit specific data types; explanations must align with clinical logic; balance accuracy and transparency.	Mandate explainability in clinical systems, tailor explanations to user roles, and validate their clinical relevance.
Clinical Integration	Workflow integration remains difficult; human–AI collaboration and mobile health solutions are emerging.	Seamless integration and clinician training are critical; organizational readiness varies widely.	Apply user-centered design, implement training initiatives, and develop change management strategies.
Ethical Considerations	Algorithmic bias and privacy concerns persist; accountability mechanisms are still limited.	Bias mitigation must be proactive; privacy-preserving approaches are advancing; legal liability remains unclear.	Establish bias auditing frameworks, promote federated learning, and define accountability standards.
Regulatory Compliance	Regulatory evolution is slow; global alignment limited; validation requirements increasing.	Traditional frameworks struggle with adaptive AI; pre-market approvals are lengthy; post-market surveillance essential.	Develop adaptive regulatory pathways, align international standards, and enforce ongoing monitoring.
Future Directions	Federated learning enhances privacy; generative AI improves efficiency; quantum computing offers new potential.	Technology progresses faster than adoption; infrastructure and workforce adaptation remain major barriers.	Invest in emerging technologies, strengthen digital infrastructure, and promote AI literacy and skill development.

[2] I. Rehman and H.-A. Pham, "Cortex vision: Detection of ophthalmic disease using machine learning algorithm," in *International Conference on Smart Objects and Technologies for Social Good*. Springer, 2024, pp. 138–149.

[3] S. K. GU, A. Purushothaman *et al.*, "Alzfusionformer: Integrating multiple transformers for early alzheimer's disease detection from multi-modal data," *Biomedical Signal Processing and Control*, vol. 112, p. 108601, 2026.

[4] A. Sethi, S. Dharmavaram, and S. K. Somasundaram, "Explainable artificial intelligence (xai) approach to heart disease prediction," in *2024 3rd International Conference on Artificial Intelligence For Internet of Things (AIIoT)*, 2024, pp. 1–6.

[5] A.-M. G. Alhejaily, "Artificial intelligence in healthcare," *Biomedical Reports*, vol. 22, no. 1, pp. 1–8, 2025.

[6] M. Y. Shaheen, "Applications of artificial intelligence (ai) in healthcare: A review," *ScienceOpen Preprints*, 2021.

[7] P. Kandhare, M. Kurlekar, T. Deshpande, and A. Pawar, "A review on revolutionizing healthcare technologies with ai and ml applications in pharmaceutical sciences," *Drugs and Drug Candidates*, vol. 4, no. 1, p. 9, 2025.

[8] A. Chaddad, Y. Hu, Y. Wu, B. Wen, and R. Kateb, "Generalizable and explainable deep learning for medical image computing: An overview," *Current Opinion in Biomedical Engineering*, vol. 33, p. 100567, 2025.

[9] K. Thenmozhi and P. Deepika, "Heart disease prediction using classification with different decision tree techniques," *International Journal of Engineering Research and General Science*, vol. 2, no. 6, pp. 6–11, 2014.

[10] S. A. Sanchula, "Explainable ai (xai) for a machine learning heart disease prediction model," 2025.

[11] D. A. Bilal, A. Alzahrani, K. Almohammadi, M. Saleem, M. S. Farooq, and R. Sarwar, "Explainable ai-driven intelligent system for precision forecasting in cardiovascular disease," *Frontiers in Medicine*, vol. 12, p. 1596335, 2025.

[12] O. M. Yaseen and M. M. Rashid, "An explainable artificial intelligence (xai) methodology for heart disease classification."

[13] D. B. Olawade, A. A. Soladoye, B. A. Omodunbi, N. Aderinto, and I. A. Adeyanju, "Comparative analysis of machine learning models for coronary artery disease prediction with optimized feature selection," *International Journal of Cardiology*, p. 133443, 2025.

[14] I. Kiran, S. Ali, M. Alhussein, S. Aslam, K. Aurangzeb *et al.*, "An ai-enabled framework for transparency and interpretability in cardiovascular disease risk prediction." *Computers, Materials & Continua*, vol. 82, no. 3, 2025.

[15] M. H. Al-Adhaileh, M. I. Ahmed Al-mashhadani, E. M. Alzahrani, and T. H. Aldhyani, "Improving heart attack prediction accuracy performance using machine learning and deep learning algorithms," *Iraqi Journal for Computer Science and Mathematics*, vol. 6, no. 2, p. 3, 2025.

[16] S. K. Mishra, R. Sreelakshmy, G. Kumar, D. Kumar, and S. Kumar, "Advancing heart attack prediction:

Machine learning for enhanced cardiac risk analysis," in *Pioneering Approaches in Data Management*. IGI Global Scientific Publishing, 2025, pp. 215–234.

[17] A. Gnanavelu, C. Venkataramu, and R. Chintakunta, "Cardiovascular disease prediction using machine learning metrics," *Journal of Young Pharmacists*, vol. 17, no. 1, pp. 226–233, 2025.

[18] W. Alsabhan and A. Alfadhly, "Effectiveness of machine learning models in diagnosis of heart disease: a comparative study," *Scientific Reports*, vol. 15, no. 1, p. 24568, 2025.

[19] S. J. Mukhyber, "Classification of heart disease using feature selection and machine learning techniques," *Physical Sciences, Life Science and Engineering*, vol. 2, no. 3, pp. 9–9, 2025.

[20] B. Ayesha Akram, M. Irfan, A. Zafar, S. Khan, and R. Shaheen, "Impact of computing platforms on classifier performance in heart disease prediction," *Mehran University Research Journal of Engineering and Technology*, vol. 44, no. 2, pp. 155–163, 2025.

[21] S. I. Saimon, I. Islam, S. I. Abir, N. Sultana, M. S. Hossain, and S. A. Al Shiam, "Advancing neurological disease prediction through machine learning techniques," *Journal of Computer Science and Technology Studies*, vol. 7, no. 1, pp. 139–156, 2025.

[22] A. O. Esan, D. B. Olawade, A. A. Soladoye, B. A. Omodunbi, I. A. Adeyanju, and N. Aderinto, "Explainable ai for parkinson's disease prediction: A machine learning approach with interpretable models," *Current Research in Translational Medicine*, p. 103541, 2025.

[23] J. Li, C. Song, T. Li, W. Jia, Z. Qian, Y. Peng, Y. Xu, and Z. Jin, "Construction and validation of a nomogram model for predicting the risk of neonatal sepsis complicated by purulent meningitis," *Journal of Inflammation Research*, pp. 7183–7194, 2025.

[24] F. Lin, C. Chen, Y. Li, and H. Liu, "Machine learning–based diagnosis of cryptococcal meningitis and tuberculous meningitis: A single-center retrospective clinical study," in *Open Forum Infectious Diseases*, vol. 12, no. 5. Oxford University Press US, 2025, p. ofaf217.

[25] Y. Chen, S. Wang, C. Wang, N. Zhang, Y. Li, H. Shi, P. Zou, H. He, and Y. Wang, "Establishment of a machine learning-based prediction model for short-term adverse prognosis in neonatal bacterial meningitis," *iLABMED*, vol. 3, no. 3, pp. 292–302, 2025.

[26] M. S. Elhadidy, A. T. Elgohr, M. El-Geneedy, S. Akram, and H. M. Kasem, "Comparative analysis for accurate multi-classification of brain tumor based on significant deep learning models," *Computers in Biology and Medicine*, vol. 188, p. 109872, 2025.

[27] M. N. E. Farandi, A. K. Muda, S. Winarno, and H. Basiron, "Comparative study of deep learning models for mri-based brain tumor classification," *Journal of Future Artificial Intelligence and Technologies*, vol. 2, no. 3, pp. 370–387, 2025.

[28] M. Nahiduzzaman, L. F. Abdulrazak, H. B. Kibria, A. Khandakar, M. A. Ayari, M. F. Ahamed, M. Ahsan, J. Haider, M. A. Moni, and M. Kowalski, "A hybrid explainable model based on advanced machine learning and deep learning models for classifying brain tumors using mri images," *Scientific Reports*, vol. 15, no. 1, p. 1649, 2025.

[29] K. M. Hosny, M. A. Mohammed, R. A. Salama, and A. M. Elshewey, "Explainable ensemble deep learning-based model for brain tumor detection and classification," *Neural Computing and Applications*, vol. 37, no. 3, pp. 1289–1306, 2025.

[30] M. A. Ilani, D. Shi, and Y. M. Banad, "T1-weighted mri-based brain tumor classification using hybrid deep learning models," *Scientific Reports*, vol. 15, no. 1, p. 7010, 2025.

[31] E. Güvenç, M. Ersoy, and G. Çetin, "Deep learning-based automated segmentation of brain tumors using synthetic mr images generated with dcgan," *Computer Standards & Interfaces*, p. 104054, 2025.

[32] S. S. Hussain, N. A. Wani, J. Kaur, N. Ahmad, and S. Ahmad, "Next-generation automation in neuro-oncology: advanced neural networks for mri-based brain tumor segmentation and classification," *IEEE Access*, 2025.

[33] A. La Moglia and K. Mohamad Almustafa, "Breast cancer prediction using machine learning classification algorithms," *Intelligence-Based Medicine*, vol. 11, p. 100193, 2025. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S2666521224000607

[34] B. Almarri, G. Gupta, R. Kumar, V. Vandana, F. Asiri, and S. B. Khan, "The bcpm method: decoding breast cancer with machine learning," *BMC medical imaging*, vol. 24, no. 1, p. 248, 2024.

[35] M. Montazeri, M. Montazeri, M. Montazeri, and A. Beigzadeh, "Machine learning models in breast cancer survival prediction," *Technology and Health Care*, vol. 24, no. 1, pp. 31–42, 2016.

[36] X. Qian, J. Pei, C. Han, Z. Liang, G. Zhang, N. Chen, W. Zheng, F. Meng, D. Yu, Y. Chen *et al.*, "A multimodal machine learning model for the stratification of breast cancer risk," *Nature Biomedical Engineering*, vol. 9, no. 3, pp. 356–370, 2025.

[37] Y. Cakmak and I. Pacal, "Enhancing breast cancer diagnosis: A comparative evaluation of machine learning algorithms using the wisconsin dataset," *Journal of Operations Intelligence*, vol. 3, no. 1, pp. 175–196, 2025.

[38] A. La Moglia and K. M. Almustafa, "Breast cancer prediction using machine learning classification algorithms," *Intelligence-Based Medicine*, vol. 11, p. 100193, 2025.

[39] M. A. Naji, S. El Filali, K. Aarika, E. H. Benlahmar, R. Ait Abdelouhahid, and O. Debauche, "Machine learning algorithms for breast cancer prediction and diagnosis," *Procedia computer science*, vol. 191, pp.

487–492, 2021.

[40] O. Tarawneh, M. Otair, M. Husni, H. Y. Abuaddous, M. Tarawneh, and M. A. Almomani, "Breast cancer classification using decision tree algorithms," *International Journal of Advanced Computer Science and Applications*, vol. 13, no. 4, 2022.

[41] R. Sumbaly, N. Vishnusri, and S. Jeyalatha, "Diagnosis of breast cancer using decision tree data mining technique," *International Journal of Computer Applications*, vol. 98, no. 10, 2014.

[42] A. T. Garba and H. S. Hamza, "Interpretable machine learning approach for breast cancer classification," *Human-Centric Intelligent Systems*, pp. 1–15, 2025.

[43] H. Duan, Y. Zhang, H. Qiu, X. Fu, C. Liu, X. Zang, A. Xu, Z. Wu, X. Li, Q. Zhang *et al.*, "Machine learning-based prediction model for distant metastasis of breast cancer," *Computers in Biology and Medicine*, vol. 169, p. 107943, 2024.

[44] Y. A. Asaye, P. Annamalai, and L. G. Ayalew, "Detection of kidney stone from ultrasound images using machine learning algorithms," *Scientific African*, vol. 28, p. e02618, 2025.

[45] R. Rawal, "Breast cancer prediction using machine learning," *Journal of Emerging Technologies and Innovative Research (JETIR)*, vol. 13, no. 24, p. 7, 2020.

[46] Z. Yu, T. D. Nguyen, L. Ju, Y. Gal, M. Sashindranath, P. Bonnington, L. Zhang, V. Mar, and Z. Ge, "Hierarchical skin lesion image classification with prototypical decision tree," *npj Digital Medicine*, vol. 8, no. 1, p. 26, 2025.

[47] K. M. Almustafa, "Predictive modeling and optimization in dermatology: Machine learning for skin disease classification," *Computers in Biology and Medicine*, vol. 189, p. 109946, 2025.

[48] G. Yang, S. Luo, and P. Greer, "Advancements in skin cancer classification: a review of machine learning techniques in clinical image analysis," *Multimedia tools and applications*, vol. 84, no. 11, pp. 9837–9864, 2025.

[49] S. Verma and M. Kumar, "A hybrid machine learning model for skin disease classification using discrete wavelet transform and gray level co-occurrence matrix (glcm)," *Multimedia Tools and Applications*, vol. 84, no. 14, pp. 12 835–12 853, 2025.

[50] S. S. Mohammed and J. M. Al-Tuwaijari, "Skin disease classification system based on machine learning technique: a survey," in *IOP conference series: materials science and engineering*, vol. 1076, no. 1. IOP Publishing, 2021, p. 012045.

[51] M. Ahammed, M. Al Mamun, and M. S. Uddin, "A machine learning approach for skin disease detection and classification using image segmentation," *Healthcare Analytics*, vol. 2, p. 100122, 2022.

[52] D. Bordoloi, V. Singh, K. Kaliyaperumal, M. Ritonga, M. Jawarneh, T. Kassanuk, and J. Quiñonez-Choquecota, "Classification and detection of skin disease based on machine learning and image processing evolutionary models," *Computer Assisted Methods in Engineering and Science*, vol. 30, no. 2, pp. 247–256, 2023.

[53] W. Gao, L. Shao, F. Li, L. Dong, C. Zhang, Z. Deng, P. Qin, W. Wei, and L. Ma, "Fundus photograph-based cataract evaluation network using deep learning," *Frontiers in Physics*, vol. 11, 2024. [Online]. Available: https://www.frontiersin.org/articles/10.3389/fphy.2023.1235856

[54] M. S. Junayed, M. B. Islam, A. Sadeghzadeh, and S. Rahman, "Cataractnet: An automated cataract detection system using deep learning for fundus images," *IEEE Access*, vol. 9, pp. 128 799–128 808, 2021.

[55] A. T. Khalaf and S. K. Abdulateef, "Ophthalmic diseases classification based on yolov8," *Journal of Robotics and Control (JRC)*, vol. 5, no. 2, 2024.

[56] N. Ranjan, R. H. A. Shejul, K. Harne, and S. Bhat, "Detection of cataract and its level based on deep learning using mobile application," 2023.

[57] C. S. Vasan, S. Gupta, M. Shekhar, K. Nagu, L. Balakrishnan, R. D. Ravindran, T. Ravilla, and G.-B. B. Subburaman, "Accuracy of an artificial intelligence-based mobile application for detecting cataracts: Results from a field study," *Indian Journal of Ophthalmology*, vol. 71, no. 8, pp. 2984–2989, 2023.

[58] M. Yang, J.-J. Yang, Q. Zhang, Y. Niu, and J. Li, "Classification of retinal image for automatic cataract detection," in *2013 IEEE 15th International Conference on e-Health Networking, Applications and Services (Healthcom 2013)*, 2013, pp. 674–679.

[59] V. Agarwal, V. Gupta, V. M. Vashisht, K. Sharma, and N. Sharma, "Mobile application based cataract detection system," in *2019 3rd International Conference on Trends in Electronics and Informatics (ICOEI)*, 2019, pp. 780–787.

[60] M. K. Behera, S. Chakravarty, A. Gourav, and S. Dash, "Detection of nuclear cataract in retinal fundus image using radialbasis functionbasedsvm," in *2020 Sixth International Conference on Parallel, Distributed and Grid Computing (PDGC)*, 2020, pp. 278–281.

[61] Y. N. Fuadah, A. W. Setiawan, T. L. Mengko, and Budiman, "Mobile cataract detection using optimal combination of statistical texture analysis," in *2015 4th International Conference on Instrumentation, Communications, Information Technology, and Biomedical Engineering (ICICI-BME)*, 2015, pp. 232–236.

[62] E. N. Mutlu, A. Devim, A. A. Hameed, and A. Jamil, "Deep learning for liver disease prediction," in *Mediterranean Conference on Pattern Recognition and Artificial Intelligence*. Springer, 2021, pp. 95–107.

[63] T. M. Hassan, M. Elmogy, and E.-S. Sallam, "Diagnosis of focal liver diseases based on deep learning technique for ultrasound images," *Arabian Journal for Science and Engineering*, vol. 42, no. 8, pp. 3127–3140, 2017.

[64] R. Manjunath, A. Ghanshala, and K. Kwadiki, "Deep learning algorithm performance evaluation in detection

and classification of liver disease using ct images," *Multimedia Tools and Applications*, vol. 83, no. 1, pp. 2773–2790, 2024.

[65] K. Gupta, N. Jiwani, N. Afreen, and D. Divyarani, "Liver disease prediction using machine learning classification techniques," in *2022 IEEE 11th International conference on communication systems and network technologies (CSNT)*. IEEE, 2022, pp. 221–226.

[66] O. M. Khaled, A. Z. Elsherif, A. Salama, M. Herajy, and E. Elsedimy, "Evaluating machine learning models for predictive analytics of liver disease detection using healthcare big data," *International Journal of Electrical and Computer Engineering (IJECE)*, vol. 15, no. 1, pp. 1162–1174, 2025.

[67] G. Zhu, Y. Song, Z. Lu, Q. Yi, R. Xu, Y. Xie, S. Geng, N. Yang, L. Zheng, X. Feng *et al.*, "Machine learning models for predicting metabolic dysfunction-associated steatotic liver disease prevalence using basic demographic and clinical characteristics," *Journal of Translational Medicine*, vol. 23, no. 1, p. 381, 2025.

[68] S. S. Dash, S. K. Nayak, D. Mishra, and B. R. Senapati, "Ensemble machine learning techniques for the identification of liver diseases: A comparative approach," in *2025 International Conference on Innovations in Intelligent Systems: Advancements in Computing, Communication, and Cybersecurity (ISAC3)*. IEEE, 2025, pp. 1–6.

[69] B. Bwanya, S. Lodhi, T. M. de Kok, L. Ladeira, M. C. Verheijen, D. G. Jennen, and F. Caiment, "Machine learning classification of steatogenic compounds using toxicogenomics profiles," *Toxicology*, p. 154237, 2025.

[70] National Institutes of Health (NIH) / National Institute of Environmental Health Sciences (NIEHS), "Toxicogenomics database (toxicodb)," https://www.toxicodb.ca/datasets/1, 2023, a resource for toxicogenomics research, providing access to datasets including the Open TG-GATEs database. [Online]. Available: https://www.toxicodb.ca/

[71] S. H. Chowdhury, M. Mamun, T. A. Shaikat, M. I. Hussain, S. Iqbal, and M. M. Hossain, "An ensemble approach for artificial neural network-based liver disease identification from optimal features through hybrid modeling integrated with advanced explainable ai," *Medinformatics*, vol. 2, no. 2, pp. 107–119, 2025.

[72] M. Mamun, S. H. Chowdhury, M. M. Hossain, M. Khatun, and S. Iqbal, "Explainability enhanced liver disease diagnosis technique using tree selection and stacking ensemble-based random forest model," *Informatics and Health*, vol. 2, no. 1, pp. 17–40, 2025.

[73] P. Kumar, D. Singh, and J. S. Samagh, "A hybrid model for kidney stone detection using deep learning," *IJSTM*, vol. 13, pp. 65–85, 2024.

[74] Ö. Sabuncu, B. Bilgehan, E. Kneebone, and O. Mirzaei, "Effective deep learning classification for kidney stone using axial computed tomography (ct) images," *Biomedical Engineering/Biomedizinische Technik*, vol. 68, no. 5, pp. 481–491, 2023.

[75] E. G. Onal and H. Tekgul, "Assessing kidney stone composition using smartphone microscopy and deep neural networks," *BJUI compass*, vol. 3, no. 4, pp. 310–315, 2022.

[76] V. Rathva and S. Degadwala, "Ensemble deep learning for enhanced ct-scan kidney stone classification," 2025.

[77] A. Pimpalkar, D. K. J. B. Saini, N. Shelke, A. Balodi, G. Rapate, and M. Tolani, "Fine-tuned deep learning models for early detection and classification of kidney conditions in ct imaging," *Scientific Reports*, vol. 15, no. 1, p. 10741, 2025.

[78] O. Iparraguirre-Villanueva, G. Paucar-Palomino, and C. Paulino-Moreno, "From data to diagnosis: evaluation of machine learning models in predicting kidney stones," *Neural Computing and Applications*, pp. 1–14, 2025.

[79] A. Khan, R. Das, and M. Parameshwara, "Detection of kidney stone using digital image processing: a holistic approach," *Engineering Research Express*, vol. 4, no. 3, p. 035040, 2022.

[80] A. R. Panda, J. Tripathy, M. K. Mishra, L. Mohanty, J. J. Jena, and M. K. Gourisaria, "Kidney stone prediction based on urine analysis: A comprehensive study of machine learning models," in *2025 International Conference on Emerging Systems and Intelligent Computing (ESIC)*, 2025, pp. 748–753.

[81] M. E. Febrian, F. X. Ferdinan, G. P. Sendani, K. M. Suryanigrum, and R. Yunanda, "Diabetes prediction using supervised machine learning," *PCS*, vol. 216, pp. 21–30, 2023.

[82] A. e. a. G R, "Early detection of diabetes using ml based classification algorithms," 03 2024, pp. 148–157.

[83] K. Dwivedi, H. O. Sharan, and V. Vishwakarma, "Analysis of decision tree for diabetes prediction," *International Journal of Engineering and Technical Research*, vol. 9, no. 10.31873, 2019.

[84] M. Soni and S. Varma, "Diabetes prediction using machine learning techniques," *International Journal of Engineering Research & Technology (IJERT)*, vol. 9, no. 9, pp. 921–925, 2020.

[85] T. M. Alam, M. A. Iqbal, Y. Ali, A. Wahab, S. Ijaz, T. I. Baig, A. Hussain, M. A. Malik, M. M. Raza, S. Ibrar *et al.*, "A model for early prediction of diabetes," *Informatics in Medicine Unlocked*, vol. 16, p. 100204, 2019.

[86] P. Sonar and K. JayaMalini, "Diabetes prediction using different machine learning approaches," in *2019 3rd International Conference on Computing Methodologies and Communication (ICCMC)*, 2019, pp. 367–371.

[87] A. M. Posonia, S. Vigneshwari, and D. J. Rani, "Machine learning based diabetes prediction using decision tree j48," in *2020 3rd International Conference on Intelligent Sustainable Systems (ICISS)*, 2020, pp. 498–502.

[88] T. Dudkina, I. Meniailov, K. Bazilevych, S. Krivtsov,

and A. Tkachenko, "Classification and prediction of diabetes disease using decision tree method." in *IT&AS*, 2021, pp. 163–172.

[89] R. R. Kothinti, "Deep learning in healthcare: Transforming disease diagnosis, personalized treatment, and clinical decision-making through ai-driven innovations," *World Journal of Advanced Research and Reviews*, vol. 24, no. 2, pp. 2841–2856, 2024.

[90] S. S. A. Ali, K. Memon, N. Yahya, and S. Khan, "Deep learning frameworks for mri-based diagnosis of neurological disorders: A systematic review and meta-analysis," *Artificial Intelligence Review*, vol. 58, no. 6, p. 171, 2025.

[91] R. K. Patel, A. Choudhary, N. Kumari, and H. S. Lamkuche, "Pneumonia screening from radiology images using homomorphic transformation filter-based fawt and customized vgg-16," *International Journal of Imaging Systems and Technology*, vol. 35, no. 3, p. e70093, 2025.

[92] C.-T. Hsu, C.-Y. Huang, C.-H. Chen, Y.-L. Deng, S.-Y. Lin, and M.-J. Wu, "Machine learning models to predict osteoporosis in patients with chronic kidney disease stage 3–5 and end-stage kidney disease," *Scientific Reports*, vol. 15, no. 1, p. 11391, 2025.

[93] R. M. Abdullah, L. A. Saad, Z. M. Alasmari, G. A. Ali, and A. Muniasamy, "Human disease prediction mobile application using machine learning," in *International Conference on Business and Technology*. Springer, 2024, pp. 177–186.

[94] G. Çınarer and B. G. Emiroğlu, "Classificatin of brain tumors by machine learning algorithms," in *2019 3rd international symposium on multidisciplinary studies and innovative technologies (ISMSIT)*. IEEE, 2019, pp. 1–4.

[95] H. Chen, N. Wang, X. Du, K. Mei, Y. Zhou, and G. Cai, "Classification prediction of breast cancer based on machine learning," *Computational intelligence and neuroscience*, vol. 2023, no. 1, p. 6530719, 2023.

[96] A. Nadeem, M. Naveed, M. Islam Satti, H. Afzal, T. Ahmad, and K.-I. Kim, "Depression detection based on hybrid deep learning sscl framework using self-attention mechanism: An application to social networking data," *Sensors*, vol. 22, no. 24, p. 9775, 2022.

[97] M. Islam, M. Usman, A. Mahmood, A. A. Abbasi, and O.-Y. Song, "Predictive analytics framework for accurate estimation of child mortality rates for internet of things enabled smart healthcare systems," *International Journal of Distributed Sensor Networks*, vol. 16, no. 5, p. 1550147720928897, 2020.

[98] M. I. Satti, M. W. Ali, A. Irshad, and M. A. Shah, "Studying infant mortality: A demographic analysis based on data mining models," *Open Life Sciences*, vol. 18, no. 1, p. 20220643, 2023.

[99] F. Iqbal, M. I. Satti, A. Irshad, and M. A. Shah, "Predictive analytics in smart healthcare for child mortality prediction using a machine learning approach," *Open Life Sciences*, vol. 18, no. 1, p. 20220609, 2023.

[100] J. A. Muhammad, and Khan, M. Abaker, A. Daud, and A. Irshad, "Unified large language models for misinformation detection in low-resource linguistic settings," *arXiv preprint arXiv:2506.01587*, 2025.

[101] A. B. E. Ghazali, A. Fiaz, and M. Islam, "Lightweight multi-stage holistic attention-based network for image super-resolution," *IET Image Processing*, vol. 19, no. 1, p. e70013, 2025.

[102] M. Islam and M. Azhar, "Sarcasm detection in multilingual text through embedding-enhanced language models: Bert variants," in *2024 26th International Multi-Topic Conference (INMIC)*. IEEE, 2024, pp. 1–6.

[103] Y. Shah, Y. Liu, F. Shah, F. Shah, M. I. Satti, E. Asenso, M. Shabaz, and A. Irshad, "Covid-19 and commodity effects monitoring using financial & machine learning models," *Scientific African*, vol. 21, p. e01856, 2023.

[104] A. Garg, N. B. Garg, and M. Bansal, "Revolutionizing heart attack prevention: Machine learning models in smart healthcare," *SN Computer Science*, vol. 6, no. 2, pp. 1–14, 2025.

[105] X. Sun, R. Jing, and Y. Li, "Predicting purulent meningitis in very preterm infants: a novel clinical model," *BMC pediatrics*, vol. 25, no. 1, p. 3, 2025.

[106] F. J. Dorfner, J. B. Patel, J. Kalpathy-Cramer, E. R. Gerstner, and C. P. Bridge, "A review of deep learning for brain tumor analysis in mri," *NPJ Precision Oncology*, vol. 9, no. 1, p. 2, 2025.

[107] F. M. Abdulatif and A. W. Ali, "Diagnosis of skin diseases in children by ensemble machine learning techniques," in *2025 International Conference on Computer Science and Software Engineering (CSASE)*. IEEE, 2025, pp. 160–167.

[108] Y. Yang, J. Liu, C. Sun, Y. Shi, J. C. Hsing, A. Kamya, C. A. Keller, N. Antil, D. Rubin, H. Wang *et al.*, "Nonalcoholic fatty liver disease (nafld) detection and deep learning in a chinese community-based population," *European Radiology*, vol. 33, no. 8, pp. 5894–5906, 2023.

[109] M. T. Ribeiro, S. Singh, and C. Guestrin, "" why should i trust you?" explaining the predictions of any classifier," *Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining*, pp. 1135–1144, 2016.

[110] P. N. Srinivasu, N. Sandhya, R. H. Jhaveri, and R. Raut, "From blackbox to explainable ai in healthcare: existing tools and case studies," *Mobile Information Systems*, vol. 2022, no. 1, p. 8167821, 2022.

[111] S. M. Lundberg and S.-I. Lee, "A unified approach to interpreting model predictions," *Advances in neural information processing systems*, vol. 30, 2017.

[112] R. R. Selvaraju, M. Cogswell, A. Das, R. Vedantam, D. Parikh, and D. Batra, "Grad-cam: Visual explanations from deep networks via gradient-based localization," in *Proceedings of the IEEE international conference on computer vision*, 2017, pp. 618–626.

[113] K. Lamba and S. Rani, "A novel approach of brain-computer interfacing (bci) and grad-cam based explainable artificial intelligence: Use case scenario for smart healthcare," *Journal of Neuroscience Methods*, vol. 408, p. 110159, 2024.

[114] G. Chen, C. Liu, G. A. Ooi, M. Tan, Z. Xie, J. Yin, J. W. L. Yip, W. Zhang, J. Zhu, and B. C. Ooi, "Generative ai for healthcare: Fundamentals, challenges, and perspectives," *arXiv preprint arXiv:2510.24551*, 2025.

[115] L. J. Fahrner, E. Chen, E. Topol, and P. Rajpurkar, "The generative era of medical ai," *Cell*, vol. 188, no. 14, pp. 3648–3660, 2025.

[116] B. Pramanik, D. Ghosh, D. Ghosh, and K. Paul, "Beyond prediction: How generative ai is creating new healthcare realities," in *Revolutionizing Healthcare 5.0: The Power of Generative AI: Advancements in Patient Care Through Generative AI Algorithms*. Springer, 2025, pp. 219–233.

[117] S. Corli, L. Moro, D. Dragoni, M. Dispenza, and E. Prati, "Quantum machine learning algorithms for anomaly detection: A review," *Future Generation Computer Systems*, vol. 166, p. 107632, 2025.

[118] R. S. Gupta, C. E. Wood, T. Engstrom, J. D. Pole, and S. Shrapnel, "A systematic review of quantum machine learning for digital health," *npj Digital Medicine*, vol. 8, no. 1, p. 237, 2025.

[119] M. K. Saggi, A. S. Bhatia, I. K. Mensah, H. Gowher, and S. Kais, "Multi-omic and quantum machine learning integration for lung subtypes classification," *Future Generation Computer Systems*, vol. 174, p. 107905, 2026.

[120] A. Sonavane, S. Jaiswar, M. Mistry, A. Aylani, and D. Hajoary, "Quantum machine learning models in healthcare: Future trends and challenges in healthcare," *Quantum Computing for Healthcare Data*, pp. 167–187, 2025.

[121] D. Gandolfi, J. Mapelli, and F. M. Puglisi, "Brain-inspired computing: from neuroscience to neuromorphic electronics for new forms of artificial intelligence," p. 1565811, 2025.

[122] R. Sille, "Neuromorphic horizons: Exploring the intersection of generative ai and brain-inspired computing in secured healthcare," in *CyberMedics*. CRC Press, 2025, pp. 51–72.