真空泵/Vacuum Pump


型式 VP0125









空气量和消耗功率 / Airflow & Electric Current







/The characteristic charts are for reference only and are not guaranteed.

外形及安装尺寸图 / Dimensional Outline Drawing (单位 / Unit:mm)



规格/Specifications

-33.3 kPa (-250 mmHg) -333 mbar -9.84 in. Hg		
7 L/min 0.247 cfm		
100 V AC	115 V AC	230 V AC
15 W / 14 W	14 W	15 W
50 Hz / 60 Hz	60 Hz	50 Hz
10,000 小时 / hours		
<i>φ</i> 6 mm (外径) 软管接头 /6mm O.D. hose barb		
φ6 mm (外径) 软管接头 / 6mm O.D. hose barb		
连续 / Continuous		
UL 规格品:相当于 B 类 /BtarUL		
48 (L) x 62 (W) mm 1-57/64" (L) x 2-7/16" (W)		
0.7 kg 1.54 Lbs		
200 mm 7-7/8"		
	-333 100 V AC 15 W / 14 W 50 Hz / 60 Hz Φ6 mm (2) Φ6 mm (2) UL 48 1-57/	-333 mbar -9.84 ir 7 L/min 0.247 cfm 100 V AC 115 V AC 15 W / 14 W 14 W 50 Hz / 60 Hz 10,000 小时 /hours 中6 mm (外径) 软管接头 /er 年续 /continuous UL 规格品:相当于 E/Bfor UL 48 (L) x 62 (W) m 1-57/64" (L) x 2-7/16 0.7 kg 1.54 Lb 200 mm

用途例 / Application Examples



