

The integretion of Apache Flink SQL and Apache Calcite

陈玉兆 Danny Chan Apache Calcite PMC & Committer

FLINK FORWARD # ASIA

实时即未来 # Real-time Is The Future





Contents 目录

01 Calcite 基础介绍


The background of Apache Calcite.

02 Flink SQL 集成 Calcite

The integretion of Flink SQL and Apache Calcite

03 展望未来

The future work







Calcite 基础介绍 | 项目背景

Apache Calcite 是一个用于构建数据管理系统的可扩展框架

Apache Calcite is an extensible framework for building data management systems

起源 2012 - 进入 Apache 孵化器孵化 Apache incubator in 2012

问题 构建一个高质量的数据库需要 ~ 20 自然人年(的努力)
Building a high-quality database requires ~ 20 person years (effort)

方案 开源框架构建数据库系统
Create an open source framework to build their own DBMS

设计 Flexible → Relational algebra Extensible → Volcano style planner

替待 PostgreSQL, Apache Spark, GPORCA






Calcite 基础介绍 | 核心组件

Core – Operator expressions (relational algebra) and planner (based on Volcano/Cascades)

External – Data storage, algorithms and catalog

Optional – SQL parser, JDBC & ODBC drivers

Extensible – Planner rewrite rules, statistics, cost model, algebra, UDFs







Calcite 基础介绍 | Flink 用到的组件

System	Query Language	JDBC Driver	SQL Parser and Validator	Relational Algebra	Execution Engine
Apache Drill	SQL + extensions	✓	✓	✓	Native
Apache Hive	SQL + extensions			✓	Apache Tez, Apache Spark
Apache Solr	SQL	✓	✓	✓	Native, Enumerable, Apache Lucene
Apache Phoenix	SQL	✓	✓	✓	Apache HBase
Apache Kylin	SQL	✓	✓		Enumerable, Apache HBase
Apache Apex	Streaming SQL	✓	✓	✓	Native
Apache Flink	Streaming SQL	✓	✓	✓	Native
Apache Samza	Streaming SQL	✓	√.	✓	Native
Apache Storm	Streaming SQL	✓	✓	✓	Native
MapD [32]	SQL		✓	✓	Native
Lingual [30]	SQL		✓	✓	Cascading
Qubole Quark [42]	SQL	✓	✓	✓	Apache Hive, Presto



Calcite 基础介绍 | Flink SQL 体系结构







Flink SQL 集成 Calcite

The integretion of Flink SQL and Apache Calcite

02



Flink SQL 集成 Calcite | 语法扩展

DDL

CREATE TABLE - FLIP-6962

Computed Column – FLIP-70 CALCITE-3379

Time Attribute – FLIP-66

Type Parse Extension – CALCITE-3213

```
CREATE TABLE t (
  a int,
  b varchar(20),
  c as to_timestamp(b), -- computed column
  -- watermark strategy
  watermark for `c` as myfunc(c, 1) - interval '5' second
) WITH (
  'kl' = 'vl'
  ...
);
```



Flink SQL 集成 Calcite | 语法扩展

Hive Dialect

PARTITION Support – FLIP-12742 FLINK-12867

Whole PARTITION Story - FLIP-63

```
CREATE TABLE t (
...
)

PARTITIONED BY (column1, column2)

WITH (
...
);

INSERT INTO t PARTITION(a = 2, b = 'abc') SELECT FROM ...;
```




Why Catalog?


Manage tables - Catalog -> DataBase -> Object(Table)

Table metadata persistence – Store table schema, the statistics

Bridge Alien Systems – Load meta from Hive metastore to read and write









Calcite Schema Flink Schema







Flink Schema Flink Catalog



How To Use

```
// Register a catalog instance named "my_catalog" into the session.
tEnv.registerCatalog("my_catalog", catalog_instance);

// Use the catalog1 by specifying the name
tEnv.useCatalog("catalog1");

// Use the database
tEnv.useDataBase("database1");
```



Flink SQL 集成 Calcite | Metadata Extension

Column Interval - The column values interval, to make more accurate estimate of selectivity with predicates


Column Null Cnt – Column null values count, to filter out the null values of inner join inputs to reduce the skewed nulls


Minimum Unique Keys – Minimus unique keys permutation to reduce hash key computation burden

In CALCITE-3446, we also promote the extensibility of the RelMetadataQuery



Flink SQL 集成 Calcite | Metadata Extension





Number of Distinct Value = 5

Use Case of ColumnInterval



Flink SQL 集成 Calcite | Planner Rules

Multi Sink - Support DAG plan promotion


Sub plan reuse – Reuse the result of the pipline data sets


Self-join promotion – Use uniform Rank instead of agg and self join

Shuffle Reduction – Ajust the shuffle distribution atomatically to reduce data shuffle (Network IO)



Flink SQL 集成 Calcite | Planner Rules





Select col1, col2 from T1 where col3 = (select max(col3) from T1 T2 where T2.col1 = T1.col1 and T2.col2 = T1.col2)

self-join promotion



Flink SQL 集成 Calcite | Implicit Type Coercion

Why Implicit Type Coercion?

Int > VARCHAR

INT = BOOLEAN

For convenience!

VARCHAR BETWEEN DATE and TIMESTAMP



Flink SQL 集成 Calcite | Implicit Type Coercion

How To Use


```
CREATE TABLE t (
  f_data DATE,
  f_timestamp TIMESTAMP WITHOUT TIME ZONE
) WITH (
    ...
);

SELECT ... FROM ... WHERE 1 = true or '2019-11-03' BETWEEN f_date and f_timestamp;
```



Flink SQL 集成 Calcite | Implicit Type Coercion

The Internal



- 1. SqlValidate fires the validation of the call
- Operand type checker asks the TypeCoercion for the implicit type coercion
- TypeCoercion wrap the operand with CAST and replace the operand with the new one
- 4. update node type cache



Flink SQL 集成 Calcite | SQL Hint

Why SQL Hint?

Planner Enforcers – There's no perfect planner, so it makes sense to implement hints to allow user better control the execution. For instance: "never merge this subquery with others" (/*+ no_merge */).

Append meta data/statistics – Some statistics like "skew info of some shuffle keys" are somewhat dynamic for the query, config them with hints if our planning metadata is not that accurate.

Operator resource constraints – It would be very flexible to profile the resource with hints per query (not the Job).




Flink SQL 集成 Calcite | SQL Hint

The Syntax

```
SELECT /*+ NO_HASH_JOIN, RESOURCE(mem='128mb', parallelism='24') */
FROM
  emp /*+ INDEX(idx1, idx2) */
  JOIN
  dept
  ON emp.emono = dept.deptno
```



Flink SQL 集成 Calcite | SQL Hint



Hints Propagation







展望未来

Expression Reuse – Reuse the nested referenced expression witnin the projection list

Hign Level Algebra Expression – Recursion, Loop

Traits Propagation – CALCITE-2970

