

problem2tex

version = 0.8.6 (2022-01-13)

David Johns,
david.johns@icewire.ca

Document Date - 2022-01-13

Contents

1	The need for problem to tex	1
2	Installation and Setup	1
3	Running problem2tex	2
3.1	Command Line Options	2
3.2	Error Logging	2
3.3	Examples	2
3.4	Configuration settings	4
3.5	Commands for .prb files	5
3.5.1	PARAM command	6
3.5.2	RUN commands	6
3.5.3	VAL command	7
3.6	Expression Solver	7
3.6.1	Functions	7
3.6.2	More on Units	8
4	License	8
4.1	Files created by problem2tex	8
4.2	Software License	8

1 The need for problem to tex

Latex is an excellent way to create educational material such as textbooks, examples, exams, and problem sets. The purpose of **problem2tex** creating a .tex file is to allow one to create a numerical example (or problem) .prb file so that parameters can change and have the solution be automatically updated for that choice of parameters. In addition, **problem2tex** has an expression solver that is used to quickly write the solution for an example (or problem).

Example usage:

```
problem2tex -export=example.tex -random=false -sigDigits=4 example.prb
```

2 Installation and Setup

For installation/setup of problem2tex, see <https://www.icewire.ca>

3 Running problem2tex

3.1 Command Line Options

The command line options for `problem2tex` are the following:

- `-help`
Print out help info
- `-version`
Print out version info
- `-export=path/filename.tex`
where the output should be placed
[path](#) is the directory path that can include `..` or `.` and subdirectories
- `-random=option`
where option is one of ... (problem to tex option)
[true](#): Parameters are randomized
[false](#): Parameters are the first values in the sets (default setting)
[positive integer](#): Seed for random number generator
[min](#): All smallest numbers
[max](#): All largest numbers
[minMax](#): Random mix of largest and smallest numbers
- `-sigDigits=value`
where value is an integer that sets the default number of significant digits in the output (If not specified, then it is set to 4). RunConfig can also be used to set number of significant digits.

3.2 Error Logging

When running `problem2tex`, error information is placed as comments at the beginning of the output `.tex` file. If things do not work as you expect, check the error log information first as Latex error information can sometimes be misleading.

3.3 Examples

`problem2tex` is a way to make problems have parameters that can change and the solution is re-calculated for that solution. In addition, the solution is easily written as equations which are then displayed as latex solutions. For this to work, `problem2tex` has a built-in expression solver similar to Julia or Matlab.

This example is available at [testBasic.zip](#)

In this example, `basic01.prb` is a user generated problem file and contains the following text:

```
PARAM{x = [2, 3, 4, 5]}
PARAM{y = [6, 7, 8, 9]}
PARAM{k = [8]}
Given VAL{x,=}, VAL{y,=}, and VAL{k,=} find $z = x^2+y-k$
BEGIN{SOLUTION}
RUN(){z=x^2+y-k}
HILITE{VAL{z,=}}
END{SOLUTION}
```

For the above problem, x , y and k are all parameters where x is any one of 2,3,4 or 5 and y is any one of 6,7,8 or 9 and k is 8. For the solution, it is simply written as the equation and a built-in expression solver solves the expression and writes it out in correct Latex form. The solution in this case is written as

`RUN() { z=x^2+y-k }`

and when running with the following command

```
problem2tex -export=example.tex example.prb
```

a tex file is created that can be included in a latex document.

In the same testBasic.zip file, the second example basic01.prb contains the following text:

```
PARAM{V_1 = [2, 3, 4, 5]# UNITS{V}}
PARAM{R_1 = [6, 7, 8, 9]# UNITS{k \Omega}}
Given VAL{V_1=} and VAL{R_1=}, find the current $I_R = V_1/R_1$
BEGIN{SOLUTION}
RUN() { I_R=V_1/R_1 }
HILITE{\val={I_R}}
END{SOLUTION}
```

What is interesting here is that units can be assigned to parameters and the expression solver takes into account unit prefixes to generate the correct solution value prefix (i.e, f, p, n, μ , m, k, M, G, etc).

Also related to units, the units for any variable can be set using the UNITS{} command. In addition, a parameter in CONFIG called defaultUnits can be used to set the default units depending on the first letter of the variable. (see CONFIG settings)

NOTE: micro uses `\mu` (and not the letter u)

In this example, the above 2 problem files are included in a file called basic.tex which contains the following text:

```
\documentclass[11pt]{exam}
\usepackage{import,xcolor}
\newcommand{\incProb}[1]{
  \immediate\write18{problem2tex -export=Problems/tmp/#1.tex
    -random=false -sigDigits=4 Problems/#1.prb}
  \import{Problems/tmp/}{#1.tex}
}
\newcommand{\hlite}[1]{%
  \colorbox{yellow!50}{#1} }
\newcommand{\units}{\,\,\mathrm{}}

\begin{document}
\begin{questions}

\incProb{basic01}
\incProb{basic02}

\end{questions}
\end{document}
```

The tex file is using the exam class (for question numbering) and has 3 commands defined: `\incProb`; `\hlite`; `\units`.

When the above basic.tex is compiled as a text document, the following output is generated:

1. Given $x = 2$, $y = 6$, and $k = 8$ find $z = x^2 + y - k$

Solution

$$z = x^2 + y - k = (2)^2 + (6) - (8)$$

$$z = 2$$

2. Given $V_1 = 2 \text{ V}$ and $R_1 = 6 \text{ k}\Omega$, find the current $I_R = V_1/R_1$

Solution

$$I_R = V_1/R_1 = (2)/(6e3)$$

$$I_R = 333.3 \mu\text{A}$$

In this case, all default parameters are used but it is one line change to obtain random parameters and change the significant number of digits.

`problem2tex -export=Problems/tmp/#1.tex -random=true -sigDigits=6 Problems/#1.prb`

When run using the above random flag, one example random case is the following: (each run will be random)

1. Given $x = 5$, $y = 8$, and $k = 8$ find $z = x^2 + y - k$

Solution

$$z = x^2 + y - k = (5)^2 + (8) - (8)$$

$$z = 25$$

2. Given $V_1 = 3 \text{ V}$ and $R_1 = 7 \text{ k}\Omega$, find the current $I_R = V_1/R_1$

Solution

$$I_R = V_1/R_1 = (3)/(7e3)$$

$$I_R = 428.571 \mu\text{A}$$

3.4 Configuration settings

Configuration settings can be changed at any time and then they are used going forward until changed again. Configuration settings can be changed using the CONFIG command. Each CONFIG command should be on a separate line with no other commands on the same line.

Example: `CONFIG{random = min}`

- random - choice of false, true, min, max, minMax and positive integer
 - false: defaults elements chosen
 - true: random elements chosen
 - min: min sized elements chosen
 - max: max sized elements chosen
 - minMax: random choice of min and max sized elements chosen
 - positive integer: seed for random generator so same elements can be chosen
- fmtVal - format of output values for \val
 - set as `CONFIG{format=X}` where X is one of ...
(the number of significant digits can be from 1-9)
 - E4 for engineering format with 4 significant digits
 - S4 for scientific format with 4 significant digits

- D4 for decimal format with 4 significant digits
- \$ for dollar format (always has 2 digits after decimal point)
- U4 for SI format (including units) with 4 significant digits
- DEFAULT IS U4
- fntRun= - format of output values after equal in RUN= or RUN()= commands
 - Same as format above
 - DEFAULT IS U4
- fntRun() - format of output values in bracketed numbers in RUN() or RUN()= commands
 - Same as format above
 - DEFAULT IS E4
- KFactor - Used for default set generation if PARAM sets variable to a nominal number.
 - Set KFactor example: CONFIG{KFactor = 1.5:5} where 1.5 is the factor and 5 is the number of elements in the set.
 - Factor must be a number greater than 1.
 - The range of the elements are from nominal/factor to nominal*factor and are geometrically spaced.
- defaultUnits - used to set the default units depending on the first letter of a variable
 - example: CONFIG{defaultUnits = [[iI:A][vV:V][R:\Omega]]}
 - above example results in variables starting with the letter i or I having default units of "A"
 - variables starting with letter v or V having default units of "V"
 - variables starting with letter R having default units of "\Omega"
 - use of UNITS within a run command will override the default unit setting
- verbose - choice of true or false (default false)
 - prints out the elements sets in commented out lines in the .tex file (useful for debugging)
 - Also prints out the configuration settings

3.5 Commands for .prb files

There are 4 main commands for problem to tex:

- CONFIG (discussed above)
- PARAM
- RUN, RUN(), RUN()=
- VAL

3.5.1 PARAM command

The command PARAM can be used for setting the randomly generated variables (i.e. parameters). Each PARAM command must be on a separate line with no other commands on the same line.

- `PARAM{var = [x1, x2, x3, ...]# UNITS{units} SYMBOL{varLatex} }`
 - var will be a random selection from the set of x1, x2, x3, ...
 - if random=false, the default value for var is the first element
 - if UNITS{units} is present, then the units for that variable will be units
 - if SYMBOL{varLatex} is present, then when printing out, the symbol for var will be replaced with varLatex
- `PARAM{var = min;max;stepsize# UNITS{units} SYMBOL{varLatex} }`
 - The set for var will be generated from min;max;stepsize
 - The first element will be min so the default will be the min element
 - Otherwise, it is the same as the array generation above
- `PARAM{var = nominal# UNITS{units} SYMBOL{varLatex} }`
 - The set for var will be generated from nominal and the KFactor configuration parameter
 - KFactor: factor:numElements... factor is a number greater than 1 and numElements is a positive integer (numElements is the number of elements in the set).
 - Elements range from nominal/factor to nominal*factor and are geometrically spaced
 - Example: if nominal is 10 and factor is 1.5, then the range is from 6.667 to 15
 - The default is nominal which would be 10 in the above example
 - Otherwise, it is the same as the array generation above

3.5.2 RUN commands

The commands RUN are used for evaluating expressions and setting new variables.

The format for an expression is the same as Matlab or Julia (NOT a latex equation).

See the Expression Solver section below for more information.

Options are the same as in PARAM.

In all cases below, the `expr` is evaluated and the result is assigned to `var`

- `RUN{var = expr # options} }`
 - Print out `var = expr`.
 - There can be multiple `var = expr` separated by ";"
- `RUNSILENT{var = expr # options}`
 - Do not print anything out
- `RUN(){var = expr # options}`
 - Print out `var = expr` AND print out intermediate () `expr` for clarity
- `RUN={var = expr # options}`
 - Print out `var = expr` AND print out "`= result`"
- `RUN()={var = expr # options}`
 - Print out `var = expr` AND print out intermediate () `expr` AND print out "`= result`"

3.5.3 VAL command

Below is the VAL command for printing out variable value or an expression value.

- VAL{`expr`,`format`}
- Print out the result of `expr` with format set by `format` (see below for format choices)
- `,format` is optional. If not present, then the default setting for format is used which was set by `CONFIG{format = X}`
- `expr` in a `\val` command should NOT contain a `"`,
- `expr` in a `\run` command may contain `"`,`"`s
- `expr` can be a single variable or a full expression
- VAL format types
- E4 for engineering format with 4 significant digits
- S4 for scientific format with 4 significant digits
- D4 for decimal format with 4 significant digits
- \$ for dollar format (always has 2 digits after decimal point)
- U4 for SI format (including units) with 4 significant digits
- L for only printing VAL latex symbol (not the value of VAL)
- = for printing "latex symbol = value"
- DEFAULT IS U4

3.6 Expression Solver

Problem to tex makes use of a built in expression solver to solve `expr` within `RUN{expr}`. Expressions are made similar to Julia or Matlab.

Example valid `expr` are:

- `RUN{A = sqrt(B)*abs(-4)}`
- `RUN{R_4 = parll(R_1,parll(R_2,R_3))}`

3.6.1 Functions

The functions currently available in problem2tex are:

`abs`, `asin`, `asinh`, `acos`, `acosh`, `atan`, `atanh`, `ceil`, `cos`, `cosh`, `exp`, `floor`, `log`, `log10`, `round`, `sin`, `sinh`, `sqrt`, `tan`, `tanh`

the above make use of the math package for golang.

In addition, extra functions are:

- `cosd(x)`, `sind(x)`, `tand(x)`
returns `cos(x)/sin(x)/tan(x)` but x value is in degrees
- `acosd(x)`, `asind(x)`, `atand(x)`
returns `acos(x)/asin(x)/atan(x)` but returns the value in degrees
- `dB(x)`

returns $10 \cdot \log_{10}(x)$

- `dbV(x)`

returns $20 \cdot \log_{10}(x)$

- `parll(a,b)`

returns the numeric parallel value (returns $(1/a + 1/b)^{-1}$)

the latex printout of this function is `||` to make it more readable

3.6.2 More on Units

`problem2tex` will automatically calculate proper unit prefixes IF SI unit notation is used. For micro, `"\mu"` must be used instead of `"u"`. In some situations, one might want to use a unit notation that is NOT officially SI correct. For example, one might want to use $V/\mu\text{m}$ instead of MV/m . In this case a way to achieve this is shown with the following example...

```
PARAM{V_Aprime = [5,3,4,6]# UNITS{V/\mu m} SYMBOL{V_A'}}
PARAM{V_A = [6, 7, 8, 9]}
Given VAL{V_Aprime,=} and VAL{V_A,=}, find $L$
BEGIN{SOLUTION}
RUNSILENT{V_Aprime = 1e6*V_Aprime}
RUN()={L=V_A/V_Aprime#UNITS{m}}
END{SOLUTION}
```

The use of `RUNSILENT` corrects the value for `V_Aprime` (since μm is in the denominator of a unit) by multiplying the values by $1e6$. In this example, `"L"` would default to units of `"H"` so it is corrected to meters using `\UNITS{m}`.

The output becomes ...

1. Given $V'_A = 5 \text{ V}/\mu\text{m}$ and $V_A = 6 \text{ V}$, find L

Solution

$$L = V_A/V'_A = (6)/(5e6) = 1.2 \mu\text{m}$$

4 License

4.1 Files created by `problem2tex`

All files created by `problem2tex` are owned by the creators of the work (that is you) and/or by the original authors of the work in cases you use derivative works.

4.2 Software License

Copyright © 2021 David Johns.

This license applies to `problem2tex` the program, its packages, extensions and source code as published or made available through any third party.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.