




Programming Basics – WiSe21/22

I/O: Files and Data Streams

Prof. Dr. Silke Lechner-Greite

Table of contents – planned topics

1. Introduction
2. Fundamental language concepts
3. Control structures
4. Methods
5. Arrays
6. Object orientation
7. Classes
8. Packages
9. Characters and Strings
10. Unit Testing
11. Exceptions
12. I/O



Source: [2]

- How do you store data persistently?
 - ⌘ Files
 - ⌘ Databases
- How do you read or write in files?

Core classes: file input and output

- **java.io** (since Java 1.0)
 - ⊞ Still widely used
 - ⊞ **File** class used for everything!
 - ⊞ Create, delete, copy files; structure in directories

- **java.nio.file** (since Java 7)
 - ⊞ Aim: stronger decoupling of platform, abstraction of file system
 - ⊞ New classes replace **File** completely.
 - ⊞ Core classes
 - ⊞ **FileSystem**: abstract top-level class, uniform interface independent of implementation (hard disk, RAM, floppy disk, ...).
 - ⊞ **FileSystems**: factory methods to get to a specific **FileSystem**.
 - ⊞ Represents file/directory path, path-related methods.
 - ⊞ Generated from string or URI path object.
 - ⊞ Create, delete, copy, manipulate files

java.nio: example

- **Path** object
 - ⊞ Represents a path.
- **Files**: manipulation of files and directories

```
// generate absolute Path object using a relative path
Path filePath = Paths.get("lecture10/src/test.txt").toAbsolutePath();
System.out.println(filePath.toString());
// print root directory
System.out.println("Root directory is: " + filePath.getRoot().toString());
// size of file
try {
    // size of file
    long fileSize = Files.size(filePath);
    // copy a file
    Files.copy(filePath, Paths.get("vorlesung10/src/test-kopie.txt"),
        StandardCopyOption.REPLACE_EXISTING);
    // create a new directory
    Files.createDirectory(Paths.get("vorlesung10/src/newDir"));
} catch (IOException e) {
    e.printStackTrace();
}
```

Overview: access to file content

➤ **Random vs. sequential access**

- ⊞ *Random access*: jump back and forth as desired within a file.
- ⊞ : data is read or written in a fixed order.

➤ In Java, file content is usually accessed via **streams**!

- ⊞ Definition: continuous sequences of data of one type.
- ⊞ Areas of application: files, sockets,
- ⊞ **Files** class has methods for creating streams
 - ⊞ `Files.newXXXStream()`

➤ **Granularity of access for streams**

- ⊞ *Byte-based*: each read/write accesses the next byte in the stream.
- ⊞ *Character-based*: each read/write accesses the next character in the stream.
 - ⊞ Some characters have different byte lengths.
 - ⊞ Example: UTF-8 encoding: <http://www.utf8-zeichentabelle.de/>
- ⊞ [line by line]



Streams / data streams

- **Abstraction of a stream** (= typical methods)
 - ⊞ **open()** : Open stream from/to file, device, etc.
 - ⊞ **read()** : Read the next item from stream
 - ⊞ **write()** : Write the next item in stream
 - ⊞ **close()** : Close stream
- There are many different streams for all kinds of different tasks
 - ⊞ Inheritance hierarchy!
- **Abstract base classes of the streams**
 - ⊞ **Character streams**: Usually UTF-8 encoded
 - ⊞ Input: class
 - ⊞ Output: class
 - ⊞ **Byte streams**: 8 bits
 - ⊞ Input: class **InputStream**
 - ⊞ Output: class **OutputStream**



Character streams: input

➤ **Basis:** abstract class `java.io.Reader`

- ⌘ Parameterless constructor
- ⌘ Series of `read()` methods
- ⌘ `ready()`, `close()`, `mark()`, `reset()`, `skip()`

➤ Classes derived from `Reader` (selection of input device)

- ⌘ `InputStreamReader`, `FileReader`,
`StringReader`, `CharArrayReader`

➤ Classes derived from `Reader`
(nesting of input streams)

- ⌘ `FilterReader`, `PushbackReader`,
`BufferedReader`,
`LineNumberReader`, `PipedReader`

```
java.io.Reader (implements ...)  
- java.io.BufferedReader  
- java.io.LineNumberReader  
- java.io.CharArrayReader  
- java.io.FilterReader  
- java.io.PushbackReader  
- java.io.InputStreamReader  
- java.io.FileReader  
- java.io.PipedReader  
- java.io.StringReader
```


Example: character-based reading

- **BufferedReader** is a subclass of Reader
 - ✚ Additional methods, e.g. **readLine()**
 - ✚ Temporary storage of data in internal buffers
 - ✚ Efficient reading of files!

```
// generate absolute Path object using a relative path
Path filePath = Paths.get("vorlesung10/src/test.txt").toAbsolutePath();
try {
    BufferedReader bf = Files.newBufferedReader(filePath);
    String line;
    while ((line = bf.readLine()) != null) {
        System.out.println(line);
    }
} catch (IOException e) {
    e.printStackTrace();
}
```

Variant 1:
Create
a
buffered
file stream
using
java.nio



Character streams: output

- Basis: abstract class **java.io.Writer**
 - ⊞ Parameterless constructor (open the output stream and prepare for subsequent `write` call)
 - ⊞ `close()`: Close the output stream
 - ⊞ `flush()`: Empty the buffers & pass on the data within to the output device
 - ⊞ Multiple `write` methods
- Classes derived from `Writer` (selection of output device)
 - ⊞ `OutputStreamWriter`, `FileWriter`, `StringWriter`, `CharArrayWriter`, `PipedWriter`
- Classes derived from `Writer` (nesting of output streams)
 - ⊞ `BufferedWriter`, `PrintWriter`, `FilterWriter`

```
java.io.Writer (implements ...)  
- java.io.BufferedWriter  
- java.io.CharArrayWriter  
- java.io.FilterWriter  
- java.io.OutputStreamWrite  
- java.io.FileWriter  
- java.io.PipedWriter  
- java.io.PrintWriter  
- java.io.StringWriter
```

Byte streams: example output

➤ Basis: abstract class `java.io.OutputStream`

- ✚ Parameterless constructor
- ✚ `close()`, `flush()`
- ✚ write methods

```
java.io.OutputStream (implements ...)  
○ java.io.ByteArrayOutputStream  
○ java.io.FileOutputStream  
○ java.io.FilterOutputStream  
    ○ java.io.BufferedOutputStream  
    ○ java.io.DataOutputStream (implements ...)  
    ○ java.io.PrintStream (implements ...)  
○ java.io.ObjectOutputStream (implements ...)  
○ java.io.PipedOutputStream
```

Byte streams: input


- Basis: abstract class **java.io.InputStream**
 - ⌘ Parameterless constructor
 - ⌘ `skip()`, `available()`, `close()`, `markSupported()`,
`mark()`, `reset()`
 - ⌘ read methods

```
java.io.InputStream (implements ...)  
○ java.io.ByteArrayInputStream  
○ java.io.FileInputStream  
○ java.io.FilterInputStream  
    ○ java.io.BufferedInputStream  
    ○ java.io.DataInputStream (implements ...)  
    ○ java.io.PushbackInputStream  
○ java.io.ObjectInputStream (implements ...)  
○ java.io.PipedInputStream  
○ java.io.SequenceInputStream
```

Chaining (concatenation) of streams

- Streams can be chained to each other!
 - ⊞ Creation of the 1st stream as normal through a constructor.
 - ⊞ Handover in constructor!
- **Example 1:** concatenation of FileReader and BufferedReader
 - ⊞ 1st stream: reads character-based data from file.
 - ⊞ 2nd stream: buffers data before it is passed on.

```
FileReader fReader = new FileReader(fileName);
BufferedReader bReader = new BufferedReader(fReader);
```



Variant 2:
Create
a
buffered
file stream
using chaining
(concatenation)
of streams,
see slide 7

Chaining (concatenation) of streams

➤ Applications

- ⊞ Saving Java objects in a file or database
- ⊞ Transferring Java objects over a network
- ⊞
 - ⊞ Conversion of an object into a byte stream.
 - ⊞ Standard serialisation of Java, but rarely used.

➤ Outlook: prerequisite for serialisation

- ⊞ Object must be serialisable.
- ⊞ The object must implement the `Serializable` interface
 - ⊞ Marker interface, does not prescribe any methods!
- ⊞ All attributes must be serialisable, otherwise overwrite the following method of the attribute's class:
 - ⊞ `writeObject(java.io.ObjectOutputStream)`
 - ⊞ `readObject(java.io.ObjectInputStream)`

Outlook: Java serialisation

```
public class Account implements Serializable {  
    // ...  
}
```

```
String pathName = "test.out";  
Account salaryAccount = new Account(1000); // ...
```

```
// Write object to file  
ObjectOutputStream oos = new ObjectOutputStream(new FileOutputStream(pathName));  
oos.writeObject(salaryAccount);  
// ...
```

```
// Read object from file  
ObjectInputStream ois = new ObjectInputStream(new FileInputStream(pathName));  
Account sa = (Account) ois.readObject();  
// ...
```

Chaining :

concatenation

Rarely used in practice!