



Programming Basics – WiSe21/22

Characters and Strings

Prof. Dr Silke Lechner-Greite

Table of contents – planned topics

1. Introduction
2. Fundamental language concepts
3. Control structures
4. Methods
5. Arrays
6. Object orientation
7. Classes
8. Packages
9. Characters and Strings
10. Unit Testing
11. Exceptions
12. I/O

Chapter 9: Characters and Strings

8.1 Characters

8.2 Strings

Character encoding

Aim: enabling the transfer of data and exchange of documents within different countries

ASCII	ISO/IEC 8859-1	ISO 8859-1	Unicode
<ul style="list-style-type: none"> • 7-bit encoding • Contains 128 characters • Code point: each character has a unique position • Basis for subsequent standards • 1963 	<ul style="list-style-type: none"> • 8-bit encoding • Space for 256 characters • Contains 197 characters → empty slots • Latin-1: extended by the Latin script • Extended ASCII, ASCII code points are retained • Without control characters • 1985 	<ul style="list-style-type: none"> • Extension of Latin-1 with control characters at code points 0-31 and 127 • Contains complete ASCII • Fills additional empty spaces with additional special characters. 	<ul style="list-style-type: none"> • Aim: encoding every character in the world • Unicode includes ISO 8859-1 → easier file conversion • Describes over 100,000 characters • Representation: Hexadecimal with the prefix U+ followed by hexadecimal numbers • A : U+0041 • Java 8 supports Unicode 6.2

Character sets

- Character set = table of characters <-> code point
- Different character sets

Character Set	Range	Description
ASCII	0-127	Aimed at US applications; no German umlauts and other special characters from European languages.
Latin-1 ISO-8859-1	0-255	0-127 = ASCII 128-255: predominantly characters from west European languages
Latin-15	0-255	Like Latin-1, except code 164 = currency symbol €
Unicode	0-1000000+	0-127 = ASCII 0-255 = Latin-1 256+: Zeichen von Weltssprachen

- Java uses Unicode: <https://home.unicode.org/>

Translated from source: Schiedermeier

Dez	Hex	Okt	ASCII	Dez	Hex	Okt	ASCII	Dez	Hex	Okt	ASCII	Dez	Hex	Okt	ASCII
0	00	000	NUL	32	20	040	SP	64	40	100	@	96	60	140	`
1	01	001	SOH	33	21	041	!	65	41	101	A	97	61	141	a
2	02	002	STX	34	22	042	"	66	42	102	B	98	62	142	b
3	03	003	ETX	35	23	043	#	67	43	103	C	99	63	143	c
4	04	004	EOT	36	24	044	\$	68	44	104	D	100	64	144	d
5	05	005	ENQ	37	25	045	%	69	45	105	E	101	65	145	e
6	06	006	ACK	38	26	046	&	70	46	106	F	102	66	146	f
7	07	007	BEL	39	27	047	'	71	47	107	G	103	67	147	g
8	08	010	BS	40	28	050	(72	48	110	H	104	68	150	h
9	09	011	HT	41	29	051)	73	49	111	I	105	69	151	i
10	0A	012	LF	42	2A	052	*	74	4A	112	J	106	6A	152	j
11	0B	013	VT	43	2B	053	+	75	4B	113	K	107	6B	153	k
12	0C	014	FF	44	2C	054	,	76	4C	114	L	108	6C	154	l
13	0D	015	CR	45	2D	055	-	77	4D	115	M	109	6D	155	m
14	0E	016	SO	46	2E	056	.	78	4E	116	N	110	6E	156	n
15	0F	017	SI	47	2F	057	/	79	4F	117	O	111	6F	157	o
16	10	020	DLE	48	30	060	0	80	50	120	P	112	70	160	p

More details:
<https://en.wikipedia.org/wiki/ASCII>

Graphs taken from:
[https://de.wikipedia.org/wiki/American Standard Code for Information Interchange](https://de.wikipedia.org/wiki/American_Standard_Code_for_Information_Interchange)

Character code = unique `int` value for each character

17	11	021	DC1	49	31	061	1	81	51	121	Q	113	71	161	q
18	12	022	DC2	50	32	062	2	82	52	122	R	114	72	162	r
19	13	023	DC3	51	33	063	3	83	53	123	S	115	73	163	s
20	14	024	DC4	52	34	064	4	84	54	124	T	116	74	164	t
21	15	025	NAK	53	35	065	5	85	55	125	U	117	75	165	u
22	16	026	SYN	54	36	066	6	86	56	126	V	118	76	166	v
23	17	027	ETB	55	37	067	7	87	57	127	W	119	77	167	w
24	18	030	CAN	56	38	070	8	88	58	130	X	120	78	170	x
25	19	031	EM	57	39	071	9	89	59	131	Y	121	79	171	y
26	1A	032	SUB	58	3A	072	:	90	5A	132	Z	122	7A	172	z
27	1B	033	ESC	59	3B	073	;	91	5B	133	[123	7B	173	{
28	1C	034	FS	60	3C	074	<	92	5C	134	\	124	7C	174	
29	1D	035	GS	61	3D	075	=	93	5D	135]	125	7D	175	}
30	1E	036	RS	62	3E	076	>	94	5E	136	^	126	7E	176	~
31	1F	037	US	63	3F	077	?	95	5F	137	_	127	7F	177	DEL

Type `char`

- Individual text characters are represented by the primitive type `char` (*character*)
- Representation of characters using 16 bits
- `char` literals: Characters in inverted commas (*quotation marks*)

Examples:

Literal	Meaning
'a'	lower case letter "a"
'8'	number "8", not <code>int</code> value 8
'%'	percent sign
' '	space

- Escape sequences: saves typing complicated Unicodes
 - ⊞ Newline: `'\n'` Single quote: `'\''`
 - ⊞ Tabulator: `'\t'` Double quote: `'\"'`

Operations with `char`

- Declaration and assignment of a **variable**:

```
char letter;  
letter = 'a';
```

- **Comparison** of characters for equality and inequality:

```
char seven = '7';  
if (seven == 'a')           //false  
    ...
```

- **Size comparison** for lower case or upper case letters according to the alphabet:

```
char capitalA = 'A';  
if (capitalA < 'B')           //true  
    ...  
else if (capitalA > 'B')      //false  
    ...
```


Arithmetic with `char` values

- Increment/decrement of `char` variables leads to the "next" character
- Example:

```
for(char letter = 'Z'; letter >= 'A'; letter--)  
    System.out.print(letter);
```

Library methods for characters

- Static methods of the `Character` class
- Test methods – shown with prefix "is"
- Selection:

Let's look at
the API about
Character class
and the
definition of
whitespaces

<code>boolean isLetter(char ch)</code>	is ch a letter (upper or lower case?)
<code>boolean isDigit(char ch)</code>	is ch a digit
<code>boolean isWhitespace(char ch)</code>	is ch a space character (whitespace)
<code>boolean isLowerCase(char ch)</code>	is ch a lower-case letter
<code>boolean isUpperCase(char ch)</code>	is ch an upper-case letter
<code>char toLowerCase(char ch)</code>	small letter to ch if it exists; ch otherwise
<code>char toUpperCase(char ch)</code>	capital letter to ch if it exists; ch otherwise

- More:

- ✚ <https://docs.oracle.com/javase/8/docs/api/java/lang/Character.html>
- ✚ [https://docs.oracle.com/javase/7/docs/api/java/lang/Character.html#isWhitespace\(int\)](https://docs.oracle.com/javase/7/docs/api/java/lang/Character.html#isWhitespace(int))

Exercise – Library methods for characters



➤ Live exercise

- ✦ Complete **Task 1** on the live exercises sheet “Characters and Strings”
- ✦ You have 15 minutes.



Chapter 9: Characters and Strings


8.1 Characters

8.2 Strings

Type String

- Text /strings are represented by the type `String`
- Container type: stores items of other types
 - ⊞ Individual elements of strings: `char`
 - ⊞ Any number of `char` elements

- Structure of a string:



String literals

- In order to work with strings, a string object must exist.
- **String literals**: text between **double** quotation marks → is automatically a string object
- Therefore, a method call can be executed with **.** after a string literal.

- Examples:

```
"Java"  
"I am a string!"  
" "  
""
```

All character representations are allowed


```
" 'a' "  
"two\n\lines"  
"M\u00FCnchen"
```

- **Length** of a string = number of characters

Creating a string object

- Create and reference to the string object:

```
String text;  
text = new String("Programming with Java");
```



- Short form (and preferred version):

```
String text = "Programming with Java";
```

Special feature of `strings`

- Strings are **unchangeable (immutable)**
 - ✚ Insertion, replacement or removal of individual characters is not possible
- **Note:** `String` variables are changeable, except they are defined as `final`

```
String text;  
text = "Java";           // ok  
text = "Compiler";       // ok  
  
final String fixed;  
fixed = "I never change"; // ok  
fixed = "error";          // error because of final
```


Concatenation

- **Concatenation:** + with strings
 - ⊞ Chaining (concatenation) with the + operator
 - ⊞ Produces a **new, third string** from the operands

- **Example:**

```
"Java" + "compiler" → "Javacompiler"
```

- Different data types and one of them is a string: the other data types are implicitly type casted to a String followed by a concatenation
- Polymorphism:
 - ⊞ 3 + 5 → 8 int
 - ⊞ 3.0 + 5.0 → 8.0 double
 - ⊞ "3" + "5" → "35" string

- Documentation of the class:

<http://docs.oracle.com/javase/8/docs/api/java/lang/String.html>

- Selection:

```
// constructors
public String();
public String(String value);

// methods
public char charAt(int index);
public int length();
public boolean equals(Object anObject);
public String toLowerCase();
public String toUpperCase();
public String substring(int beginIndex);
public String substring(int beginIndex, int endIndex);
public int compareTo(String anotherString)


...
```

(Object) methods of the `String` class (1)

➤ `charAt` copies **individual characters** from the string

⊞ Argument: **index** of the desired character

⊞ Acceptable values: 0, 1, ..., string length -1



⊞ Index < 0 or index >= string length: index error, programme termination

➤ Examples:

```
String s = "Java";
char c;
c = s.charAt(1);           // c = 'a'
c = s.charAt(-1);          // error
c = s.charAt(4);           // error
```

(Object) methods of the `String` class (2)

➤ `length()` returns the number of characters

- ⊞ Result never negative, 0 for empty string
- ⊞ Length conceptually unlimited

➤ Examples:

- ⊞ Determining the length of a string

```
String s = "Java";  
int len = s.length();           // len = 4
```

- ⊞ Outputting all characters of a string

```
for(int i = 0; i < s.length(); i++)  
    System.out.println(s.charAt(i));
```

(Object) methods of the `String` class (3)

➤ **Comparison** of strings (test for equal contents)

✚ `boolean equals (Object anObject)`

✚ Compares character-by-character and returns `true` if equal

```
String      s1 = "Hello";  
String      s3 = new String("Hello");  
boolean b3 = s3.equals(s1); // b3 is true
```



Operator `==` checks the identity of `String` objects, not the contents!

(Object) methods of the `String` class (4)

➤ Converting strings: changing upper case and lower case

✚ `toLowerCase() : String`
converts all letters of the string to lower case

✚ `toUpperCase() : String`
converts all letters of the string to upper case

➤ Examples:

✚ `"Java compiler".toLowerCase() → "java compiler"`

✚ `"Java compiler".toUpperCase() → "JAVA COMPILER"`

(Object) methods of the `String` class (5)

➤ Splitting strings

✚ `String substring(int from)`

Partial string (i.e. substring) from index `from` to the end of the string

✚ `String substring(int from, int to)`

Partial string (i.e. substring) from index `from` to (exclusively) index `to`

➤ Examples:

✚ `"Java compiler".substring(2)` → `"va compiler"`

✚ `"Java compiler".substring(2, 7)` → `"va co"`

(Object) methods of the `String` class (6)

➤ Lexicographical order

⌘ `int compareTo(String anotherString)`

⌘ Two strings are given: `s1` , `s2`

⌘ Comparison using `s1.compareTo(s2)`

⌘ Result

⌘ `< 0` if `s1` is alphabetically before `s2`

⌘ `= 0` if `s1` equals `s2`

⌘ `> 0` if `s1` is alphabetically after `s2`

➤ Examples:

⌘ `"hello".compareTo("java")` → -2

⌘ `"hello".compareTo("hello")` → 0

⌘ `"hello".compareTo("compiler")` → 5

Static methods of the `String` class

➤ **Convert** numbers and strings into one another

- ⌘ `static String valueOf(int i)`
- ⌘ `static String valueOf(long l)`
- ⌘ `static String valueOf(float f)`
- ⌘ `static String valueOf(double d)`
- ⌘ `. . .`


➤ **Examples:**

- ⌘ `String s1 = String.valueOf(99.9);`

StringBuilder class

- If the programme works extensively with strings, new string objects are created continuously as intermediate results
=> possible performance loss
- Switch to `StringBuilder` class
 - ⌘ `StringBuilder` objects are like `String` objects, but they can be changed -> **changeable strings**
 - ⌘ Within the `StringBuilder` class, strings are treated as arrays of `chars` that can change in length.
 - ⌘ `StringBuilder` makes it possible to modify a string at any time in terms of length and content -> **provides dedicated methods to achieve this**
- Note: it is preferable to use strings, unless there is an advantage to using the `StringBuilder`, e.g. performance. Example: concatenation of long strings
-> more efficient with `StringBuilder`

StringBuilder class



<https://docs.oracle.com/javase/tutorial/java/data/buffers.html>

➤ Constructors:

- ✚ `StringBuilder ()` : empty `StringBuilder` object (capacity = 16)
- ✚ `StringBuilder (CharSequence cs)` : `StringBuilder` with `cs` as contents in the `StringBuilder` object + 16 empty elements
- ✚ `StringBuilder (int initCapacity)` : empty `StringBuilder` object with `initCapacity` elements
- ✚ `StringBuilder (String s)` : `StringBuilder` with `cs` as contents in the `StringBuilder` object + 16 empty elements

➤ Simple conversion:

- ✚ `String -> StringBuilder`

```
String s = "Java";  
StringBuilder b = new StringBuilder(s);
```

- ✚ `StringBuilder -> String`

```
StringBuilder b = new StringBuilder("Java");  
String s = b.toString();
```

Methods of `StringBuilder` (1)

✚ Initial situation:

```
StringBuilder b = new StringBuilder("Java compiler");
```

✚ `StringBuilder append(char c)` adds the character `c` at the end

```
b.append('#') → "Java compiler#"
```

✚ `StringBuilder insert(int at, char c)` inserts the character `c` at index `at`; the rest moves backwards

```
b.insert(4, '#') → "Java# compiler"
```

Methods of `StringBuilder` (2)

- ✚ `StringBuilder deleteCharAt(int at)`
deletes the character at index `at`; the rest moves forwards

```
b.deleteCharAt(4) → "Javacompiler"
```

- ✚ `StringBuilder delete(int from, int to)`
deletes the substring from index `from` to (exclusively) index `to`;
the rest moves forwards

```
b.delete(4, 8) → "Javapiler"
```



Methods do **not** create a **new** `StringBuilder` object,
but modify **this**

<https://docs.oracle.com/javase/8/docs/api/java/lang/StringBuilder.html>

Exercise – Applying methods



➤ Live exercise

- ✦ Complete **Task 2** on the live exercises sheet “Characters and strings”
- ✦ You have 15 minutes.



StringBuffer class

- `StringBuffer` objects are like `String` objects, but they can be changed -> **changeable strings**
- `StringBuffer` is a thread-safe, changeable string -> methods are synchronised as needed, so that all operations on a specific instance behave as if they occur in a serial order, which matches the order of the method calls of the individual participating threads.
- Most important operations: `append()` (appends at the end of the buffer) and `insert()` (inserts the characters at a specific location)
- <https://docs.oracle.com/javase/8/docs/api/java/lang/StringBuffer.html>

Outputting formatted text

- You are already familiar with the use of the `print()` and `println()` methods for printing strings as standard output (`System.out`).
- The `java.io` package contains a `PrintStream` class with two formatting methods: `format()` and `printf()` (are equivalent)
- `System.out == PrintStreamObject`
 - ⊞ `System.out.format(.....)`
 - ⊞ `System.out.printf(.....)`
- Example:

```
float floatVar = 3.45f;  
String stringVar = "Auto";  
System.out.format("%s: %f Euro\n", stringVar, floatVar);
```


Example: converter for formatted text

Converters and Flags Used in `TestFormat.java`

Converter	Flag	Explanation
d		A decimal integer.
f		A float.
n		A new line character appropriate to the platform running the application. You should always use <code>%n</code> , rather than <code>\n</code> .
tB		A date & time conversion—locale-specific full name of month.
td, te		A date & time conversion—2-digit day of month. td has leading zeroes as needed, te does not.
ty, tY		A date & time conversion—ty = 2-digit year, tY = 4-digit year.
tl		A date & time conversion—hour in 12-hour clock.
tM		A date & time conversion—minutes in 2 digits, with leading zeroes as necessary.
tp		A date & time conversion—locale-specific am/pm (lower case).
tm		A date & time conversion—months in 2 digits, with leading zeroes as necessary.
tD		A date & time conversion—date as <code>%tm%td%ty</code>

<https://docs.oracle.com/javase/tutorial/java/data/numberformat.html>

Date formatting

```
Calendar c = Calendar.getInstance();

System.out.format("%te. %tB %tY%n", c, c, c);
// --> 30 November 2019

System.out.format("%tl:%tM %tp%n", c, c, c);
// --> 8:54 am

System.out.format("%tD%n", c);
// --> 11/30/19
```

- The String class provides the ability to pre-format the string to be created:

```
String fs;  
fs = String.format("The value of the float " +  
                  "variable is %f, while " +  
                  "the value of the " +  
                  "integer variable is %d, " +  
                  " and the string is %s",  
                  floatVar, intVar, stringVar);  
System.out.println(fs);
```

More on this here:

<https://docs.oracle.com/javase/tutorial/essential/io/formatting.html>